

Packet Tracer Lab 4 - Configure Initial Router Settings

Part 1: Verify the Default Router Configuration

1. What is the router's hostname? **Router**
2. How many Fast Ethernet interfaces does the Router have? **04**
3. How many Gigabit Ethernet interfaces does the Router have? **02**
4. How many Serial interfaces does the router have? **02**
5. What is the range of values shown for the vty lines? **0 - 4**
6. Why does the router respond with the "startup-config is not present" message? **Because the startup config has not been saved from the running-config so currently NVRAM is empty**

Part 2: Configure and Verify the Initial Router Configuration

7. What command do you use? **show running-config**
8. Why should every router have a message-of-the-day (MOTD) banner? **To notify all who attempt access to the router are aware of security features turned on.**
9. Why would the **enable secret** password allow access to the privileged EXEC mode and the **enable password** no longer be valid? **Because the security features are set to accept the encrypted secret before the clear text password**
10. If you configure any more passwords on the router, are they displayed in the configuration file as plain text or in encrypted form? **Plain text**
 - a. Explain. **Because the service password-encrypted hasn't been initiated yet. If service password-encryption is not enabled, new passwords (like vty or console passwords) are displayed in plain text.**

Part 3: Save the Running Configuration File

11. What command did you enter to save the configuration to NVRAM? **Copy running-config start-config**
12. What is the shortest, unambiguous version of this command? **cop r st**

Step 2: Optional: Save the startup configuration file to flash.

13. How many files are currently stored in flash? **4**
14. Which of these files would you guess is the IOS image?
c1900-universalk9-mz.SPA.151-4.M4.bin
15. Why do you think this file is the IOS image? **Because of the bin extension. Binary files are executables**