Die Letzten Folien nit Fragen im Test!



Programming 2

Object-Oriented Programming with Java

Oscar Nierstrasz

```
double size() {
   double total = 0;
   for (Shape shape : shapes) {
      total += shape.size();
   }
   return total;
}
```

P2 — Object-Oriented Programming

Lecturer:	Oscar Nierstrasz
Assistants:	Claudio Corrodi, Pooja Rani Silas Berger, Alvaro Lahiguera, Jonas Richner
www:	scg.unibe.ch/teaching/p2

Roadmap




- > Goals, Schedule
- > What is programming all about?
- > What is Object-Oriented programming?
- > Foundations of OOP
- > Why Java?
- > Programming tools, version control

Roadmap




- > Goals, Schedule
- > What is programming all about?
- > What is Object-Oriented programming?
- > Foundations of OOP
- > Why Java?
- > Programming tools, version control

Your Learning Targets



The Big Picture



Recommended Texts

> Java in Nutshell: 6th edition. David Flanagan, O'Reilly, 2014.



> An Introduction to Object-Oriented Programming, Timothy Budd, Addison-Wesley, 2004.

> Object-Oriented Software Construction, Bertrand Meyer, Prentice Hall, 1997.









- > Design Patterns: Elements of Reusable Object-Oriented Software, Erich Gamma, Richard Helm, Ralph Johnson and John Vlissides, Addison Wesley, Reading, Mass., 1995.
- > The Unified Modeling Language Reference Manual, James Rumbaugh, Ivar Jacobson, Grady Booch, Addison-Wesley, 1999





Schedule

- 1. Introduction
- 2. Object-Oriented Design Principles
- 3. Design by Contract
- 4. A Testing Framework
- 5. Debugging and Tools
- 6. Iterative Development
- 7. Inheritance and Refactoring
- 8. GUI Construction
- 9. Advanced Design Lab
- 10. Guidelines, Idioms and Patterns
- 11. A bit of C++
- 12.A bit of Smalltalk
- 13. Guest Lecture Einblicke in die Praxis


This is a note (a hidden slide). You will find some of these scattered around the PDF versions of the slides.

Plagiarism

Don't copy!

The purpose of exercises is *training*. Copying answers defeats this purpose!

NB: Plagiarism is a serious offense and is not tolerated.



Please consult the U Bern guidelines and regulations: http://www.unibe.ch/universitaet/organisation/rechtliches/rechtssammlung/ reglemente_richtlinien_weisungen_der_universitaetsleitung/ wissenschaftliche_integritaet/index_ger.html

Roadmap



- > Goals, Schedule
- > What is programming all about?
- > What is Object-Oriented programming?
- > Foundations of OOP
- > Why Java?
- > Programming tools, version control

What is the hardest part of programming?



What constitutes programming?

- > Understanding requirements
- > Design
- > Testing
- > Debugging
- > Developing data structures and algorithms
- > User interface design
- > Profiling and optimization
- > Reading code
- > Enforcing coding standards
- > ...


Roadmap



- > Goals, Schedule
- > What is programming all about?
- > What is Object-Oriented programming?
- > Foundations of OOP
- > Why Java?
- > Programming tools, version control

Three views of OO


The <u>Scandinavian</u> view is that an OO system is one whose creators realise that programming is modelling.



The <u>mystical</u> view is that an OO system is built out of objects that send messages to each other, and computation is the messages flying between objects.



The <u>software engineering</u> view is that an OO system is one that supports *data* abstraction, polymorphism by latebinding of function calls, and *inheritance*.



This slightly tongue-in-cheek description was attributed to Ralph Johnson by James Noble in *The Myths of Object-Orientation*. ECOOP 2009.


http://dx.doi.org/10.1007/978-3-642-03013-0 29

http://scgresources.unibe.ch/Literature/P2/Nobl09a-MythsOfOO.pdf

None of these views is "wrong", but each emphasizes different important aspects of OOP:

- The Scandinavian view originates from *Simula* (1960s), a language that uses OO concepts to simulate real world objects. Good OO design reflects this principle as domain encepts are directly modeled (simulated) in your code.
- The "mystical" view originates from *Smalltalk* (1970s), which establishes that the model og objects passing messages offers a universal computational model.
- The SE view (1980) expresses the realization that OOP offers a way to master complexity of very large software systems.

Programming is modeling



Programs are executable models that are used to achieve some effect in the real world. With a good design, the program code reflects clearly the models as we want them to be.

Programming languages offer us a variety of different tools for expressing executable models. If we pick the right tool, the job is easier.

What is Object-Oriented Programming?

Encapsulation

Abstraction & Information Hiding

Composition


Nested Objects

Car Carburetor

Pond Ducks

Distribution of Responsibility

Separation of concerns (e.g., HTML, CSS)




Message Passing

Delegating responsibility

Inheritance

Conceptual hierarchy, polymorphism and reuse



Encapsulation means that related entities are bundled together, for example, a Shape object encapsulates data and related operations for shapes.

Abstraction means that we ignore irrelevant details, for example, we abstract from the details of a Shape object and just use its interface (i.e., its operations).

Information hiding means that we hide (forbid access to) the representation behind an abstraction, for example, you may not directly access the state of a Shape but must access it only through its interface.

These three concepts are closely related, but clearly different.

Composition refers to the fact that we can compose complex objects from simpler ones. A Picture may be composed of many shapes.

Distribution of Responsibility means that we break complex tasks into simpler ones, and handle them at the appropriate level of abstraction, and close to where the relevant knowledge is. If you need to resize a shape object, that task should be handled by the shape itself.

Message Passing refers to the idea that you do not "apply procedures to objects", but that you politely ask them to do something by sending them a message. The object *itself* then decides whether it has a *method* to handle that message.

Inheritance is, simply seen, just a mechanism to share behaviour and state (i.e., methods and instance variables) between a class and its subclasses.


As we shall see, inheritance can be used in object-oriented design for three different, but related purposes:

- 1. Conceptual hierarchy (a Rectangle is a Shape)
- 2. Polymorphism (I can use a rectangle anywhere I expect a shape)
- 3. Reuse (the Rectangle class reuses everything it inherits from Shape)

In a good object-oriented design, all three of these come together.

Procedural versus OO designs

Problem: compute the total area of a set of geometric shapes



How to compute the size?

Procedural approach: centralize computation

```
double size() {
   double total = 0;
   for (Shape shape : shapes) {
       switch (shape.kind()) {
       case SQUARE:
           Square square = (Square) shape;
           total += square.width * square.width;
           break:
       case RECTANGLE:
           Rectangle rectangle = (Rectangle) shape;
           total += rectangle.width * rectangle.height;
           break;
       case CIRCLE:
           Circle circle = (Circle) shape;
           total += java.lang.Math.PI * circle.radius * circle.radius / 2;
           break:
   return total;
```

Here we see a classical procedural design consisting of algorithms and data structures. Squares, Rectangles and Shapes are passive data structures, and algorithms have complete control to manipulate them.

Object-oriented approach: distribute computation


```
double size() {
   double total = 0;
   for (Shape shape : shapes) {
      total += shape.size();
   return total;
                        public class Square extends Shape {
                           public double size() {
                              return width*width;
```

What are the <u>advantages</u> and <u>disadvantages</u> of the two solutions?

In the object-oriented design, the responsibility of computing the size of a shape is distributed to the objects with the necessary knowledge to perform the computation. The resulting design is *fundamentally different*.

There are clear tradeoffs between the two approaches. Although OO design has certain advantages, it is not "better" in absolute terms.

Exercise: what are the tradeoffs?



Roadmap



- > Goals, Schedule
- > What is programming all about?
- > What is Object-Oriented programming?
- > Foundations of OOP
- > Why Java?
- > Programming tools, version control

Object-Oriented Design in a Nutshell

- > Identify *minimal* requirements
- > Make the requirements *testable*
- > Identify objects and their *responsibilities*
- > Implement and *test* objects
- > Refactor to *simplify* design
- > Iterate!



Responsibility-Driven Design



- > Objects are responsible to maintain information and provide services
- > A good design exhibits:
 - —*high cohesion* of operations and data within classes
 - low coupling between classes and subsystems
- > Every method should perform *one, well-defined task:*
 - High level of abstraction write to an interface, not an implementation

Cohesion refers to the notion that related entities should be close together. This is supported by encapsulation mechanisms, like classes and packages. A good design is cohesive, so that when you have to change something or add new features, then the parts to change can be found together.

Coupling refers to the dependencies between parts of a software system, i.e., what parts call each other, use each other, etc. High coupling is bad because if you change something, it will affect many other parts. A good design exhibits low coupling.

Design by Contract

- > Formalize client/server contract as obligations
- > Class invariant formalize valid state
- > Pre- and post-conditions on all public services
 - —clarifies responsibilities
 - -simplifies design
 - -simplifies debugging



Extreme Programming

Some key practices:

- > Simple design
 - —Never anticipate functionality that you "might need later"
- > Test-driven development
 - —Only implement what you test!
- > Refactoring
 - —Aggressively simplify your design as it evolves
- > Pair programming
 - —Improve productivity by programming in pairs



Testing

- > Formalize requirements
- > Know when you are done
- > Simplify debugging
- > Enable changes
- > Document usage



Code Smells

- > Duplicated code
- > Long methods
- > Large classes
- > Public instance variables
- > No comments
- > Useless comments
- > Unreadable code
- > ...



Refactoring

"Refactoring is the process of **rewriting** a computer program or other material to improve its structure or readability, while explicitly **keeping its meaning** or behavior."

wikipedia.org

Common refactoring operations:

- > Rename methods, variables and classes
- > Redistribute responsibilities
- > Factor out helper methods
- > Push methods up or down the hierarchy
- > Extract class
- > ...



Design Patterns

"a general repeatable solution to a commonly-occurring problem in software design."

Example


> Adapter — "adapts one interface for a class into one that a client expects."

Patterns:

- > Document "best practice"
- > Introduce standard vocabulary
- > Ease transition to OO development

But ...

> May increase flexibility at the cost of simplicity



We will see several design patterns during the course, but we'll only look in detail near the end. Most of the design patterns we will see are described in the classic book by the "Gang of Four." An electronic version is available to students of this course.



Roadmap



- > Goals, Schedule
- > What is programming all about?
- > What is Object-Oriented programming?
- > Foundations of OOP
- > Why Java?
- > Programming tools, version control

Why Java?

Special characteristics

- > Resembles C++ minus the complexity
- > Clean integration of many features
- > Dynamically loaded classes
- > Large, standard class library


Simple Object Model

- "Almost everything is an object"
- No pointers
- > Garbage collection
- > Single inheritance; multiple subtyping
- Static and dynamic type-checking

Few innovations, but reasonably clean, simple and usable.



History



Java adopts much of its syntax from C++, to make it appeal to seasoned C++ programmers, but adopts many language features from Smalltalk, such as single inheritance, implementation based on a virtual machine, and automatic garbage collection.

Roadmap



- > Goals, Schedule
- > What is programming all about?
- > What is Object-Oriented programming?
- > Foundations of OOP
- > Why Java?
- > Programming tools, version control

Programming Tools

Know your tools!

- —IDEs (Integrated Development Environment)— e.g., Eclipse
- —Version control system e.g., svn, git
- —Build tools e.g., maven, ant, make
- —Testing framework e.g., Junit
- —Debuggers e.g., jdb
- —Profilers e.g., java -prof, jip
- —Documentation generation e.g., javadoc

Version Control Systems

A <u>version control system</u> keeps track of multiple file revisions:

- > check-in and check-out of files
- > logging changes (who, where, when)
- > merge and comparison of versions
- > retrieval of arbitrary versions
- > "freezing" of versions as releases
- > reduces storage space (manages sources files + multiple "deltas")

Version Control

Version control enables you to make radical changes to a software system, with the assurance that *you can always go back* to the last working version.

- When should you use a version control system?
- ✓ Use it whenever you have one available, for even the smallest project!

Version control is as **important** as **testing** in iterative development!

What you should know!

- √ Substitute of the property of the prope
- ₹ Why do real programs change?
- How does object-oriented programming support incremental development?
- ⁴ [∞] What is a class invariant?
- [™] What are coupling and cohesion?
- b ≈ How do tests enable change?
- ₹ Why are long methods a bad code smell?

1) It means that you can break a problem into simpler smaller ones. Then you can solve those seperated problems individually. 2) Because we need to refactor the code from time to time. And then we see, that maybe our code doesn't nock anymore as me mould 4) "Black box". The object should contain variables that are not visible public. 5) See slide 23.2 6) Tests are showing that something doesn't nork. You have to change what isn't working. 7) You should break long methods into parts.

Can you answer these questions?

- Why does up-front design increase risk?
- Why do objects "send messages" instead of "calling methods"?
- What are good and bad uses of inheritance?
- What does it mean to "violate encapsulation"?
- Why is strong coupling bad for system evolution?
- How can you transform requirements into tests?
- How would you eliminate duplicated code?
- When is the right time to refactor your code?



Attribution-ShareAlike 4.0 International (CC BY-SA 4.0)

You are free to:

Share — copy and redistribute the material in any medium or format

Adapt — remix, transform, and build upon the material for any purpose, even commercially.

The licensor cannot revoke these freedoms as long as you follow the license terms.

Under the following terms:



Attribution — You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.



ShareAlike — If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

No additional restrictions — You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits.

http://creativecommons.org/licenses/by-sa/4.0/