SECURITY, LAYER BY LAYER

# Five things stand between a click and your data.

Three permission checks, strict merge gates and locked brand blocks. Swipe through each one.

1. Proxy
2. Server action
3. Screen
4. Merge gates
5. Locked blocks

STEP 1 OF 5

# The proxy checks the session first.

proxy.ts reads the Better Auth session before an admin page loads. Signed-out visitors never reach it.

1 Proxy

2 Server action

3 Screen

4 Merge gates

5 Locked blocks

STEP 2 OF 5

# Every admin action checks again.

Each admin server action starts with requireAdmin, so a hand-crafted request is refused on the server.

1 Proxy

2 **Server action**

3 Screen

4 Merge gates

5 Locked blocks

STEP 3 OF 5

# The screen only shows what you may use.

Buttons render from the same permission rules the server uses, so the UI never offers a forbidden action.

1 Proxy

2 Server action

3 **Screen**

4 Merge gates

5 Locked blocks

STEP 4 OF 5

# No change merges until every check passes.

Types, lint, unit, integration, browser and accessibility tests run on every pull request. Red never merges.

1 Proxy

2 Server action

3 Screen

4 **Merge gates**

5 Locked blocks

STEP 5 OF 5

# Brand blocks stay locked.

The email header and footer cannot be edited by campaign authors, and every saved change keeps its history.

1. Proxy
2. Server action
3. Screen
4. Merge gates
5. **Locked blocks**

LET'S TALK

# Hiring for a build like this?

The case study walks through the architecture, the tests and the trade-offs behind every decision.

Scan to read

CASE STUDY

**momo-audio.adudev.co.uk**

/docs/case-study-email-platform

**Open to roles and contract work. Scan the code or email me.**

**admin@adudev.co.uk**