

Loop Transformations for Parallelism & Locality

Last week

- Data dependences and loops
- Loop transformations
 - (Parallelization)
 - Scalar expansion
- Value data dependences

Today and Monday

- Loop transformations and transformation frameworks
 - Loop reversal
 - Loop fusion
 - Loop fission
 - Loop interchange
 - Unroll and Jam

Review

Distance vectors

- Concisely represent dependences in loops (*i.e.*, in iteration spaces)
- Dictate what transformations are legal
 - *e.g.*, Permutation and parallelization

Legality

- A dependence vector is **legal** when it is lexicographically nonnegative

Loop-carried dependence


- A dependence $D=(d_1, \dots, d_n)$ is **carried** at loop level i if d_i is the first nonzero element of D

Loop Permutation

Idea


- Swap the order of two loops to increase parallelism, to improve spatial locality, or to enable other transformations
- Also known as **loop interchange**

Example

<pre>do i = 1,n do j = 1,n x = A(2,j) enddo enddo</pre>		<pre>do j = 1,n do i = 1,n x = A(2,j) enddo enddo</pre>
<p>This access strides through a row of A</p>		<p>This code is invariant with respect to the inner loop, yielding better locality</p>

Loop Interchange (cont)

Example

<pre>do i = 1,n do j = 1,n x = A(i,j) enddo enddo</pre>		<pre>do j = 1,n do i = 1,n x = A(i,j) enddo enddo</pre>
<p>This array has stride n access</p>		<p>This array now has stride 1 access</p>

(Assuming column-major order for Fortran)

Legality of Loop Interchange

Case analysis of the direction vectors

(=,=)

The dependence is loop independent, so it is unaffected by interchange

(=,<)

The dependence is carried by the j loop.

After interchange the dependence will be (<=), so the dependence will still be carried by the j loop, so the dependence relations do not change.

(<=)

The dependence is carried by the i loop.

After interchange the dependence will be (=,<), so the dependence will still be carried by the i loop, so the dependence relations do not change.

Legality of Loop Interchange (cont)

Case analysis of the direction vectors (cont.)

(<,<)

The dependence distance is positive in both dimensions.

After interchange it will still be positive in both dimensions, so the dependence relations do not change.

(<,>)

The dependence is carried by the outer loop.

After interchange the dependence will be (>,<), which changes the dependences and results in an illegal direction vector, so interchange is illegal.

(>,*) (=,>)


Such direction vectors are not possible for the original loop.

Loop Interchange Example

Consider the ($<, >$) case

```

do i = 1,n
  do j = 1,n
    C(i,j) = C(i+1,j-1)
  enddo
enddo
  
```



```

do j = 1,n
  do i = 1,n
    C(i,j) = C(i+1,j-1)
  enddo
enddo
  
```

Before

(1,1) C(1,1) = C(2,0)
 (1,2) C(1,2) = C(2,1)
 ...
 (2,1) C(2,1) = C(3,0)

↙ $d = (<, >) \delta^a$

After

(1,1) C(1,1) = C(2,0)
 (2,1) C(2,1) = C(3,0)
 ...
 (1,2) C(1,2) = C(2,1)

↘ $d = (>, <) \delta^f$

Frameworks for Loop Transformations

Unimodular Loop Transformations [Banerjee 90],[Wolf & Lam 91]

- can represent loop permutation, loop reversal, and loop skewing
- unimodular linear mapping (determinant of matrix is + or - 1)
 - $T i = i'$, T is a matrix, i and i' are iteration vectors

$$\begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} i_1 \\ i_2 \end{bmatrix} = \begin{bmatrix} i'_1 \\ i'_2 \end{bmatrix}$$

- transformation is legal if the transformed dependence vector remain lexicographically positive
- limitations
 - only perfectly nested loops
 - all statements are transformed the same

Legality of Loop Interchange, Reprise

Reduced case analysis of the direction vectors $\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} = \begin{bmatrix} j \\ i \end{bmatrix}$

(=,=)

The dependence is loop independent, so it is unaffected by interchange

$$\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} 0 \\ 0 \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$$

(=,<)

The dependence is carried by the j loop.

After interchange the dependence will be (<,<), so the dependence will still be carried by the j loop, so the dependence relations do not change.

$$\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} 0 \\ < \end{bmatrix} = \begin{bmatrix} < \\ 0 \end{bmatrix}$$

(<,>)

The dependence is carried by the outer loop.

After interchange the dependence will be (>,<), which changes the dependences and results in an illegal direction vector, so interchange is illegal.

$$\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} \begin{bmatrix} < \\ > \end{bmatrix} = \begin{bmatrix} > \\ < \end{bmatrix}$$

CS553 Lecture

Loop Transformations

10

Loop Reversal

Idea


- Change the direction of loop iteration
(i.e., From low-to-high indices to high-to-low indices or vice versa)

Benefits

- Improved cache performance
- Enables other transformations (coming soon)

Example

```
do i = 6,1,-1
  A(i) = B(i) + C(i)
enddo
```



```
do i = 1,6
  A(i) = B(i) + C(i)
enddo
```

CS553 Lecture

Loop Transformations

11

Loop Reversal and Distance Vectors

Impact

- Reversal of loop i negates the i^{th} entry of all distance vectors associated with the loop
- What about direction vectors?

When is reversal legal?

- When the loop being reversed does not carry a dependence
(i.e., When the transformed distance vectors remain legal)

Example

```
do i = 1,5
  do j = 1,6
    A(i,j) = A(i-1,j-1)+1
  enddo
enddo
```

$$\begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} = \begin{bmatrix} i \\ -j \end{bmatrix}$$

Dependence: Flow
Distance Vector: (1,1)
Transformed
Distance Vector: (1,-1) **legal**

Loop Reversal Example

Legality

- Loop reversal will change the direction of the dependence relation

Is the following legal?

```
do i = 1,6
  A(i) = A(i-1)
enddo
```

Dependence: Flow
Distance Vector: (1)




```
do i = 6,1,-1
  A(i) = A(i-1)
enddo
```

Dependence: Anti Flow
Distance Vector: (1) (-1)

Loop Skewing

Original code

```
do i = 1,6
  do j = 1,5
    A(i,j) = A(i-1,j+1)+1
  enddo
enddo
```




Distance vector: (1, -1)

Can we permute the original loop?

Skewing:


$$\begin{bmatrix} 1 & 0 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} = \begin{bmatrix} i \\ i+j \end{bmatrix}$$



Transforming the Dependences and Array Accesses

Original code

```
do i = 1,6
  do j = 1,5
    A(i,j) = A(i-1,j+1)+1
  enddo
enddo
```



Dependence vector:

$$\begin{bmatrix} 1 & 0 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} 1 \\ -1 \end{bmatrix} = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$$


New Array Accesses:

$$A\left(\begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \end{bmatrix}, \begin{bmatrix} 0 & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \end{bmatrix}\right) = A(i, j)$$

$$A\left(\begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ -1 & 1 \end{bmatrix} \begin{bmatrix} i' \\ j' \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \end{bmatrix}, \begin{bmatrix} 0 & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ -1 & 1 \end{bmatrix} \begin{bmatrix} i' \\ j' \end{bmatrix} + \begin{bmatrix} 0 \\ 0 \end{bmatrix}\right) = A(i', j' - i')$$

$$A\left(\begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} + \begin{bmatrix} -1 \\ 0 \end{bmatrix}, \begin{bmatrix} 0 & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} + \begin{bmatrix} 0 \\ 1 \end{bmatrix}\right) = A(i-1, j+1)$$


$$A\left(\begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ -1 & 1 \end{bmatrix} \begin{bmatrix} i' \\ j' \end{bmatrix} + \begin{bmatrix} -1 \\ 0 \end{bmatrix}, \begin{bmatrix} 0 & 0 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} 1 & 0 \\ -1 & 1 \end{bmatrix} \begin{bmatrix} i' \\ j' \end{bmatrix} + \begin{bmatrix} 0 \\ 1 \end{bmatrix}\right) = A(i'-1, j'-i'+1)$$



Transforming the Loop Bounds

Original code

```
do i = 1, 6
  do j = 1, 5
    A(i, j) = A(i-1, j+1) + 1
  enddo
enddo
```



Bounds:

$$\begin{bmatrix} -1 & 0 \\ 1 & 0 \\ 0 & -1 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} \leq \begin{bmatrix} -1 \\ 6 \\ -1 \\ 5 \end{bmatrix}$$


$$\begin{bmatrix} -1 & 0 \\ 1 & 0 \\ 0 & -1 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} \leq \begin{bmatrix} -1 \\ 6 \\ -1 \\ 5 \end{bmatrix}$$

$$\begin{bmatrix} -1 & 0 \\ 1 & 0 \\ 0 & -1 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} \leq \begin{bmatrix} -1 \\ 6 \\ -1 \\ 5 \end{bmatrix}$$

$$\begin{bmatrix} -1 & 0 \\ 1 & 0 \\ 0 & -1 \\ 0 & 1 \end{bmatrix} \begin{bmatrix} i \\ j \end{bmatrix} \leq \begin{bmatrix} -1 \\ 6 \\ -1 \\ 5 \end{bmatrix}$$

Transformed code

```
do i' = 1, 6
  do j' = 1+i', 5+i'
    A(i', j'-i') = A(i'-1, j'-i'+1) + 1
  enddo
enddo
```



CS553 Lecture

Loop Transformations

16

Loop Fusion

Idea

- Combine multiple loop nests into one

Example

```
do i = 1, n
  A(i) = A(i-1)
enddo
do j = 1, n
  B(j) = A(j) / 2
enddo
```



```
do i = 1, n
  A(i) = A(i-1)
  B(i) = A(i) / 2
enddo
```

Pros

- May improve data locality
- Reduces loop overhead
- Enables **array contraction** (opposite of scalar expansion)
- May enable better instruction scheduling

Cons

- May hurt data locality
- May hurt icache performance

CS553 Lecture

Loop Transformations


17

Legality of Loop Fusion

Basic Conditions

- Both loops must have same structure
 - Same loop depth
 - Same loop bounds
 - Same iteration directions
 - Dependences must be preserved

e.g., Flow dependences must not become anti dependences
- Can we relax any of these restrictions?



CS553 Lecture

Loop Transformations

18

Loop Fusion Example

What are the dependences?

```

do i = 1, n
s1   A(i) = B(i) + 1
enddo
do i = 1, n
s2   C(i) = A(i) / 2
enddo
do i = 1, n
s3   D(i) = 1/C(i+1)
enddo
  
```

Dependence arrows: $s_1 \delta^f s_2$ (from A(i) to C(i)), $s_2 \delta^f s_3$ (from C(i) to D(i+1)).

What are the dependences?

```

do i = 1, n
s1   A(i) = B(i) + 1
s2   C(i) = A(i) / 2
s3   D(i) = 1/C(i+1)
enddo
  
```

Dependence arrows: $s_1 \delta^f s_2$ (from A(i) to C(i)), $s_3 \delta^a s_2$ (from C(i+1) to C(i)).

Fusion changes the dependence between s_2 and s_3 , so fusion is illegal

Is there some transformation that will enable fusion of these loops?

CS553 Lecture


Loop Transformations

19

Loop Fusion Example (cont)

Loop reversal is legal for the original loops

- Does not change the direction of any dep in the original code
- Will reverse the direction in the fused loop: $s_3 \delta^a s_2$ will become $s_2 \delta^f s_3$



CS553 Lecture

Loop Transformations

20

Concepts

Using direction and distance vectors

Transformations:

- What is the benefit?
- What do they enable?
- When are they legal?

Unimodular transformation framework

- represents loop permutation, loop reversal, and loop skewing
- provides mathematical framework for ...
 - testing transformation legality,
 - transforming array accesses and loop bounds*,
 - and combining transformations

* The example did not require Fourier Motzkin elimination.

CS553 Lecture

Loop Transformations

21

Next Time

Lecture

- More loop transformations
- An even cooler transformation framework