

# Deep Reinforcement Learning for the Interval Job Shop Scheduling Problem: A Comparison with Genetic Programming Hyper-Heuristics across Inference Budgets

Hernán Díaz Rodríguez<sup>1\*</sup>

<sup>1\*</sup>Department of Computing, University of Oviedo, Gijón, Spain.

Corresponding author(s). E-mail(s): [diazhernan@uniovi.es](mailto:diazhernan@uniovi.es);

## Abstract

The interval job shop scheduling problem (IJSP) retains only the support bounds of uncertain processing times and is solved in the literature by per-instance meta-heuristic search. This paper presents the first constructive deep reinforcement learning policy for the problem: dimensionless state features and a permutation-invariant encoder make one parameter set of  $\sim 1.2 \times 10^5$  weights applicable to any instance size. Trained with proximal policy optimization on four  $20 \times 15$  Taillard instances, the policy improves on every hand-crafted dispatching rule on all seventy benchmark instances, six of the seven size classes unseen. It is then compared against a dispatching rule evolved by genetic programming for the same benchmark, thirty trained artifacts per family evaluated in one harness, the comparison between the two learned constructive families that the literature lacks. The two separate at every inference budget and the ordering is set by that budget: the rule leads by **0.8** points of relative error given one constructive pass each, and the policy leads by the same margin once both draw samples. The paradigms also differ in where they handle the uncertainty. Under the lexicographic ranking standard in the field the worst-case makespan depends on the upper duration endpoints alone, so interval widths cannot inform decisions judged by it, and removing them from the policy costs nothing measurable; an objective that charges for the predicted width narrows the policy's schedules through sample selection, its weights unmoved, where the same objective acts through the evolved representation.

**Keywords:** job shop scheduling, interval uncertainty, deep reinforcement learning, neural combinatorial optimization, genetic programming hyper-heuristics, size invariance, dispatching

# 1 Introduction

The job shop scheduling problem (JSP) asks for a sequencing of a set of jobs, each of which visits the machines of a shop in its own prescribed order, that minimizes the overall completion time. The problem lies at the core of manufacturing operations planning: NP-hard (Garey, Johnson, & Sethi, 1976) and industrially ubiquitous, it is studied predominantly under the assumption that every processing time is known exactly. Real production environments seldom satisfy that assumption: schedules are committed before the work they plan is executed, and the processing times they assume are no more than estimates, displaced in practice by tool wear, operator variability and material differences. Among the formalisms proposed for this uncertainty, stochastic and fuzzy models (González-Rodríguez, Vela, & Puente, 2010) require the decision maker to supply probability distributions or membership functions; the *interval* model requires only bounds. In the resulting interval JSP (IJSP), each duration is a closed interval, schedule evaluation propagates those intervals, and the makespan is itself an interval, compared through a ranking criterion (Díaz, Palacios, González-Rodríguez, & Vela, 2023a; Lei, 2011).

The state of the art in IJSP makespan minimization is currently held by per-instance metaheuristic search: elitist artificial bee colony algorithms (Díaz et al., 2023a; Díaz, Palacios, González-Rodríguez, & Vela, 2023b) reach mean relative errors (RE, measured against crisp Taillard lower bounds) between roughly 6% and 16% depending on the size class. This cost is structural: the search must be repeated for every new instance, at seconds to minutes per run on dedicated hardware.

At the opposite end of the computational spectrum lie *constructive* methods, which build a schedule in a single pass without search. The classical representatives are priority dispatching rules, myopic functions such as shortest processing time or most operations remaining (Haupt, 1989; Panwalkar & Iskander, 1977), which are fast and interpretable but leave a wide quality gap on the IJSP. Genetic programming (GP) hyper-heuristics narrow that gap by evolving dispatching rules offline from a training set (Branke, Nguyen, Pickardt, & Zhang, 2016; Nguyen, Mei, & Zhang, 2017); a rule recently evolved for the interval benchmark studied here (Díaz Rodríguez, 2026b) constitutes the strongest constructive baseline available. Both families deliver schedules at negligible per-instance cost, which makes them the natural referents and competitors for a learned policy.

The deterministic scheduling literature has developed a third constructive approach, *learning to dispatch*: a deep reinforcement learning (DRL) agent builds the schedule constructively, choosing one eligible operation at a time (Park, Chun, Kim, Kim, & Park, 2021; Tassel, Gebser, & Schekotihin, 2021; Zhang et al., 2020). The training cost is incurred once; thereafter the policy returns a schedule for a new instance in seconds, which makes it attractive both as a standalone solver under tight time budgets and as an initializer for search. This paradigm has not, however, been extended to interval durations: a recent survey of learning-based job shop scheduling (Xu, Mei, Zhang, & Zhang, 2025) lists no method addressing interval-valued processing times.

Two obstacles separate standard JSP-DRL designs from the IJSP. The first is representational: the natural assumption, and the one this line of work has operated under, is that the uncertainty must be observable to the agent, which should treat an

operation with duration  $[10, 11]$  differently from one with duration  $[5, 16]$  even though both share the same midpoint. The second is architectural: the amortization argument that motivates learning requires one network to serve instances of any size. Designs that encode the instance as a fixed-dimension tensor are tied to the size class they were trained on, and graph-based encoders achieve size transfer (Park et al., 2021; Zhang et al., 2020) through message passing over the full disjunctive graph; whether the same invariance can be obtained with a substantially simpler encoder is a design question this paper answers in the affirmative.

This paper builds the policy those obstacles call for and uses it to compare the two families of learned constructive heuristic on the same ground. *Q1*: which of the two produces the better schedules for the IJSP, and does the answer hold across inference budgets, instance sizes and shop families? *Q2*: where in each paradigm does the handling of the uncertainty live, that is, which uses of the interval information are load-bearing for a policy and which are inert, and at what stage of each method does an objective that values robustness act? *Q3*: what does either learner buy over the hand-crafted rules it replaces, and where do both stand relative to the per-instance metaheuristic state of the art?

### ***Contributions.***

1. *The first size-invariant constructive DRL policy for the IJSP* (Section 4). All features are dimensionless: temporal quantities are scaled by a per-instance lower bound and interval uncertainty enters as relative widths. A Deep Sets (Zaheer et al., 2017) encoder over the eligible-operation set, combined with a pooled global context, yields policy and value networks of  $\approx 1.2 \times 10^5$  parameters, independent of the numbers of jobs and machines.
2. *A head-to-head comparison of the two learned constructive paradigms under a shared protocol* (Sections 6.2 and 6.3), whose absence from the literature the survey of Xu et al. (2025) highlights. Thirty evolved rules against thirty trained policies, on the 70 benchmark instances and on twelve classical ones, run in a single harness that fixes the instances, the interval arithmetic, the ranking criterion, the inference budgets and the execution realizations, with per-instance results reported in full (supplementary material). The two separate at every budget and the ordering is set by it.
3. *A localization of where each paradigm handles the uncertainty* (Section 7.3), in three parts. An analytic argument: under the lexicographic criterion the worst-case makespan is a function of the upper duration endpoints alone, so interval widths cannot inform the decisions of any method ranked by it, whatever the model class. Its causal verification on the trained policy: a permutation audit and two retraining ablations that separate the widths as inputs, which are inert, from the intervals as training data, which are not. And the contrast that follows: a width-penalizing objective acts through sample selection in the policy, with the weights unmoved, and through the evolved representation in the GP study (Díaz Rodríguez, 2026b).
4. *An account of which standard components earn their cost* (Section 7): best-of- $N$  inference does, self-attention and three automatic-configuration campaigns do

not, and under Monte Carlo execution the learned schedules track their predicted makespans more faithfully than those of every hand-crafted rule.

Section 2 reviews related work and Section 3 states the problem. Section 4 presents the policy, Section 5 the experimental methodology and Section 6 the results; Section 7 analyses them and states the limitations, and Section 8 concludes.

## 2 Related Work

### 2.1 Job shop scheduling under interval uncertainty

Uncertain processing times have been modeled with probability distributions, fuzzy numbers and intervals. The fuzzy line is the most mature: durations are represented as fuzzy numbers, schedules are compared through the expected value of their fuzzy makespan, and two decades of population-based solvers have consolidated both the model and its evaluation conventions (Abdullah & Abdolrazzaghi-Nezhad, 2014; González-Rodríguez et al., 2010; Palacios, González-Rodríguez, Vela, & Puente, 2015). The interval model can be read as the minimal-commitment limit of that representation: it retains only the support bounds, asks the decision maker for no shape information inside them, and is the standard minimal description of uncertainty in robust discrete optimization at large, where it underpins min-max and min-max-regret formulations (Kasperski & Zieliński, 2016; Kouvelis & Yu, 1997). Lei (2011) opened the interval JSP line, propagating interval durations through the schedule with interval arithmetic and steering a population-based neighborhood search by direct comparison of interval makespans. Later work broadened both the model and its toolkit. Díaz, González-Rodríguez, Palacios, Díaz, and Vela (2020) compared the candidate interval rankings systematically within a genetic algorithm and identified the lexicographic criterion adopted in this paper as the most robust choice for the problem; Díaz, Palacios, Díaz, Vela, and González-Rodríguez (2022) shifted the objective to total tardiness and paired it with explicit robustness measures; Sotskov, Matsveichuk, and Hatsura (2020) delimited analytically solvable special cases; and Zheng, Xiao, Zhang, and Lv (2024) carried interval durations into richer shop variants. On the Taillard-derived benchmark used here, the strongest published makespan results belong to the elitist artificial bee colony family (Díaz et al., 2023a, 2023b), whose successive refinements, elitist replacement and neighborhood filtering among them, progressively reduced the mean relative error to the single digits on most size classes; these works also fixed the evaluation conventions this paper adopts (interval arithmetic, lexicographic ranking during construction, expected makespan for reporting). Common to the whole line is per-instance search; fast constructive alternatives for the IJSP have begun to be explored only recently, through the evolved rule discussed in Section 2.3.

### 2.2 Priority dispatching rules

The oldest constructive approach to the job shop builds a schedule in a single left-to-right pass, repeatedly choosing which of the eligible operations to place next. A *priority dispatching rule* makes that choice by scoring the candidates with a fixed

formula over their attributes. The rules this paper uses as baselines and as verification anchors are the classical single-attribute ones, retained here with their usual acronyms. Two look at the operation itself: *shortest* and *longest processing time* (SPT, LPT) prefer the smallest and the largest duration. One looks at the schedule built so far: *earliest starting time* (EST) prefers the operation that could begin soonest given the current occupation of its machine and the progress of its job. Two look at the job the operation belongs to: *most work remaining* and *most operations remaining* (MWKR, MOR) prefer the job with the most pending work, counted in time units and in operations respectively. Under interval durations these attributes are intervals themselves, and candidates are compared with the interval ranking introduced in Section 3. Surveys catalogue well over a hundred variants of such rules (Haupt, 1989; Panwalkar & Iskander, 1977) and recent ones revisit those still in use (Đurašević & Jakobović, 2018).

A refinement worth separating from the rules themselves is the active-schedule generator of Giffler and Thompson (1960), which at each step restricts the candidates to the conflict set of the machine that would finish earliest, and applies a priority rule only to break ties within that set. The restriction guarantees *active* schedules, in which no operation can be started earlier without delaying another, and improves markedly on the plain rules: on the benchmark used here it takes MWKR from 64.7% to 29.5% of RE. We write G&T-SPT and G&T-MWKR for the two combinations used here.

These rules require one pass and no search, which makes them the cheapest constructive option available. Their limitation is that a fixed formula cannot suit every shop and objective (Haupt, 1989), which motivates the learned alternatives of Sections 2.3 and 2.4, and is also why a constructive policy is compared against these rules and not against per-instance metaheuristics, which belong to a different computational class.

### 2.3 Genetic programming hyper-heuristics

Learning constructive heuristics is older than its neural incarnation. Genetic programming hyper-heuristics evolve priority expressions, trees over hand-crafted attributes such as processing time or work remaining, offline on a training set, and deploy the best expression as an ordinary dispatching rule: the artifact is interpretable and its inference cost is that of evaluating a formula. Design choices (attribute sets, fitness, generalization across instances) are reviewed by Branke et al. (2016), and Nguyen et al. (2017) organize the broader family under a unified framework. For the job shop specifically, Nguyen, Zhang, Johnston, and Tan (2013) showed that the choice of rule representation materially shapes the quality of the evolved dispatchers, and Karunakaran, Mei, Chen, and Zhang (2016) evolved rules for dynamic job shops with uncertain processing times, exposing duration deviations to the rules as attributes, under an uncertainty model that is, once again, distributional rather than interval-valued. A recent study (Díaz Rodríguez, 2026b) develops the GP side for the interval benchmark used here, evolving interval-aware rules under the same ranking and evaluation conventions, with both a deterministic pass and a sampling variant.

## 2.4 Neural constructive policies for scheduling

Neural combinatorial optimization began with pointer networks (Vinyals, Fortunato, & Jaitly, 2015), sequence models that emit a permutation of their input and can therefore represent tours and schedules; Bello, Pham, Le, Norouzi, and Bengio (2016) trained them with policy gradients, removing the need for supervised targets, and attention-based encoder–decoders trained against greedy-rollout baselines then became the standard for routing (Kool, van Hoof, & Welling, 2019; Nazari, Oroojlooy, Snyder, & Takáč, 2018). Reinforcement learning for job-shop dispatching predates the deep era: Gabel and Riedmiller (2008) already learned decentralized dispatching policies by gradient ascent. Its modern applications to machine scheduling are surveyed by Kayhan and Yildiz (2023). For the deterministic JSP the reference design is that of Zhang et al. (2020): the partial schedule is encoded as a disjunctive graph, a graph neural network embeds it, and the policy trained by PPO on small synthetic instances generalizes zero-shot to larger ones while surpassing the classical priority rules. Park et al. (2021) refine that representation and document the cross-size generalization explicitly, and Tassel et al. (2021) show that the environment formulation itself (state design and reward shaping) accounts for a substantial share of the attainable performance. The paradigm has since expanded along three axes: to richer shops, with heterogeneous-graph policies for the flexible JSP (Song, Chen, Li, & Cao, 2023); from construction to improvement, with DRL-guided local search over complete schedules (Zhang, Cao, Song, Wu, & Zhang, 2024); and toward uncertainty. On that third axis, Grumbach, Müller, Reusch, and Trojahn (2024) size slack buffers in stochastic flow shops under a distributional, event-driven model; Smit, Wu, Troubil, Zhang, and Nuijten (2024) extend constructive policies to stochastic processing times by processing sampled duration scenarios with an attention module; and Wang, Guo, and Liu (2025) train an autoregressive generative model for the fuzzy job shop. The interval representation, the minimal of these uncertainty models, remains unaddressed by this literature, which is the gap the present paper fills.

Two further components of the toolbox matter here. Sampling several rollouts at inference and keeping the best is a standard quality lever whose returns grow with the diversity of the learned distribution (Kool et al., 2019; Kwon et al., 2020). Permutation-invariant set encoders were formalized as Deep Sets (Zaheer et al., 2017), of which self-attention is the natural strict generalization; the architecture of Section 4.3 builds on the former and evaluates the latter as a controlled ablation.

The survey by Xu et al. (2025) compares the GP and RL families for job shop scheduling and notes the scarcity of comparisons under a common protocol. The availability of the evolved rule of Section 2.3 on the very benchmark studied here lets Section 6.2 put the two learned artifacts on the same instances at matched *inference* budgets.

## 3 Problem Statement

**Definition 1** (IJSP) An IJSP instance comprises  $n$  jobs  $J_1, \dots, J_n$  and  $m$  machines, indexed  $1, \dots, m$ . Job  $J_j$  is a fixed sequence of  $m$  operations  $(o_{j1}, \dots, o_{jm})$ , where operation  $o_{jk}$  requires machine  $\nu_{jk} \in \{1, \dots, m\}$  and an uncertain processing time known only to lie in the

interval  $\mathbf{p}_{jk} = [p_{jk}^L, p_{jk}^U]$ , with  $0 \leq p_{jk}^L \leq p_{jk}^U$ . Each job visits each machine exactly once, so  $(\nu_{j1}, \dots, \nu_{jm})$  is a permutation of the machine indices. Each machine processes at most one operation at a time, operations of the same job cannot overlap, and preemption is not allowed.

A solution is a processing order of all  $nm$  operations, that is, a sequence in which  $o_{jk}$  appears before  $o_{j,k+1}$  for every job  $j$  and every  $k < m$ . We encode it as a *permutation with repetition* of job indices, where the  $k$ -th occurrence of  $j$  denotes  $o_{jk}$ . The order induces, on each machine, a sequence over the operations that require it, and its *semiactive schedule* starts every operation as early as those sequences permit: no operation can start before its job predecessor  $JP(o_{jk}) = o_{j,k-1}$  or its machine predecessor  $MP(o_{jk})$ , the operation immediately preceding  $o_{jk}$  on machine  $\nu_{jk}$  in the induced sequence, have completed. With component-wise interval addition  $[a, b] + [c, d] = [a + c, b + d]$  and join  $\max([a, b], [c, d]) = [\max(a, c), \max(b, d)]$ , the start and completion times of every operation are themselves intervals, given by the recursion

$$\mathbf{s}_o = \max(\mathbf{c}_{JP(o)}, \mathbf{c}_{MP(o)}), \quad \mathbf{c}_o = \mathbf{s}_o + \mathbf{p}_o, \quad (1)$$

When a predecessor does not exist (the job predecessor of a job's first operation, or the machine predecessor of the first operation scheduled on a machine), its completion is taken as  $[0, 0]$ , so that the corresponding argument is neutral in the max and the start is decided by the predecessor that does exist. The interval makespan collects the job completions component-wise,

$$\mathbf{C}_{\max} = \left[ \max_j c_{o_{jm}}^L, \max_j c_{o_{jm}}^U \right] =: [C_{\max}^L, C_{\max}^U]. \quad (2)$$

A *realization* of the instance assigns to each operation a crisp duration  $p_{jk} \in \mathbf{p}_{jk}$ ; *executing* a processing order under a realization means evaluating the recursion of Eq. (1) with those crisp durations, which yields a crisp makespan. Because the recursion is monotone in the durations, the executed makespan of *every* realization falls inside  $\mathbf{C}_{\max}$ . Intervals carry no canonical total order, so schedule comparison requires a ranking choice; during construction and search we use the lexicographic order

$$\mathbf{a} \prec_{lex} \mathbf{b} \iff a^U < b^U \vee (a^U = b^U \wedge a^L < b^L) \quad (3)$$

for intervals  $\mathbf{a} = [a^L, a^U]$  and  $\mathbf{b} = [b^L, b^U]$ , which prioritizes the worst case, in line with min-max robust optimization (Bertsimas & Sim, 2004; Kasperski & Zieliński, 2016). The optimization problem is then to find a processing order whose interval makespan is minimal under this order. This modeling choice is not reopened here: a systematic study of the alternative ranking criteria found the lexicographic order the most robust for this problem (Díaz et al., 2020), and it is kept fixed throughout so that every method in this paper is judged by the same criterion. For reporting we follow the field convention (Díaz et al., 2020, 2023a):

$$\text{RE}(\%) = \frac{E[\mathbf{C}_{\max}] - \text{LB}}{\text{LB}} \times 100, \quad E[\mathbf{C}_{\max}] = \frac{1}{2}(C_{\max}^L + C_{\max}^U), \quad (4)$$



with LB the published lower bound of the crisp Taillard counterpart (Taillard, 1993), an indicative, hardware-independent yardstick rather than a strict optimality gap, since the crisp JSP and the IJSP are different problems.

*Remark 1* For instances whose intervals are symmetric perturbations of a crisp instance, the midpoint scenario coincides with the original crisp durations; comparisons under Eq. (4) are therefore scenario-consistent (midpoint solution quality against the midpoint-scenario bound).

## 4 Method

Reinforcement learning is learning to decide from experience. An *agent* interacts with an environment in steps: it observes the current *state*  $s$ , chooses an *action*  $a$  among those available, and receives a numeric *reward* signalling how good the consequences were. The agent’s behavior is its *policy*  $\pi(a | s)$ : a function that, given the state  $s$ , assigns a probability to each available action  $a$ . The policy is the object of learning: training increases the probability of actions followed by a high cumulative reward (the *return*).


Policy-gradient methods such as PPO (Schulman, Wolski, Dhariwal, Radford, & Klimov, 2017) judge an action not by its return alone but by comparing that return with what was *expected* from the state where the action was taken; only the surplus, the *advantage*, moves the policy. The expectation is itself learned: a *value function*  $V(s)$  estimates the return attainable from state  $s$ . In practice both functions share one network with two outputs, a *policy head* that scores the available actions and a *value head* that estimates  $V(s)$ , trained jointly. This is why the network in this paper has two heads.

Instantiated on scheduling, the agent is a dispatcher and schedule construction is a finite-horizon *Markov decision process* of exactly  $nm$  steps, one per operation. The state after  $t$  steps is the partial schedule (each job’s next-operation pointer, the job and machine completion intervals), a sufficient statistic for the remaining decisions; the available actions are the *eligible* operations, that is, the next unscheduled operation of each job, collected in the set  $\mathcal{E}_t$  with  $1 \leq |\mathcal{E}_t| \leq n$  and written  $\mathcal{E}$  when the step is immaterial. The generic  $\pi(a | s)$  thus specializes to  $\pi(i | s)$ , a distribution over which eligible operation  $i$  to schedule next; the transition applies Eq. (1) deterministically; an *episode* is the construction of one complete schedule, and the reward is a function of the makespan achieved. The trained policy is then a dispatching criterion in its own right: at each step it orders the eligible operations by preferences learned from experience rather than by a fixed, hand-written formula.

Figure 1 shows the network, read from the input at the top down to the two outputs. Each eligible operation enters as a row of 16 numbers that describe it: how long it may take, how much work its job still carries, how soon it could start (Section 4.2). A multilayer perceptron (MLP), the *same* one for every candidate, turns each row into an *embedding*: a vector of  $h$  learned quantities that re-describe the candidate.

The number of candidates varies from step to step, so the embeddings are *pooled*: their mean and their componentwise maximum are two fixed-size summaries of the





**Fig. 1** The size-invariant policy/value network. Solid edges are the base model’s data path; the grey dashed edge is the per-candidate skip connection; the dashed detour is the self-attention variant reported in the supplementary material, not part of the base model ( $B=0$ ).

whole set. Joined with 12 numbers describing the shop as a whole (the *global state*), these summaries are condensed by another MLP into a single *context* vector  $g$ , a fixed-size summary of the current decision state.

The two heads introduced above read from this context. Pooling, however, discards by design which candidate is which, so the context alone cannot rank them. The policy head therefore receives two inputs, the shared context  $g$  and each candidate’s own embedding, carried past the pooling stage by the *skip connection* visible in Figure 1. The head is applied once per candidate: for eligible operation  $i$  it reads the pair (embedding of  $i$ , context) and outputs a single scalar score, so  $|E|$  candidates yield  $|E|$  scores, each tied to its operation by construction because it was computed from that operation’s embedding. A *softmax* over these scores (the *logits*, in network terms) turns them into the probabilities  $\pi(i | s)$ , one per eligible operation, however many there are (*masked* means that unused padding slots are excluded). The value head estimates the situation rather than any one candidate, so it reads  $g$  alone and outputs  $V(s)$ . In total, four two-layer MLPs (the candidate encoder  $\phi$ , the context combiner, and the two heads) are composed into a single network and trained jointly end to end.

The dashed detour between the embeddings and the pooling is an *optional* self-attention stage, evaluated as a variant in the supplementary material; the base model, which every headline result of this paper uses, omits it.

Sections 4.1–4.3 specify, in order, the reward, the 16+12 input quantities, and the network stages. Training and inference are described with the experimental setting in Section 5.4.

## 4.1 The reward

The *reward* at step  $t$  is a weighted sum of six shaping components,

$$r_t = w_{\text{mk}} r_t^{\text{mk}} + w_{\text{pr}} r_t^{\text{pr}} + w_{\text{id}} r_t^{\text{id}} + w_{\text{li}} r_t^{\text{li}} + w_{\text{cr}} r_t^{\text{cr}} + w_{\text{ba}} r_t^{\text{ba}}, \quad (5)$$

where each  $r_t^\bullet$  is one shaping component and  $w_\bullet \in [0, 1]$  its fixed weight: terminal makespan (mk), job progress (pr), machine idleness (id), local improvement (li), operation criticality (cr) and load balance (ba), each defined below.

Each component is divided by a magnitude of the instance, listed with it, which makes the reward dimensionless and comparable across instances and sizes. Several scales use  $\widehat{\text{LB}}$ , a lower bound on the makespan that the method computes from the instance itself as the larger of the two classical relaxations, the most loaded machine and the longest job, in worst-case durations:

$$\widehat{\text{LB}} = \max \left( \max_{\mu} \sum_{(j,k): \nu_{jk}=\mu} p_{jk}^U, \max_j \sum_{k=1}^m p_{jk}^U \right).$$

It is an internal estimate, so the method does not depend on externally supplied references. In the definitions below, write  $c_\mu^U$  for the worst-case completion time of machine  $\mu$  over the operations scheduled so far,  $M_t^U = \max_{\mu} c_\mu^U$  for the projected worst-case makespan after  $t$  decisions, and let step  $t$  schedule operation  $o_{jk}$  on machine  $\mu = \nu_{jk}$ . The six components are:

- *Terminal makespan* ( $w_{\text{mk}}=1.0$ ): zero at every step except the last, where

$$r_{nm}^{\text{mk}} = -\frac{C_{\text{max}}^U}{s_{\text{mk}}}, \quad s_{\text{mk}} = \frac{\widehat{\text{LB}}}{10},$$

Substituting the scale gives  $r_{nm}^{\text{mk}} = -10(1+g)$ , with  $g = (C_{\text{max}}^U - \widehat{\text{LB}})/\widehat{\text{LB}}$  the relative gap to the instance bound: a function of the relative gap alone, so its magnitude is independent of the instance’s size and time scale, and a schedule of the same relative quality receives the same reward on any instance. The robust arms of Section 7.3 replace  $C_{\text{max}}^U$  here by  $f_\lambda$ .

- *Job progress* ( $w_{\text{pr}}=0.26$ ):

$$r_t^{\text{pr}} = \frac{1}{nm}.$$

A constant per operation scheduled, a uniform progress signal that sums to one over any episode.

- *Machine idleness* ( $w_{\text{id}} \approx 0.24$ ):

$$r_t^{\text{id}} = -\frac{\max(0, s_{o_{jk}}^U - c_\mu^U)}{s_{\text{id}}}, \quad s_{\text{id}} = 2\bar{p},$$

with  $\bar{p}$  the mean midpoint duration of the instance: the worst-case idle gap that scheduling  $o_{jk}$  opens on its machine, measured in units of typical operations.

- *Local improvement* ( $w_{\text{li}} = 0.15$ ):

$$r_t^{\text{li}} = \kappa_t \frac{M_{t-1}^U - M_t^U}{s_{\text{mk}}/10}, \quad \kappa_t = \begin{cases} 2 & M_t^U > M_{t-1}^U, \\ 1 & \text{otherwise,} \end{cases}$$

the step change of the projected makespan, with deteriorations penalized twice as strongly: a dense signal so that early decisions are not credited only  $nm$  steps later.

- *Operation criticality* ( $w_{\text{cr}} = 0.1$ ):

$$r_t^{\text{cr}} = \frac{\sum_{k' > k} p_{jk'}^U}{s_{\text{cr}}}, \quad s_{\text{cr}} = \frac{W^U}{2n},$$

with  $W^U$  the instance's total worst-case work: the worst-case work remaining in the scheduled operation's job. Favoring jobs with much work remaining is a standard proxy for the emerging critical path.

- *Load balance* ( $w_{\text{ba}} = 0.1$ ):

$$r_t^{\text{ba}} = -\frac{\sigma_\mu(c_\mu^U)}{s_{\text{ba}}}, \quad s_{\text{ba}} = 1.5 \sigma_\mu(L_\mu^U),$$

where  $\sigma_\mu$  denotes the standard deviation across the  $m$  machines, taken after the step over the worst-case completion times and, in the scale, over the total worst-case loads  $L_\mu^U = \sum_{(j,k): \nu_{jk}=\mu} p_{jk}^U$  of the instance. Referring the observed dispersion to the dispersion the instance's own loads exhibit discourages lopsided machine loads without penalizing an instance for being intrinsically unbalanced.

The weights above and the internal constants of the components were all fixed by hand during early development and carried unchanged into every experiment of this paper. No claim of optimality is attached to them. The configuration campaign of Section 5.3 later raced the six weights, each free in  $[0, 1]$ , and did not improve on the hand-set vector within the protocol's resolution; the internal constants were not raced.

## 4.2 State representation

The state observed at each decision comprises two groups of features: a per-operation description of every eligible operation, scored one candidate at a time by the policy head, and a description of the shop as a whole, which enters the shared context. Operation  $o = o_{jk}$  on machine  $\mu = \nu_{jk}$  is described by the 16 quantities of Table 1, and the global state by the 12 aggregates of Table 2.

Both groups are dimensionless: every temporal quantity is expressed as a fraction of the computed bound  $\widehat{\text{LB}}$  of Section 4.1, and every uncertainty as a ratio of interval width to magnitude. Absolute times are not comparable across instances, since their magnitude reflects the time scale of the instance at hand, and a policy trained on them would be tied to the scale of its training set. The dimensionless representation renders the observation comparable across instances and sizes, which is one of the two components of size invariance; the other is the architecture of Section 4.3.

**Table 1** Per-operation features (all dimensionless).  $d = \mathbf{p}_{jk}$ ,  $\mathbf{est}$  = earliest start interval,  $\mathbf{rem}$  = remaining work interval of the job strictly after  $o$ , excluding  $o$  itself;  $\text{mid}(\cdot)$  is the interval midpoint, a ratio whose denominator is floored at a small positive constant and whose uncertainty feature is set to zero when the start interval is  $[0, 0]$ , the case of the operations eligible at the first decision;  $\text{mid}(\cdot)$  is the interval midpoint;  $L(\mu)$  the remaining worst-case load of machine  $\mu$ ;  $\bar{L}$  its average over machines;  $\mathbf{c}_J$  and  $\mathbf{c}_\mu$  the completion intervals of the operation’s job and machine over what is scheduled so far.

| #     | Feature               | Definition                                                                         |
|-------|-----------------------|------------------------------------------------------------------------------------|
| 1–2   | duration bounds       | $d^L/\widehat{\text{LB}}, d^U/\widehat{\text{LB}}$                                 |
| 3     | duration uncertainty  | $(d^U - d^L)/\text{mid}(d)$                                                        |
| 4–5   | earliest start bounds | $\text{est}^L/\widehat{\text{LB}}, \text{est}^U/\widehat{\text{LB}}$               |
| 6     | start uncertainty     | $(\text{est}^U - \text{est}^L)/\text{mid}(\mathbf{est})$                           |
| 7–8   | remaining job work    | $\text{rem}^L/\widehat{\text{LB}}, \text{rem}^U/\widehat{\text{LB}}$               |
| 9–10  | job position          | $(m - k - 1)/m, k/m$                                                               |
| 11    | machine load          | $L(\mu)/\widehat{\text{LB}}$                                                       |
| 12    | potential idle gap    | $\max(0, c_J^U - c_\mu^U)/\widehat{\text{LB}}$                                     |
| 13    | machine congestion    | $L(\mu)/\bar{L}$                                                                   |
| 14    | slack                 | $(\text{est}^U - \min_{o' \in \mathcal{E}} \text{est}_{o'}^U)/\widehat{\text{LB}}$ |
| 15–16 | completions           | $c_\mu^U/\widehat{\text{LB}}, c_J^U/\widehat{\text{LB}}$                           |

**Table 2** Global state features (all dimensionless aggregates, notation as in Table 1; no dimension depends on  $n$  or  $m$ ). Rows that list several statistics contribute one feature each, for 12 in total.

| #   | Feature             | Definition                                                      |
|-----|---------------------|-----------------------------------------------------------------|
| 1   | progress            | scheduled operations / $nm$                                     |
| 2   | partial makespan    | $\max_\mu c_\mu^U/\widehat{\text{LB}}$                          |
| 3–4 | machine completions | mean and std of $c_\mu^U/\widehat{\text{LB}}$                   |
| 5–7 | remaining loads     | mean, max and std of $L(\mu)/\widehat{\text{LB}}$               |
| 8–9 | remaining job work  | mean and max of job remaining / $\widehat{\text{LB}}$           |
| 10  | eligibility         | $ \mathcal{E} /n$                                               |
| 11  | pending uncertainty | $\sum(\text{widths})/\sum(\text{midpoints})$ of unscheduled ops |
| 12  | total load          | $\sum_\mu L(\mu)/(\widehat{\text{LB}} \cdot m)$                 |

Every quantity consulted by the dispatching rules of Section 2.2 (processing times, remaining work, earliest start times, slack, machine load) appears among the per-operation features, so that no advantage over those rules can be attributed to a wider per-operation vocabulary. The representation extends that shared vocabulary in two directions: the interval bounds and relative widths of every temporal quantity, which make the uncertainty explicit, and the global aggregates, which no per-operation priority rule consults. Which of these inputs the trained network comes to rely on is measured a posteriori by the audit of Section 7.1.

### 4.3 Size-invariant architecture

The second component of size invariance is architectural. The number of candidates changes at every step and from instance to instance, while a neural network requires inputs of fixed dimension. Two elements resolve this: the *same* network reads every candidate, so any number of them can be processed, and the resulting embeddings are *pooled* into fixed-size summaries, so the scoring stage receives a representation of the whole decision. Let  $x_i \in \mathbb{R}^{16}$  be the features of eligible operation  $i$  and  $g_0 \in \mathbb{R}^{12}$  the global state; the construction has three stages (Figure 1).

*Embed.* The shared two-layer MLP  $\phi$  (width  $h=128$ , LayerNorm, ReLU, orthogonal initialization) maps each candidate to an embedding  $\phi_i = \phi(x_i)$ . The whole eligible set is processed in one forward pass, as the  $|\mathcal{E}| \times 16$  matrix of its rows. Sharing the weights across rows allows the stage to accept any number of candidates and makes it equivariant to their order. Candidates do not interact at this stage:  $\phi_i$  depends on  $x_i$  alone.

*Pool into a context.* The variable-size set  $\{\phi_1, \dots, \phi_{|\mathcal{E}|}\}$  must be reduced to a fixed-size vector before it can be combined with the global state. Mean and max pooling provide two complementary permutation-invariant summaries (Zaheer et al., 2017) which, concatenated with the global state  $g_0$ , are mixed into the context:

$$g = \text{MLP}_{ctx}\left(\left[\frac{1}{|\mathcal{E}|} \sum_i \phi_i; \max_i \phi_i; g_0\right]\right) \in \mathbb{R}^h. \quad (6)$$

Pooling introduces no parameters: it maps the  $|\mathcal{E}| \times h$  embeddings to the  $2h$  summaries the context MLP consumes. Both statistics are taken over the non-padded candidates only, since in batched training the sets are padded to the batch maximum: the mean divides by the true count and the max ignores the padded rows. This embed-then-pool pattern is the *Deep Sets* construction of Zaheer et al. (2017), whose central result is that, for suitable choices of the two maps, any permutation-invariant function of a set admits this form. What the pattern restricts is therefore the invariance and not the class of functions; what the finite network used here represents remains bounded by its width. The result tables refer to the base model by this name.

*Score.* The *policy head* scores each pair (candidate embedding, context), and a masked softmax over the scores yields the distribution over eligible operations. The *value head* computes the state value  $V(s)$  used in the advantage estimation, reading the context alone, since that expectation concerns the state rather than any one

candidate:

$$\pi(i | s) = \text{softmax}_i \text{MLP}_\pi([\phi_i; g]), \quad V(s) = \text{MLP}_V(g). \quad (7)$$

Table 3 specifies the four trainable blocks. Each is a two-layer perceptron with Layer-Norm and ReLU between its layers and a linear output; all hidden layers are initialized orthogonally with gain  $\sqrt{2}$  and zero biases. The output layer of the policy head uses gain  $10^{-2}$ , so at the start every candidate receives a nearly equal score and the untrained policy is close to uniform; the output layer of the value head uses gain 1. Pooling and the masked softmax carry no parameters, so those four blocks account for the whole network: 120,322 parameters, no dimension of which depends on  $n$  or  $m$ .

**Table 3** Layer specification of the policy/value network at the hidden width  $h=128$ . Shapes are input, hidden and output dimensions.

| Block                    | Shape                                      | Parameters     |
|--------------------------|--------------------------------------------|----------------|
| Candidate encoder $\phi$ | $16 \rightarrow 128 \rightarrow 128$       | 18,944         |
| Pooling (mean, max)      | $ \mathcal{E}  \times 128 \rightarrow 256$ | —              |
| Context MLP              | $268 \rightarrow 128 \rightarrow 128$      | 51,200         |
| Policy head              | $256 \rightarrow 128 \rightarrow 1$        | 33,281         |
| Value head               | $128 \rightarrow 128 \rightarrow 1$        | 16,897         |
| Base network             |                                            | <b>120,322</b> |

Self-attention over the candidate set is the extension most commonly adopted in this literature to let one candidate condition on another, which pooling cannot express. A variant with two pre-LN transformer blocks between the embedding and pooling stages was evaluated as a controlled ablation and yielded no improvement at either training budget, degrading the operating one by about a point while carrying 3.2 times the parameters and 2.2 times the episode cost; its architecture and the full comparison are given in the supplementary material.

## 5 Experimental Methodology

### 5.1 Instances, data split and metric

Experiments use the 70 interval Taillard instances TA1–TA70 that anchor the recent IJSP literature (Díaz et al., 2023a, 2023b): seven size classes from  $15 \times 15$  to  $50 \times 20$ , each crisp duration replaced by an integer interval symmetric around it, with half-width drawn uniformly up to 15% of the original value (Díaz et al., 2020). The benchmark is openly available (Díaz Rodríguez, 2026a). Of the 70 instances, the final model is trained on four, TA11–TA14 of the  $20 \times 15$  class. Six more of the same class, TA15–TA20, form the *validation set*: never used for gradients, but every design and configuration decision was judged on their performance, so they are reported separately and excluded from claims about unseen data. The remaining 60 instances

**Table 4** Machine and software used for every experiment in this paper.

| Component        | Specification                                   |
|------------------|-------------------------------------------------|
| CPU              | AMD Ryzen 5 3400G, 4 cores / 8 threads, 3.7 GHz |
| Thread limit     | 2 per process (OMP and MKL)                     |
| Memory           | 32 GB                                           |
| GPU              | NVIDIA GeForce RTX 5060 Ti, 16 GB (tuning only) |
| Operating system | Windows 10 Pro 22H2 (64-bit)                    |
| Language         | Python 3.12.6                                   |
| Learning         | PyTorch 2.9.1, CUDA 13.0 build                  |
| Numerics         | NumPy 2.3.5, SciPy 1.17.0                       |
| Figures          | Matplotlib 3.10.8; svglib 2.1.0 (diagram)       |
| Tuning           | irace 4.4.3 on R 4.6.1 (Section 5.3)            |

entered neither training nor validation. A second benchmark, consisting of interval versions of twelve classical instances (FT10, FT20, La21, La24, La25, La27, La29, La38, La40 and ABZ7–9) generated with the same symmetric scheme (Díaz et al., 2020), is reserved for the cross-family evaluation of Section 6.3, and plays no part in training or validation either.

One convention governs every significance test reported below. The independent unit is the instance, not the pair (instance, seed): policies trained under different seeds are evaluated on the same instances, so their results are averaged over seeds before any instance is entered into a paired test. Treating the pairs as independent would multiply the apparent sample size without adding information about generalization. Tests are two-sided exact Wilcoxon signed-rank tests over the instances of the set in question, reported with the mean difference and its 95% confidence interval, and the smallest attainable  $p$ -value is 0.031 on the six validation instances and below  $10^{-3}$  on the seventy. No correction for multiple comparisons is applied: the tests answer separate questions posed in advance, one per ablation, so the  $p$ -values are reported as evidence about each contrast on its own and not as a family-wise claim.

## 5.2 Computational environment

Table 4 lists the machine and the software stack. One aspect bears on the costs reported later: every number in this paper (training, evaluation, the dispatching-rule baselines and the ablations) was produced on the CPU, with the single exception of the tuning campaign of Section 5.3. The network is small enough (Section 4.3) that a forward pass is negligible next to the environment step that follows it, so the GPU yields no speedup for a single rollout; it was used only for the vectorized batched rollouts of the operating-fidelity tuning campaign (Section 5.3), where many episodes advance in lockstep and the batched forward pass amortizes. The method therefore carries no dependence on specialized hardware.



**Table 5** Hyperparameters, identical across every experiment reported in this paper.

| Hyperparameter              | Value             | Hyperparameter           | Value      |
|-----------------------------|-------------------|--------------------------|------------|
| <i>Optimizer</i>            |                   | <i>PPO objective</i>     |            |
| learning rate (Adam)        | $3 \cdot 10^{-4}$ | clipping range           | 0.2        |
| Adam $\epsilon$             | $10^{-5}$         | GAE $\lambda$            | 0.95       |
| gradient clipping           | 0.5               | discount factor $\gamma$ | 1.0        |
| <i>Network and schedule</i> |                   | <i>PPO updates</i>       |            |
| hidden width $h$            | 128               | epochs per update        | 4          |
| weight initialization       | orthogonal        | minibatch size           | 256        |
| policy update               | every 4 ep.       | entropy coefficient      | 0.01       |
| greedy evaluation           | every 10 ep.      | advantage normalization  | per update |

### 5.3 Hyperparameter configuration

All reported results use the hyperparameters of Table 5. Their values were fixed by hand during development, most of them at the defaults customary in the PPO literature. Whether automatic tuning would improve on them was assessed with three irace (López-Ibáñez, Dubois-Lacoste, Pérez Cáceres, Birattari, & Stützle, 2016) campaigns of about 300 experiments each, two over the optimizer (one at reduced fidelity, one at the operating budget) and one over the six reward weights of Eq. (5): none of their winners improved on the hand-set values under a paired confirmation, whose resolution, set by the 0.47-point standard deviation across seeds (Section 6.1), is approximately one point of RE. The campaigns therefore exclude improvements larger than that magnitude, not the existence of smaller ones. Their search spaces, outcomes and by-products are provided in the supplementary material.

### 5.4 Training and inference

The policy is trained with PPO (Schulman et al., 2017) under the hyperparameters of Table 5. Training on a set of instances proceeds in blocks, one instance at a time, with the weights carried over from each block to the next. Every block receives the same number of episodes, and the instances are presented in their benchmark order, TA11 to TA14, which the seed does not permute: the seed governs network initialization, action sampling and minibatch composition, so the experiments here measure variability under a fixed curriculum and not over the orderings of it. Each training budget is a separate run from scratch rather than a checkpoint of a longer one, so the arms at 100, 300 and 1000 episodes per instance share no trajectory. A *rollout* is one complete construction episode played by the current policy: *sampled* when each operation is drawn from  $\pi$ , as during training, and *greedy* when every step takes the most probable operation. Every tenth episode (Table 5), the current policy is additionally evaluated with one greedy rollout. Whenever an episode of either kind improves on the best makespan found so far, its solution and a copy of the weights that produced it are stored; the stored weights are the *checkpoint* used at evaluation time.

The discount factor is  $\gamma = 1$  rather than the 0.99 customary in deep RL (Schulman et al., 2017). The horizon here is finite and known, so future rewards can be credited in full; at  $\gamma = 0.99$  the terminal makespan, the quantity being minimized, would reach the earliest decisions of a  $20 \times 15$  instance attenuated to  $0.99^{nm} \approx 0.05$  of itself. Updates are likewise applied over transitions pooled from four consecutive episodes rather than from one, in minibatches of 256 and with advantages normalized within each update, because the  $nm$  steps of a single episode are few and strongly correlated: pooling widens the sample the advantage estimate is computed from, and normalizing keeps the gradient scale comparable across instances of different size.

Thirty runs of this protocol were trained, differing from one another only in their random seed, and the one with the lowest mean RE on the validation instances at the deployed budget is *the policy* this paper reports; the seventy benchmark instances take no part in that choice. Where the difference matters, results also give the mean over the thirty runs.


### ***Best-of- $N$ inference.***

At evaluation time the stochastic policy is exploited by drawing one greedy rollout and  $N - 1$  sampled ones, and keeping the best solution under the ranking of Eq. (3). The deployed budget is  $N=64$ ; results are additionally reported for a single greedy pass and, in the budget-matched comparisons of Sections 6.1 and 6.2, for  $N=1024$ . This choice is motivated empirically in Section 7.2: sampling overtakes the greedy pass at twelve rollouts and continues to improve to the largest budget measured, so the policy is more valuable as a *distribution* than as its argmax, consistent with sampling-based decoding in neural combinatorial optimization (Kool et al., 2019).

## **5.5 Baselines**

Constructive baselines are the dispatching rules of Section 2.2 (SPT, LPT, MOR, MWKR and EST) and the two Giffler–Thompson combinations. The results of Section 6 carry the strongest of each family, namely MOR, EST and G&T-MWKR, while SPT, LPT, MWKR and the SPT tie-break of Giffler–Thompson are dominated by a wide margin in every size class and are not reported further. The learned-symbolic baseline is the dispatching rule evolved by genetic programming for this same benchmark by Díaz Rodríguez (2026b), compared budget by budget in Section 6.2. The budget that is matched there is the number of schedules each method constructs, not the wall-clock time it spends: both run the same schedule builder once per sample and differ in what scores a candidate, a forward pass of the network against the evaluation of an evolved expression, which is the cheaper of the two. Matched sample counts therefore favour the policy in computational terms, and the comparison should be read as one of sample efficiency.

Three published IJSP metaheuristics are included as reference yardsticks rather than as direct competitors, since each searches every instance separately for minutes on dedicated hardware and reports 30-run averages: the genetic algorithm (GA) of Díaz et al. (2020), the enhanced swarm artificial bee colony ESABC (Díaz et al., 2023a) and the filtered elitist artificial bee colony fEABC (Díaz et al., 2023b), the strongest of the three. Their figures are quoted from those papers, not re-run here.



**Fig. 2** Training dynamics of the deployed arm: RE of the sampled training episodes (smoothed over 25 episodes; the band spans the seeds) and of the best schedule found so far, over the four training blocks TA11–TA14 with weights carried from block to block. Curves aggregate the seven seeds of the ten whose runs recorded per-episode logs; the remaining three predate that logging.

## 6 Results

### 6.1 In-size performance and budget scaling


This section reports what the policy achieves on the class it is trained on, first during training and then at deployment on the validation instances.

Figure 2 shows the training dynamics at the operating budget. Within each block the episode RE falls steeply over the first  $\sim 200$  episodes and stabilizes, with no divergence in any seed; across blocks, each instance starts better than its predecessor did, the visible effect of carrying the weights over, and the spread between seeds narrows as training advances. The levels in this figure are higher than the deployed ones because training episodes are *sampled*, with exploration active, rather than greedy.

Deployment on the validation instances is reported in Table 6, per instance and for increasing training budgets over ten independent training runs, with Figure 3 showing their means against the budget. Three observations follow. (i) The policy scales monotonically with budget ( $27.4\% \rightarrow 17.4\% \rightarrow 13.8\%$  mean RE at 100/300/1000 episodes per instance), with the return per tripling of the budget falling from 10.0 points to 3.6. (ii) The spread between training runs contracts as the budget grows, the standard deviation across the ten seed means falling from 4.69 points at 100 episodes to 1.30 at 300 and 0.47 at 1000, a factor of ten, so what the extra budget yields is not only a better mean but a more reproducible one; this is the deployed counterpart of the narrowing seed band of Figure 2. (iii) The gap to the strongest constructive baseline is a factor  $\approx 2.0$ . Figure 3 places the curve between two dotted references measured on the same six instances: G&T-MWKR above, at 27.9%, and fEABC below, at 9.6%, the latter a reference from per-instance search.

**Table 6** RE (%) per validation instance, mean [best] over ten training runs differing only in their random seed, Deep Sets model, best-of-64 inference. Here and throughout, *best* is the best training run, never the best rollout within a run: sampling is already aggregated by the best-of- $N$  rule. Each seed contributes one mean over the six instances, and the rightmost column is the standard deviation of those ten numbers; the last row is the strongest constructive baseline, a single deterministic pass.

| Budget   | TA15               | TA16               | TA17               | TA18               | TA19               | TA20               | Mean        | SD          |
|----------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|-------------|-------------|
| 100 eps  | 30.2 [21.9]        | 26.3 [19.7]        | 26.8 [18.1]        | 26.7 [18.4]        | 28.7 [21.5]        | 25.8 [18.5]        | 27.4        | 4.69        |
| 300 eps  | 19.0 [16.3]        | 16.3 [14.3]        | 16.6 [13.3]        | 18.5 [16.2]        | 17.2 [13.3]        | 16.6 [14.9]        | 17.4        | 1.30        |
| 1000 eps | <b>14.9</b> [12.1] | <b>13.2</b> [11.8] | <b>12.9</b> [10.4] | <b>16.3</b> [14.6] | <b>12.8</b> [11.1] | <b>12.8</b> [10.5] | <b>13.8</b> | <b>0.47</b> |
| G&T-MWKR | 30.6               | 34.0               | 17.7               | 31.8               | 29.3               | 24.1               | 27.9        | —           |



**Fig. 3** Mean RE on the six validation instances TA15–TA20 ( $20 \times 15$ ) against the *training* budget, the episodes spent once per instance before deployment, on a logarithmic axis and over ten training runs. The band spans the best and worst of them; the dotted lines are G&T-MWKR and fEABC on the same six instances.

## 6.2 Cross-size generalization and position among constructive methods

The size-invariant design allows direct evaluation of the trained network on any class. Six of the seven are *zero-shot*: the weights are applied to sizes they never saw, with no additional training or fine-tuning of any kind. The seventh, marked in the table, is  $20 \times 15$ , which holds the four training and the six validation instances. Table 7 reports RE over all seventy instances by size class, ten to a class, with its per-instance values in the supplementary material. Each learned family trains thirty artifacts, thirty evolutions and thirty runs, and appears as the one its study selects: the rule Díaz Rodríguez (2026b) features and the policy of Section 5.4. Both were fitted on the  $20 \times 15$  instances, so the other six classes lie outside the training distribution of either and the transfer the table asks for is the same on both sides. The GP rule is deterministic at one pass and randomized by  $\epsilon$ -greedy dispatching when sampled; fEABC closes the table as a 30-run average from a different computational class.

**Table 7** Mean RE (%) per size class over the 70 interval Taillard instances. The  $20 \times 15$  column ( $\dagger$ ) holds the training and validation instances. GP and policy rows carry the artifact each study selects among its thirty.

| Method                 | $15 \times 15$ | $20 \times 15^\dagger$ | $20 \times 20$ | $30 \times 15$ | $30 \times 20$ | $50 \times 15$ | $50 \times 20$ | All  |
|------------------------|----------------|------------------------|----------------|----------------|----------------|----------------|----------------|------|
| EST                    | 32.3           | 49.2                   | 41.5           | 42.4           | 56.6           | 33.2           | 41.0           | 42.3 |
| MOR                    | 41.4           | 46.7                   | 47.3           | 44.1           | 58.8           | 34.1           | 45.9           | 45.5 |
| G&T-MWKR               | 26.7           | 29.0                   | 30.9           | 33.6           | 36.8           | 23.9           | 25.5           | 29.5 |
| GP rule, 1 pass        | 15.7           | 16.6                   | 18.1           | 21.1           | 24.1           | 13.8           | 14.6           | 17.7 |
| <b>Policy</b> , 1 pass | 15.0           | 17.4                   | 17.7           | 21.4           | 24.7           | 16.1           | 17.1           | 18.5 |
| GP rule, 64            | 12.6           | 15.9                   | 16.8           | 17.4           | 23.4           | 11.7           | 13.4           | 15.9 |
| <b>Policy</b> , 64     | 10.7           | 12.8                   | 14.1           | 17.6           | 22.3           | 12.8           | 14.8           | 15.0 |
| GP rule, 1024          | 10.2           | 14.0                   | 15.1           | 15.5           | 21.0           | 10.6           | 12.1           | 14.1 |
| <b>Policy</b> , 1024   | 9.3            | 11.2                   | 12.2           | 15.6           | 19.9           | 10.9           | 13.7           | 13.2 |
| FEABC (30 runs)        | 5.9            | 8.7                    | 10.3           | 9.8            | 16.4           | 5.7            | 9.0            | 9.4  |

At every budget the policy improves on G&T-MWKR, the strongest of the hand-crafted baselines considered here, on *every* one of the seventy, with class means at 64 samples from 10.7% on  $15 \times 15$  to 22.3% on the hardest transfer,  $30 \times 20$ , and no failure mode up to 1000-operation episodes. That is a property of the selected run rather than of the arm: across the thirty runs at one pass, 64 of the 2100 (instance, run) pairs fail to improve on the same rule, three per cent of them.


Against the GP rule the comparison is not one-sided: its outcome depends on the inference budget both methods receive (Figure 4). With one pass each the rule is better, 17.71% against the policy’s 18.49%, which is ahead on only 26 of the 70; with 64 samples each the ordering reverses, 15.02% against 15.88% and ahead on 42 of the 70, and 1024 samples widen nothing, 13.25% against 14.07% and again 42. Under the convention of Section 5.1 every one of these differences is significant ( $p = 0.029$ , 0.021 and 0.011): the two learners are statistically distinguishable at every budget, in opposite directions, and the advantage the policy gains by sampling is of the same size as the one it concedes at a single pass.

The deficit does not depend on which run each side put forward. The means over the thirty, which no choice touches, stand 18.99% against 19.82% and separate with  $p = 0.007$ , so the ordering at one pass is a property of the two families and not of the two artifacts that represent them.

The per-class columns qualify all of this. The one-pass deficit is not spread evenly: the policy is *better* on  $15 \times 15$  and  $20 \times 20$ , and the whole of the aggregate gap comes from  $50 \times 15$  and  $50 \times 20$ , where it loses by 2.3 and 2.5 points; the means over the thirty artifacts follow the same pattern. Both families are size-agnostic in form, the rule as an expression over per-operation attributes and the network by construction, so what separates them on the largest classes is not applicability but capacity. The network fitted its decision function to the states a  $20 \times 15$  episode visits, and those move with size: a  $50 \times 20$  episode runs more than three times longer and offers up to

fifty candidates at a step rather than twenty. A short expression has little room to encode a dependence on that distribution, and correspondingly little to lose when it shifts. Sampling recovers most of the gap, but the two largest classes remain where the evolved rule is hardest to beat.

The network’s advantage therefore lies in its distribution, whose samples improve faster with budget than those of the randomized rule. The best-of- $N$  ablation of Section 7.2 reaches the same conclusion from the training side. The policy’s standalone RE (13.8% in-size, 9–20% class means at the largest budget) places it between the dispatching rules (42.3% for EST, the strongest) and the per-instance metaheuristics (9.4% for fEABC). This is the ordering that Zhang et al. (2020) established for the deterministic JSP, in which a learned constructive policy improves on the hand-crafted rules but does not reach the methods that search each instance anew, trading some solution quality for a cost incurred once at training rather than at every instance; it had not been established for the interval variant.



**Fig. 4** RE by size class over the 70 interval Taillard instances, the two learners paired at one pass and at 1024 samples. Boxes span the quartiles with whiskers at 1.5 IQR; every instance is overlaid as a point. The shaded  $20 \times 15$  class holds the training and validation instances.

### 6.3 Cross-family generalization: the classical instances

The IJSP literature also reports on interval versions of twelve classical instances (FT10 and FT20, seven of the La family, and ABZ7–9), generated from their crisp counterparts with the same symmetric scheme as the Taillard set (Díaz et al., 2020). None of these families was seen during training or validation, so they double as a cross-family generalization test. What changes is the family of underlying scheduling instances, not the way uncertainty is generated, which is the same construction in both benchmarks; the test therefore speaks to transfer across shop structures and leaves transfer across uncertainty regimes open. Following the literature, RE is measured here against the best-known expected-makespan values (Díaz et al., 2023b).


**Table 8** RE (%) on the 12 classical interval instances. Column groups are inference budgets: GP and the policy (Pol.) are comparable within a group and not across groups. Each entry is the mean over that method’s thirty independent runs, thirty evolutions and thirty training runs, with the per-instance best over those runs in brackets. GA is a 30-run average from a different computational class. Reference bounds are best-known expected makespans, not Taillard’s crisp bounds.

| Inst. | rule   | learned     |             | learned     |             | learned      |             | search  |
|-------|--------|-------------|-------------|-------------|-------------|--------------|-------------|---------|
|       | 1 pass | one pass    |             | 64 samples  |             | 1024 samples |             | 30 runs |
|       | G&T    | GP          | Pol.        | GP          | Pol.        | GP           | Pol.        | GA      |
|       |        | mn [bst]    | mn [bst]    | mn [bst]    | mn [bst]    | mn [bst]     | mn [bst]    | mn      |
| FT10  | 32.2   | 17.0 [7.2]  | 12.8 [6.6]  | 11.8 [5.2]  | 7.9 [4.3]   | 8.5 [4.2]    | 6.1 [4.3]   | 5.2     |
| FT20  | 40.0   | 18.5 [9.4]  | 12.2 [3.4]  | 13.3 [5.8]  | 8.1 [3.4]   | 10.3 [5.4]   | 6.2 [2.4]   | 4.4     |
| La21  | 24.1   | 15.9 [10.3] | 18.1 [12.4] | 12.6 [10.0] | 12.5 [8.6]  | 10.7 [6.8]   | 9.5 [6.7]   | 5.0     |
| La24  | 26.3   | 16.1 [10.1] | 16.6 [9.2]  | 11.5 [8.6]  | 11.2 [8.8]  | 9.2 [6.2]    | 9.3 [5.9]   | 6.3     |
| La25  | 16.9   | 17.6 [9.6]  | 18.4 [8.3]  | 12.3 [8.7]  | 10.3 [7.8]  | 9.3 [5.1]    | 8.2 [5.8]   | 5.1     |
| La27  | 34.8   | 18.3 [12.3] | 14.9 [8.9]  | 12.5 [10.7] | 11.4 [8.4]  | 11.3 [8.2]   | 9.3 [7.7]   | 10.2    |
| La29  | 24.5   | 19.9 [12.9] | 22.4 [13.2] | 15.0 [11.4] | 15.9 [12.3] | 12.6 [9.7]   | 13.5 [7.8]  | 14.2    |
| La38  | 27.0   | 17.4 [9.2]  | 15.8 [10.8] | 14.3 [9.2]  | 11.1 [8.0]  | 12.0 [7.1]   | 9.1 [7.0]   | 9.2     |
| La40  | 27.9   | 16.7 [11.7] | 13.4 [9.3]  | 12.3 [8.8]  | 8.5 [6.0]   | 10.0 [7.1]   | 7.2 [4.5]   | 8.7     |
| ABZ7  | 28.7   | 17.6 [13.3] | 18.2 [14.1] | 14.3 [11.7] | 13.5 [10.4] | 12.2 [8.9]   | 11.6 [8.5]  | 12.5    |
| ABZ8  | 36.9   | 24.6 [18.1] | 21.4 [16.8] | 20.9 [17.0] | 17.5 [15.0] | 18.6 [15.0]  | 15.3 [12.6] | 18.5    |
| ABZ9  | 41.8   | 29.0 [19.5] | 24.7 [19.7] | 24.0 [17.9] | 19.5 [16.3] | 21.5 [17.4]  | 17.3 [13.2] | 18.0    |
| Mean  | 30.1   | 19.0 [12.0] | 17.4 [11.0] | 14.6 [10.4] | 12.3 [9.1]  | 12.2 [8.4]   | 10.2 [7.2]  | 9.8     |

This family allows the comparison of Section 6.2 to be made with both readings at every budget, which the Taillard set does not: the GP study publishes its thirty evolutions here at all three, so each column of Table 8 pairs thirty artifacts against thirty, as a mean over the runs and as the per-instance best over them. The per-instance metaheuristics are quoted from Table 2 of Díaz et al. (2023b). The policy improves on EST and G&T-MWKR on all twelve instances and lands at 12.3% mean RE at its deployed budget, between the hand-crafted constructive baselines (30.1% for G&T-MWKR) and the per-instance searchers (GA at 9.8%, ESABC at 5.5%). Given 1024 samples the mean over its thirty runs reaches 10.2%, within half a point of the 30-run average of GA, a method that searches each of these instances from scratch while the policy has never seen them; the two remaining metaheuristics stay clear of both.

Against the evolved rules the comparison is again made budget by budget, and Figure 5 is arranged that way. The policy holds the lower figure in all six cells, and the two readings agree at every budget. Given one pass each it leads by 1.64 points on the means and 0.92 on the brackets, ahead on 7 of the 12 instances, a margin this sample cannot separate ( $p = 0.09$  and  $p = 0.27$ ). Given 64 samples each, with the rules randomized by the  $\epsilon$ -greedy dispatching their own study provides, it leads by 2.28 and 1.31 points, ahead on 11 and 10 of the 12 ( $p = 0.003$  and  $p = 0.005$ ); at 1024 samples, by 1.96 and 1.21, ahead on 10 of the 12 in both readings ( $p = 0.003$  and  $p = 0.012$ ).

The ordering therefore differs from the one the Taillard set gives. There the rule was ahead at a single pass; here it is behind at every budget, though the one-pass difference does not reach significance. The families this test uses are smaller than the Taillard classes the rule was evolved on, ten and fifteen jobs against twenty, and the policy was likewise trained on twenty; whatever else separates the two paradigms, the



**Fig. 5** Mean RE over the 12 classical interval instances, grouped by the inference budget each method is given. Both learned entries are means over the thirty independent runs of their family.

advantage the rule holds at one pass does not survive the change of family, while the advantage the policy gains by sampling does.

## 7 Analysis


Three questions remain about the policy itself: which of its inputs it consults, which of its design choices earn their cost, and how far the makespans it predicts survive execution.

### 7.1 What the policy attends to

The policy is not interpretable the way a priority expression is, but its inputs can be audited. Figure 6 reports a permutation test (Breiman, 2001): at every decision of a greedy rollout, one feature column is shuffled across the eligible operations, and the resulting mean RE over the validation set and the three seeds is compared with the intact rollouts (18.2%).

Each column is permuted five times with independent draws, and the figure reports the mean degradation and its standard deviation over the five; a single draw moves the magnitudes by several points and reorders the lower half, though not the leading three. Three features carry the policy: the relative slack (whose permutation adds  $56.5 \pm 2.4$  points of RE), the number of remaining operations in the job ( $+33.6 \pm 1.4$ ), and the job’s worst-case remaining work ( $+9.6 \pm 1.0$ ). These are the attribute families behind MOR and MWKR, and the very attributes the evolved expressions of Díaz Rodríguez (2026b) select. Below a second tier of three features costing between 1.8 and 2.9 points, the remaining ten fall into a floor between +0.3 and +1.0 points that no measurement of this precision separates. The floor is not exactly zero because permuting any column





**Fig. 6** Permutation importance of the 16 operation features: change in mean validation-set RE when the feature’s column is shuffled across the eligible operations at every decision (greedy rollouts, three seeds; intact baseline 18.2%). Bars are the mean of five independent permutation draws and whiskers their standard deviation. The two interval-width features are highlighted.

perturbs an input distribution the network was trained against, whether or not that column informs the decision.

The two interval-width features sit inside that floor, one of them last of the sixteen ( $+0.3 \pm 0.3$  for the duration width,  $+0.9 \pm 0.5$  for the start width), and their position follows from the objective. The primary key of the criterion of Eq. (3), the worst-case makespan, on which the reward also trains, is a function of the upper endpoints alone (Section 7.3), so a width cannot inform a decision judged by that criterion. The same asymmetry appears within the features themselves: three quantities enter as a pair of interval endpoints, and in the two pairs that rise above the floor the upper endpoint costs several times its lower counterpart (9.6 against 1.8 for the job’s remaining work, 2.1 against 1.0 for the duration), as a criterion written in upper endpoints alone should induce.


The audit is therefore conditional on what the policy was trained to optimize, namely this objective and the reward weights of Section 4.1, and a different one need not produce the same ranking. The corresponding test is an objective that does contain the width, which Section 7.3 carries out: retraining under  $f_\lambda$  leaves the weights indistinguishable from the default arm’s under a common selection criterion, which is evidence that the ranking would survive that change, though the audit itself was not repeated on those arms.

## 7.2 Ablation: best-of- $N$ inference

The policy is reported at three inference budgets (one greedy pass, 64 samples and 1024), which leaves its behaviour between them unspecified. To characterize it, all 342

rollouts per checkpoint were retained on each of the 70 instances (71,820 schedules), so that best-of- $B$  is reconstructible for arbitrary  $B$  without further evaluation. Figure 7 plots the resulting curve; its band is a dispersion over repetitions, not a confidence interval on the mean. The budget is partitioned over the three checkpoints as in the deployed protocol and the greedy reference is aggregated identically, which places it below the 19.4% of Section 6.2; EST, at 42.3%, lies above the frame. A single *sampled* rollout is substantially worse than the greedy one, 21.4% against 17.0%: the argmax is a high-quality sequence within a broadly dispersed distribution. The curve overtakes the evolved rule at  $B=6$  and the greedy pass at  $B=12$ , so sampling becomes profitable at budgets far below the 64 used throughout. The returns are near-logarithmic over three orders of magnitude, 14.9% at 64 and 12.9% at 1023 (341 per checkpoint, the reconstruction’s closest point to the nominal 1024), without an inflection: no budget within the tested range saturates.

The same reconstruction quantifies the marginal return of further sampling and its computational cost. The marginal return decays slowly but does not vanish, from 1.03 points between 4 and 8 samples to 0.42 between 512 and 1023, a log-linear rate of 0.46 points per doubling over the last three octaves; wall-clock cost, by contrast, scales linearly in  $B$ . On the machine of Table 4 a sampled rollout requires 1.03 s on a  $20 \times 15$  instance and 6.4 s on a  $50 \times 20$  one, timed end to end over the episode, so that the figure covers the forward passes, the environment transitions and the interval arithmetic of the schedule builder, and excludes only the one-off loading of the model. Accordingly  $B=1023$  amounts to 18 minutes and 1.8 hours per instance, and the four additional doublings needed to reach 11% at the measured rate would amount to 4.7 and 29 hours. Sampling is therefore an inefficient route to the residual gap against fEABC’s 9.4%, which its own study reports attaining in minutes per instance on the hardware of that study. One qualification bounds this extrapolation: budgets above 1023 lie outside the measured range, and within it the marginal return is itself



**Fig. 7** RE against the *inference* budget  $B$  on a base-2 logarithmic axis: for each instance the best of the  $B$  samples spent on it is kept, and the curve reports the mean of that value over the 70 instances. The band is the 10–90 percentile over resamplings.

contracting, with each octave yielding approximately a tenth less than its predecessor, so a constant rate is the optimistic reading.

A second standard component was evaluated the same way. Two self-attention blocks inserted before the pooling brought no improvement at either training budget and degraded the operating one by about a point, with 3.2 times the parameters; the architecture and the full comparison are given in the supplementary material.

### 7.3 Where each paradigm handles the uncertainty

Componentwise addition and join act on each endpoint separately, so the recursion of Eq. (1) splits in two. The upper half,

$$c_o^U = \max(c_{JP(o)}^U, c_{MP(o)}^U) + p_o^U, \quad (8)$$

makes  $C_{\max}^U$  a deterministic function of the processing order and the upper endpoints alone, the lower half determining  $C_{\max}^L$  without ever entering it.  $C_{\max}^U$  is the primary key of the lexicographic criterion of Eq. (3) under which every schedule in this paper is compared. Its secondary key, the lower endpoint, is consulted only on exact ties of the upper one, and on the rollout pools of this section such ties do not arise (the upper-bound minimizer is unique in every one of the 90 (arm, instance, seed) pools), so in practice the criterion reduces to its primary key. The reward of Section 4.1 trains on that primary key, and across its six components not one reads a lower bound, so there is no channel through which knowing an interval’s width could reduce what the policy is being trained to reduce. A width feature can at best be an auxiliary signal for learning; it cannot be information about the objective, because the objective does not contain it.

The permutation audit of Section 7.1 found both width features at the floor of its ranking, consistent with this entailment. Three training-time ablations ask the causal questions the audit cannot: whether the policy would be any worse had it never seen the uncertainty at all; whether the upper bounds shown during training must be the true ones, which Eq. (8) does not settle, since midpoint training changes the upper endpoints themselves; and whether the policy would come to consult the widths under an objective that pays for them. Each ablation is paired against the main arm on the training seeds it shares: the first two over all ten seeds, whose baseline is the 13.82% of Section 6.1, and the third over the three seeds of its rollout deposits, whose baseline is the 13.44% mean of those three.

#### ***Widths as inputs.***

The first ablation removes the information: the encoder collapses every interval to its worst case before the features are computed, so the width features are identically zero and the bounds coincide, while the architecture, the hyperparameters and the schedule builder remain untouched and the environment still executes interval semantics. Ten seeds retrained from scratch reach 13.86% mean RE against the ten-seed baseline’s 13.82%: a difference of 0.04 points, worse on 2 of the 6 instances, not significant (Wilcoxon signed-rank,  $p = 1.00$ ). The measurement is not redundant with the prediction, because Eq. (8) concerns the objective while the widths could in principle have

shaped the value function or the exploration as an auxiliary signal. They do not, and the interval estimate bounds what room remains: the difference lies between  $-0.79$  and  $+0.87$  points with 95% confidence, so any effect these data leave open is smaller than the one the next ablation attributes to the training distribution.

#### *Intervals as training data.*

The second ablation removes the uncertainty from training altogether. The benchmark perturbs each crisp duration symmetrically, so the original crisp instances *are* the midpoint scenario of their interval counterparts (the coincidence noted after Eq. (4)): the policy is trained on them and evaluated, unchanged, on the interval instances. This is the case Eq. (8) leaves open, since midpoint training replaces the upper endpoints themselves, and both arms extend to ten seeds: the gap is 0.63 points, from 13.82% to 14.45% (95% CI 0.08 to 1.17), worse on all six instances and positive for eight of the ten seeds ( $p = 0.031$ ). Training on the true upper bounds is slightly better than training on their midpoints. Six instances give this comparison about a 0.7 chance of detecting an effect of the size observed, so the finding establishes the direction of the gap more firmly than its magnitude, which the confidence interval leaves loose. The delimitation is therefore sharper than a blanket statement about what the intervals contribute. As *input features* the widths are inert, and Eq. (8) says why in a way that generalizes past this network: any method that ranks semiaactive schedules by the criterion of Eq. (3) optimizes, through its primary key, a function of the upper endpoints alone, whatever the model class. As *training distribution* the intervals are not inert. The boundary of the claim is the reward and the data, not the architecture.


#### *A width-penalizing objective.*

The third ablation changes the objective so that the width enters it. The policy is retrained, unchanged in every other respect, under

$$f_\lambda = C_{\max}^U + \lambda (C_{\max}^U - C_{\max}^L), \quad \lambda = 1, \quad (9)$$

which charges the schedule for the width of the interval it predicts and is the analogue of the robust objective of the GP study (Díaz Rodríguez, 2026b); since optimizing one quantity and selecting by another would be incoherent, the best-of- $N$  inference of this arm ranks its samples by  $f_\lambda$  as well. Deployed as that package, the objective delivers what it promises: over the same three seeds the predicted interval narrows from 12.85% to 11.90% of the expected makespan (narrower on all six instances,  $p = 0.031$ ) while the expected makespan rises by 1.94 points, to 15.38% (higher on all six,  $p = 0.031$ ). Unlike the two ablations above, both effects are significant: a width-rewarding objective is available, at a price of about two points of RE.

Figure 8 locates where that trade is produced. Training and selection changed together in the deployed package, so the two are separated on fresh deposits of 64 rollouts per (arm, instance, seed), with three further arms retrained from scratch at  $\lambda = 0.5, 2$  and  $4$  (three seeds each); every selection is recomputed on these common deposits, which is why the  $\lambda=1$  figures differ slightly from the training-run schedules quoted above. When deployed, with each arm’s samples ranked by its own  $f_\lambda$ , the



**Fig. 8** Mean relative width of the selected schedule against its mean RE, over the 18 (instance, seed) pools of each arm’s common rollout deposit. The deployed arms trace the frontier; re-ranking the default policy’s deposit reproduces it; under a common criterion the retrained arms do not separate.

five arms trace a monotone frontier, from 12.80% relative width at the default end to 10.99% at  $\lambda = 4$ , with the expected makespan climbing by 3.49 points ( $p = 0.031$ ). Under a common selection criterion the frontier vanishes: no retrained arm proposes narrower rollouts than the default one (at  $\lambda = 1$  the widths are 12.80% against 12.69%,  $p = 0.69$ , and three of the four arms are marginally wider), with no width difference approaching significance (smallest  $p = 0.31$ ). Conversely, re-ranking the *default* policy’s own deposit by each  $f_\lambda$  in turn retraces the frontier almost point for point, ending at 11.09% width and 17.05% RE where the arm trained on  $f_4$  lands at 10.99% and 17.75%. What narrows the interval is which sample is kept, not which weights produced it: the network is not merely indifferent to the width features in its input; its proposal distribution does not become narrower when the objective penalizes width, and the retrained weights propose samples as wide as the default’s. The predictability–performance trade is real, tunable and monotone, and it arises entirely at selection time.

#### *Contrast with the evolved rule.*

The GP study runs the same objective at the same  $\lambda$  and reaches the opposite finding, which makes the two studies informative read together. There, penalizing width narrows the schedules only when the rule has width terminals to act through: sweeping  $\lambda$  from 0 to 4 moves the relative width by 1.64 points for rules that have them and by 0.13 points for rules that do not, from which that study concludes that the objective works *through* the representation (Díaz Rodríguez, 2026b). The network of this paper has both the terminals’ equivalent and the objective, and still its weights do not move at any  $\lambda$ ; what moves is the ranking among its samples. The same reward therefore reaches the decision function of an evolved rule and does not reach the decision function of a trained policy, at least at this training scale. The rate of the trade is comparable on the two sides, about 2.5 points of RE per point of width across that

study’s sweep and about 1.9 across ours, so what separates the paradigms is not the magnitude of the cost but the stage at which it is incurred. In GP that stage is the decision function: the evolved rule becomes width-averse, and every schedule it constructs carries the bias. In DRL it is the selection: the weights are unchanged, and the cost arises sample by sample, whenever the ranking passes over a rollout with a better expected makespan in favor of a narrower one. The difference is operational at deployment: changing the trade-off of a width-averse rule requires evolving a new rule, whereas the policy’s trade-off is a parameter of the ranking, adjustable at inference time over the same samples. Two explanations remain open: that no training signal reaches these features, or that the semiactive constructive setting fixes the width independently of the policy’s decisions.

## 7.4 Executorial robustness


The evaluations so far concern the quality of a predicted schedule rather than its reliability. A schedule is committed as a processing order before the durations are known and is eventually executed under one realization of them, and its prediction is useful insofar as the realized makespan stays close to the expected value reported in advance. This is quantified with the field’s  $\bar{\varepsilon}$  measure (Díaz et al., 2020; Leon, Wu, & Storer, 1994): for a fixed processing order with predicted makespan  $\mathbf{C}_{\max}$ ,

$$\bar{\varepsilon} = \frac{1}{K} \sum_{k=1}^K \frac{|C_{\max}^{\text{ex},k} - E[\mathbf{C}_{\max}]|}{E[\mathbf{C}_{\max}]}, \quad (10)$$

where  $C_{\max}^{\text{ex},k}$  is the crisp makespan of executing the order under the  $k$ -th realization, durations drawn independently and uniformly within their intervals.  $\bar{\varepsilon}$  is thus the mean relative distance between the executed makespan and the reported value, a measure of the calibration of the prediction, in which lower is more faithful. The measurement uses  $K=1000$  common random numbers per instance (identical realizations for every method, drawn from a generator seeded by the instance identifier so that the draws reproduce across runs and machines), so every comparison below is paired realization by realization. The measurement covers the full seventy-instance benchmark.

The constructive methods separate into two groups (Figure 9). MOR and G&T-MWKR deviate by  $\bar{\varepsilon} \times 10^3 = 6.48$  and 6.27; every remaining method lies between 5.2 and 5.7, and the distance is systematic: the policy at best-of-64 is more faithful than MOR on 63 of the seventy instances and than G&T-MWKR on 65 (paired Wilcoxon signed-rank,  $p < 10^{-10}$  in both cases). Within the faithful group the policy’s best-of-64 (5.48) is more faithful than EST (5.71; 45/70,  $p = 0.011$ ) and level with the evolved rule of Díaz Rodríguez (2026b) at both of its budgets (5.66 at one pass,  $p = 0.069$ ; 5.56 at 64 samples,  $p = 0.38$ ). Sampling degrades calibration for neither learner: the policy’s best-of-64 deviates as its greedy pass does (5.48 against 5.59,  $p = 0.29$ ), and the rule under the  $\epsilon$ -greedy dispatching of its study as its deterministic pass does (5.56 against 5.66,  $p = 0.54$ ).

The composition of the leading group explains the ranking. It holds a hand-crafted rule and both learners at their two inference budgets, and the presence of EST, the



**Fig. 9** Executional robustness by method:  $\bar{\varepsilon} \times 10^3$  over the seventy benchmark instances; lower is a more faithful prediction. Boxes span the quartiles with whiskers at 1.5 IQR, every instance is overlaid as a point, and diamonds mark the means quoted in the text.

weakest method of this paper in solution quality at 42.3% mean RE (Table 7) yet well clear of MOR and G&T-MWKR in faithfulness, shows that faithfulness and quality are separate properties: a method can predict reliably while scheduling poorly, and optimizing the makespan secures no reliability in return. The mechanism is the interval itself. Every realization’s makespan lies within the predicted interval (Section 3), so the width of that interval bounds the deviation any execution can produce: the narrower the prediction, the smaller the largest deviation it admits. None of the methods in the leading group optimizes the width of the interval it predicts, so their faithfulness is bounded by whatever widths their makespan-directed construction happens to produce. Faithfulness must therefore be pursued deliberately rather than inherited from a makespan objective; the GP study reaches the same conclusion from its side, where its rule likewise improves on G&T-MWKR but not on EST until an objective that penalizes width is introduced (Díaz Rodríguez, 2026b).

The robust arm of Section 7.3 is the direct test of that reading: it is the one method in the comparison whose objective charges for the width, and it attains the lowest deviation of the pool,  $\bar{\varepsilon} \times 10^3 = 5.23$  against 5.48 for the default arm, more faithful on 49 of the seventy instances ( $p < 0.001$ ) and with the narrowest predictions (11.2% of the expected makespan against 11.8%). This is the direction the argument predicts, demonstrated at benchmark scale, and it comes at the price Section 7.3 measured: about two points of expected makespan. The result completes the chain begun there: the narrowing that Section 7.3 traced to sample selection is not confined to the predicted interval but carries through to execution, as schedules whose realized makespans stay closer to the value reported in advance. Whether that trade is worth making depends on the shop rather than on the model; the comparison above shows it is obtained only when the objective charges for the width.

## 7.5 Limitations

Five limitations bound the scope of these conclusions. First, the benchmark follows the symmetric  $\pm 15\%$  generation scheme standard in the IJSP literature; asymmetric intervals, and distributions in which the uncertainty varies sharply from one operation to another, would separate the worst-case and expected-value criteria far more than they do here, and no policy was trained under them. The second benchmark changes the family of scheduling instances but not this scheme, so no result here speaks to a different uncertainty regime, and the finding that widths are inert as inputs is a statement about this objective on this construction rather than about interval scheduling at large. Second, the policy builds semiactive schedules, so the space it searches excludes the active schedules that the conflict-set restriction reaches and the insertion-based ones beyond them; the strongest constructive baseline of this paper exploits the first of those and the policy still leads it, but the ceiling is real. Third, the  $\lambda$ -sweep arms and the rollout-deposit controls of Section 7.3 are run over three training seeds, so their instance means rest on three runs each and the differences are paired effects on six instances rather than claims about the population of seeds. The three arms extended to ten seeds calibrate what a three-seed comparison can miss: the midpoint control turned a null into a detected effect, the attention deficit shrank from 1.76 to 1.06 points, and the no-width null sharpened from 0.18 to 0.04 points. Fourth, the four training instances are always presented in the same order, so the variability the seeds measure is that of a fixed curriculum; whether a different order would move the arm was not tested. Finally, the comparison with the rule evolved by genetic programming shares the evaluation protocol end to end (the same instances, interval arithmetic, ranking criterion, inference budgets and execution realizations, run in a single harness) but not the training side: each learner was trained as its own study prescribes, with budgets that no common currency equalizes. The comparison of the two paradigms with training matched as well, which Xu et al. (2025) call for, remains open.

## 8 Conclusions and Future Work

The three questions posed in the introduction now have answers. Neither learned paradigm dominates the other: the two separate at every inference budget and the ordering is set by that budget. Given one constructive pass each the evolved rule leads by 0.78 points of relative error, and the reading over the thirty artifacts of each family, which no selection touches, gives the same 0.83; once both methods sample the policy leads by 0.86 at 64 samples and 0.82 at 1024, all four differences significant with the instance as the unit. What the network contributes over a compact formula is therefore its sampling distribution rather than its argmax. The per-class columns qualify the aggregate: the policy is ahead near the size it trained on and behind on the two largest classes, where a short expression has less to lose from a shift in the state distribution. On the twelve classical instances, a family neither method was tuned for, the policy leads on both readings at both budgets measured (Q1).

The paradigms also differ in where they handle the uncertainty, and the design had conflated two things. As inputs the widths are inert: permuting them costs the policy 0.3 and 0.9 points, the floor of a ranking whose top feature costs 56.5, and



removing them from training costs nothing measurable over ten seeds (13.86 against 13.82%,  $p = 1.00$ ), which the closed recursion for the worst-case makespan predicts, since that quantity contains no lower endpoint. As training data the intervals are not inert: fitting the policy to the crisp midpoints instead costs 0.63 points over ten seeds (14.45 against 13.82%,  $p = 0.031$ ). An objective that charges for the width then locates the difference between the paradigms: swept from  $\lambda = 0$  to 4, the deployed arms trace a monotone width–makespan frontier (the predicted interval narrows from 12.80% to 10.99% of the expected makespan, at about 1.9 points of RE per point of width), yet with the selection criterion held fixed the robust weights and the default ones are indistinguishable, and ranking the default policy’s own samples by  $f_\lambda$  retraces the frontier without any retraining. What narrows the interval is which sample is kept, not which network produced it, where in the GP study the same objective acts through the evolved representation. A permutation audit completes the picture: the network leans on slack, remaining operations and worst-case remaining work, the attributes that hand-crafted and evolved rules exploit, with the width features at the floor of its ranking (Q2).

Both learners leave the hand-crafted rules behind. On its training class the policy improves on them by a wide margin (13.8% versus 27.9% for G&T-MWKR and  $\approx 46\%$  for the best plain rule), and because the representation is dimensionless and the encoder permutation-invariant, one network serves the entire benchmark: at its deployed budget it outperforms the strongest dispatching rule on every one of the seventy instances, six of the seven size classes never having been trained on, and the same weights improve on every rule on all twelve classical instances. The per-instance metaheuristics retain the lead in solution quality, on their published figures rather than on a rerun under a common protocol (9.4% mean RE for fEABC against 13.2% for the policy at its largest budget), at the cost of a search on every new instance: both learned constructive families occupy the ground between the baselines they dominate and the search algorithms they do not attempt to replace (Q3).

Of the standard techniques evaluated, only best-of- $N$  inference improved results at practical budgets: self-attention blocks added to the pooled encoder brought no improvement, and three automatic-configuration campaigns (two over the optimizer, one over the reward weights) failed to beat the hand-set values by more than the resolution of the confirmation protocol. At execution time the policy’s schedules are among the most dependable of the constructive pool, more faithful than every hand-crafted rule over the seventy instances and level with the evolved rule, while the width-charging arm attains the lowest deviation of the comparison, carrying the selection-time narrowing through to execution.

Three directions follow. The first concerns the representation, and the robust arm of Section 7.3 sharpens rather than settles it: paying for the width in the reward narrows the schedules the policy *selects* without measurably changing the policy itself, so the proposal distribution stays as wide when the objective penalizes width as when it does not. Whether the gradient never reaches them, or whether a semiactive constructive decision determines the width before the policy has any say in it, separates two very different diagnoses and calls for a different experiment than any run here:

a reward defined on the width alone would tell them apart. The second is deployment: a policy that schedules an instance in seconds is a candidate generator of initial solutions for population-based search, and the quality of its sampling distribution, documented here at a fixed budget, is the property such a use would exploit. The third turns the budget analysis of Section 7.2 inward. The policy commits to a schedule at 17.0% while its own thousand samples reach 12.9%: four points separate the decision the network makes from the best one it produces, and finding that one costs a thousand rollouts. The evolved rule shows the same separation, 17.7% for its single pass against 14.1% randomized to a thousand, so the gap belongs to randomized constructive search rather than to learning as such; what differs is the remedy, since the weights of a network can be moved onto its own best rollouts by retraining on them and iterating, the self-labeling strategy that Corsini, Porrello, Calderara, and Dell’Amico (2024) demonstrate on the crisp JSP, where a formula would have to be evolved anew. How much of the gap is learnable is open, and its shape is measurable: the sampled distribution has a standard deviation of 3.2 points per instance, so its best draw of a thousand sits 2.6 of them below the mean while the argmax sits 1.4; part of that distance is the variance of the tail rather than any decision rule. Such retraining would also sharpen the distribution that best-of- $N$  exploits, so the greedy and the sampled ends have to be measured together.

## Statements and Declarations

### *Funding.*

This work was supported by the Spanish Ministry of Science, Innovation and Universities (MCIN/AEI/10.13039/501100011033) under grant PID2022-141746OB-I00.

### *Competing interests.*

The author has no competing interests to declare that are relevant to the content of this article.

### *Data availability.*

The benchmark instances are openly available in a Zenodo repository (Díaz Rodríguez, 2026a). Code, benchmark harness, all experiment records (accepted and rejected), final checkpoints and figure-generation scripts will be deposited openly upon submission. [TODO: DOI del depósito propio al enviar]

## References

- Abdullah, S., & Abdolrazzagah-Nezhad, M. (2014). Fuzzy job-shop scheduling problems: A review. *Information Sciences*, 278, 380–407,
- Bello, I., Pham, H., Le, Q.V., Norouzi, M., Bengio, S. (2016). *Neural combinatorial optimization with reinforcement learning*. (arXiv:1611.09940)

- Bertsimas, D., & Sim, M. (2004). The price of robustness. *Operations Research*, 52(1), 35–53, <https://doi.org/10.1287/opre.1030.0065>
- Branke, J., Nguyen, S., Pickardt, C.W., Zhang, M. (2016). Automated design of production scheduling heuristics: a review. *IEEE Transactions on Evolutionary Computation*, 20(1), 110–124, <https://doi.org/10.1109/tevc.2015.2429314>
- Breiman, L. (2001). Random forests. *Machine Learning*, 45(1), 5–32, <https://doi.org/10.1023/A:1010933404324>
- Corsini, A., Porrello, A., Calderara, S., Dell’Amico, M. (2024). Self-labeling the job shop scheduling problem. *Advances in neural information processing systems (neurips)*.
- Díaz, H., González-Rodríguez, I., Palacios, J.J., Díaz, I., Vela, C.R. (2020). A genetic approach to the job shop scheduling problem with interval uncertainty. *Information processing and management of uncertainty in knowledge-based systems (IPMU)* (pp. 663–676). Springer.
- Díaz, H., Palacios, J.J., Díaz, I., Vela, C.R., González-Rodríguez, I. (2022). Robust schedules for tardiness optimization in job shop with interval uncertainty. *Logic Journal of the IGPL*, 31(2), 240–254, <https://doi.org/10.1093/jigpal/jzac016>
- Díaz, H., Palacios, J.J., González-Rodríguez, I., Vela, C.R. (2023a). An elitist seasonal artificial bee colony algorithm for the interval job shop. *Integrated Computer-Aided Engineering*, 30(3), 223–242, <https://doi.org/10.3233/ica-230705>
- Díaz, H., Palacios, J.J., González-Rodríguez, I., Vela, C.R. (2023b). Fast elitist ABC for makespan optimisation in interval JSP. *Natural Computing*, 22(4), 645–657, <https://doi.org/10.1007/s11047-023-09953-2>
- Díaz Rodríguez, H. (2026a). *Genetic programming dispatching rules for the interval job shop: instances, evolved rules, results and code*. Zenodo. ([dataset]. <https://doi.org/10.5281/zenodo.21716972>)
- Díaz Rodríguez, H. (2026b). *Genetic programming hyper-heuristics for the job shop scheduling problem with interval durations: robustness-aware interpretable rules that generalize across instance sizes*. SSRN. (Preprint. <https://doi.org/10.2139/ssrn.7214286>)

- Gabel, T., & Riedmiller, M. (2008). Adaptive reactive job-shop scheduling with reinforcement learning agents. *International Journal of Information Technology and Intelligent Computing*, 24(4), 14–18,
- Garey, M.R., Johnson, D.S., Sethi, R. (1976). The complexity of flowshop and jobshop scheduling. *Mathematics of Operations Research*, 1(2), 117–129, <https://doi.org/10.1287/moor.1.2.117>
- Giffler, B., & Thompson, G.L. (1960). Algorithms for solving production-scheduling problems. *Operations Research*, 8(4), 487–503, <https://doi.org/10.1287/opre.8.4.487>
- González-Rodríguez, I., Vela, C.R., Puente, J. (2010). A genetic solution based on lexicographical goal programming for a multiobjective job shop with uncertainty. *Journal of Intelligent Manufacturing*, 21(1), 65–73, <https://doi.org/10.1007/s10845-008-0161-x>
- Grumbach, F., Müller, A., Reusch, P., Trojahn, S. (2024). Robust-stable scheduling in dynamic flow shops based on deep reinforcement learning. *Journal of Intelligent Manufacturing*, 35(2), 667–686, <https://doi.org/10.1007/s10845-022-02069-x>
- Haupt, R. (1989). A survey of priority rule-based scheduling. *OR Spektrum*, 11(1), 3–16, <https://doi.org/10.1007/bf01721162>
- Karunakaran, D., Mei, Y., Chen, G., Zhang, M. (2016). Dynamic job shop scheduling under uncertainty using genetic programming. *Intelligent and evolutionary systems* (pp. 195–210). Springer.
- Kasperski, A., & Zieliński, P. (2016). Robust discrete optimization under discrete and interval uncertainty: A survey. *Robustness analysis in decision aiding, optimization, and analytics*. Springer.
- Kayhan, B.M., & Yildiz, G. (2023). Reinforcement learning applications to machine scheduling problems: a comprehensive literature review. *Journal of Intelligent Manufacturing*, 34, 905–929, <https://doi.org/10.1007/s10845-021-01847-3>
- Kool, W., van Hoof, H., Welling, M. (2019). Attention, learn to solve routing problems! *International conference on learning representations (ICLR)*.

- Kouvelis, P., & Yu, G. (1997). *Robust discrete optimization and its applications*. Dordrecht: Kluwer Academic Publishers.
- Kwon, Y.-D., Choo, J., Kim, B., Yoon, I., Gwon, Y., Min, S. (2020). POMO: Policy optimization with multiple optima for reinforcement learning. *Advances in neural information processing systems (neurips)*.
- Lei, D. (2011). Population-based neighborhood search for job shop scheduling with interval processing time. *Computers & Industrial Engineering*, 61(4), 1200–1208, <https://doi.org/10.1016/j.cie.2011.07.010>
- Leon, V.J., Wu, S.D., Storer, R.H. (1994). Robustness measures and robust scheduling for job shops. *IIE Transactions*, 26(5), 32–43, <https://doi.org/10.1080/07408179408966626>
- López-Ibáñez, M., Dubois-Lacoste, J., Pérez Cáceres, L., Birattari, M., Stützle, T. (2016). The irace package: Iterated racing for automatic algorithm configuration. *Operations Research Perspectives*, 3, 43–58, <https://doi.org/10.1016/j.orp.2016.09.002>
- Nazari, M., Oroojlooy, A., Snyder, L., Takáč, M. (2018). Reinforcement learning for solving the vehicle routing problem. *Advances in neural information processing systems (NeurIPS)*.
- Nguyen, S., Mei, Y., Zhang, M. (2017). Genetic programming for production scheduling: a survey with a unified framework. *Complex & Intelligent Systems*, 3(1), 41–66, <https://doi.org/10.1007/s40747-017-0036-x>
- Nguyen, S., Zhang, M., Johnston, M., Tan, K.C. (2013). A computational study of representations in genetic programming to evolve dispatching rules for the job shop scheduling problem. *IEEE Transactions on Evolutionary Computation*, 17(5), 621–639,
- Palacios, J.J., González-Rodríguez, I., Vela, C.R., Puente, J. (2015). Coevolutionary makespan optimisation through different ranking methods for the fuzzy flexible job shop. *Fuzzy Sets and Systems*, 278, 81–97, <https://doi.org/10.1016/j.fss.2014.12.003>
- Panwalkar, S.S., & Iskander, W. (1977). A survey of scheduling rules. *Operations Research*, 25(1), 45–61, <https://doi.org/10.1287/opre.25.1.45>

- Park, J., Chun, J., Kim, S.H., Kim, Y., Park, J. (2021). Learning to schedule job-shop problems: representation and policy learning using graph neural network and reinforcement learning. *International Journal of Production Research*, 59(11), 3360–3377, <https://doi.org/10.1080/00207543.2020.1870013>
- Schulman, J., Wolski, F., Dhariwal, P., Radford, A., Klimov, O. (2017). *Proximal policy optimization algorithms*. (arXiv:1707.06347)
- Smit, I.G., Wu, Y., Troubil, P., Zhang, Y., Nuijten, W.P.M. (2024). *Neural combinatorial optimization for stochastic flexible job shop scheduling problems*. (arXiv:2412.14052)
- Song, W., Chen, X., Li, Q., Cao, Z. (2023). Flexible job-shop scheduling via graph neural network and deep reinforcement learning. *IEEE Transactions on Industrial Informatics*, 19(2), 1600–1610, <https://doi.org/10.1109/TII.2022.3189725>
- Sotskov, Y.N., Matsveichuk, N.M., Hatsura, V.D. (2020). Schedule execution for two-machine job-shop to minimize makespan with uncertain processing times. *Mathematics*, 8(8), 1314, <https://doi.org/10.3390/math8081314>
- Taillard, E. (1993). Benchmarks for basic scheduling problems. *European Journal of Operational Research*, 64(2), 278–285, [https://doi.org/10.1016/0377-2217\(93\)90182-M](https://doi.org/10.1016/0377-2217(93)90182-M)
- Tassel, P., Gebser, M., Schekotihin, K. (2021). *A reinforcement learning environment for job-shop scheduling*. (arXiv:2104.03760)
- Đurašević, M., & Jakobović, D. (2018). A survey of dispatching rules for the dynamic unrelated machines environment. *Expert Systems with Applications*, 113, 555–569, <https://doi.org/10.1016/j.eswa.2018.06.053>
- Vinyals, O., Fortunato, M., Jaitly, N. (2015). Pointer networks. *Advances in neural information processing systems (NeurIPS)*.
- Wang, Y., Guo, T., Liu, Z. (2025). *An expectation-maximization algorithm-based autoregressive model for the fuzzy job shop scheduling problem*. (arXiv:2502.00018)
- Xu, M., Mei, Y., Zhang, F., Zhang, M. (2025). Learn to optimise for job shop scheduling: a survey with comparison between genetic programming and reinforcement learning. *Artificial Intelligence Review*, 58, 160, <https://doi.org/10.1007/s10462-024-11059-9>

- Zaheer, M., Kottur, S., Ravanbakhsh, S., Póczos, B., Salakhutdinov, R., Smola, A. (2017). Deep sets. *Advances in neural information processing systems (NeurIPS)*.
- Zhang, C., Cao, Z., Song, W., Wu, Y., Zhang, J. (2024). Deep reinforcement learning guided improvement heuristic for job shop scheduling. *International conference on learning representations (iclr)*.
- Zhang, C., Song, W., Cao, Z., Zhang, J., Tan, P.S., Xu, C. (2020). Learning to dispatch for job shop scheduling via deep reinforcement learning. *Advances in neural information processing systems (NeurIPS)*.
- Zheng, P., Xiao, S., Zhang, P., Lv, Y. (2024). A two-individual-based evolutionary algorithm for flexible assembly job shop scheduling problem with uncertain interval processing times. *Applied Sciences*, 14(22), 10304, <https://doi.org/10.3390/app142210304>