```
# ============================
# Step 1: Wages with f-strings
# ==================================
# Create variables with my own values
# ==================================
name = "Marc"
hourly_wage = 22.5
hours = 30

# Compute weekly pay
weekly_pay = hourly_wage * hours

# print using an f-string
print(f"{name} earns {weekly_pay:.1f} per week.")
```

```
Marc earns 675.0 per week.
```

```
# ============================
# Step 2: Count the warm days
# ========================================
# Create the provided list of temperatures
# ========================================
temps = [61, 65, 72, 58, 70, 74, 68]

#Loop and condition pattern to count days strictly above 65
warm_day_count = 0
for t in temps:
  if t > 65: # Strictly greater than 65 (not >=)
    warm_day_count += 1

print(warm_day_count)
```

```
4
```

```
# ====================================
# Step 3: Write a temperature converter
# ====================================
# Define the conversion function
# ==============================
def to_celsius(f):
  return (f - 32) * 5/9

# Call it on the first tempurature in the list (temps[0] is 61)
converted_temp = to_celsius(temps[0])

# Round the result to 1 decimal place and print
print(round(converted_temp, 1))
```

```
16.1
```

```
# ==========================
# Step 4: A movie dictionary
# ================================
# Create a dictionary for one movie
# ================================
movie = {"title": "Toy Story 3", "year": 2010, "rating": 9.9}

# Print eack key and value usinf a loop
for key, value in movie.items():
  print(f"{key}: {value}")
```

```
title: Toy Story 3
year: 2010
rating: 9.9
```

```
import pandas as pd

# Load the file with pandas
df = pd.read_csv("chickwts.csv")

# Move 1: Display a 5-row preview
print(df.head())

# Move 2: Inspect general structure properties
print(df.info())

#Move 3: Generate a descriptive summary table for the weight column
print(df["weight"].describe())
```

```
   Unnamed: 0  weight       feed
0           1     179  horsebean
1           2     160  horsebean
2           3     136  horsebean
3           4     227  horsebean
4           5     217  horsebean
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 71 entries, 0 to 70
Data columns (total 3 columns):
 #   Column      Non-Null Count  Dtype
---  ------      --------------  -----
 0   Unnamed: 0  71 non-null     int64
 1   weight      71 non-null     int64
 2   feed        71 non-null     object
dtypes: int64(2), object(1)
memory usage: 1.8+ KB
None
count     71.000000
mean     261.309859
std       78.073700
min      108.000000
```

```
25%      204.500000
50%      258.000000
75%      323.500000
max      423.000000
Name: weight, dtype: float64
```

The describe() command output shows that the mean weight of a 6-week old chick is 261.3g, with a median value of 258g. The the weights spread in a spectrum ranging from a minimum of 108g to a maximum of 423g. This high variation and wide spread reflects the various feeding conditions and their impact on growth rates.

https://github.com/HeroOfAThousandFaces/cs82a-portfolio

```
Start coding or generate with AI.
```