

» PLP-HD63

Pragmatic Laser Projector

Simple, Powerful, Affordable Laser Projector

- ✓ Energy efficient high-performance design
- ✓ 6200 ANSI lumens brightness
- ✓ 1920 x 1200 @ 60Hz WUXGA resolution
- ✓ High-reliability, high-efficiency laser light source
- ✓ Designed for 24 hours x 7 days continuous usage
- ✓ Interchangeable lens for widest throw ratio
- ✓ 3-LCD TFT Active Matrix display engine
- ✓ 20,000 hours of trouble-free operation
- ✓ Multiple video input formats and connectors
- ✓ Optional device control via RS-232, IR or network
- ✓ High brightness and wider color gamut
- ✓ Horizontal and vertical keystone correction
- ✓ Auto focus, Optical zoom, horizontal and vertical lens shift
- ✓ Lower total cost of ownership (TCO)



TO PLACE an ORDER or for QUESTIONS,
Emails Us: sales@Pragmatic1.com, Call Us: (408) 748-1100 or Fax Us: (408) 663-9783

Digital Signage In: Hospitals, Pharmacies, Medical clinic, Shopping Malls, Hotel Lobbies, Restaurants, Boutique shops, College campus, Sports Bar, Health & Fitness Clubs, Retail stores, Casinos, etc.

Cost Effective / Energy Efficient Design
The PLD-HD63 laser projector is a very cost-effective, energy-efficient unit for deployment in cost sensitive digital signage applications.

- Professional laser light source for 20000 hours service
- High brightness and color stability system

RELATED PRODUCTS

- PDP-1 Pragmatic Digital Signage player
- PLP-HD83 laser projector
- PLP-HD72 laser projector
- PLP-HD65 laser projector
- PHA (compact directional line-array speakers)
- SAA (compact Stereo Audio Amplifier)
- MBA (compact mono-block Audio Amplifier)
- PTS-4077F Directional drop-tile, ceiling speaker

Specifications

DISPLAY TECHNOLOGY	3-LCD TFT Active Matrix
NATIVE RESOLUTION	1920x1200 @60Hz WUXGA
LIGHT SOURCE	Laser light source
BRIGHTNESS	6200 ANSI lumens
CONTRAST RATIO	5,000,000:1
KEystone CORRECTION	Corner correction, Horizontal & Vertical +/- 30°
VIDEO RESOLUTIONS	640x480i/p, 800x600i/p, 1024x768i/p, 1280x1024i/p, 1280x768i/p, 1366x768i/p, 1920x1080i/p, 1920x1200@60Hz, 3840x2160@30p
THROW RATIO	1.22-1.98, optional lenses:1.4 - 2.52, 2.9 - 4.7
SCREEN ROTATION	Landscape, portrait (+90°, -90°)
VIDEO INPUT CONNECTIONS	HDMI 2X, VGA, HDBaseT (optional), USB
OUTPUT CONNECTIONS	VGA
AUDIO INPUT CONNECTIONS	3.5mm Stereo jack, RCA L/R Audio input jacks
OUTPUT CONNECTIONS	3.5mm Stereo jack, SPDIF Audio output interface, OPTICAL out
CONTROL INTERFACE PORTS	RS-232 input/output, 100Base-T/10Base-T RJ-45, IR control
POWER	100V-240V AC, 360W active, less than 0.5W standby mode
OPERATING CONDITIONS	Temperature 41°-104°F (5°- 40°C), Humidity 20-80% (non-condensing)
DIMENSIONS (HxWxD)	15.9" x 14.1" x 5.4" (405mm x 358mm x 136mm)
WEIGHT	16.98 lbs (7.7 kg)
REGULATIONS	CE, RoHS
PACKAGE CONTENTS	Projector unit, IR remote control, AC power cord
WARRANTY	One year limited warranty on parts and labor



TO PLACE an ORDER or for QUESTIONS,
Emails Us: sales@Pragmatic1.com, Call Us: (408) 748-1100 or Fax Us: (408) 663-9783