

» TUNRF-1

Mini FM / TV / CATV Tuner

HideAway™ Mini FM / TV / CATV Tuner

The HideAway™ Mini FM / TV / CATV Tuner is the ideal choice for receiving broadcast FM / TV signals from antenna and CATV signals from cable system. It is also the perfect choice for broadcast studios that employ numerous field monitors.

The Mini Tuner now translates the signal in close proximity to the audio amplifier, monitor screen or projector. This exciting feature eliminates noise and interference typically encountered when routing FM / TV / CATV sources over a long distance. The unit outputs an FM stereo audio signal and a composite video signal. It is operated via IR remote control and contains an elegant LCD display. The IR detector is located on the front panel and a remote IR input connector is provided on the rear panel.

There are a number of optional features available for the Mini Tuner, which include S-Video output, RS-485 serial digital control for networking, remote IR detector and MTS stereo audio decoding. There is also the option for a customized unit to better suit your needs with rack mounting brackets. This unit is designed and



Specifications:

Dimensions: 5.5" W x 1.75" H x 6.5" D

Weight: 1.2 lb. Approx.

Power: 12 V DC

Video Signal-to-Noise: 40 dB

Video Bandwidth: 4.2 MHz

VHF Channels: 2 thru 13

UHF Channels: 14 thru 69

CATV Channels: 1 thru 125

Audio Signal-to-Noise: 38 dB

Audio Distortion: >0.5%

Antenna Sensitivity: 20 dBuV

FM Radio: 88 thru 108 MHz

Image Shown Above: back and front

Applications:

- High-end projection systems that access cable television or a traditional antenna
- High performance FM radio receiver
- Broadcast studios that employ multiple monitors
- Health and Fitness Clubs
- Lightweight and compact design

Feature & Benefits:

- Efficient 12 V DC
- Antenna Sensitivity of 20 dBuV
- LCD display
- Measures 5.5"W x 1.75"H x 6.5"D
- Weighs 1.2 lbs
- Video bandwidth 4.2 MHz
- Video signal-to-noise 40 dB
- LED display, S-Video output, MTS stereo
- Signal can be translated in close proximity to audio amplifiers, monitors or projectors

*US and International patents pending

TO PLACE an ORDER or for QUESTIONS,

Emails Us: sales@pragmatic1.com, Call Us: (408) 748-1100 or Fax Us: (408) 663-9783