1. All local variables are declared in one file and the same variables are declared as extem in all other files using them.

- True
- False (this is the answer)

2. The static variables are permanent variables within their own functions or files.

- True (this is the answer)
- False

3. For declaring a function it is necessary to put a return type before the function name.

- True (this is the answer)
- False

4. Function strcmp(strl, str2) will return less than zero, if str2==strl .

- True
- False (this is the answer)

5. printf() format code: %lf is used for

- Floating point (decimal notation) (this is the answer)
- Unsigned decimal integer
- Signed decimal integer
- None of the above

6. The header file _____ contains the macros for many of the input/ output functions used in C.

1. <iostream.h>

2. <stdio.h>

3. <conio.h>

- 1
- 2 (this is the answer)
- 3
- 1,2,3

7. The formatted functions are getchar() and putcharO.

- True
- False (this is the answer)

8. The allocation of memory in this manner, that is, as and when required in a program is known as

- Dynamic Memory Allocation (this is the answer)

- Static Memory Allocation
- Content Memory Allocation
- None of the above.

9. In _____ sort, each element in the array is examined and inserted into its proper place among the elements that have already been sorted.

- bubble
- insertion (this is the answer)
- binary
- None of the above.

10. The fflush() function flushes out the buffer.

- True (this is the answer)
- False

11. _____is a set of statements, which perform a specific task. It may or may not return a value.

- procedure
- sub procedure
- function (this is the answer)
- None of the above.

12. In _____sort, values of the elements are compared with the value in the adjacent element. In this method, the smaller elements bubble up and at the end, the array is sorted.

- bubble (this is the answer)
- insertion
- binary
- None of the above.

13. rewind() returns the file position at the beginning of the file.

- True
- False (this is the answer)

14. _____writes a character to a file.

- fputc() (this is the answer)
- fgetc()
- fread()
- write()

15. A _____provides a way of accessing a variable without referring to the variable directly.

- Pointer (this is the answer)

- Structure
- Array
- None of the above

16. The feof() function is used to indicate end-of-file when the file is opened for binary operation.

- True (this is the answer)
- False

17. The remove() function erases the specified _____

- File (this is the answer)
- Contents of the file
- Directory
- None of the above