1. A _____can appear between the characters in string values to make code more comprehensible.

- White space (this is the answer)
- Solidus
- Backspace
- Reverse solidus

2. Which of the following MIME type is the unofficial one for JSON?

- text/json
- document/json
- text/javascript (this is the answer)
- application/json

3. Which of the following function resolves the XSS and CSRF issues?

- jsoneval()
- jsonparse()
- jsonstring() false
- jsonify() (this is the answer)

4. Which of the following solutions are useful to process JSON data securely? (multiple choices)

- Using JSON2 parse
- Using the jsonstring() method
- Using JSON-RPC (this is the answer)
- Using XMLHttRequests (this is the answer)

5. Which of the following Gson methods are useful for implementing JSON? (multiple choices)

- json_encode() (this is the answer)
- toJson() (this is the answer)
- fromJson() (this is the answer)
- json_decode() (this is the answer)

6. Which of the following is a drawback of a document-oriented database?

- Tight coupling (this is the answer)
- Abstraction between logical and physical data
- Normalization
- Partial document navigation

7. A series of zero or other Unicode characters within double quotes and backslash escapes is termed as _____

- Array
- String (this is the answer)
- Object

- Number

8. _____ accepts data in the form of key and value pairs and each key is distinct.

- Vector
- Set
- List
- Map (this is the answer)

9. The following are steps to create Internal DTDs. Can you arrange them in order?

1. Declare all the possible elements
2. Declare all the possible element attributes
3. Set the attribute data types and values.
4. Declare all the possible entities.
5. Set the order in which elements must appear.
6. Specify the permissible element children, if any.

- 1,2,3,4,5,6
- 2,3,5,4,1,6
- 1,6,5,2,3,4 (this is the answer)
- 5,3,6,1,2,4