

AUTOMATIC SHRINK WRAPPING MACHINE

SWM 50 | SWM 100



Max. Conv. Strokes*

80

Cycles/Minutes

IDEAL FOR

- Companies / Traders who want to wrap variety of products

ADVANTAGES

- Continuous wrapping motion without stopping machine
- Consistent wrapping performance
- Easy to operate & low in maintenance
- Lower heat loss to surroundings
- High thickness (50+ μm) sealing capabilities at higher speed
- Save 1000 recipes of product in PLC for quick job change
- Less wastage
- Savings in man power cost

REC. ADD-ONS

- Different Infeed Conveyors
- Insertion Unit
- Drive Roll Conveyor
- Free Roll Conveyor

Technical Specification

Model	SWM 50	SWM 100
Packing Capacity* (cycles/minute)	50	80
Packaging Product Size (mm) (L x W x H)	75-1000 x 80-400 x 5-180 (W + H \leq 480)	75-1000 x 80-400 x 5-180 (W + H \leq 480)
Max. Film Reel Diameter (mm)	300	300
Front Sealing Blade Size (mm)	500	500
Max. Film Width (mm)	610	610
Film Type	POF & LDPE	POF & LDPE
Sealing Blade Temperature($^{\circ}\text{C}$)	180-210	180-210
Rec. Floor Space (L x W x H) (meter)	13 X 6 X 4	13 X 6 X 4

* Depends upon product size, product type, Film type & thickness.

* Rec. Floor Space is considered for offline machine.

END PRODUCT

