

Docker

1. Creating and Using Containers

- Check versions of our docker cli and engine
 - Create a Nginx (web server) container
 - Common container management commands
 - Docker Networking Basics
-

2. Docker Commands

- ***docker version***

This command simply returns the version of our client and the server (also called the engine) which runs in the background on our machine - called a daemon on macOS. Our docker command line is actually talking to the server on the machine and returning its values as well as the client's values.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker version
Client: Docker Engine - Community
  Version:           19.03.8
  API version:      1.40
  Go version:       go1.12.17
  Git commit:       afacb8b
  Built:            Wed Mar 11 01:21:11 2020
  OS/Arch:          darwin/amd64
  Experimental:    true

Server: Docker Engine - Community
  Engine:
    Version:          19.03.8
    API version:     1.40 (minimum version 1.12)
    Go version:      go1.12.17
    Git commit:      afacb8b
    Built:           Wed Mar 11 01:29:16 2020
    OS/Arch:          linux/amd64
    Experimental:   true
    containerd:
      Version:        v1.2.13
      GitCommit:      7ad184331fa3e55e52b890ea95e65ba581ae3429
    runc:
      Version:        1.0.0-rc10
      GitCommit:      dc9208a3303feef5b3839f4323d9beb36df0a9dd
    docker-init:
      Version:        0.18.0
      GitCommit:      fec3683
```

- **docker info**

This command returns a lot more stuff than just the version. It'll actually give us a lot of details about our configuration and setup for our engine.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker info
Client:
  Debug Mode: false
  Plugins:
    app: Docker Application (Docker Inc., v0.8.0)
    buildx: Build with BuildKit (Docker Inc., v0.3.1-tp-docker)

Server:
  Containers: 0
    Running: 0
    Paused: 0
    Stopped: 0
  Images: 0
  Server Version: 19.03.8
  Storage Driver: overlay2
    Backing Filesystem: <unknown>
    Supports d_type: true
    Native Overlay Diff: true
  Logging Driver: json-file
  Cgroup Driver: cgroupfs
  Plugins:
    Volume: local
    Network: bridge host ipvlan macvlan null overlay
    Log: awslogs fluentd gcplogs gelf journalctl json-file local logentries splunk syslog
  Swarm: inactive
  Runtimes: runc
  Default Runtime: runc
  Init Binary: docker-init
  containerd version: 7ad184331fa3e55e52b890ea95e65ba581ae3429
  runc version: dc9208a3303feef5b3839f4323d9beb36df0a9dd
  init version: fec3683
  Security Options:
    seccomp
      Profile: default
  Kernel Version: 4.19.76-linuxkit
  Operating System: Docker Desktop
  OSType: linux
  Architecture: x86_64
  CPUs: 2
  Total Memory: 3.848GiB
  Name: docker-desktop
  ID: 6UPS:2KP3:FQBB:LDQL:4TYV:FLBN:G306:2V03:3KE6:AJBX:JKWM:DITI
  Docker Root Dir: /var/lib/docker
  Debug Mode: true
    File Descriptors: 37
    Goroutines: 43
    System Time: 2020-06-06T21:41:09.570812627Z
    EventsListeners: 3
  HTTP Proxy: gateway.docker.internal:3128
  HTTPS Proxy: gateway.docker.internal:3129
  Registry: https://index.docker.io/v1/
  Labels:
```

Cd

- **docker**

This returns a list of all the commands we can use in Docker.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker
Usage: docker [OPTIONS] COMMAND
      A self-sufficient runtime for containers

Options:
  --config string        Location of client config files (default "/Users/hetanshmehta/.docker")
  -c, --context string   Name of the context to use to connect to the daemon (overrides DOCKER_HOST env var and default context set with "docker context use")
  -D, --debug             Enable debug mode
  -H, --host list         Daemon socket(s) to connect to
  -l, --log-level string  Set the logging level ("debug"|"info"|"warn"|"error"|"fatal") (default "info")
  --tls                  Use TLS; implied by --tlsv1.2
  --tlscacert string     Trust certs signed only by this CA (default "/Users/hetanshmehta/.docker/ca.pem")
  --tlscert string        Path to TLS certificate file (default "/Users/hetanshmehta/.docker/cert.pem")
  --tlskey string          Path to TLS key file (default "/Users/hetanshmehta/.docker/key.pem")
  --tlsv1.2                Use TLS and verify the remote
  -v, --version            Print version information and quit

Management Commands:
  app*      Docker Application (Docker Inc., v0.8.0)
  builder   Manage builds
  buildx*   Build with BuildKit (Docker Inc., v0.3.1-tp-docker)
  checkpoint Manage checkpoints
  config    Manage Docker configs
  container Manage containers
  context   Manage contexts
  image     Manage images
  manifest  Manage Docker image manifests and manifest lists
  network   Manage networks
  node      Manage Swarm nodes
  plugin    Manage plugins
  secret    Manage Docker secrets
  service   Manage services
  stack     Manage Docker stacks
  swarm     Manage Swarm
  system    Manage Docker
  trust     Manage trust on Docker images
  volume   Manage volumes

Commands:
  attach    Attach local standard input, output, and error streams to a running container
  build     Build an image from a Dockerfile
  commit   Create a new image from a container's changes
  cp       Copy files/folders between a container and the local filesystem
  create   Create a new container
  deploy   Deploy a new stack or update an existing stack
  diff     Inspect changes to files or directories on a container's filesystem
  events   Get real time events from the server
  exec     Run a command in a running container
  export   Export a container's filesystem as a tar archive
```

Syntax for docker management commands:

NEW: *docker <management-command> <sub-command> (options)*

OLD: *docker <command> (options)*

3. Starting a Nginx Web Server

- Image vs. Container
- Run/Stop/Remove Containers
- Check container logs and processes

3.1. Image vs Container

- An **image** is the binaries and libraries and source code that make up our application, i.e., image is the application we want to run.
- A **container** is the running instance of the image. We can have many containers based off the same image.

We're going to use the Open Source Nginx web server. So we'll be starting our containers based off that Nginx image. We get all our images from registries.

Docker's default image registry is called **Docker Hub** (hub.docker.com)

3.2. Run/Stop/Remove Container


- **`docker container run -publish 80:80 nginx`**

- Downloads image 'nginx' from Docker Hub
- Starts a new container from the image
- Opens port 80 on the host IP (local machine) and sends all traffic from it to the executable running inside that container on the container (container IP) on port 80.
- Since Nginx is a web server, the traffic just forwards automatically through the web browser to the localhost and into that container

Note that we'll get a "bind" error if the left number (host port) is being used by anything else, even another container. We can use any port we want on the left, like **8080:80** or **8888:80**, then use **localhost:8888** when testing.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container run --publish 80:80 nginx
Unable to find image 'nginx:latest' locally
latest: Pulling from library/nginx
afb6ec6fdc1c: Pull complete
dd3ac8106a0b: Pull complete
8de28bdda69b: Pull complete
a2c431ac2669: Pull complete
e070d03fd1b5: Pull complete
Digest: sha256:c870bf53de0357813af37b9500cb1c2ff9fb4c00120d5fe1d75c21591293c34d
Status: Downloaded newer image for nginx:latest
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
```

Switch over to a web browser, and type **localhost**.



Saturday, June 6, 2020

Our Nginx server is listening.

We can hit refresh several times and we'll see the log entries in our command line.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container run --publish 80:80 nginx
Unable to find image 'nginx:latest' locally
latest: Pulling from library/nginx
a1b6ec6fdclc: Pull complete
dd3a8106a0b: Pull complete
8de28bdda69b: Pull complete
a2c431ac2699: Pull complete
e070d03fd1b5: Pull complete
Digest: sha256:c870b753de0357813af37b9500cb1c2ff9fb4c00120d5fe1d75c21591293c34d
Status: Downloaded newer image for nginx:latest
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: Getting the checksum of /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
172.17.0.1 - - [06/Jun/2020:22:51:01 +0000] "GET / HTTP/1.1" 200 612 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
2020/06/06 22:51:01 [error] 30#30: *2 open() "/usr/share/nginx/html/favicon.ico" failed (2: No such file or directory), client: 172.17.0.1, server: localhost, request: "GET /favicon.ico HTTP/1.1", host: "localhost", referer: "http://localhost/"
172.17.0.1 - - [06/Jun/2020:22:51:01 +0000] "GET /favicon.ico HTTP/1.1" 404 153 "http://localhost/" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
172.17.0.1 - - [06/Jun/2020:22:51:26 +0000] "GET / HTTP/1.1" 200 612 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
172.17.0.1 - - [06/Jun/2020:22:53:15 +0000] "GET / HTTP/1.1" 200 612 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
172.17.0.1 - - [06/Jun/2020:22:53:16 +0000] "GET / HTTP/1.1" 200 612 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
```

But we don't always want this running in the foreground inside of our command line.

- ***docker container run --publish 80:80 --detach nginx***

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container run --publish 80:80 --detach nginx
dab0d9a7e0b5f38f3c6a2c644a2ad193e4c3fc52296f828c3a87bcd1dde572a0
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

The **detach** tells Docker to run it in the background. And we get back the unique **container ID** of our container. Every time we run a new container, we get a new container ID.

- ***docker container ls***

Command to list all our containers. And we'll see the one that's still running here.
Only shows the running containers.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container ls
CONTAINER ID        IMAGE               COMMAND                  CREATED             STATUS              PORTS                 NAMES
dab0d9a7e0b5        nginx              "/docker-entrypoint..."   About an hour ago   Up About an hour   0.0.0.0:80->80/tcp   confident_robinson
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

- ***docker container stop <container_ID>***

Stops the container matching the container id.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container stop dab0d
dab0d
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

Now when we list our containers, nothing shows up as no containers are running.

- ***docker container ls -a***

- When we ran each time the docker container run command, it started a new container from that Nginx image. One the right we notice that there's these random names which we didn't use.
- The container IDs and the names are required to be **unique** and if we don't specify it, then it will be created for us. We can always name something ourselves, or let it pick one on its own.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container ls -a
CONTAINER ID        IMAGE               COMMAND                  CREATED             STATUS              PORTS                 NAMES
dab0d9a7e0b5        nginx              "/docker-entrypoint..."   About an hour ago   Exited (0) 2 minutes ago
4bd9cf156353        nginx              "/docker-entrypoint..."   2 hours ago       Exited (0) About an hour ago
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

- Start a new container under **detach** mode. Open the web browser and type **localhost**. Refresh it a few times.
- By running in detached mode, we are able to have access to our command line when the container spins up and runs. Without it, we would have logs constantly fed onto the screen.

- **`docker container run --publish 80:80 --detach --name webhost nginx`**

Creates a new container with name **webhost**.

- **`docker container logs <container_name>`**

It spits out the latest logs in the web host./

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container run --publish 80:80 --detach --name webhost nginx
d42da8ec7b15bc1b6f4ba1ac54590b0f2e3a399f79ce2b46a0cf4493ca5d66a
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container ls
CONTAINER ID        IMAGE               COMMAND             CREATED            STATUS              PORTS               NAMES
d42da8ec7b15        nginx              "/docker-entrypoint.."   6 seconds ago     Up 5 seconds          0.0.0.0:80->80/tcp   webhost
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container ls -a
CONTAINER ID        IMAGE               COMMAND             CREATED            STATUS              PORTS               NAMES
d42da8ec7b15        nginx              "/docker-entrypoint.."   15 seconds ago    Up 14 seconds         0.0.0.0:80->80/tcp   webhost
dabd9a7e0b5         nginx              "/docker-entrypoint.."   2 hours ago       Exited (0) 49 minutes ago   confident_robinson
4bd9cf156353       nginx              "/docker-entrypoint.."   3 hours ago       Exited (0) 2 hours ago   crazy_antonelli
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container logs webhost
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
172.17.0.1 - - [07/Jun/2020:01:27:59 +0000] "GET / HTTP/1.1" 200 612 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
172.17.0.1 - - [07/Jun/2020:01:28:00 +0000] "GET / HTTP/1.1" 200 612 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
172.17.0.1 - - [07/Jun/2020:01:28:00 +0000] "GET / HTTP/1.1" 200 612 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
172.17.0.1 - - [07/Jun/2020:01:28:01 +0000] "GET / HTTP/1.1" 200 612 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
172.17.0.1 - - [07/Jun/2020:01:28:01 +0000] "GET / HTTP/1.1" 200 612 "-" "Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_4) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/13.1 Safari/605.1.15"
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

- **`docker container top <container_name>`**

Helps to identify the processes running inside the container. In case of Nginx, there's actually a master process and then it spawns worker processes based on the configuration.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container top webhost
PID      USER      TIME      COMMAND
2109      root      0:00      nginx: master process nginx -g daemon off;
2164      101      0:00      nginx: worker process
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

- ***docker container --help***

Get a list of commands we could try on that container

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container --help

Usage: docker container COMMAND

Manage containers

Commands:
  attach      Attach local standard input, output, and error streams to a running container
  commit      Create a new image from a container's changes
  cp          Copy files/folders between a container and the local filesystem
  create      Create a new container
  diff        Inspect changes to files or directories on a container's filesystem
  exec        Run a command in a running container
  export      Export a container's filesystem as a tar archive
  inspect    Display detailed information on one or more containers
  kill        Kill one or more running containers
  logs       Fetch the logs of a container
  ls          List containers
  pause      Pause all processes within one or more containers
  port        List port mappings or a specific mapping for the container
  prune      Remove all stopped containers
  rename     Rename a container
  restart    Restart one or more containers
  rm          Remove one or more containers
  run         Run a command in a new container
  start      Start one or more stopped containers
  stats      Display a live stream of container(s) resource usage statistics
  stop       Stop one or more running containers
  top         Display the running processes of a container
  unpause    Unpause all processes within one or more containers
  update     Update configuration of one or more containers
  wait       Block until one or more containers stop, then print their exit codes

Run 'docker container COMMAND --help' for more information on a command.
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

We will now try to remove our containers. To list the containers, we can type in

docker container ls -a

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container ls -a
CONTAINER ID        IMAGE               COMMAND             CREATED            STATUS              PORTS               NAMES
d42da8ec7b15        nginx              "/docker-entrypoint..."   58 minutes ago    Up 58 minutes        0.0.0.0:80->80/tcp   webhost
dab0d9a7e0b5        nginx              "/docker-entrypoint..."   3 hours ago       Exited (0) 2 hours ago   confident_robinson
4bd9cf156353        nginx              "/docker-entrypoint..."   3 hours ago       Exited (0) 3 hours ago   crazy_antonelli
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

- **`docker container rm <container_ID_1> <container_ID_2> ... <container_ID_n>`**

Remove all the 3 containers at the same time.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container rm d42da dab0d 4bd9c  
dab0d  
4bd9c  
Error response from daemon: You cannot remove a running container d42da8ec7b15bc1b6f4ba01ec54590b0f2e3a399f79ce2b46a0cf4493ca5d66a. Stop the container before attempting removal or force remove  
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

We got an error. The first two were safely deleted. We cannot remove a running container because it's a safety measure. It makes sure that we don't accidentally remove the actual process that's still running.

We can simply stop the container first and then remove it. Alternatively,

- **`Docker container rm -f <container_ID>`**

-f is for force. We will forcefully remove our active container.

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container rm -f d42da  
d42da  
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ %
```

All our containers have been cleaned.

4. What happens when we run a Container?

When we type **`docker container run`**, in the background it's actually going to look for the image that we specified at the end of the command.

When we typed nginx at the very end, that was the name of the image we wanted to run as a new container.

1. Looks for that image locally in image cache, doesn't find anything
2. Then looks in remote image repository (defaults to Docker Hub)
3. Downloads the latest version (nginx: latest version by default) and stores it in the image cache.
4. Creates new container based on that image. It's not going to make a copy of the image. It's actually going to just start a new layer of changes, right on top of where that image left off.
5. It's going to customize the networking - give it a specific virtual IP address that's inside a Docker virtual network. Gives it a virtual IP on a private network inside docker engine.
6. Opens up port we specified on host and forwards to port 80 in container. If we didn't specify the **Publish** command, i.e., **--publish**, it's not going to open up any ports at all. Since we did the **80:80**, that's telling it to take the port 80 on the host and forward all that traffic to the port 80 in the container.
7. The container finally starts by using the command (CMD) specified in the Dockerfile.



5. Containers vs VM

Often people compare containers to VMs. True, there are some similarities, but there's so many things that aren't the same.

But actually, containers are really just a process running on your host operating system and are nothing like a virtual machine.

A few useful links:

- 1) [https://github.com/mikegcoleman/docker101/blob/master/
Docker eBook Jan 2017.pdf](https://github.com/mikegcoleman/docker101/blob/master/Docker%20eBook%20Jan%202017.pdf)
- 2) [https://www.youtube.com/watch?v=sK5i-
N34im8&feature=youtu.be&list=PLBmVKD7o3L8v7KI_XXh3KaJl9Qw2lyuFl](https://www.youtube.com/watch?v=sK5i-N34im8&feature=youtu.be&list=PLBmVKD7o3L8v7KI_XXh3KaJl9Qw2lyuFl)

Assignment 1

Assignment: Manage Multiple Containers

- docs.docker.com and `--help` are your friend
- Run a `nginx`, a `mysql`, and a `httpd` (apache) server
- Run all of them `--detach` (or `-d`), name them with `--name`
- `nginx` should listen on `80:80`, `httpd` on `8080:80`, `mysql` on `3306:3306`
- When running `mysql`, use the `--env` option (or `-e`) to pass in `MYSQL_RANDOM_ROOT_PASSWORD=yes`
- Use `docker container logs` on `mysql` to find the random password it created on startup
- Clean it all up with `docker container stop` and `docker container rm` (both can accept multiple names or ID's)
- Use `docker container ls` to ensure everything is correct before and after cleanup

Solution:

Initializing containers:

```
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container run -d -p 80:80 --name nginxServer nginx
d4f7cb3401c4403c19a3ee9239671d944c5bdb39e49cf58b8295b90c95a3b601
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container run -d -p 8080:80 --name apacheServer httpd
72794e168334ca8f367ce9140184ef015cbe099721e48aecbfbd9096b91c1d86
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker container run -d -p 3306:3306 --name sqlServer --env MYSQL_RANDOM_ROOT_PASSWORD=yes mysql
771db4b77aa21e72779135d24aceb146a8c186a873d11dec916d05d7c150a8a
(base) hetanshmehta@Hetanshs-MacBook-Pro ~ % docker ps
CONTAINER ID        IMAGE               COMMAND             CREATED            STATUS              PORTS                         NAMES
771db4b77aa2        mysql              "docker-entrypoint.s..."   3 seconds ago      Up 3 seconds       0.0.0.0:3306->3306/tcp, 33060/tcp   sqlServer
72794e168334        httpd              "httpd-foreground"    About a minute ago  Up About a minute  0.0.0.0:8080->80/tcp                  apacheServer
d4f7cb3401c4        nginx              "/docke...r-entrypoint..."  About a minute ago  Up About a minute  0.0.0.0:80->80/tcp                  nginxServer
```

SQL Password from logs:

```
(base) hetanshmehta@Metanshs-MacBook-Pro ~ % docker container logs sqlServer
2020-06-07 05:44:58+00:00 [Note] [Entrypoint]: Entrypoint script for MySQL Server 8.0.20-1debian10 started.
2020-06-07 05:44:58+00:00 [Note] [Entrypoint]: Switching to dedicated user 'mysql'.
2020-06-07 05:44:58+00:00 [Note] [Entrypoint]: Entrypoint script for MySQL Server 8.0.20-1debian10 started.
2020-06-07 05:44:58+00:00 [Note] [Entrypoint]: Initializing database files
2020-06-07T05:44:58.536493Z 0 [Warning] [MY-011070] [Server] 'Disabling symbolic links using --skip-symbolic-links (or equivalent) is the default. Consider not using this option as it's deprecated and will be removed in a future release.
2020-06-07T05:44:58.536536Z 0 [System] [MY-013169] [Server] /usr/sbin/mysqld (mysqld 8.0.20) initializing of server in progress as process 42
2020-06-07T05:44:58.542956Z 1 [System] [MY-013576] [InnoDB] InnoDB initialization has started.
2020-06-07T05:44:59.193183Z 1 [System] [MY-013577] [InnoDB] InnoDB initialization has ended.
2020-06-07T05:44:58.593649Z 0 [Warning] [MY-010453] [Server] root@localhost is created with an empty password ! Please consider switching off the --initialize-insecure option.
2020-06-07 05:45:04+00:00 [Note] [Entrypoint]: Database files initialized
2020-06-07T05:45:04.500863Z 0 [Note] [Entrypoint]: Starting temporary server
2020-06-07T05:45:04.504586Z 0 [Warning] [MY-011070] [Server] 'Disabling symbolic links using --skip-symbolic-links (or equivalent) is the default. Consider not using this option as it's deprecated and will be removed in a future release.
2020-06-07T05:45:04.958992Z 0 [System] [MY-010116] [Server] /usr/sbin/mysqld (mysqld 8.0.20) starting as process 89
2020-06-07T05:45:04.983752Z 1 [System] [MY-013576] [InnoDB] InnoDB initialization has started.
2020-06-07T05:45:05.324627Z 1 [System] [MY-013577] [InnoDB] InnoDB initialization has ended.
2020-06-07T05:45:05.542768Z 0 [System] [MY-011323] [Server] X Plugin ready for connections. Socket: '/var/run/mysqld/mysql.sock'
2020-06-07T05:45:05.796932Z 0 [Warning] [MY-010068] [Server] CA certificate ca.pem is self signed.
2020-06-07T05:45:05.801049Z 0 [Warning] [MY-011810] [Server] Insecure configuration for --pid-file: Location '/var/run/mysqld' in the path is accessible to all OS users. Consider choosing a different directory.
2020-06-07T05:45:05.849141Z 0 [System] [MY-010931] [Server] /usr/sbin/mysqld: ready for connections. Version: '8.0.20' socket: '/var/run/mysqld/mysqld.sock' port: 0 MySQL Community Server - GPL
2020-06-07 05:45:05:45+00:00 [Note] [Entrypoint]: Temporary server started.
Warning: Unable to load '/usr/share/zoneinfo/iso3166.tab' as time zone. Skipping it.
Warning: Unable to load '/usr/share/zoneinfo/leap-seconds.list' as time zone. Skipping it.
Warning: Unable to load '/usr/share/zoneinfo/zone.tab' as time zone. Skipping it.
Warning: Unable to load '/usr/share/zoneinfo/zone1970.tab' as time zone. Skipping it.
2020-06-07 05:45:11+00:00 [Note] [Entrypoint]: GENERATED ROOT PASSWORD: oelLshouxiie4ne02chathe9Ahoewohlee
2020-06-07 05:45:11+00:00 [Note] [Entrypoint]: Stopping temporary server
2020-06-07T05:45:11.712895Z 10 [System] [MY-013172] [Server] Received SHUTDOWN from user root. Shutting down mysqld (Version: 8.0.20).
2020-06-07T05:45:13.965371Z 0 [System] [MY-010910] [Server] /usr/sbin/mysqld: Shutdown complete (mysqld 8.0.20) MySQL Community Server - GPL.
2020-06-07 05:45:14+00:00 [Note] [Entrypoint]: Temporary server stopped
2020-06-07 05:45:14+00:00 [Note] [Entrypoint]: MySQL init process done. Ready for start up.
2020-06-07T05:45:14.981068Z 0 [Warning] [MY-011070] [Server] 'Disabling symbolic links using --skip-symbolic-links (or equivalent) is the default. Consider not using this option as it's deprecated and will be removed in a future release.
2020-06-07T05:45:14.981230Z 0 [System] [MY-010116] [Server] /usr/sbin/mysqld (mysqld 8.0.20) starting as process 1
2020-06-07T05:45:14.990153Z 1 [System] [MY-013576] [InnoDB] InnoDB initialization has started.
2020-06-07T05:45:15.214212Z 1 [System] [MY-013577] [InnoDB] InnoDB initialization has ended.
2020-06-07T05:45:15.393769Z 0 [System] [MY-011323] [Server] X Plugin ready for connections. Socket: '/var/run/mysqld/mysql.sock' bind-address: '::' port: 33060
2020-06-07T05:45:15.429845Z 0 [Warning] [MY-010068] [Server] CA certificate ca.pem is self signed.
2020-06-07T05:45:15.433527Z 0 [Warning] [MY-011810] [Server] Insecure configuration for --pid-file: Location '/var/run/mysqld' in the path is accessible to all OS users. Consider
```

Remove and Clean-Up:

```
(base) hetanshmehta@Metanshs-MacBook-Pro ~ % docker container ls
CONTAINER ID        IMAGE               COMMAND             CREATED            STATUS              PORTS               NAMES
771d4b77da2         mysql              "docker-entrypoint.s..."   5 minutes ago      Up 5 minutes       0.0.0.0:3306->3306/tcp, 33060/tcp          sqlServer
72794e168334        httpd              "httpd-foreground"    6 minutes ago     Up 6 minutes       0.0.0.0:8080->80/tcp                         apacheServer
d4f7cb3401c4        nginx              "/docker-entrypoint..." 7 minutes ago     Up 7 minutes       0.0.0.0:80->80/tcp                         nginxServer
(base) hetanshmehta@Metanshs-MacBook-Pro ~ % docker container stop 771 727 d4f
771
727
d4f
(base) hetanshmehta@Metanshs-MacBook-Pro ~ % docker container rm 771 727 d4f
771
727
d4f
(base) hetanshmehta@Metanshs-MacBook-Pro ~ % docker container ls
CONTAINER ID        IMAGE               COMMAND             CREATED            STATUS              PORTS               NAMES
(base) hetanshmehta@Metanshs-MacBook-Pro ~ %
(base) hetanshmehta@Metanshs-MacBook-Pro ~ % docker container ls -a
CONTAINER ID        IMAGE               COMMAND             CREATED            STATUS              PORTS               NAMES
(base) hetanshmehta@Metanshs-MacBook-Pro ~ %
```