

ПРАВИТЕЛЬСТВО РОССИЙСКОЙ ФЕДЕРАЦИИ
НАЦИОНАЛЬНЫЙ ИССЛЕДОВАТЕЛЬСКИЙ УНИВЕРСИТЕТ
«ВЫСШАЯ ШКОЛА ЭКОНОМИКИ»

Факультет компьютерных наук
Департамент программной инженерии

СОГЛАСОВАНО
Профессор департамента
программной инженерии
факультета компьютерных наук
доктор техн. наук

УТВЕРЖДАЮ
Академический руководитель
образовательной программы
«Программная инженерия»
профессор департамента программной
инженерии, канд. техн. наук

_____ Д.В. Александров
« ____ » _____ 2018 г.

_____ В.В. Шилов
« ____ » _____ 2018 г.

Сервис распознавания лиц для идентификации личности
Сервер

Текст программы
ЛИСТ УТВЕРЖДЕНИЯ
RU.17701729.04.01-01 12 01-1-ЛУ

Исполнитель
студент группы БПИ 143
_____ /Н.О. Константиновский /
« ____ » _____ 2018 г.

Име. № подл	Подп. и дата	Взам. инв. №	Име. № дубл.	Подп. и дата
RU.17701729.04.01-01 12 01-1-ЛУ				

Москва 2018

УТВЕРЖДЕН
RU.17701729.04.0-01 51 01-1-ЛУ

**Сервис распознавания лиц для идентификации личности
Сервер**

Текст программы

RU.17701729.04.01-01 12 01-1

Листов 39

<i>Инв. № подл</i>	<i>Подп. и дата</i>	<i>Взам. инв. №</i>	<i>Инв. № дубл.</i>	<i>Подп. и дата</i>
RU.17701729.04.01-01 12 01-1				

Москва 2018

Содержание

СОДЕРЖАНИЕ	134
1. ТЕКСТ ПРОГРАММЫ	135
1.1. MINDFACESERVICE.PY	135
1.2. CONFIG.PY	137
1.3. PHOTOS.PY.....	140
1.4. PERSONS.PY	145
1.5. LOGIN.PY	147
1.6. MODEL.PY.....	149
1.7. MINDFACEKERASSMALL2V1.PY	149
1.8. FACE_DETECT.PY.....	157
1.9. CLASSIFIER_CONTROLLER.PY	158
1.10. CLASSIFIER.PY	161
1.11. ALIGHNDLIB.PY	162
1.12. SVMBINARYCLASSIFICATOR.PY	165
1.13. DBMODEL.PY	166
1.14. VECTOR.PY	168
1.15. LOAD.PY	169
1.16. IMAGE.PY	170
ЛИСТ РЕГИСТРАЦИИ ИЗМЕНЕНИЙ.....	171

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0112				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

1. ТЕКСТ ПРОГРАММЫ

1.1. MindFaceService.py

```
# coding=utf-8
```

```
import os
```

```
from config import app
```

```
from WebApp.login.login import login_blueprint
```

```
from WebApp.persons.persons import persons_blueprint
```

```
from WebApp.photos.photos import photos_blueprint
```

```
from API.vector.vector import vector_blueprint
```

```
from API.load.load import load_blueprint
```

```
# from API.image.image import image_blueprint
```

```
app.register_blueprint(vector_blueprint)
```

```
app.register_blueprint(load_blueprint)
```

```
# app.register_blueprint(image_blueprint)
```

```
@app.route('/')
```

```
def home():
```

```
    return 'MindFace'
```

```
from flask import flash, redirect, render_template, request, session, abort, escape
```

```
from flask import Blueprint
```

```
import json
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

import io
from PIL import Image
from MLCore.face_detect import rewrite_alignet_resize96_face_image
import numpy as np
from config import config_model, pred_clf
# from MLCore.classifier_controller import pred_clf

from DBEngine.dbmodel import Person

```

```

img = rewrite_alignet_resize96_face_image(np.array(image))

```

```

res = ""
if img is not None:
    res = pred_clf(img)

    query = Person.query.filter_by(person_id=int(res))
    res = query.first()
    res = str(res.name) + ' ' + str(res.surname)

return res

```

```

if __name__ == '__main__':
    config_model()
    app.secret_key = os.urandom(12)
    app.debug = False
    # app.run()
    # app.run(host='192.168.0.105')
    app.run(host='172.20.10.3')

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

1.2. config.py

```
# coding=utf-8
```

```
from flask import Flask
```

```
from MLCore.MindFaceKerasSmall2V1 import create_model
```

```
import numpy as np
```

```
import pickle
```

```
app = Flask(__name__)
```

```
app.config['UPLOAD_FOLDER'] =
```

```
'/Users/apple/Documents/Development/MindFaceProject/MindFaceService/static/uploads/'
```

```
app.config['CELERY_BROKER_URL'] = 'redis://localhost:6379/0'
```

```
app.config['CELERY_RESULT_BACKEND'] = 'redis://localhost:6379/0'
```

```
predictor_face_landmark_model = \
```

```
"/Users/apple/Documents/Development/MindFaceProject/MindFaceService/MLCore/shape_predictor_68_face_landmarks.dat"
```

```
model_path =
```

```
'/Users/apple/Documents/Development/MindFaceProject/MindFaceService/MLCore/MindFaceKerasSmall2V1.h5'
```

```
clf_path =
```

```
'/Users/apple/Documents/Development/MindFaceProject/MindFaceService/MLCore/classifier.sav'
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
clf_path_local =
'/Users/apple/Documents/Development/MindFaceProject/MindFaceService/static/classifier_local.sav'
```

```
MindFaceKerasSmall2V1 = None
main_clf = pickle.load(open(clf_path, 'rb'))
main_clf_local = pickle.load(open(clf_path_local, 'rb'))
```

```
def config_model():
    create_nn()

def pred_clf(img):
    global main_clf

    img = img[..., ::-1]
    img = np.around(img / 255.0, decimals=12)
    img = np.array([img])
    vec = MindFaceKerasSmall2V1.predict(img)

    res = main_clf.predict(vec)
    return res

from DBEngine.dbmodel import Person
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
def pred_clf_vec(vec):
    global main_clf

    res = main_clf.predict([vec])
    # res = main_bin_clf.predict(vec)

    query = Person.query.filter_by(person_id=int(res))
    res = query.first()
    res = str(res.name) + ' ' + str(res.surname)

    return res
```

```
def reload_clf():
    global main_clf
    main_clf = pickle.load(open(clf_path, 'rb'))
```

```
def reload_clf_local():
    global main_clf
    main_clf_local = pickle.load(open(clf_path_local, 'rb'))
```

```
main_bin_clf = None
```

```
def retrain_bin_classifier():
    global main_bin_clf
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата


```

vecs = get_marked_vecs(1)
codes = []
labels = []
for vec in vecs:
    codes.append(vec[0])
    labels.append(vec[1])

main_bin_clf = SVMBinaryClassificator(codes, labels)

for person in Person.query.filter_by(user_id=1):
    person.is_train = True
    db.session.commit()

```

```

def get_marked_vecs(user_id):
    query = Photo.query.join(Photo.persons_list).filter_by(user_id=user_id)\
        .with_entities(Photo.features, Photo.person_id)
    result = query.all()
    return result

```

```
retrain_bin_classifier()
```

1.3. photos.py

```
# coding=utf-8
```

```

from flask import flash, redirect, render_template, request, session, abort, escape
from DBEngine.dbmodel import Photo
from DBEngine.dbmodel import Person
from flask import Blueprint

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
from Model.model import WebPhoto
from MLCore import face_detect
import os
```

```
from config import app
```

```
from DBEngine import db
import random
import string
```

```
photos_blueprint = Blueprint('photos', __name__)
```

```
ALLOWED_EXTENSIONS = set(['png', 'jpg', 'jpeg'])
```

```
return redirect("/persons")
```

```
else:
```

```
if request.args.get('pid') and request.args.get('del'):
```

```
    pid = request.args.get('pid')
```

```
    person_id = request.args.get('id')
```

```
    query = Person.query.filter_by(user_id=session.get('user_id'), person_id=person_id)
```

```
    result = query.first()
```

```
    if result:
```

```
        query = Photo.query.filter_by(person_id=person_id, photo_id=pid)
```

```
        path = query.first().path
```

```
        db.session.query(Photo).filter(Photo.photo_id == pid).delete()
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
db.session.commit()
```

```
path = app.config['UPLOAD_FOLDER'] + str(person_id) + '/' + str(path) + '.png'
```

```
if os.path.exists(path):
```

```
    os.remove(path=path)
```

```
    return redirect("/photos?id=" + person_id)
```

```
else:
```

```
    person_id = escape(request.args.get('id'))
```

```
    query = Person.query.filter_by(user_id=session.get('user_id'), person_id=person_id)
```

```
if result is not None:
```

```
    photos = []
```

```
    i = 1
```

```
    for res in result:
```

```
        path = 'static/uploads/' + str(person_id) + '/' + res.path + '.png'
```

```
        photos.append(WebPhoto(str(i), path, res.is_train, res.photo_id))
```

```
        i += 1
```

```
    return render_template("photos.html", photos=photos, person=person_name,
id=person_id)
```

```
    else:
```

```
        return redirect("/persons")
```

```
else:
```

```
    return redirect("/persons")
```

```
def allowed_file(filename):
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

return '.' in filename and \
    filename.rsplit('.', 1)[1].lower() in ALLOWED_EXTENSIONS

```

```

def random_filename_generator(size=16, chars=string.ascii_uppercase + string.digits):
    return ''.join(random.choice(chars) for x in range(size))

```

```

@photos_blueprint.route("/photos/addphoto", methods=['GET'])

```

```

def add_photo():
    if not session.get('logged_in'):
        return redirect("/login")
    else:
        if not request.args.get('id'):
            return redirect("/photos")
        else:
            id = escape(request.args.get('id'))
            return render_template('addphoto.html', id=id)

```

```

if person_id is " or 'photo' not in request.files:
    flash('No selected file!')
    return redirect("/photos/addphoto?id=" + person_id)
else:
    file = request.files['photo']
    if file.filename == "":
        flash('No selected file')
        return redirect("/photos/addphoto?id=" + person_id)

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
if file and allowed_file(file.filename):
```

```
    query = Person.query.filter_by(user_id=session.get('user_id'), person_id=person_id)
```

```
    result = query.first()
```

```
    if result:
```

```
        filename = random_filename_generator()
```

```
        while Photo.query.filter_by(path=filename).limit(1).first() is not None:
```

```
            filename = random_filename_generator()
```

```
        path = os.path.join(directory, filename+path)
```

```
        file.save(path)
```

```
        face_num = face_detect.face_num(path)
```

```
    if face_num == 1:
```

```
        photo = Photo(filename, person_id)
```

```
        db.session.add(photo)
```

```
        db.session.commit()
```

```
    elif face_num == 0:
```

```
        if os.path.exists(path):
```

```
            os.remove(path=path)
```

```
        flash('No faces on photo!')
```

```
        return redirect("/photos/addphoto?id=" + person_id)
```

```
    else:
```

```
        if os.path.exists(path):
```

```
            os.remove(path=path)
```

```
        flash('More then one face on photo!')
```

```
        return redirect("/photos/addphoto?id=" + person_id)
```

```
    return redirect("/photos?id=" + person_id)
```

```
else:
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

        flash('Incorrect person!')
        return redirect("/photos?id=" + person_id)
    else:
        flash('File not allowed')
        return redirect("/photos/addphoto?id=" + person_id)

```

1.4. persons.py

```
# coding=utf-8
```

```

from DBEngine import db
from config import app
import shutil
import os
from MLCore.classifier_controller import retrain_classifier
from multiprocessing import Pool

persons_blueprint = Blueprint('persons', __name__)

@persons_blueprint.route("/persons", methods=['GET'])
def persons():
    if not session.get('logged_in'):
        return redirect("/login")
    else:
        if request.args.get('id') and request.args.get('del'):
            person_id = request.args.get('id')

            query = Person.query.filter_by(user_id=session.get('user_id'), person_id=person_id)
            result = query.first()

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

if result:

```
db.session.query(Photo).filter(Photo.person_id == result.person_id).delete()
db.session.commit()
db.session.query(Person).filter(Person.person_id == person_id).delete()
db.session.commit()
```

```
path = app.config['UPLOAD_FOLDER'] + str(person_id)
```

```
if os.path.exists(path):
    shutil.rmtree(path=path)
```

```
return redirect("/persons")
```

```
pool = Pool(processes=1) # Start a worker processes.
```

```
# pool.apply_async(retrain_classifier, [session.get('user_id')])
retrain_classifier(session.get('user_id'))
```

```
return redirect("/persons")
```

else:

```
query = Person.query.filter_by(user_id=session.get('user_id'))
result = query.all()
```

if result is not None:

```
persons = []
i = 1
for res in result:
    persons.append(WebPerson(str(i), res.name, res.surname, res.is_train, res.person_id))
    i += 1
query = Classifier.query.filter_by(user_id=session.get('user_id'))
result = query.first()
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

    return render_template("persons.html", persons=persons, is_ready=result.is_ready)
else:
    return redirect("/login")

```

```

@persons_blueprint.route("/persons/addperson", methods=['GET'])
def add_person():
    if not session.get('logged_in'):
        return redirect("/login")
    else:
        return render_template('addperson.html')

```

```

name = str(escape(request.form['name']))
surname = str(escape(request.form['surname']))

```

```

if name is " or surname is ":
    flash('fill all fields!')
    return redirect("/persons/addperson")
else:
    person = Person(name=name, surname=surname, user_id=session['user_id'])
    db.session.add(person)
    db.session.commit()
    return redirect("/persons")

```

1.5. login.py

```
# coding=utf-8
```

```

from flask import flash, redirect, render_template, request, session, abort
from DBEngine.dbmodel import User

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата


```
from flask import Blueprint
```

```
login_blueprint = Blueprint('login', __name__)
```

```
@login_blueprint.route("/login", methods=['GET'])
```

```
def login():
```

```
    if not session.get('logged_in'):
```

```
        return render_template('login.html')
```

```
    else:
```

```
        return redirect("/persons")
```

```
POST_PASSWORD)
```

```
    result = query.first()
```

```
    if result:
```

```
        session['logged_in'] = True
```

```
        session['user_id'] = int(result.user_id)
```

```
        session['username'] = result.username
```

```
    else:
```

```
        flash('Wrong password!')
```

```
    return login()
```

```
@login_blueprint.route("/logout")
```

```
def logout():
```

```
    session['logged_in'] = False
```

```
    return login()
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

1.6. model.py

```
# coding=utf-8
```

```
class WebPerson:
```

```
    num = str()
```

```
    name = str()
```

```
    surname = str()
```

```
    is_train = bool()
```

```
    id = int()
```

```
    self.id = id
```

```
class WebPhoto:
```

```
    num = str()
```

```
    path = str()
```

```
    is_train = bool()
```

```
    id = str()
```

```
def __init__(self, num, path, is_train, id):
```

```
    self.num = num
```

```
    self.path = path
```

```
    self.is_train = is_train
```

```
    self.id = id
```

1.7. MindFaceKerasSmall2V1.py

```
from keras.layers import Activation
```

```
from keras.layers import AveragePooling2D
```

```
from keras.layers import BatchNormalization
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

from keras.layers import Convolution2D
from keras.layers import Dense
from keras.layers import Input
from keras.layers import Lambda
from keras.layers import MaxPooling2D
from keras.layers import Reshape
from keras.layers import ZeroPadding2D
from keras.layers import concatenate
from keras.models import Model

from MLCore.Torch2KerasConverter.utils import lrn, sqrt, square, mulConstant, l2Normalize

def create_model():
    inp = Input(shape=(96, 96, 3))
    x = ZeroPadding2D(padding=(3, 3))(inp)
    x = Convolution2D(64, (7, 7), strides=(2, 2))(x)
    x = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(x)
    x = Activation('relu')(x)
    x = ZeroPadding2D(padding=(1, 1))(x)
    x = Convolution2D(192, (3, 3), strides=(1, 1))(x)
    x = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(x)
    x = Activation('relu')(x)
    x = Lambda(lrn, arguments={'size': 5, 'alpha': 0.0001, 'beta': 0.75})(x)
    x = ZeroPadding2D(padding=(1, 1))(x)
    x = MaxPooling2D(pool_size=(3, 3), strides=(2, 2))(x)

```

Inception module

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
inception_0 = Convolution2D(96, (1, 1), strides=(1, 1))(x)
```

```
inception_1 = Convolution2D(16, (1, 1), strides=(1, 1))(x)
```

```
inception_1 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_1)
```

```
inception_1 = Activation('relu')(inception_1)
```

```
inception_1 = ZeroPadding2D(padding=(2, 2))(inception_1)
```

```
inception_1 = Convolution2D(32, (5, 5), strides=(1, 1))(inception_1)
```

```
inception_1 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_1)
```

```
inception_1 = Activation('relu')(inception_1)
```

```
inception_2 = MaxPooling2D(pool_size=(3, 3), strides=(2, 2))(x)
```

```
inception_2 = Convolution2D(32, (1, 1), strides=(1, 1))(inception_2)
```

```
inception_2 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_2)
```

```
inception_2 = Activation('relu')(inception_2)
```

```
inception_2 = ZeroPadding2D(padding=((3, 4), (3, 4)))(inception_2)
```

```
inception_3 = Convolution2D(64, (1, 1), strides=(1, 1))(x)
```

```
inception_3 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_3)
```

```
inception_3 = Activation('relu')(inception_3)
```

```
x = concatenate([inception_0, inception_1, inception_2, inception_3, ], axis=3)
```

```
# Inception module
```

```
inception_0 = Convolution2D(96, (1, 1), strides=(1, 1))(x)
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
inception_0 = Activation('relu')(inception_0)
inception_0 = ZeroPadding2D(padding=(1, 1))(inception_0)
inception_0 = Convolution2D(128, (3, 3), strides=(1, 1))(inception_0)
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
inception_0 = Activation('relu')(inception_0)

```

```

inception_1 = Activation('relu')(inception_1)

```

```

inception_2 = Lambda(square)(x)
inception_2 = AveragePooling2D(pool_size=(3, 3), strides=(3, 3))(inception_2)
inception_2 = Lambda(mulConstant, arguments={'const': 9})(inception_2)
inception_2 = Lambda(sqrt)(inception_2)
inception_2 = Convolution2D(64, (1, 1), strides=(1, 1))(inception_2)
inception_2 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_2)
inception_2 = Activation('relu')(inception_2)
inception_2 = ZeroPadding2D(padding=((4, 4), (4, 4)))(inception_2)

```

```

inception_3 = Convolution2D(64, (1, 1), strides=(1, 1))(x)
inception_3 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_3)
inception_3 = Activation('relu')(inception_3)

```

```

x = concatenate([inception_0, inception_1, inception_2, inception_3, ], axis=3)

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

Inception module

```
inception_0 = Convolution2D(128, (1, 1), strides=(1, 1))(x)
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
inception_0 = Activation('relu')(inception_0)
inception_0 = ZeroPadding2D(padding=(1, 1))(inception_0)
inception_0 = Convolution2D(256, (3, 3), strides=(2, 2))(inception_0)
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
inception_0 = Activation('relu')(inception_0)
```

```
inception_1 = Activation('relu')(inception_1)
```

```
inception_2 = MaxPooling2D(pool_size=(3, 3), strides=(2, 2))(x)
inception_2 = ZeroPadding2D(padding=((0, 1), (0, 1)))(inception_2)
```

```
x = concatenate([inception_0, inception_1, inception_2, ], axis=3)
```

Inception module

```
inception_0 = Convolution2D(96, (1, 1), strides=(1, 1))(x)
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
inception_0 = Activation('relu')(inception_0)
inception_0 = ZeroPadding2D(padding=(1, 1))(inception_0)
inception_0 = Convolution2D(192, (3, 3), strides=(1, 1))(inception_0)
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
inception_0 = Activation('relu')(inception_0)
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

inception_1 = Convolution2D(32, (1, 1), strides=(1, 1))(x)
inception_1 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_1)
inception_1 = Activation('relu')(inception_1)
inception_1 = ZeroPadding2D(padding=(2, 2))(inception_1)
inception_1 = Convolution2D(64, (5, 5), strides=(1, 1))(inception_1)
inception_1 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_1)
inception_1 = Activation('relu')(inception_1)

```

```

inception_2 = Lambda(squero)(x)

```

```

inception_2 = ZeroPadding2D(padding=((2, 2), (2, 2)))(inception_2)

```

```

inception_3 = Convolution2D(256, (1, 1), strides=(1, 1))(x)
inception_3 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_3)
inception_3 = Activation('relu')(inception_3)

```

```

x = concatenate([inception_0, inception_1, inception_2, inception_3, ], axis=3)

```

```

# Inception module

```

```

inception_0 = Convolution2D(160, (1, 1), strides=(1, 1))(x)
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
inception_0 = Activation('relu')(inception_0)
inception_0 = ZeroPadding2D(padding=(1, 1))(inception_0)
inception_0 = Convolution2D(256, (3, 3), strides=(2, 2))(inception_0)
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
inception_0 = Activation('relu')(inception_0)
```



```
inception_1 = Activation('relu')(inception_1)
```

```
inception_2 = MaxPooling2D(pool_size=(3, 3), strides=(2, 2))(x)
```

```
inception_2 = ZeroPadding2D(padding=((0, 1), (0, 1)))(inception_2)
```

```
x = concatenate([inception_0, inception_1, inception_2, ], axis=3)
```

```
# Inception module
```

```
inception_0 = Convolution2D(96, (1, 1), strides=(1, 1))(x)
```

```
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
```

```
inception_0 = Activation('relu')(inception_0)
```

```
inception_0 = ZeroPadding2D(padding=(1, 1))(inception_0)
```

```
inception_0 = Convolution2D(384, (3, 3), strides=(1, 1))(inception_0)
```

```
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
```

```
inception_0 = Activation('relu')(inception_0)
```

```
inception_1 = Lambda(square)(x)
```

```
inception_1 = AveragePooling2D(pool_size=(3, 3), strides=(3, 3))(inception_1)
```

```
inception_1 = Lambda(mulConstant, arguments={'const': 9})(inception_1)
```

```
inception_1 = Lambda(sqrt)(inception_1)
```

```
inception_1 = Convolution2D(96, (1, 1), strides=(1, 1))(inception_1)
```

```
inception_1 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_1)
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата


```
inception_1 = Activation('relu')(inception_1)
inception_1 = ZeroPadding2D(padding=((1, 1), (1, 1)))(inception_1)
```

```
inception_2 = Convolution2D(256, (1, 1), strides=(1, 1))(x)
inception_2 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_2)
inception_2 = Activation('relu')(inception_2)
```

```
x = concatenate([inception_0, inception_1, inception_2, ], axis=3)
x = Reshape(target_shape=(3, 3, 736, ))(x)
```

```
inception_0 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_0)
inception_0 = Activation('relu')(inception_0)
```

```
inception_1 = MaxPooling2D(pool_size=(3, 3), strides=(2, 2))(x)
inception_1 = Convolution2D(96, (1, 1), strides=(1, 1))(inception_1)
inception_1 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_1)
inception_1 = Activation('relu')(inception_1)
inception_1 = ZeroPadding2D(padding=((1, 1), (1, 1)))(inception_1)
```

```
inception_2 = Convolution2D(256, (1, 1), strides=(1, 1))(x)
inception_2 = BatchNormalization(axis=3, momentum=0.1, epsilon=1e-05)(inception_2)
inception_2 = Activation('relu')(inception_2)
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

x = concatenate([inception_0, inception_1, inception_2, ], axis=3)
x = AveragePooling2D(pool_size=(3, 3), strides=(1, 1))(x)
x = Reshape(target_shape=(736, ))(x)
x = Reshape(target_shape=(736, ))(x)
x = Dense(128)(x)
x = Lambda(l2Normalize, arguments={'axis': 1})(x)

```

```

MindFaceKerasSmall2V1 = Model(inputs=[inp], outputs=x)
MindFaceKerasSmall2V1.summary()

```

```

return MindFaceKerasSmall2V1

```

1.8. face_detect.py

```

face_detector = dlib.get_frontal_face_detector()
face_aligner = AlignDlib(predictor_face_landmark_model)

```

```

def face_num(file_name):
    image = io.imread(file_name)
    detected_faces = face_detector(image, 1)
    num = len(detected_faces)
    return num

```

```

def rewrite_alignet_resize96_face(file_name):
    image = io.imread(file_name)
    detected_faces = face_detector(image, 1)
    face_rect = detected_faces[0]

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

alignedFace = face_aligner.align(534, image, face_rect,
landmarkIndices=AlignDlib. OUTER_EYES_AND_NOSE)
alignedFace = cv2.resize(alignedFace, (96, 96))
cv2.imwrite(file_name, cv2.cvtColor(alignedFace, cv2.COLOR_RGB2BGR))

```

```

def rewrite_alignet_resize96_face_image(image1):

```

```

    alignedFace = cv2.resize(alignedFace, (96, 96))

```

```

    return alignedFace

```

```

else:

```

```

    return None

```

1.9. classifier_controller.py

```

from DBEngine import db

```

```

from DBEngine.dbmodel import Classifier

```

```

from DBEngine.dbmodel import Photo

```

```

from DBEngine.dbmodel import Person

```

```

from MLCore.face_detect import rewrite_alignet_resize96_face

```

```

import cv2

```

```

import numpy as np

```

```

from MLCore.MindFaceKerasSmall2V1 import create_model

```

```

from config import model_path

```

```

from MLCore.classifier import create_classifier

```

```

from config import clf_path, clf_path_local, reload_clf, reload_clf_local, retrain_bin_classifier

```

```

# from config import main_clf

```

```

import pickle

```

```

from MLCore.SVMBinaryClassifier.SVMBinaryClassifier import SVMBinaryClassifier

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

def retrain_classifier(user_id):
    global main_clf
    global main_bin_clf
    photos = get_unprocess_photos(user_id)
    process_faces(photos)

    photos = get_all_photos(user_id)
    code_faces(photos)

    vecs = get_marked_vecs(user_id)
    codes = []
    labels = []
    for vec in vecs:
        codes.append(vec[0])
        labels.append(vec[1])

```

```

retrain_bin_classifier()

```

```

for person in Person.query.filter_by(user_id=user_id):
    person.is_train = True
    db.session.commit()

# vecs = get_marked_vecs_names(user_id)
# codes = []
# labels = []
# for vec in vecs:
#     codes.append(vec[0])
#     labels.append(vec[1])
# clf = create_classifier(codes, labels)

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
# pickle.dump(clf, open(clf_path_local, 'wb'))
# reload_clf_local()

query = Classifier.query.filter_by(user_id=user_id)
result = query.first()
result.version = result.version + 1
result.is_ready = True
db.session.commit()
```



```
def get_all_photos(user_id):
    query = Photo.query.join(Photo.persons_list).filter_by(user_id=user_id)
    result = query.all()
    return result
```

```
def get_marked_vecs(user_id):
    query = Photo.query.join(Photo.persons_list).filter_by(user_id=user_id)\
        .with_entities(Photo.features, Photo.person_id)
    result = query.all()
    return result
```

```
def get_marked_vecs_names(user_id):
    query = Photo.query.join(Photo.persons_list).filter_by(user_id=user_id)\
        .with_entities(Photo.features, Person.surname)
    result = query.all()
    return result
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

def code_faces(photos):
    MindFaceKerasSmall2V1 = create_model()
    MindFaceKerasSmall2V1.load_weights(model_path)

    for photo in photos:
        path = photo.get_absolute_path()

        image = np.zeros((1, 96, 96, 3))
        img = cv2.imread(path, 1)
        img = img[..., ::-1]
        img = np.around(img / 255.0, decimals=12)
        image[0, :, :, :] = img
        vec = MindFaceKerasSmall2V1.predict_on_batch(image)

        photo.features = vec[0].tolist()
        db.session.commit()

```

1.10. classifier.py

```

from sklearn import svm

def create_classifier(vec, labels):
    clf = svm.LinearSVC()
    # clf = svm.SVC(decision_function_shape='ovo')
    clf.fit(vec, labels)
    return clf

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

1.11. AlignnDlib.py

```
import cv2
```

```
import dlib
```

```
import numpy as np
```

```
TEMPLATE = np.float32([
```

```
(0.0792396913815, 0.339223741112), (0.0829219487236, 0.456955367943),
(0.0967927109165, 0.575648016728), (0.122141515615, 0.691921601066),
(0.168687863544, 0.800341263616), (0.239789390707, 0.895732504778),
(0.325662452515, 0.977068762493), (0.422318282013, 1.04329000149),
(0.531777802068, 1.06080371126), (0.641296298053, 1.03981924107),
(0.738105872266, 0.972268833998), (0.824444363295, 0.889624082279),
(0.894792677532, 0.792494155836), (0.939395486253, 0.681546643421),
(0.96111933829, 0.562238253072), (0.970579841181, 0.441758925744),
(0.971193274221, 0.322118743967), (0.163846223133, 0.249151738053),
(0.21780354657, 0.204255863861), (0.291299351124, 0.192367318323),
(0.367460241458, 0.203582210627), (0.4392945113, 0.233135599851),
```

```
(0.565874114041, 0.618796581487), (0.607054002672, 0.60157671656),
(0.252418718401, 0.331052263829), (0.298663015648, 0.302646354002),
(0.355749724218, 0.303020650651), (0.403718978315, 0.33867711083),
(0.352507175597, 0.349987615384), (0.296791759886, 0.350478978225),
(0.631326076346, 0.334136672344), (0.679073381078, 0.29645404267),
(0.73597236153, 0.294721285802), (0.782865376271, 0.321305281656),
(0.740312274764, 0.341849376713), (0.68499850091, 0.343734332172),
(0.353167761422, 0.746189164237), (0.414587777921, 0.719053835073),
(0.477677654595, 0.706835892494), (0.522732900812, 0.717092275768),
(0.569832064287, 0.705414478982), (0.635195811927, 0.71565572516),
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
(0.69951672331 0.739419187253) (0.639447159575 0.805236879972)
```

```
TPL_MIN, TPL_MAX = np.min(TEMPLATE, axis=0), np.max(TEMPLATE, axis=0)
MINMAX_TEMPLATE = (TEMPLATE - TPL_MIN) / (TPL_MAX - TPL_MIN)
```

```
class AlignDlib:
```

```
    #: Landmark indices.
```

```
    INNER_EYES_AND_BOTTOM_LIP = [39, 42, 57]
```

```
    OUTER_EYES_AND_NOSE = [36, 45, 33]
```

```
    def __init__(self, facePredictor):
```

```
        assert facePredictor is not None
```

```
        self.detector = dlib.get_frontal_face_detector()
```

```
        self.predictor = dlib.shape_predictor(facePredictor)
```

```
    def getAllFaceBoundingBoxes(self, rgbImg):
```

```
        assert rgbImg is not None
```

```
        try:
```

```
            return self.detector(rgbImg, 1)
```

```
        except Exception as e:
```

```
            print("Warning: {}".format(e))
```

```
            # In rare cases, exceptions are thrown.
```

```
            return []
```

```
    def getLargestFaceBoundingBox(self, rgbImg, skipMulti=False):
```

```
        assert rgbImg is not None
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата


```

faces = self.getAllFaceBoundingBoxes(rgbImg)
if (not skipMulti and len(faces) > 0) or len(faces) == 1:
    return max(faces, key=lambda rect: rect.width() * rect.height())
else:
    return None

```

```

def findLandmarks(self, rgbImg, bb):
    assert rgbImg is not None
    assert bb is not None

    points = self.predictor(rgbImg, bb)
    return list(map(lambda p: (p.x, p.y), points.parts()))

```



```

if bb is None:
    bb = self.getLargestFaceBoundingBox(rgbImg, skipMulti)
    if bb is None:
        return

```

```

if landmarks is None:
    landmarks = self.findLandmarks(rgbImg, bb)

```

```

npLandmarks = np.float32(landmarks)
npLandmarkIndices = np.array(landmarkIndices)

```

```

a = npLandmarks[npLandmarkIndices]
b = imgDim * MINMAX_TEMPLATE[npLandmarkIndices]
c = MINMAX_TEMPLATE[npLandmarkIndices]

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
H = cv2.getAffineTransform(npLandmarks[npLandmarkIndices],
                           imgDim * MINMAX_TEMPLATE[npLandmarkIndices])
thumbnail = cv2.warpAffine(rgbImg, H, (imgDim, imgDim))

return thumbnail
```

1.12. SVMBinaryClassifier.py

```
from sklearn.cluster import KMeans
from MLCore.classifier import create_classifier
import numpy as np
```

```
class SVMBinaryClassifier:
```

```
    bin_clf = None
```

```
    next0 = None
```

```
    next1 = None
```

```
    cls0 = None
```

```
    cls1 = None
```

```
print(labels)
```

```
self.bin_clf = create_classifier(vec=vecs, labels=kmeans.labels_)
```

```
mask0 = kmeans.labels_ == 0
```

```
mask1 = kmeans.labels_ == 1
```

```
uniq0 = np.unique(labels[mask0])
```

```
if len(uniq0) > 1:
```

```
    self.next0 = SVMBinaryClassifier(vecs[mask0], labels[mask0])
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

else:
    self.cls0 = uniq0[0]

    uniq1 = np.unique(labels[mask1])
    if len(uniq1) > 1:
        self.next1 = SVMBinaryClassifier(vecs[mask1], labels[mask1])
    else:
        self.cls1 = uniq1[0]

def predict(self, vec):
    if self.bin_clf is not None:
        res = int(self.bin_clf.predict([vec]))

        if res == 0:
            if self.next0 is None:
                # [Redacted]
            else:
                return self.next1.predict(vec)
        else:
            return None

```

1.13. dbmodel.py

```

from DBEngine import db
from config import app

```

```

class User(db.Model):
    __tablename__ = 'users'

    user_id = db.Column(db.Integer, primary_key=True)

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
username = db.Column(db.String)
```

```
password = db.Column(db.String)
```

```
def __init__(self, username, password):
```

```
    self.username = username
```

```
    self.password = password
```

```
class Person(db.Model):
```

```
    __tablename__ = 'persons'
```

```
def __init__(self, name, surname, user_id):
```

```
    self.name = name
```

```
    self.surname = surname
```

```
    self.is_train = False
```

```
    self.user_id = user_id
```

```
class Photo(db.Model):
```

```
    __tablename__ = 'photos'
```

```
photo_id = db.Column(db.Integer, primary_key=True)
```

```
path = db.Column(db.String)
```

```
is_train = db.Column(db.Boolean)
```

```
features = db.Column(db.ARRAY(db.Float))
```

```
person_id = db.Column(db.Integer, db.ForeignKey('persons.person_id'))
```

```
persons_list = db.relationship("Person", foreign_keys=[person_id])
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```
def __init__(self, path, person_id):
    self.path = path
    self.is_train = False
    self.features = None
    self.person_id = person_id

def get_absolute_path(self):
    return app.config['UPLOAD_FOLDER'] + str(self.person_id) + '/' + self.path + '.png'
```

```
class Classifier(db.Model):
    __tablename__ = 'classifiers'
```

```
def __init__(self, user_id):
    self.user_id = user_id
    self.is_ready = True
```

1.14. vector.py

```
# coding=utf-8
```

```
from flask import flash, redirect, render_template, request, session, abort
from DBEngine.dbmodel import User
from flask import Blueprint
import json
from config import pred_clf_vec
```

```
vector_blueprint = Blueprint('vector', __name__)
```

```
@vector_blueprint.route("/api/vector", methods=['POST'])
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

```

def vector():
    if request.json.get('vector'):
        vec = request.json.get('vector')

        pers = pred_clf_vec(vec)

        res = {"person": str(pers)}
        res = json.dumps(res)

        return res
    else:
        abort(400)

```

1.15. load.py

```
# coding=utf-8
```

```
load_blueprint = Blueprint('load', __name__)
```

```
@load_blueprint.route("/api/load", methods=['POST'])
```

```

def load():
    if request.json.get('load'):
        return redirect('static/classifier_local.sav')
    else:
        abort(400)

```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

1.16. image.py

```
# coding=utf-8
```

```
from flask import flash, redirect, render_template, request, session, abort, escape
```

```
from MLCore.MindFaceKerasSmall2V1 import create_model
```

```
from config import model_path
```

```
# image_blueprint = Blueprint('getad', __name__)
```

```
#
```

```
#
```

```
#
```

```
#
```

```
# @image_blueprint.route("/api/image", methods=['POST'])
```

```
# def image():
```

```
#     global MindFaceKerasSmall2V1
```

```
#     image_data = request.get_data()
```

```
#     image = Image.open(io.BytesIO(image_data)).convert('RGB')
```

```
#
```

```
#     img = rewrite_alignet_resize96_face_image(np.array(image))
```

```
#
```

```
#     image = np.zeros((1, 96, 96, 3))
```

```
#     img = img[..., :-1]
```

```
#     img = np.around(img / 255.0, decimals=12)
```

```
#     image[0, :, :, :] = img
```

```
#     vec = MindFaceKerasSmall2V1.predict_on_batch(image)
```

```
#
```

```
#     print("1")
```

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата

ЛИСТ РЕГИСТРАЦИИ ИЗМЕНЕНИЙ

[illegible]

Изм.	Лист	№ докум.	Подп.	Дата
RU.17701729.04.01-0151				
Инв. № подл.	Подп. и дата.	Взам. инв. №	Инв. № дубл.	Подп. и дата