

模型	0° 验证		局部旋转均值			参数量 (M)
	Top-1	Top-5	Top-1	Top-5	100× JSD ↓	
Standard DeiT-Tiny	51.54%	79.12%	49.91%	77.45%	5.27	5.544
SHARE half4d4r + Image Look	53.68%	80.46%	51.25%	78.89%	5.65	5.501
SHARE half6d3r + dual Look	55.52%	81.80%	52.82%	79.98%	5.64	5.497
Equi-ViT / GMR	41.52%	70.40%	41.08%	70.12%	3.22	5.424
ARC Adaptive	49.38%	76.56%	47.76%	75.70%	5.25	5.986
GE-ViT p4 local	56.06%	82.04%	52.94%	79.45%	5.88	5.509

六个模型均使用同一组 5,000 张验证图。局部旋转均值覆盖 $\pm 5^\circ, \dots, \pm 30^\circ$ 。令 $m = \frac{1}{2}(p_\theta + p_0)$ ，则 $\text{JSD}(p_\theta, p_0) = \frac{1}{2}D_{\text{KL}}(p_\theta \| m) + \frac{1}{2}D_{\text{KL}}(p_0 \| m)$ ；表中报告跨样本与角度平均后的 $100 \times \text{JSD}$ 。粗体、下划线、蓝色分别表示每个评价指标的第一、第二、第三名。参数量为可训练参数，以百万（M）计。