
micropolarray

Herve Haudemand

Jan 03, 2024

CONTENTS:

1	micropolarray package	1
1.1	Subpackages	1
1.1.1	micropolarray.processing package	1
1.1.1.1	Submodules	1
1.1.1.2	micropolarray.processing.chen_wan_liang_calibration module	1
1.1.1.3	micropolarray.processing.congrid module	2
1.1.1.4	micropolarray.processing.convert module	2
1.1.1.5	micropolarray.processing.demodulation module	4
1.1.1.6	micropolarray.processing.demosaic module	6
1.1.1.7	micropolarray.processing.hotpix_cleaning module	6
1.1.1.8	micropolarray.processing.nrgf module	6
1.1.1.9	micropolarray.processing.rebin module	8
1.1.1.10	micropolarray.processing.shift module	9
1.1.1.11	Module contents	10
1.2	Submodules	10
1.3	micropolarray.cameras module	10
1.4	micropolarray.image module	11
1.5	micropolarray.micropol_image module	12
1.6	micropolarray.polarization_functions module	17
1.7	micropolarray.utils module	17
1.8	Module contents	19
2	Indices and tables	21
	Python Module Index	23
	Index	25

MICROPOLARRAY PACKAGE

1.1 Subpackages

1.1.1 micropolarray.processing package

1.1.1.1 Submodules

1.1.1.2 micropolarray.processing.chen_wan_liang_calibration module

`micropolarray.processing.chen_wan_liang_calibration.calculate_chen_wan_lian_calibration`*(polarizer_orientations, filenames_list, micropol_phases_previsions, output_dir, occulter=True, dark_filename=None, flat_filename=None)*

Performs calibration from Chen-Wang-Liang paper 2014

Parameters

- **polarizer_orientations** (*list[float]*) – List of polarizer orientations
- **filenames_list** (*list[str]*) – List of filenames coupled with
- **micropol_phases_previsions** (*list[float]*) – Previsions of the micropolarizer orientations inside a superpixel
- **output_dir** (*str*) – output path for the calibration matrices
- **occulter** (*bool, optional*) – whether to exclude the occulter area. Defaults to True.
- **dark_filename** (*str, optional*) – path to the dark to be subtracted from the images. Defaults to None.
- **flat_filename** (*str, optional*) – path to the dark to be subtracted from the images. Defaults to None.

Raises

- **ValueError** – polarizer orientation list and filenames list do not have the same length

- **ValueError** – any of 0,45,90,-45 polarizations is not included in the polarizer orientation list

`micropolarray.processing.chen_wan_liang_calibration.chen_wan_liang_calibration(data, calibration_matrices_dir: str)`

Calibrates the images using Chen-Wang-Liang 2014 paper calibration

Parameters

- **data** (*np.array*) – data to be calibrated
- **calibration_matrices_dir** (*str*) – path to the calibration matrices

Returns

calibrated data

Return type

np.array

1.1.1.3 micropolarray.processing.congrid module

`micropolarray.processing.congrid.congrid(a, newdims, kind='linear') → ndarray`

Reshapes the data into any new length and width

Parameters

- **a** (*np.array*) – data to be reshaped
- **newdims** (*tuple* / *list*) – new length and width
- **kind** (*str*, *optional*) – interpolation type. Defaults to “linear”.

Returns

numpy array of congrided image

Return type

ndarray

`micropolarray.processing.congrid.micropolarray_jitcongrid(data, width, height, scale)`

1.1.1.4 micropolarray.processing.convert module

`micropolarray.processing.convert.average_rawfiles_to_fits(filenamees: list, new_filename: str, height: int, width: int)`

Saves the mean of a list of rawfiles to a new fits file.

Parameters

- **filenamees** (*list*) – list of raw filenames
- **new_filename** (*str*) – new fits filename
- **height** (*int*) – image height in pix
- **width** (*int*) – image width in pix

Raises

ValueError – trying to save in a file that does not end with .fits

`micropolarray.processing.convert.convert_rawfile_to_fits(filename: str, height: int, width: int, remove_old: bool = False)`

Converts a raw file to a fits one, using default header

Parameters

- **filename** (*str*) – raw filename
- **height** (*int*) – file height
- **width** (*int*) – file width
- **remove_old** (*bool*, *optional*) – remove old raw file after conversion. Defaults to False.

Raises

ValueError – raised if the file does not end with “.raw”

`micropolarray.processing.convert.convert_set(filenamees, new_filename, height, width)`

ANTARTICOR ONLY: Sums a set of filenames and converts them to one fits file.

Parameters

- **filenamees** (*list*) – list of file names to be summed before being converted
- **new_filename** (*str*) – new .fits file name

`micropolarray.processing.convert.merge_rawfiles_to_fits(filenamees: list, new_filename: str, height: int, width: int, mode='sum')`

Saves the average or sum of a list of rawfiles to a new fits file.

Parameters

- **filenamees** (*list*) – list of raw filenames
- **new_filename** (*str*) – new fits filename
- **height** (*int*) – image height in pix
- **width** (*int*) – image width in pix
- **mode** (*str*) – wether to “average” or “sum” the images. Defaults to “sum”.

Raises

ValueError – trying to save in a file that does not end with .fits

`micropolarray.processing.convert.nparr_from_binary(filename)`

Converts a PolarCam binary file into a numpy array. Bytes are saved like this

- **24 bit (3 bytes)**
1 | 3 | 2 111111111111 | 1111 | 11111111
- **2 numbers**
First number 12bit | Second number (little endian) 8+4=12 bit

Parameters

filename (*str*) – name of the file to be converted

Raises

ValueError – file lenghts is indivisible by the number of chunks requested to parallelize operations

Returns

array of data from file

Return type

np.array

micropolarray.processing.convert.**three_bytes_to_two_ints**(*filecontent*)

Needed for parallelization, this will be run by each thread for a slice of the original array.

Returns

array of saved data

Return type

np.array

1.1.1.5 micropolarray.processing.demodulation module**class** micropolarray.processing.demodulation.**Demodulator**(*demo_matrices_path: str*)

Bases: object

Demodulation class needed for MicropollImage demodulation.

flip(*axis*)**rebin**(*binning*)

DO NOT USE THIS, calculate the tensor from the binned images

rot90(*k=1*)**show**(*vmin=-1, vmax=1, cmap='Greys'*) → tuple

Shows the demodulation tensor

Parameters

- **vmin** (*int, optional*) – Minimum shown value. Defaults to -1.
- **vmax** (*int, optional*) – Maximum shown value. Defaults to 1.
- **cmap** (*str, optional*) – Colormap of the plot. Defaults to “Greys”.

Returns

fig, ax tuple as returned by matplotlib.pyplot.subplots

Return type

tuple

micropolarray.processing.demodulation.**Malus**(*angle, throughput, efficiency, phase*)**micropolarray.processing.demodulation.calculate_demodulation_tensor**(*polarizer_orientations: list, filenames_list: list, micropol_phases_previsions: list, gain: float, output_dir: str, binning: int = 1, occulter: list | None = None, procs_grid: list = [4, 4], dark_filename: str | None = None, flat_filename: str | None = None, normalizing_S=None, tk_boundary: list = [0.5, 0.1, 0.999999], DEBUG: bool = False*)

Calculates the demodulation tensor images and saves them. Requires a set of images with different polarizations to fit a Malus curve model.

Parameters

- **polarizer_orientations** (*list[float]*) – List containing the orientations of the incoming light for each image.
- **filenames_list** (*list[str]*) – List of input images filenames to read. Must include [0, 45, 90, -45].
- **micropol_phases_previsions** (*list[float]*) – Previsions for the micropolarizer orientations required to initialize fit.
- **gain** (*float*) – Detector [e-/DN], required to compute errors.
- **output_dir** (*str*) – output folder to save matrix to.
- **binning** (*int, optional*) – Output matrices binning. Defaults to 1 (no binning). Be warned that binning matrices AFTER calculation is an incorrect operation.
- **occulter** (*list, optional*) – occulter y, x center and radius to exclude from calculations. Defaults to None.
- **procs_grid** (*[int, int], optional*) – number of processors per side [Y, X], parallelization will be done in a Y x X grid. Defaults to [4,4] (16 procs in a 4x4 grid).
- **dark_filename** (*str, optional*) – Dark image filename to correct input images. Defaults to None.
- **flat_filename** (*str, optional*) – Flat image filename to correct input images. Defaults to None.
- **normalizing_S** (*float or np.ndarray, optional*) – maximum signal used to normalize single pixel signal. If not set will be estimated as the 4sigma of the signal distribution.
- **tk_boundary** (*list*) – if provided, sets the transmittancy [initial guess, boundary_inf, boundary_sup] of the Malus curve (max value). Defaults to [0.5, 0.1, 1.-1.e-6].

Raises

ValueError – Raised if any among [0, 45, 90, -45] is not included in the input polarizations.

Notes

In the binning process the sum of values is considered, which is ok because data is normalized over the maximum S before being fitted.

```
micropolararray.processing.demodulation.compute_demodulation_by_chunk(splitted_normalized_dara_arr,
                                                                    splitted_pixel_erorrs,
                                                                    splitted_occulter_flag,
                                                                    polarizer_orientations,
                                                                    rad_micropol_phases_previsions,
                                                                    tk_boundary, DEBUG)
```

Utility function to parallelize calculations.

1.1.1.6 micropolararray.processing.demosaic module

`micropolararray.processing.demosaic.demosaic(image_data, option='adjacent')`

Returns a [4,n,m] array of polarized images, starting from a micropolarizer image array [n, m].

`micropolararray.processing.demosaic.demosaicadjacent(data)`

`micropolararray.processing.demosaic.demosaicmean(data)`

Loops over right polarization pixel location, takes 1/4 of that, stores it in the 2x2 superpixel. `demo_images[0] = data[y=0, x=0]` `demo_images[1] = data[y=0, x=1]` `demo_images[2] = data[y=1, x=0]` `demo_images[3] = data[y=1, x=1]`

`micropolararray.processing.demosaic.merge_polarizations(single_pol_images: ndarray)`

`micropolararray.processing.demosaic.split_polarizations(data: ndarray)`

1.1.1.7 micropolararray.processing.hotpix_cleaning module

`micropolararray.processing.hotpix_cleaning.get_hot_pixels(image, threshold=100)`

1.1.1.8 micropolararray.processing.nrgf module

`micropolararray.processing.nrgf.find_occulter_hough(data: array, **kwargs) → tuple`

Uses Hough Gradient from cv2 and computes the coronagraph occulter coordinates. Returns Y, X, Radius of the occulter.

Parameters

data (*np.array*) – input data

Returns

occulter y, x, r

Return type

tuple

`micropolararray.processing.nrgf.find_occulter_position(data: array, method: str = 'sigmoid', threshold: float = 4.0)`

Finds the occulter position of an image.

Parameters

- **data** (*np.array*) – input data
- **method** (*str, optional*) – Method to find occulter edges. If “sigmoid” it will try to fit four sigmoids at the image edges centers, inferring the occulter edges from the parameters. If “algo” it will start from the image edge center and infer the occulter position when `DN[i] > threshold*mean(DN[:i])` Defaults to “sigmoid”.
- **threshold** (*float, optional*) – Threshold for the algo method. Defaults to 4.0.

Raises

UnboundLocalError – couldn’t converge

Returns

occulter y, occulter x, occulter radius

Return type

list

`micropolarray.processing.nrgf.map_polar_coordinates(height, width, center)`

`micropolarray.processing.nrgf.nrgf(data: array, y_center: int | None = None, x_center: int | None = None, rho_min: int | None = None, step: int = 1, phi_to_mean=[0.0, 360], output_phi=[0.0, 360]) → array`

Performs nrgf filtering on the image, starting from center and radius. Mean is performed between phi_to_mean, 0 is horizontal right, anti-clockwise.

Parameters

- **data** (*np.array*) – input array
- **y_center** (*int, optional*) – pixel y coordinate of the nrgf center. Defaults to None (image y center).
- **x_center** (*int, optional*) – pixel x coordinate of the nrgf center. Defaults to (image x center).
- **rho_min** (*int, optional*) – minimum radius in pixels to perform nrgf to. Defaults to None (radius 0).
- **step** (*int, optional*) – step to which apply the nrgf from center, in pixels. Defaults to 1 pixel.
- **phi_to_mean** (*list[float, float], optional*) – polar angle to calculate the mean value from. Defaults to [0, 360].
- **output_phi** (*list[float, float], optional*) – polar angle to include in output data. Defaults to [0, 360].

Returns

nrgf-filtered input data

Return type

np.array

`micropolarray.processing.nrgf.reject_outliers(data, m=2.0)`

`micropolarray.processing.nrgf.remove_outliers_simple(original, neighbours=2)`

EXPERIMENTAL DO NOT USE, for improving fitting on occulter position

`micropolarray.processing.nrgf.roi_from_polar(data: array, center: list | None = None, rho: list | None = None, theta=[0, 360], fill: float = 0.0, return_boolean: bool = False, include_superpixels: bool = True) → array`

Returns the input array in a circular selection, otherwise an arbitrary number. If a pixel is not in the selection the ENTIRE superpixel is considered out of selection. If return_boolean is True then a boolean array is returned instead (useful for mean/stdev operations).

Parameters

- **data** (*np.array*) – input data
- **center** (*list, optional*) – pixel coordinates of the circle center. Defaults to None (image center).
- **rho** (*list, optional*) – radius to exclude. Defaults to None (center to image border).
- **theta** (*list, optional*) – polar selection angle, 0 is horizontal, anti-clockwise direction. Defaults to [0, 360].
- **fill** (*float, optional*) – number to fill the outer selection. Defaults to 0.0.

- **return_boolean** (*bool*, *optional*) – if set to true, function returns a boolean array of the roi. Defaults to False.
- **include_superpixels** (*bool*, *optional*) – if set to true then exclude entire superpixel if one pixel is in the occulter

Returns

array containing the input data inside the selection, and fill otherwise

Return type

np.array

`micropolarray.processing.nrgf.sigmoid(x, max, min, slope, intercept)`

`micropolarray.processing.nrgf.tile_double(a)`

1.1.1.9 micropolarray.processing.rebin module

`micropolarray.processing.rebin.micropolarray_jitrebin(data, new_height, new_width, binning=2)`

Fast rebinning function for the micropolarray image. Needs to be wrapped to print info.

`micropolarray.processing.rebin.micropolarray_jitrebin_old(data, height, width, binning=2)`

Fast rebinning function for the micropolarray image.

`micropolarray.processing.rebin.micropolarray_rebin(data: ndarray, binning=2)`

Wrapper for the faster rebinning donw with numba. First deletes last row/column until binning is possible, then calls binning on the result shape.

Parameters

- **data** (*np.ndarray*) – data to rebin
- **height** (*int*) – lenght of first axis
- **width** (*int*) – lenght of second axis
- **binning** (*int*, *optional*) – Binning to be performed. Defaults to 2.

Returns

binned data, trimmed if necessary

Return type

ndarray

`micropolarray.processing.rebin.print_trimming_info(height, width, new_height, new_width)`

`micropolarray.processing.rebin.standard_jitrebin(data, new_height, new_width, binning=2)`

`micropolarray.processing.rebin.standard_rebin(data, binning: int) → array`

Rebins the data, binned each $\text{binning} \times \text{binning}$.

Parameters

- **image** (*np.array*) – data to be binned
- **binning** (*int*) – binning to be applied. A value of 2 will result in a 2x2 binning (1 pixel is a sum of 4 neighbour pixels)

Raises

KeyError – cannot divide image height/width by the binning value

Returns

binned data

Return type

np.array

`micropolarray.processing.rebin.trim_to_match_2xbinning(height: int, width: int, binning: int)`

Deletes the last image pixels until superpixel binning is compatible with new dimensions

Parameters

- **height** (*int*) – image height
- **width** (*int*) – image width
- **binning** (*int*) – image binning

Returns

image new height and width

Return type

int, int

`micropolarray.processing.rebin.trim_to_match_binning(height, width, binning, verbose=True)`

Deletes the last image pixels until simple binning is compatible with new dimensions

Parameters

- **height** (*int*) – image height
- **width** (*int*) – image width
- **binning** (*int*) – image binning
- **verbose** (*bool, optional*) – warns user of trimming. Defaults to True.

Returns

image new height and width

Return type

int, int

1.1.1.10 micropolarray.processing.shift module

`micropolarray.processing.shift.shift(data: ndarray, y: int, x: int)``micropolarray.processing.shift.shift_micropol(data: ndarray, y: int, x: int)`

Splits the image into single polarizations, shifts each of them by y,x and then merges them back.

Parameters

- **data** (*np.ndarray*) – array to shift
- **y** (*int*) – vertical shift (positive inside the image)
- **x** (*int*) – horizontal shift (positive inside the image)

Returns

shifted array

Return type

np.ndarray

1.1.1.11 Module contents

1.2 Submodules

1.3 micropolarray.cameras module

class micropolarray.cameras.**Antarticor**

Bases: object

class micropolarray.cameras.**Camera**

Bases: object

occulter_mask(*overoccult: int = 0, rmax: int | None = None*) → array

Returns an array of True inside the roi, False elsewhere. Useful for mean/std operations (where=occulter_mask).

Parameters

- **overoccult** (*int, optional*) – Pixels to overoccult. Defaults to 15.
- **rmax** (*int, optional*) – Maximum r of the ROI. Defaults to image nearest border.

Returns

Boolean roi array

Return type

np.array

occulter_roi(*data: array, fill: float = 0.0, overoccult: int = 0*) → array

Returns the array in the polar ROI, else fill

Parameters

- **data** (*np.array*) – Input array
- **fill** (*float, optional*) – Value for filling. Defaults to 0.0.
- **overoccult** (*int, optional*) – Pixels to overoccult. Defaults to 0.

Returns

Array if in ROI, fill elsewhere

Return type

np.array

class micropolarray.cameras.**Kasi**

Bases: [Camera](#)

class micropolarray.cameras.**PolarCam**

Bases: [Camera](#)

1.4 micropolarray.image module

class micropolarray.image.**Image**(*initializer: str | np.ndarray | Image, averageimages: bool = True*)

Bases: object

Basic image class. Can be initialized from a filename, a filenames list, a numpy array or another Image instance. If multiple filenames are provided, will perform the mean of them unless averageimages is False.

property data: ndarray

save_as_fits(*filename: str, fixto: str[float, float] = None*)

Saves image as fits with current header

Parameters

- **filename** (*str*) – output filename
- **fixto** (*str[float, float], optional*) – Set a maximum and minimum range for the data. Defaults to None.

Raises

ValueError – filename does not end with “.fits”

save_as_raw(*filename: str*)

Saves the image as a raw binary file

Parameters

filename (*str*) – output filename

Raises

ValueError – filename does not end with “.raw”

show(*cmap='Greys_r', vmin=None, vmax=None*) → tuple

Shows the image data

Parameters

- **cmap** (*str, optional*) – figure colorbar. Defaults to “Greys_r”.
- **vmin** (*_type_, optional*) – Minimum value to plot. Defaults to None.
- **vmax** (*_type_, optional*) – Maximum value to plot. Defaults to None.

Returns

fig, ax tuple as returned by matplotlib.pyplot.subplots

Return type

tuple

show_histogram(*bins: int = 1000*) → tuple

Print the histogram of the flattened image data

Parameters

bins (*int, optional*) – Numbers of bin to compute the histogram from. Defaults to 1000.

Returns

fig, ax tuple as returned by matplotlib.pyplot.subplots

Return type

tuple

1.5 micropolararray.micropol_image module

```
class micropolararray.micropol_image.MicropolImage(initializer: str | np.ndarray | list | MicropolImage,  
                                                    angle_dic: dict = None, dark: MicropolImage =  
                                                    None, flat: MicropolImage = None, averageimages:  
                                                    bool = True)
```

Bases: *Image*

Micro-polarizer array image class. Can be initialized from a 2d array, a list of 1 or more file names (use the boolean keyword averageimages to select if sum or average is taken) or another MicropolImage. Dark and flat micropolararray images can also be provided to automatically correct the result.

property AoLP: *PolParam*

property DoLP: *PolParam*

property I: *PolParam*

property Q: *PolParam*

property U: *PolParam*

clean_hot_pixels(flagged_hot_pix_map: *MicropolImage*)

Returns a copy of the image with gaussian smeared pixels where flagged_hot_pix_map == 1.

Parameters

flagged_hot_pix_map (*MicropolImage*) – hot pixels map.

Returns

copy of the original image, gaussian smeared where flagged_hot_pix_map == 1

Return type

MicropolImage

congrid(newdim_y: int, newdim_x: int) → *MicropolImage*

correct_flat(flat: *MicropolImage*) → *MicropolImage*

Normalizes the flat and uses it to correctStokes_vecct the image.

Parameters

flat (*MicropolImage*) – flat image, does not need to be normalized.

Returns

copy of input image corrected by flat

Return type

MicropolImage

correct_ifov() → *MicropolImage*

Corrects differences in single pixels fields of view inside each superpixel

Returns

image with data corrected for field of view differences

Return type

MicropolImage

demodulate(*demodulator*: [Demodulator](#), *demosaicing*: *bool = False*) → [MicropollImage](#)

Returns a MicropollImage with polarization parameters calculated from the demodulation tensor provided.

Parameters

- **demodulator** ([Demodulator](#)) – Demodulator object containing the demodulation tensor components (see `processing.new_demodulation`)
- **demosaicing** (*bool*, *optional*) – whether to apply demosaicing to the image or not. Set it to False if demodulation matrices have half the dimension of the image. Defaults to True.

Raises

ValueError – raised if image and demodulator do not have the same dimension, for example in case of different binning

Returns

copy of the input image with I, Q, U, pB, DoLP, AoLP calculated from the demodulation tensor.

Return type

[MicropollImage](#)

demosaic(*demosaic_mode*='adjacent') → [MicropollImage](#)

Returns a demosaiced copy of the image with updated polarization parameters. Demosaicing is done IN PLACE.

Parameters

demosaic_mode (*str*, *optional*) – demosaicing mode (see `processing.demosaic`). Defaults to “adjacent”.

Returns

demosaiced image

Return type

[MicropollImage](#)

first_call = True

mask_occult(*y*: *int = 919*, *x*: *int = 950*, *r*: *int = 531*, *overocult*: *int = 0*) → None

Masks occulter for all image parameters

Parameters

- **y** (*int*, *optional*) – Occulter y position. Defaults to `PolarCam().occulter_pos_last[0]`.
- **x** (*int*, *optional*) – Occulter x position. Defaults to `PolarCam().occulter_pos_last[1]`.
- **r** (*int*, *optional*) – Occulter radius. Defaults to `PolarCam().occulter_pos_last[2]`.
- **overocult** (*int*, *optional*) – Pixels to overocult. Defaults to 0.
- **camera** (*_type_*, *optional*) – Camera image type. Defaults to `PolarCam()`.

Returns

None

property **pB**: [PolParam](#)

property **pol0**: [PolParam](#)

property **pol45**: [PolParam](#)

property **pol90**: [PolParam](#)

property **pol_45**: *PolParam*

property **polparam_list**: list

rebin(*binning: int*) → *MicropollImage*

Rebins the micropolarizer array image, binned each $\text{binning} \times \text{binning}$. Sum bins by default.

Parameters

binning (*int*) – binning to perform. A value of n will be translated in a $n \times n$ binning.

Raises

ValueError – negative binning provided

Returns

copy of the input image, rebinned.

Return type

MicropollImage

rotate(*angle: float*) → *MicropollImage*

Rotates an image of angle degrees, counter-clockwise.

save_all_pol_params_as_fits(*filename: str*) → None

Saves the image and all polarization parameters as fits file with the same name

Parameters

filename (*str*) – filename of the output image. Will be saved as filename_[I, Q, U, pB, AoLP, DoLP].fits

Raises

ValueError – filename is not a valid .fits file

save_demosaiiced_images_as_fits(*filename: str, fixto: list[float, float] = None*) → None

Saves the four demosaiced images as fits files

Parameters

- **filename** (*str*) – filename of the output image. The four images will be saved as filename_POLXX.fits
- **fixto** (*list[float, float], optional*) – set the minimum and maximum value for the output images. Defaults to None.

Raises

ValueError – an invalid file name is provided

save_param_as_fits(*polparam: str, filename: str, fixto: list[float, float] = None*) → None

Saves chosen polarization parameter as a fits file

Parameters

- **polparam** (*str*) – polarization parameter to save. Can be one among [I, Q, U, pB, AoLP, DoLP]
- **filename** (*str*) – filename of the output image.
- **fixto** (*list[float, float], optional*) – set the minimum and maximum value for the output images. Defaults to None.

Raises

ValueError – filename is not a valid .fits file

save_single_pol_images(*filename: str, fixto: list[float, float] = None*) → None

Saves the four polarized images as fits files

Parameters

- **filename** (*str*) – filename of the output image. The four images will be saved as file-name_POLXX.fits
- **fixto** (*list[float, float], optional*) – set the minimum and maximum value for the output images. Defaults to None.

Raises

ValueError – an invalid file name is provided

shift(*y: int, x: int*) → *MicropollImage*

Shifts image by y, x pixels and fills with 0 the remaining space. Positive numbers for up/right shift and negative for down/left shift. Image is split into polarizations, each one is shifted, then they are merged again.

Parameters

- **y** (*int*) – vertical shift in pix
- **x** (*int*) – horizontal shift in pix

Returns

shifted image copied from the original

Return type

MicropollImage

show_demo_images(*cmap='Greys_r', vmin=None, vmax=None, **kwargs*)

Plots the four demosaiced images.

Parameters

- **cmap** (*str, optional*) – colormap for the plot. Defaults to “Greys_r”.
- ****kwargs** – arguments passed to matplotlib.pyplot.imshow.

Returns

a (figure, axis) couple same as matplotlib.pyplot.subplots

Return type

tuple

show_pol_param(*polparam: str, cmap='Greys_r', vmin=None, vmax=None, **kwargs*)

Plots a single polarization parameter given as input

Parameters

- **polparam** (*str*) – image PolParam containing the parameter to plot. Can be one among [I, Q, U, pB, AoLP, DoLP]
- **cmap** (*str, optional*) – colormap for the plot. Defaults to “Greys_r”.
- ****kwargs** – arguments passed to matplotlib.pyplot.imshow.

Returns

a (figure, axis) couple same as matplotlib.pyplot.subplots

Return type

tuple

show_single_pol_images(*cmap*='Greys_r', ***kwargs*)

Plots the four polarizations images.

Parameters

- **cmap** (*str*, *optional*) – colormap for the plot. Defaults to “Greys_r”.
- ****kwargs** – arguments passed to matplotlib.pyplot.imshow.

Returns

a (figure, axis) couple same as matplotlib.pyplot.subplots

Return type

tuple

show_with_pol_params(*cmap*='Greys_r') → tuple

Returns a tuple containing figure and axis of the plotted data, and figure and axis of polarization parameters (3x2 subplots). User must call plt.show after this is called.

Parameters

cmap (*str*, *optional*) – colormap string. Defaults to “Greys_r”.

Returns

a (figure, axis, figure, axis) couple same as matplotlib.pyplot.subplots for the image data and another for the six polarization parameters

Return type

tuple

property single_pol_subimages

subtract_dark(*dark*: MicropollImage) → MicropollImage

Correctly subtracts the input dark image from the image

Parameters

dark (MicropollImage) – dark to subtract

Returns

copy of input image with dark subtracted

Return type

MicropollImage

class micropolarray.micropol_image.**PolParam**(*ID*: str, *data*: ndarray, *title*: str, *measure_unit*: str, *fix_data*: bool = False)

Bases: object

Auxiliary class for polarization parameters.

Members:

ID (str): parameter identifier data (np.array): parameter image as numpy 2D array **title** (str): brief title of the parameter, useful for plotting **measure_unit** (str): initial measure units of the parameter **fix_data** (bool): controls whether data has to be constrained to [0, 4096] interval (not implemented yet)

ID: str

data: ndarray

fix_data: bool = False

measure_unit: str

title: str

`micropolarray.micropol_image.set_default_angles(angles_dic: dict)`

Sets the default micropolarizer orientations for images.

Parameters

angles_dic (*dict*) – dictionary {value : pos} where value is the angle in degrees from -90 to 90 and pos is the pixel position in superpixel, from 0 to 3 (position [y, x], fast index x)

1.6 micropolarray.polarization_functions module

`micropolarray.polarization_functions.AoLP(Stokes_vec_components)`

Angle of linear polarization in [rad]

`micropolarray.polarization_functions.DoLP(Stokes_vec_components)`

Degree of linear polarization in [%]

`micropolarray.polarization_functions.normalize2pi(angles_list)`

Normalizes the input angle list in the -90,90 range

Parameters

angles_list (*_type_*) – list of input angles in degrees

Returns

normalized angles

Return type

type

`micropolarray.polarization_functions.pB(Stokes_vec_components)`

Polarized brightness in [%]

1.7 micropolarray.utils module

`micropolarray.utils.align_keywords_and_data(header, data, sun_center, platescale, binning=1)`

Fixes antarticor keywords and data to reflect each other.

Parameters

- **header** (*dict*) – fits file header
- **data** (*ndarray*) – data as np array
- **platescale** (*float*) – plate scale in arcsec/pixel
- **binning** (*int*, *optional*) – binning applied to image. Defaults to 1 (no binning).

Returns

new fixed header and data

Return type

header, data

`micropolarray.utils.fix_data(data: array, min, max)`

`micropolarray.utils.get_Bsun_units(diffuser_I: float, texp_image: float = 1.0, texp_diffuser: float = 1.0) → float`

Returns the conversion unit for expressing brightness in units of sun brightness. Usage is `data [units of B_sun] = data[DN] * get_Bsun_units(mean_Bsun_brightness, texp_image, texp_diffuser)`

Parameters

- **mean_sun_brightness** (*float*) – diffuser mean in DN.
- **texp_image** (*float, optional*) – image exposure time. Defaults to 1.0.
- **texp_diffuser** (*float, optional*) – diffuser exposure time. Defaults to 1.0.

Returns

Bsun units conversion factor

Return type

float

`micropolarray.utils.get_malus_normalization(four_peaks_images, show_hist=False)`

`micropolarray.utils.mean_minus_std(data: array, stds_n: int = 1) → float`

Returns the value at the mean - standard deviation for the input data

Parameters

- **data** (*np.array*) – input data
- **stds_n** (*int, optional*) – number of standard deviations. Defaults to 1.

Returns

mean value - n*stdevs

Return type

float

`micropolarray.utils.mean_plus_std(data: array, stds_n: int = 1) → float`

Returns the value at the mean + standard deviation for the input data

Parameters

- **data** (*np.array*) – input data
- **stds_n** (*int, optional*) – number of standard deviations. Defaults to 1.

Returns

mean value + n*stdevs

Return type

float

`micropolarray.utils.median_minus_std(data: array, stds_n: int = 1) → float`

Returns the value at the median - median deviation for the input data

Parameters

- **data** (*np.array*) – input data
- **stds_n** (*int, optional*) – number of standard deviations. Defaults to 1.

Returns

median value - n*mediandevs

Return type

float

`micropolarray.utils.median_plus_std(data: array, stds_n: int = 1) → float`

Returns the value at the median + median deviation for the input data

Parameters

- **data** (*np.array*) – input data
- **stds_n** (*int, optional*) – number of standard deviations. Defaults to 1.

Returns

median value + n*mediandevs

Return type

float

`micropolarray.utils.normalize2pi(angles_list)`

`micropolarray.utils.sigma_DN(pix_DN)`

`micropolarray.utils.timer(func)`

Use this to time function execution

Parameters

func (*function*) – function of which to measure execution time

1.8 Module contents

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

m

- `micropolarray`, 19
- `micropolarray.cameras`, 10
- `micropolarray.image`, 11
- `micropolarray.micropol_image`, 12
- `micropolarray.polarization_functions`, 17
- `micropolarray.processing`, 10
- `micropolarray.processing.chen_wan_liang_calibration`,
1
- `micropolarray.processing.congrid`, 2
- `micropolarray.processing.convert`, 2
- `micropolarray.processing.demodulation`, 4
- `micropolarray.processing.demosaic`, 6
- `micropolarray.processing.hotpix_cleaning`, 6
- `micropolarray.processing.nrgf`, 6
- `micropolarray.processing.rebin`, 8
- `micropolarray.processing.shift`, 9
- `micropolarray.utils`, 17

A

`align_keywords_and_data()` (in module `micropolar-ray.utils`), 17
`Antarticator` (class in `micropolararray.cameras`), 10
`AoLP` (`micropolararray.micropol_image.MicropollImage` property), 12
`AoLP()` (in module `micropolar-ray.polarization_functions`), 17
`average_rawfiles_to_fits()` (in module `micropolar-ray.processing.convert`), 2

C

`calculate_chen_wan_lian_calibration()` (in module `micropolar-ray.processing.chen_wan_liang_calibration`), 1
`calculate_demodulation_tensor()` (in module `micropolararray.processing.demodulation`), 4
`Camera` (class in `micropolararray.cameras`), 10
`chen_wan_liang_calibration()` (in module `micropolar-ray.processing.chen_wan_liang_calibration`), 2
`clean_hot_pixels()` (`micropolar-ray.micropol_image.MicropollImage` method), 12
`compute_demodulation_by_chunk()` (in module `micropolararray.processing.demodulation`), 5
`congrid()` (in module `micropolar-ray.processing.congrid`), 2
`congrid()` (`micropolar-ray.micropol_image.MicropollImage` method), 12
`convert_rawfile_to_fits()` (in module `micropolar-ray.processing.convert`), 2
`convert_set()` (in module `micropolar-ray.processing.convert`), 3
`correct_flat()` (`micropolar-ray.micropol_image.MicropollImage` method), 12
`correct_ifov()` (`micropolar-ray.micropol_image.MicropollImage` method),

12

D

`data` (`micropolararray.image.Image` property), 11
`data` (`micropolararray.micropol_image.PolParam` attribute), 16
`demodulate()` (`micropolar-ray.micropol_image.MicropollImage` method), 12
`Demodulator` (class in `micropolar-ray.processing.demodulation`), 4
`demosaic()` (in module `micropolar-ray.processing.demosaic`), 6
`demosaic()` (`micropolar-ray.micropol_image.MicropollImage` method), 13
`demosaicadjacent()` (in module `micropolar-ray.processing.demosaic`), 6
`demosaicmean()` (in module `micropolar-ray.processing.demosaic`), 6
`DoLP` (`micropolararray.micropol_image.MicropollImage` property), 12
`DoLP()` (in module `micropolar-ray.polarization_functions`), 17

F

`find_occultor_hough()` (in module `micropolar-ray.processing.nrgf`), 6
`find_occultor_position()` (in module `micropolar-ray.processing.nrgf`), 6
`first_call` (`micropolar-ray.micropol_image.MicropollImage` attribute), 13
`fix_data` (`micropolararray.micropol_image.PolParam` attribute), 16
`fix_data()` (in module `micropolararray.utils`), 17
`flip()` (`micropolararray.processing.demodulation.Demodulator` method), 4

G

`get_Bsun_units()` (in module `micropolararray.utils`), 17

`get_hot_pixels()` (in module `micropolararray.processing.hotpix_cleaning`), 6
`get_malus_normalization()` (in module `micropolararray.utils`), 18

I

`I` (`micropolararray.micropol_image.MicropollImage` property), 12
`ID` (`micropolararray.micropol_image.PolParam` attribute), 16
`Image` (class in `micropolararray.image`), 11

K

`Kasi` (class in `micropolararray.cameras`), 10

M

`Malus()` (in module `micropolararray.processing.demodulation`), 4
`map_polar_coordinates()` (in module `micropolararray.processing.nrgf`), 6
`mask_occulter()` (`micropolararray.micropol_image.MicropollImage` method), 13
`mean_minus_std()` (in module `micropolararray.utils`), 18
`mean_plus_std()` (in module `micropolararray.utils`), 18
`measure_unit` (`micropolararray.micropol_image.PolParam` attribute), 16
`median_minus_std()` (in module `micropolararray.utils`), 18
`median_plus_std()` (in module `micropolararray.utils`), 18
`merge_polarizations()` (in module `micropolararray.processing.demosaic`), 6
`merge_rawfiles_to_fits()` (in module `micropolararray.processing.convert`), 3
`micropolararray`
 module, 19
`micropolararray.cameras`
 module, 10
`micropolararray.image`
 module, 11
`micropolararray.micropol_image`
 module, 12
`micropolararray.polarization_functions`
 module, 17
`micropolararray.processing`
 module, 10
`micropolararray.processing.chen_wan_liang_calibration`
 module, 1
`micropolararray.processing.congrid`
 module, 2
`micropolararray.processing.convert`
 module, 2

`micropolararray.processing.demodulation`
 module, 4
`micropolararray.processing.demosaic`
 module, 6
`micropolararray.processing.hotpix_cleaning`
 module, 6
`micropolararray.processing.nrgf`
 module, 6
`micropolararray.processing.rebin`
 module, 8
`micropolararray.processing.shift`
 module, 9
`micropolararray.utils`
 module, 17
`micropolararray_jitcongrid()` (in module `micropolararray.processing.congrid`), 2
`micropolararray_jitrebin()` (in module `micropolararray.processing.rebin`), 8
`micropolararray_jitrebin_old()` (in module `micropolararray.processing.rebin`), 8
`micropolararray_rebin()` (in module `micropolararray.processing.rebin`), 8
`MicropollImage` (class in `micropolararray.micropol_image`), 12
module
 `micropolararray`, 19
 `micropolararray.cameras`, 10
 `micropolararray.image`, 11
 `micropolararray.micropol_image`, 12
 `micropolararray.polarization_functions`, 17
 `micropolararray.processing`, 10
 `micropolararray.processing.chen_wan_liang_calibration`, 1
 `micropolararray.processing.congrid`, 2
 `micropolararray.processing.convert`, 2
 `micropolararray.processing.demodulation`, 4
 `micropolararray.processing.demosaic`, 6
 `micropolararray.processing.hotpix_cleaning`, 6
 `micropolararray.processing.nrgf`, 6
 `micropolararray.processing.rebin`, 8
 `micropolararray.processing.shift`, 9
 `micropolararray.utils`, 17

N

`normalize2pi()` (in module `micropolararray.polarization_functions`), 17
`normalize2pi()` (in module `micropolararray.utils`), 19
`nparr_from_binary()` (in module `micropolararray.processing.convert`), 3
`nrgf()` (in module `micropolararray.processing.nrgf`), 7

O

`occulter_mask()` (`micropolararray.cameras.Camera`

- method*), 10
- `occulter_roi()` (*micropolarray.cameras.Camera method*), 10
- ## P
- `pB` (*micropolarray.micropol_image.MicropollImage property*), 13
- `pB()` (*in module micropolarray.polarization_functions*), 17
- `pol10` (*micropolarray.micropol_image.MicropollImage property*), 13
- `pol145` (*micropolarray.micropol_image.MicropollImage property*), 13
- `pol190` (*micropolarray.micropol_image.MicropollImage property*), 13
- `pol_45` (*micropolarray.micropol_image.MicropollImage property*), 13
- `PolarCam` (*class in micropolarray.cameras*), 10
- `PolParam` (*class in micropolarray.micropol_image*), 16
- `polparam_list` (*micropolarray.micropol_image.MicropollImage property*), 14
- `print_trimming_info()` (*in module micropolarray.processing.rebin*), 8
- ## Q
- `Q` (*micropolarray.micropol_image.MicropollImage property*), 12
- ## R
- `rebin()` (*micropolarray.micropol_image.MicropollImage method*), 14
- `rebin()` (*micropolarray.processing.demodulation.Demodulator method*), 4
- `reject_outliers()` (*in module micropolarray.processing.nrgf*), 7
- `remove_outliers_simple()` (*in module micropolarray.processing.nrgf*), 7
- `roi_from_polar()` (*in module micropolarray.processing.nrgf*), 7
- `rot90()` (*micropolarray.processing.demodulation.Demodulator method*), 4
- `rotate()` (*micropolarray.micropol_image.MicropollImage method*), 14
- ## S
- `save_all_pol_params_as_fits()` (*micropolarray.micropol_image.MicropollImage method*), 14
- `save_as_fits()` (*micropolarray.image.Image method*), 11
- `save_as_raw()` (*micropolarray.image.Image method*), 11
- `save_demosaiiced_images_as_fits()` (*micropolarray.micropol_image.MicropollImage method*), 14
- `save_param_as_fits()` (*micropolarray.micropol_image.MicropollImage method*), 14
- `save_single_pol_images()` (*micropolarray.micropol_image.MicropollImage method*), 14
- `set_default_angles()` (*in module micropolarray.micropol_image*), 17
- `shift()` (*in module micropolarray.processing.shift*), 9
- `shift()` (*micropolarray.micropol_image.MicropollImage method*), 15
- `shift_micropol()` (*in module micropolarray.processing.shift*), 9
- `show()` (*micropolarray.image.Image method*), 11
- `show()` (*micropolarray.processing.demodulation.Demodulator method*), 4
- `show_demo_images()` (*micropolarray.micropol_image.MicropollImage method*), 15
- `show_histogram()` (*micropolarray.image.Image method*), 11
- `show_pol_param()` (*micropolarray.micropol_image.MicropollImage method*), 15
- `show_single_pol_images()` (*micropolarray.micropol_image.MicropollImage method*), 15
- `show_with_pol_params()` (*micropolarray.micropol_image.MicropollImage method*), 16
- `sigma_DN()` (*in module micropolarray.utils*), 19
- `sigmoid()` (*in module micropolarray.processing.nrgf*), 8
- `single_pol_subimages` (*micropolarray.micropol_image.MicropollImage property*), 16
- `split_polarizations()` (*in module micropolarray.processing.demosaic*), 6
- `standard_jitrebin()` (*in module micropolarray.processing.rebin*), 8
- `standard_rebin()` (*in module micropolarray.processing.rebin*), 8
- `subtract_dark()` (*micropolarray.micropol_image.MicropollImage method*), 16
- ## T
- `three_bytes_to_two_ints()` (*in module micropolarray.processing.convert*), 4
- `tile_double()` (*in module micropolarray.processing.nrgf*), 8
- `timer()` (*in module micropolarray.utils*), 19

`title` (*micropolarray.micropol_image.PolParam* attribute), [16](#)

`trim_to_match_2xbinning()` (in module *micropolarray.processing.rebin*), [9](#)

`trim_to_match_binning()` (in module *micropolarray.processing.rebin*), [9](#)

U

`U` (*micropolarray.micropol_image.MicropollImage* property), [12](#)