

HPE Reference Configuration for Red Hat OpenShift Container Platform on HPE Synergy Composable Infrastructure

Automated deployment of bare metal servers using HPE Synergy Image Streamer and Red Hat Ansible Tower

Contents

Executive summary.....	3
Introduction.....	3
Solution overview.....	4
Solution components.....	5
Solution hardware.....	5
Solution management software.....	8
Best practices and configuration guidance for the solution.....	10
Red Hat OpenShift Container Platform deployment best practices utilizing HPE Synergy Image Streamer and Ansible Tower.....	10
Utilizing HPE Synergy Image Streamer and Red Hat Ansible Tower to deploy bare metal servers for Red Hat OpenShift Container Platform.....	11
Performance benefits of Red Hat OpenShift Container Platform deployment using HPE Synergy Image Streamer.....	30
Summary.....	30
Appendix A: Bill of materials.....	31
Appendix B: Creating golden images for Red Hat OpenShift Container Platform deployment.....	33
Install Red Hat Enterprise Linux 7.4.....	33
Customize the OS deployment.....	35
Capture the deployed image.....	38
Creating the smaller golden image.....	38
Appendix C: Setting the custom attributes in the Red Hat OpenShift deployment plans.....	39
Appendix D: Configuring Red Hat Satellite Server.....	40
Configuration to support Red Hat OpenShift Container Platform.....	40
Appendix E: Using Red Hat CloudForms to monitor the Red Hat OpenShift Container Platform.....	42
Red Hat CloudForms configuration steps.....	42
Appendix F: Deploying a sample application.....	48
Deploying the application.....	48
Monitoring the application from Red Hat CloudForms.....	49
Appendix G: Red Hat Ansible Playbooks and customization.....	51
Ansible Playbooks.....	51
Customizing the inventory and variables.....	51
Ansible vault.....	53
Appendix H: Red Hat OpenShift Container Platform deployment validation and troubleshooting.....	54
Post deployment verification.....	54
Resources and additional links.....	56

Executive summary

Container technology is rapidly changing the way organizations develop, deploy and manage applications. Red Hat® OpenShift Container Platform provides organizations with a reliable platform for deploying and scaling container based applications. This Reference Configuration provides architectural guidance for deploying, scaling and managing a Red Hat OpenShift environment on Hewlett Packard Enterprise Synergy Composable Infrastructure. It describes:

- How to leverage HPE Synergy strengths in rapid provisioning along with the automation capabilities of Red Hat Ansible® Tower to provide a one-click deployment of a Red Hat OpenShift Container Platform on HPE Synergy.
- How to deploy an application and monitor the status of the Red Hat OpenShift Container Platform environment with Red Hat CloudForms including Chargeback reporting.
- How to scale the infrastructure to allow for deployment of additional services.

This Reference Configuration demonstrates the following benefits of utilizing HPE Synergy for Red Hat OpenShift Container Platform:

- Automated initial installation of a highly available Red Hat OpenShift Container Platform on HPE Synergy reduces the initial solution deployment from several days as provided by a services organization to less than 2 hours.
- The fluid pool of HPE Synergy resources allows for rapid expansion or reduction of worker nodes to support changing business needs.
- The automated provisioning and lifecycle management provided by HPE Synergy Image Streamer and Red Hat Ansible Tower allows for best practices to be built in to the solution, reducing the chances for human error.

Target audience: This document is intended for systems engineers, systems administrators, architects, and installers responsible for installing and maintaining Red Hat OpenShift Container Platform on a large scale running on Hewlett Packard Enterprise Synergy Composable Infrastructure. The reader of this document should be familiar with Red Hat OpenShift Container Platform, Red Hat Satellite, Red Hat Ansible Tower, Red Hat Enterprise Linux®, HPE OneView, and HPE Synergy Composable Infrastructure.

Introduction

This Reference Configuration describes a Red Hat OpenShift Container Platform deployment on HPE Synergy Composable Infrastructure and includes details on how the environment was configured and links to download the Red Hat Ansible Tower workflows and HPE Synergy Image Streamer artifacts used to automate the deployment. The document describes best practices and detailed instructions on configuring the environment for a successful deployment.

In this solution, Red Hat OpenShift Container Platform is automatically deployed on physical servers. The management software used to deploy this solution, including Red Hat Ansible Tower, Red Hat Satellite, and Red Hat CloudForms (used to manage the environment), can be deployed either on physical servers or virtual machines.

Solution overview

This Reference Configuration provides a solution architected for Red Hat OpenShift Container Platform on bare metal HPE Composable Infrastructure and integrations to provide automated server provisioning and container management as shown in Figure 1. This creates a scalable and highly available platform for Red Hat OpenShift Container Platform components.




Figure 1: Red Hat OpenShift Container Platform high availability deployment on HPE Synergy

This solution uses Red Hat Ansible Tower and Red Hat Satellite in combination with HPE OneView and HPE Synergy Image Streamer to automate the deployment of the following on physical servers:

- 3 Red Hat OpenShift master nodes (manage the Kubernetes cluster and schedule pods to run on worker nodes)
- 3 Red Hat OpenShift container-native storage nodes (provide containers with persistent storage)
- 3 Red Hat OpenShift worker nodes (host the application pods)
- 3 Red Hat OpenShift infrastructure nodes (run routing services, container application registry)
- 1 Red Hat OpenShift load balancer/NFS node (runs HAProxy to distribute requests, provides persistent storage for image registry)
- 2 Additional Red Hat OpenShift worker nodes for scaling

Golden images and automated deployment plans configured and stored in HPE Synergy Image Streamer enable the rapid deployment of bare metal Red Hat OpenShift infrastructure. The bare metal servers boot from HPE Synergy Image Streamer volumes and make use of (optional) HPE Synergy 480 internal storage and the HPE Synergy D3940 for ephemeral container storage. The HPE Synergy D3940 is used for persistent storage via Red Hat Gluster Storage.

Red Hat Ansible Tower workflows deploy playbooks utilizing the Ansible Modules for HPE OneView to apply server profiles to available HPE Synergy compute modules. The server profiles identify the server hardware type, networking, storage, and OS deployment plan to apply to the server. After the OS has been deployed and customized via HPE Synergy Image Streamer, additional playbooks pull the required components from the Red Hat Satellite Server, deploy Red Hat OpenShift, and configure Red Hat Gluster Storage.

Red Hat CloudForms management engine was used to manage the Red Hat OpenShift Container Platform deployment. Red Hat CloudForms helps define and maintain performance for the Red Hat OpenShift deployment through policies, quotas and system profiles. After enabling cluster metrics on Red Hat OpenShift deployments, Red Hat CloudForms can collect node, pod and container metrics. Workloads and capacity can be tracked through SmartState analytics, chargeback and reports.

A sample microservice application based on Red Hat JBoss® Enterprise Application Platform 7 was downloaded and deployed onto Red Hat OpenShift Container Platform. The application was then monitored via Red Hat CloudForms.

Solution components

The solution hardware and software components used to build the HPE Reference Configuration for Red Hat OpenShift Container Platform on HPE Composable Infrastructure are detailed in this section.

Solution hardware

The following hardware components were utilized in this Reference Configuration as listed in Table 1.

Table 1: Hardware components

Component	Purpose
HPE Synergy 12000 Frame	Infrastructure for compute, storage, fabric and management
HPE Synergy Composer	Infrastructure management
HPE Synergy Image Streamer	Infrastructure deployment
HPE Synergy 480 Gen10 Compute nodes	Red Hat OpenShift master and worker nodes
HPE Synergy D3940 Storage Module	Composable storage for Red Hat OpenShift
HPE FlexFabric 5900AF Switch	Top of Rack network connectivity

HPE Synergy

HPE Synergy, the first platform built from the ground up for composable infrastructure, empowers IT to create and deliver new value instantly and continuously. This single infrastructure reduces operational complexity for traditional workloads and increases operational velocity for the new breed of applications and services. Through a single interface, HPE Synergy composes compute, storage and fabric pools into any configuration for any application. It also enables a broad range of applications from bare metal to virtual machines to containers, and operational models like hybrid cloud and DevOps. HPE Synergy enables IT to rapidly react to new business demands.

HPE Synergy Frames contain a management appliance called the HPE Synergy Composer which hosts HPE OneView. HPE Synergy Composer manages the composable infrastructure and delivers:

- Fluid pools of resources, where a single infrastructure of compute, storage and fabric boots up ready for workloads and demonstrates self-assimilating capacity.
- Software-defined intelligence, with a single interface that precisely composes logical infrastructures at near-instant speeds; and demonstrates template-driven, frictionless operations.
- Unified API access, which enables simple line-of-code programming of every infrastructure element; easily automates IT operational processes; and effortlessly automates applications through infrastructure deployment.

HPE Synergy Composer

HPE Synergy Frame's unique design physically embeds HPE Synergy Composer powered by HPE OneView to compose compute, storage, and fabric resources in any configuration. HPE Synergy Composer provides the enterprise-level management to compose and deploy system resources to your application needs. This management appliance uses software-defined intelligence to aggregate compute, storage, and fabric resources in a manner that scales to your application needs, instead of being restricted to the fixed ratios of traditional resource offerings. HPE Synergy template-based provisioning enables fast time to service with a single point for defining compute module state, pooled storage, network connectivity, and boot image.

HPE OneView is a comprehensive unifying platform designed from the ground up for converged infrastructure management. A unifying platform increases the productivity of every member of the internal IT team across servers, storage, and networking. By streamlining processes, incorporating best practices, and creating a new holistic way to work, HPE OneView provides organizations with a more efficient way to work. It is designed for open integration with existing tools and processes to extend these efficiencies.

HPE OneView is instrumental for the deployment and management of HPE servers and enclosure networking. It collapses infrastructure management tools into a single resource-oriented architecture that provides direct access to all logical and physical resources of the solution. Logical resources include server profiles and server profile templates, enclosures and enclosure groups, and logical interconnects and logical interconnect groups. Physical resources include server hardware blades, networking interconnects, and computing resources.

The HPE OneView converged infrastructure platform offers a uniform way for administrators to interact with resources by providing a RESTful API foundation. The RESTful APIs enable administrators to utilize a growing ecosystem of integrations to further expand the advantages of the integrated resource model that removes the need for the administrator to enter and maintain the same configuration data more than once and keep all versions up to date. It encapsulates and abstracts many underlying tools behind the integrated resource model, so the administrator can operate with new levels of simplicity, speed, and agility to provision, monitor, and maintain the solution.

The [Ansible Modules for HPE OneView](#) provide an interface to manage all HPE OneView resources and were used in the development of this solution.

HPE Synergy Image Streamer

HPE Synergy Image Streamer is a new approach to deployment and updates for composable infrastructure. This management appliance works with HPE Synergy Composer for fast software-defined control over physical compute modules with operating system and application provisioning. HPE Synergy Image Streamer enables true stateless computing combined with the capability for image lifecycle management. This management appliance rapidly deploys and updates infrastructure.

HPE Synergy Image Streamer adds a powerful dimension to 'infrastructure as code'—the ability to manage physical servers like virtual machines. In traditional environments, deploying an OS and applications or hypervisor is time consuming because it requires building or copying the software image onto individual servers, possibly requiring multiple reboot cycles. In HPE Synergy, the tight integration of HPE Synergy Image Streamer with HPE Synergy Composer enhances server profiles with images and personalities for true stateless operation.

HPE Synergy Composer, powered by HPE OneView, captures the physical state of the server in the server profile. HPE Synergy Image Streamer enhances this server profile (and its desired configuration) by capturing your golden image as the 'deployed software state' in the form of bootable image volumes. These enhanced server profiles and bootable OS, plus application images, are software structures ('infrastructure as code') and no compute module hardware is required for these operations. The bootable images are stored on redundant HPE Synergy Image Streamer appliances, and they are available for fast implementation onto multiple compute nodes at any time. This enables bare metal compute modules to boot directly into a running OS with applications and multiple compute nodes to be quickly updated.

Figure 2 shows an overview of the process to use Red Hat Ansible Tower workflows to select HPE OneView server profile templates, identify available compute hosts and automatically deploy Red Hat OpenShift Container Platform ready servers. The server profile specifies the required networking, storage and firmware as well as the OS deployment plan from HPE Synergy Image Streamer. After the customized images are deployed, Ansible Playbooks are used to install and configure the entire Red Hat OpenShift Container Platform.




Figure 2: Deploying Red Hat OpenShift Container Platform with HPE OneView, HPE Synergy Image Streamer and Red Hat Ansible Tower

HPE Synergy D3940 Storage Module

Each HPE Synergy D3940 Storage Module utilizes HPE Smart Array technology to accelerate performance, plus RAID protection and encryption to improve security and availability providing a fluid pool of storage resources for the composable infrastructure. Additional capacity for compute modules is easily provisioned and intelligently managed with integrated data services for availability and protection. The 40 SFF drive bays per storage module can be populated with 12 G SAS or 6 G SATA drives.

The HPE Synergy D3940 Storage Module provides local storage to compute resources and can meet the demands of a wide range of data workloads. Pooled storage resources provide the flexibility and performance needed to accommodate a wide range of workloads. Changes such as updating firmware are automatically implemented with the infrastructure online significantly reducing errors and delivering real-time compliance.

For this Reference Configuration the HPE Synergy D3940 Storage Module was used both for container images, as well as for container-native storage using Red Hat Gluster Storage. The server profiles for Red Hat OpenShift Container Platform masters, workers, infrastructure, load balancer, and container-native storage nodes including the configuration of local storage. Either the HPE Synergy 480 internal storage or the HPE Synergy D3940 based storage can be used for container ephemeral storage. Configuring the storage in this manner minimizes the use of limited storage on the HPE Synergy Image Streamer. The server profiles for Red Hat OpenShift Container Platform container-native storage nodes also include the configuration of persistent storage volumes using Red Hat Gluster Storage.

HPE Synergy 480 Gen10 Compute Module

The HPE Synergy 480 Gen10 Compute Module delivers superior capacity, efficiency, and flexibility in a two-socket, half-height form factor to support demanding workloads. Powered by Intel® Xeon® Scalable Family of processors, up to 3TB DDR4, more storage capacity and controllers and a variety of GPU options, the HPE Synergy 480 Gen10 Compute Module provides a composable compute resource that can be self-discovered, quickly provisioned, easily managed, and seamlessly redeployed to deliver the right compute capacity for changing workload needs.

HPE Synergy 480 Gen10 Compute Module provides flexible enterprise solutions that allow IT to quickly and confidently implement changes through intelligent template-based operations, reducing downtime and errors from manual operations. The HPE Synergy 480 Gen10 Compute Module provides unmatched threat protection with Hardware Root of Trust and unique chain of trust architecture to protect, detect and recover firmware, and Intelligent System Tuning to smooth performance and match customer workloads through security features that include:

- iLO5 with Silicon Root of Trust for a secure start
- Tamper-proof updates with digital validation
- Enhanced scripting and API capabilities
- Secure firmware recovery
- Standards compliance
- Supply-chain attack detection

Solution management software

The following software components were utilized in this Reference Configuration as listed in Table 2 and Table 3.

Table 2: Red Hat components

Component	Version
Red Hat Ansible Tower	3.2.1
Red Hat CloudForms	5.8.1.5
Red Hat Enterprise Linux	7.4
Red Hat Gluster Storage	3.3
Red Hat OpenShift Container Platform	3.7
Red Hat Satellite	6.2

Table 3. Hewlett Packard Enterprise solution management software

Component	Version
HPE Synergy Composer	3.10.07
HPE Synergy Image Streamer	3.10.02
HPE Synergy Image Streamer artifacts for Red Hat OpenShift Container Platform	HPE-RHEL-7.4-OpenShift-2017-11-27-v3.1.zip

Red Hat Ansible Tower

Red Hat Ansible Automation is a powerful configuration management and orchestration tool, which can be used to automate complicated infrastructure or application deployment tasks. At its core, Ansible ships with hundreds of modules to manage different host types and software. These hosts can be traditional servers running Red Hat Enterprise Linux and other operating systems, as well as an impressive count of network switches and storage arrays. Modules are also included to interact with Application Program Interfaces (APIs) directly, or wrapped up in a separate module to present a standard set of arguments. For example, the `openstack (os_)` modules are provided to orchestrate an OpenStack cloud.

An Ansible Playbook is built by defining tasks. A given task will call a module with the desired set of arguments. The playbook is then run against an inventory which specifies the hosts to run those tasks.

Red Hat Ansible Tower takes those Ansible constructs, and presents them in a clean, modern web GUI. This Reference Configuration used Red Hat Ansible Tower to orchestrate the provisioning of HPE Synergy 480 Gen10 servers, integration with HPE OneView and HPE Synergy Image Streamer for installation of Red Hat Enterprise Linux 7.4, and deployment of Red Hat OpenShift Container Platform with container-native storage. This was accomplished using Red Hat Ansible Tower inventory, templates, roles, tasks, and workflows, to execute the multiple Ansible Playbooks required for this Reference Configuration. The installation of Red Hat Ansible Tower is beyond the scope of this Reference

Configuration. Refer to the [Red Hat Ansible Tower documentation](#) for complete instructions on the installation and configuration of Red Hat Ansible Tower.

Red Hat CloudForms

Red Hat CloudForms delivers the insight, control and automation that enterprises need to address the challenges of managing virtual and containerized environments. This technology enables enterprises to build and operate new environments as well as improve visibility and control of existing environments.

For this Reference Configuration, Red Hat CloudForms was used to monitor the Red Hat OpenShift Container Platform through integration with the Hawkular services running on Red Hat OpenShift. The Hawkular monitoring and logging services are enabled as part of the initial Red Hat OpenShift Container Platform installation via Ansible Playbooks. The installation of Red Hat CloudForms is beyond the scope of this document. Refer to the [Red Hat CloudForms deployment planning guide](#) for more information.

Details on how Red Hat CloudForms was configured to monitor and manage the Red Hat OpenShift infrastructure are found in Appendix E: Using Red Hat CloudForms to monitor Red Hat OpenShift Container Platform.

Red Hat Gluster Storage

Containerized Red Hat Gluster Storage provides the persistent storage for Red Hat OpenShift Container Platform containers in this Reference Configuration. In this hyper-converged solution, the storage containers that host Red Hat Gluster Storage co-reside with the compute containers and serve out storage from the hosts that have local or direct attached storage to the compute containers. This solution integrates Red Hat Gluster Storage deployment and management with Red Hat OpenShift services. As a result, persistent storage is delivered within a Red Hat OpenShift pod that provides both compute and file storage.

Container-native storage for Red Hat OpenShift Container Platform is built around three key technologies:

- Red Hat OpenShift Container Platform provides the Platform-as-a-Service (PaaS) infrastructure based on Kubernetes container management. Basic Red Hat OpenShift architecture is built around multiple master systems where each system contains a set of nodes.
- Red Hat Gluster Storage provides the containerized distributed storage based on Red Hat Gluster Storage 3.3 container. Each Red Hat Gluster Storage volume is composed of a collection of bricks, where each brick is the combination of a node and an export directory.
- Heketi provides the Red Hat Gluster Storage volume life cycle management. It creates the Red Hat Gluster Storage volumes dynamically and supports multiple Red Hat Gluster Storage clusters.

Refer to [Container-native storage for OpenShift Container Platform](#) for more details on Red Hat Gluster Storage.

Red Hat OpenShift Container Platform

Red Hat OpenShift Container Platform is a Platform-as-a-Service (PaaS) offering from Red Hat that brings together Docker and Kubernetes, and provides an API to manage these services. Red Hat OpenShift Container Platform helps application development and IT operations teams modernize applications, deliver new services, and accelerate development processes.

Red Hat OpenShift Container Platform provides developers with an optimal platform for provisioning, building, and deploying applications and their components in a self-service fashion. With automated workflows like the source-to-image (S2I) process, it is easy to get source code from version control systems into ready-to-run, docker-formatted container images. Red Hat OpenShift Container Platform integrates with continuous integration (CI) and continuous delivery (CD) tools, making it an ideal solution for any organization.

Red Hat OpenShift Container Platform gives IT operations a secure, enterprise-grade Kubernetes that provides policy-based control and automation for applications. Cluster services, scheduling, and orchestration provide load-balancing and auto-scaling capabilities. Security features prevent tenants from compromising other applications or the underlying host. And because Red Hat OpenShift can attach persistent storage directly to Linux containers, IT organizations can run both stateful and stateless applications on one platform.

For more information on Red Hat OpenShift Container Platform, see the [Red Hat OpenShift Container Platform 3.7 datasheet](#).

Red Hat Satellite

Red Hat Satellite is used to manage Red Hat infrastructure. For this Reference Configuration, Red Hat Satellite provides a local mirror of all available Red Hat packages for faster software delivery inside the data center. A built in DNS server provides automated DNS entry when a host is created, and deletion when the host is decommissioned.

Configuration of Red Hat Satellite for the Red Hat OpenShift Container Platform deployment is described in Appendix D: Configuring Red Hat Satellite.

Best practices and configuration guidance for the solution**Red Hat OpenShift Container Platform deployment best practices utilizing HPE Synergy Image Streamer and Ansible Tower**

This Reference Configuration outlines deployment of Red Hat OpenShift Container Platform on physical servers using HPE Synergy Image Streamer and Ansible Tower as shown in Figure 3. This configuration provides an optimized solution with highly available OpenShift master, OpenShift container-native storage, and OpenShift worker deployments.

This solution is ideal for organizations who are developing cloud native applications or refactoring existing applications using containers and want to maximize resource, performance and cost efficiencies. Additional Red Hat OpenShift Container Platform master or worker nodes can be rapidly deployed as needed on the fluid pool of HPE Synergy resources.

HPE Synergy configuration

The three HPE Synergy frames used for this Reference Configuration include HA deployment of HPE Synergy Composer and HPE Synergy Image Streamer as shown in Figure 3. The HPE Synergy D3940 Storage Modules are used for ephemeral storage for container deployments and for the container-native storage.

The initial deployment of the solution deploys HPE Synergy 480 Gen10 Compute Modules deployed as:

- 13x HPE Synergy 480 Gen10 Compute Modules, decomposed in:
 - Red Hat OpenShift masters: 3x servers, 1 per frame
 - Red Hat OpenShift container-native storage: 3x servers, 1 per frame
 - Red Hat OpenShift infrastructure nodes: 3x servers, 1 per frame
 - Red Hat OpenShift workers 3x servers, 1 per frame
 - Load balancer/NFS: 1x server
- 2x HPE Synergy 480 Gen10 Compute Modules available in the environment were used to demonstrate scaling out Red Hat OpenShift Container Platform workers.

Each HPE Synergy D3940 was configured with 16x 300GB SAS HDD allowing for all container and Red Hat Gluster Storage volumes to be created using redundant volumes.




Figure 3: HPE Synergy configuration

HPE Synergy Image Streamer best practices

Best practices for HPE Synergy Image Streamer deployment and usage include:

- As shown in Figure 3, redundant HPE Synergy Image Streamers were deployed as part of this Reference Configuration, and are required for a production installation. If you need to scale your environment beyond 3 HPE Synergy Frames, be sure to follow [HPE recommended guidelines](#) to ensure your configuration meets minimum requirements.
- Deploy container images to a storage system such as the HPE Synergy D3940 used for this Reference Configuration. Do not deploy the container images to your root filesystem on the HPE Synergy Image Streamer to avoid large and rapidly-growing smart clones.
- Create artifact bundles of your working deployment plans, build plans, build scripts and golden images and download them to alternate storage so they can be restored if necessary.
- As existing images and deployment plans are updated, be sure to remove any that are no longer used to preserve available storage. Monitor the available storage from the Deployment Appliances page under Storage.

Utilizing HPE Synergy Image Streamer and Red Hat Ansible Tower to deploy bare metal servers for Red Hat OpenShift Container Platform

For this Reference Configuration, HPE Synergy Image Streamer is used to deploy the initial images and perform customizations in preparation for Red Hat OpenShift Container Platform deployment. Red Hat Ansible Tower is used to deploy and configure Red Hat OpenShift Container Platform on the provisioned servers and storage volumes.

The deployment of Red Hat OpenShift Container Platform is greatly simplified through the use of HPE Synergy Image Streamer and Red Hat Ansible Tower. The process to use Red Hat Ansible Tower and HPE Synergy Image Streamer to automatically provision bare metal servers requires the following steps:

1. Configure the networking in HPE OneView
2. Download and import the HPE Synergy Image Streamer artifacts for Red Hat OpenShift
3. Configure Red Hat Satellite
4. Create golden images for masters, container-native storage nodes and workers
5. Create server profile templates in HPE OneView
6. Configure Ansible Tower for Red Hat OpenShift Container Platform deployment
7. Deploy Red Hat OpenShift Container Platform from Red Hat Ansible Tower
8. Monitor the solution from Red Hat CloudForms

Additional optional steps include:

1. Configure container-native storage
2. Lifecycle management for Red Hat OpenShift Container Platform on HPE Synergy
3. Deploying a sample application

Configure the networking in HPE OneView

Two networks were configured for the Red Hat OpenShift Container Platform deployment. A corresponding network set was created which includes a single network as a best practice. The network set is used in the server profiles. Using network sets inside the server profile allows for modification of the networks included in the network set without having to modify a server profile. This makes it easier to add or remove networks without having to power off the server.

The following Ethernet networks are required in the HPE Synergy environment, for usage in the server profiles for Red Hat OpenShift Container Platform deployment:

- Public management network (ns_mgmt)
- HPE Image Streamer deployment network (ns_deployment)

Table 4 summarizes the configuration for each network. Networks were created with a preferred bandwidth of 2.5 Gb/second and maximum bandwidth of 20 Gb/second because they share a single Virtual Connect SE 40Gb F8 module.

Table 4: Networks for Red Hat OpenShift deployment

Network set name	VLAN	Subnet ID	Uplink set	Description
ns_mgmt	60	10.60.0.0/16	sus_prod	Management network for Red Hat OpenShift deployment
ns_deployment	10	10.10.10.0/24	i3s-iscsi	HPE Synergy Image Streamer deployment network

Download and import the HPE Synergy Image Streamer artifacts for Red Hat OpenShift

Hewlett Packard Enterprise has created HPE Synergy Image Streamer artifacts and published them to HPE's GitHub location for customer download. The following artifact bundle was used in the development of this Reference Configuration: [HPE-RHEL-7.4-OpenShift-2017-11-27-v3.1.zip](#). Import the downloaded artifact bundle into HPE Synergy Image Streamer and extract the contents. The artifact bundle includes:

- Deployment plans
- OS build plans

- Plan scripts

Configure Red Hat Satellite

This solution requires an installation of Red Hat Satellite and licenses to Red Hat OpenShift software. Pre-requisite packages are pulled from Red Hat Satellite for the golden image creation. The HPE Synergy Image Streamer scripts register deployed servers with Red Hat Satellite and Ansible Playbooks pull down the required Red Hat OpenShift packages as part of server deployment. See Appendix D: Configuring Red Hat Satellite for details on how to configure Red Hat Satellite.

Create golden images for masters, container-native storage nodes and workers

The golden images for Red Hat OpenShift Container Platform deployment are the captured content of a previously deployed Red Hat Enterprise Linux 7.4 boot disk customized with the pre-requisites for Red Hat OpenShift deployment. Two golden images were captured. Red Hat OpenShift masters require 50GB boot disks. Red Hat OpenShift container-native storage and Red Hat OpenShift workers require 25GB. The only difference between the two golden images is the initial volume size created before OS deployment. The process to capture an image automatically removes system-specific information such as hostname and IP addresses, enabling the image to be re-deployed and automatically customized for deployment using HPE Synergy Image Streamer artifacts such as plan scripts, OS build plans and deployment plans.

The process to create the Red Hat Enterprise Linux 7.4 golden images is described in Appendix B: Creating golden images for Red Hat OpenShift Container Platform deployment.

Customize the HPE supplied deployment plans

Five deployment plans are provided for Red Hat OpenShift Container Platform deployments.

- HPE-RHEL7.4-OpenShiftMaster
- HPE-RHEL7.4-OpenShiftWorker
- HPE-RHEL7.4-OpenShiftCNS
- HPE-RHEL7.4-OCP-Infra
- HPE-RHEL7.4-OpenShiftLBNFS

The deployment plans for Red Hat OpenShift Container Platform as shown in Figure 4 needs to be customized before they can be used. Make copies of the plans and edit the values for the Plan Attributes to match the settings for your environment. You will want to hide some of the custom attributes and their values so that they are pre-configured when server profile templates are created. For example, if you always specify the same NTP server, set this value and hide the corresponding custom attributes and values. Details on the custom attribute definitions and values are found in Appendix C: Setting the custom attributes in the Red Hat OpenShift deployment plans. Set the golden image which corresponds to the Red Hat OpenShift component for the selected deployment plan. The 50GB golden image is used for the Red Hat OpenShift master and the 25GB golden image is used for worker, infra, load balancer, and container-native storage nodes.

HPE-RHEL7.4-OpenShiftMaster

General ▾

⌵

General

Description

not set

Created

Nov 3, 2017 05:14 am

Modified

Nov 6, 2017 09:34 pm

Read-only

No

Used by

none

Plan Attributes

OS build plan

[RHEL74-OpenShift-10-24-2017](#)

Custom attributes

Name	Type	Visible on deployment	Default value
▶ ActivationKey	string	No	HPE-OCF
▶ AnsibleSSHKey	string	No	ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQD root@ansible.doudra.local
▶ DeviceMapperDrive	string	Yes	/dev/sdd
▶ DeviceMapperForceDelete	string	No	Yes
▶ DNSKey	password	No	*****
▶ NewRootPassword	password	No	*****
▶ NtpServer	string	No	10.60.1123
▶ OrgName	string	No	hpe_cloud
▶ ServerFQDN	string	Yes	
▶ SSH	string	No	Enabled
▶ TeamONIC1	nic	Yes	n/a
▶ TeamONIC2	nic	Yes	n/a

Golden image

[OpenShift-Master](#)

Figure 4: Deployment plan for Red Hat OpenShift master

Create server profile templates in HPE OneView

From HPE OneView, create server profile templates for the Red Hat OpenShift master, Red Hat OpenShift container-native storage, Red Hat OpenShift load balancer/NFS, Red Hat OpenShift infra and Red Hat OpenShift worker nodes. By using the server profile template feature within HPE OneView you can specify and maintain a single configuration for the system firmware, BIOS, and boot-order at time of initial deployment as well as orchestrate updates to that configuration as needed. This provides a location to centrally manage and update configuration settings, such as system firmware, and provides assurance that each server is running with the same configuration and has event and health data being exposed up to HPE OneView. The server profile template requirements for Red Hat OpenShift Container Platform deployment are listed in Table 5.

Table 5: Red Hat OpenShift Container Platform server profile template requirements

Component	Image Streamer Boot Volume	Storage	RAID level	Networks
Red Hat OpenShift master	50GB	300GB container	1	Mgmt
Red Hat OpenShift worker	25GB	300GB container	1	Mgmt
Red Hat OpenShift infra	25GB	300GB container	1	Mgmt
Red Hat OpenShift load balancer / NFS	25GB	300GB nfs	1	Mgmt
Red Hat OpenShift container-native storage	25GB	300GB container 300GB gluster	1 6	Mgmt

Note

The 300GB RAID 6 storage configuration for Red Hat Gluster Storage provides 600GB of useable storage.

The server profile template for Red Hat OpenShift master is shown in Figure 5.

✓

OCP-Master

OS Deployment

⌵

⌵

OS Deployment

OS deployment plan

HPE-RHEL7.4-OpenShiftMaster

OS volume

pending assignment

DeviceMapperDrive

/dev/sdd

ServerFQDN

ocp-masterXX.cloudra.local

▶ TeamONIC1

Management1 MGMT1

▶ TeamONIC2

Management2 MGMT1

Firmware

Firmware baseline

managed manually

Connections

Expand all


Collapse all

ID	Name	Network	Port	Boot
▶ 1	DeploymentNetwork A	<u>DEPLOY</u> VLAN10	Mezzanine 3:1-a	iSCSI primary
▶ 2	DeploymentNetwork B	<u>DEPLOY</u> VLAN10	Mezzanine 3:2-a	iSCSI secondary
▶ 3	Management1	<u>MGMT1</u> VLAN60	Mezzanine 3:1-c	Not bootable
▶ 4	Management2	<u>MGMT1</u> VLAN60	Mezzanine 3:2-c	Not bootable

Figure 5: Server profile for Red Hat OpenShift master

The server profile template settings are customized as described below:

- Specify the OS deployment plan you created for the Red Hat OpenShift master node. The deployment network is automatically added when an OS deployment plan is selected.
- Under Connections, add 2 instances of the management network for NIC teaming. Specify either the management network or the management network set.
- Under Local Storage, select to edit SAS Mezz 1 storage controller. Select the checkboxes for Manage Mezz 1 storage controller and Re-initialize controller on next profile application and click Select Create logical drive.
- Creation of logical drives depends on whether or not you wish to use internal server storage or external storage from the HPE Synergy D3940. Select the storage you wish to use for container storage as shown in Figure 6. For this solution RAID 1 was used for container storage.



The screenshot shows a 'Create Logical Drive' configuration window. It contains the following fields and options:

- Name:** A text input field containing the value 'container'.
- RAID level:** A dropdown menu showing 'RAID 1'.
- Storage Location:** Two radio buttons, 'Internal' and 'External'. The 'External' button is selected.
- Number of physical drives:** A text input field containing the value '2'.
- Select drives by:** Two radio buttons, 'Drive type' and 'Size and technology'. The 'Drive type' button is selected.
- Drive type:** A dropdown menu showing '300 GB SAS HDD (29 available)'.

Figure 6: Create ephemeral storage for containers

- After the connections and storage are configured, preset values for the custom attributes. Set a value for FQDN, Team0NIC1 and Team0NIC2. The values for NIC attributes will be overwritten by the Ansible Playbooks so it does not really matter what values you set here. It is more important to set custom attributes correctly in the deployment plan.

Follow the same process to create server profile templates for Red Hat OpenShift workers, Red Hat OpenShift load balancer, Red Hat OpenShift infra and Red Hat OpenShift container-native storage. Each server profile template must include the corresponding deployment plan for the Red Hat OpenShift component. Each requires the same management network configuration and a logical drive for container storage. Container-native storage nodes must be configured with an additional logical drive for Red Hat Gluster Storage. When creating the logical drive for Red Hat Gluster Storage, set the RAID level to RAID 6. As shown in Figure 7, internal logical drives are used for container deployments and external logical drives (HPE Synergy D3940) are used for Red Hat Gluster Storage.

OCP-CNS-Node

Connections

Connections

Expand all
Collapse all

ID	Name	Network	Port	Boot
▶ 1	Deployment Network A	DEPLOY VLAN10	Mezzanine 3:1-a	iSCSI primary
▶ 2	Deployment Network B	DEPLOY VLAN10	Mezzanine 3:2-a	iSCSI secondary
▶ 3	Management1	MGMT1 VLAN60	Mezzanine 3:1-c	Not bootable
▶ 4	Management2	MGMT1 VLAN60	Mezzanine 3:2-c	Not bootable

Local Storage

Integrated storage controller

Mode

managed manually

SAS Mezz 1 storage controller

Controller will be re-initialized on next profile application.

Name	Type	RAID Level	Number of Drives	Size GB	Drive Technology	Boot
docker	Internal logical drive	RAID 1	2	n/a	not specified	No
gluster	External logical drive	RAID 6	4	300	SAS HDD	No

Figure 7: Connections and storage information from server profile template for Red Hat OpenShift container-native storage

After the server profile templates have been created, perform test deployments manually.

1. Create a server profile from the OCP-Master profile template you created and apply it to an available compute module.
2. Power on the server.
3. Use SSH to connect to the server.
4. Use the `df` and `cat /proc/partitions` commands to identify which partition is used for boot and which is used for docker containers. Be sure the custom attribute `DeviceMapperDrive` is set to the partition you want to use for container deployments and not to the boot partition. The device specified is wiped to ensure a successful installation.
5. Use `nslookup` to verify that the hostname you provided in the server profile template resolves correctly.
6. Verify that the server registered with Red Hat Satellite. If it did not register automatically, validate that the `ActivationKey` and `OrgName` custom attributes are set correctly in your deployment plan.
7. Power off the test deployment, delete the server profile and remove the entry from Red Hat Satellite to free up the license.
8. Follow the same process to deploy an OCP-CNS node using the server profile template you created.
9. The OCP-CNS node has both container and gluster storage. Validate that the values you set for `DeviceMapperDrive` match what you see from logging in via SSH. The `DeviceMapperDrive` parameter requires that the first value is the partition for container storage and the second

value is for gluster storage on the HPE Synergy D3940. It should be specified as a comma separated value, for example:
`/dev/sdc,/dev/sdb`

10. Power off the server, delete the server profile and remove the entry from Red Hat Satellite to free up the license.

Configure Ansible Tower for Red Hat OpenShift Container Platform deployment

This section provides information about the Ansible Playbooks created for this Reference Configuration and how the Red Hat Ansible Tower workflow ties it all together. The set of playbooks were created with modularity in mind. Rather than create one monolithic playbook to interact with the various services, a role was created for each major step. This makes debugging sections easier, as well as allowing for re-use of certain roles in other infrastructures. For instance, the provisioning playbook could be used in another Ansible Tower workflow, with the Red Hat OpenShift Container Platform deployment swapped out for another infrastructure stack.

The Red Hat OpenShift Container Platform installer is based on Red Hat Ansible Automation, and an [advanced install](#) exposes this to a systems administrator. Inventory and variables can be configured and the playbook can be run using the standard `ansible-playbook` command. The use of these playbooks is well documented on the [Red Hat OpenShift site](#). This Reference Configuration only covers integrating and running those playbooks in Ansible Tower. Playbooks to handle all of the provisioning steps leading up to the Red Hat OpenShift Container Platform installation are available in a [GitHub repository](#). Some modifications will be required to work in different environments, outlined below.

Note

The scripts described in this Reference Configuration and provided in the associated GitHub repository are not supported by Red Hat. They merely provide a mechanism to build out your infrastructure.

Clone and modify GitHub Repository

In order to deploy the playbooks created for this Reference Configuration, some modifications of the content are required. Notably, a password file encrypted with `ansible-vault` needs to be copied to `/var/lib/awx/projects/ocp-on-synergy/roles/passwords/vars/passwords.yml`. Environment specific changes should be made to the variables found under `./group_vars/`.

If an organization has an existing git infrastructure (such as gitlab) they may choose to clone the public repository and maintain their changes internally. Otherwise, the repository can be forked on GitHub to track the requisite changes. In either case, the modified playbooks must be stored in a git repository that is accessible to Ansible Tower.

HPE OneView Modules

The Ansible Modules for HPE OneView are not a core module yet, so they are not included in a standard installation. They must be installed on the Ansible Tower server along with the required python packages.

First, install the HPE OneView SDK via pip:

```
curl -o get-pip.py https://bootstrap.pypa.io/get-pip.py
python get-pip.py
pip install hpOneView dnspython
```

Then clone the modules and make them accessible to Ansible Tower:

```
git clone https://github.com/HewlettPackard/oneview-ansible.git /tmp/oneview-ansible
mkdir -p /usr/share/ansible/oneview-ansible
rsync -avh --progress /tmp/oneview-ansible/library /usr/share/ansible/oneview-ansible
```

Modified nsupdate module

The set of playbooks written for this Reference Configuration require a modified `nsupdate` module to support one to many DNS creation. A pull request has been submitted to support this feature and is merged in the Ansible 2.4 release. The updated file is included in the `ocp-on-synergy` [GitHub repository](#) for those using Ansible 2.3 or earlier and included during playbook execution via a custom `ansible.cfg` file also stored in the repository.

Credentials

Red Hat Ansible typically communicates to a target host via SSH, using a public key. Ansible Tower can store and encrypt these credentials to run playbooks. An SSH key pair is generated:

```
ssh-keygen -f tower
Generating public/private rsa key pair.
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in tower.
Your public key has been saved in tower.pub.
The key fingerprint is:
...
```

The SSH key pair is then stored in Ansible Tower by clicking the gear icon, then credentials and finally +ADD as shown in Figure 8.

The screenshot displays the Ansible Tower web interface. The top navigation bar includes 'TOWER', 'PROJECTS', 'INVENTORIES', 'TEMPLATES', 'JOBS', and a user profile 'admin'. The breadcrumb trail is 'SETTINGS / CREDENTIALS / EDIT CREDENTIAL'. The main content area is titled 'root-ssh' and has two tabs: 'DETAILS' (selected) and 'PERMISSIONS'. The 'DETAILS' tab contains the following fields:

- * NAME**: root-ssh
- DESCRIPTION**: root ssh access
- ORGANIZATION**: Default
- * CREDENTIAL TYPE**: Machine

Below these is the 'TYPE DETAILS' section:

- USERNAME**: root
- PASSWORD**: A field with a 'SHOW' button and a 'Prompt on launch' checkbox.

The 'SSH PRIVATE KEY' section shows a 'REPLACE' button and a large 'ENCRYPTED' area. At the bottom, there are fields for 'PRIVATE KEY PASSPHRASE' (with a 'SHOW' button and 'Prompt on launch' checkbox), 'PRIVILEGE ESCALATION METHOD' (a dropdown menu), and 'PRIVILEGE ESCALATION USERNAME'.

Figure 8: Configure Red Hat Ansible Tower SSH keys

The password used to encrypt the password playbook is also stored under 'Vault Password'. The public SSH key is deployed via Red Hat Satellite when a host is provisioned. In some cases, the git repository may require login details, which can also be stored safely in Ansible Tower.

Projects

The locally maintained git repository ocp-on-synergy is added to Ansible Tower as shown in Figure 9.




Figure 9: ocp-on-synergy project

Add the publicly accessible openshift-ansible project to Ansible Tower as shown in Figure 10.

The screenshot shows the Ansible Tower web interface. The top navigation bar includes 'TOWER', 'PROJECTS', 'INVENTORIES', 'TEMPLATES', and 'JOBS'. The user is logged in as 'admin'. The breadcrumb trail is 'PROJECTS / openshift-ansible'. The main content area is titled 'openshift-ansible' and has three tabs: 'DETAILS', 'PERMISSIONS', and 'NOTIFICATIONS'. The 'DETAILS' tab is active. The form contains the following fields:

- * NAME: openshift-ansible
- DESCRIPTION: (empty)
- * ORGANIZATION: Default
- * SCM TYPE: Git
- SOURCE DETAILS:
 - * SCM URL: https://github.com/openshift/openshift-ansible.git
 - SCM BRANCH/TAG/COMMIT: release-3.6
 - SCM CREDENTIAL: (empty)
- SCM UPDATE OPTIONS:
 - ☒ Clean
 - ☐ Delete on Update
 - ☐ Update on Launch

At the bottom right are 'CANCEL' and 'SAVE' buttons.

Figure 10: openshift-ansible project

The list of hosts and variables for this Reference Configuration can be entered via the web GUI, however for complex playbooks with a lot of variables, this can be cumbersome. Ansible Tower provides a handy [CLI tool](#), “tower-manage inventory import”, that can be used to import this data. Before using the tool, the empty inventory must first be created in the web GUI as shown in Figure 11.

The screenshot shows the Ansible Tower web interface for creating a new inventory. The top navigation bar is the same as in Figure 10. The breadcrumb trail is 'INVENTORIES / CREATE INVENTORY'. The main content area is titled 'NEW INVENTORY' and has six tabs: 'DETAILS', 'PERMISSIONS', 'GROUPS', 'HOSTS', 'SOURCES', and 'COMPLETED JOBS'. The 'DETAILS' tab is active. The form contains the following fields:

- * NAME: ocp-on-synergy
- DESCRIPTION: (empty)
- * ORGANIZATION: Default
- INSIGHTS CREDENTIAL: (empty)
- INSTANCE GROUPS: (empty)
- VARIABLES: (empty text area)

At the bottom right are 'CANCEL' and 'SAVE' buttons.

Figure 11: Create inventory

Creating the inventory from the browser interface creates the host file and variable files on the Ansible Tower server in `/etc/ansible/ocp-on-synergy`. Sample hosts file and variable files as well as instructions to import the files can be found in the [GitHub repository](#) or in Appendix G: Red Hat Ansible Playbooks and customization. Modify the sample files to meet your organization's requirements and import the variable files.

Templates

Once the credentials, projects and inventories are configured, the job templates can be created in Red Hat Ansible Tower. From Templates, select to add a job template as shown in Figure 12.

The screenshot shows the 'TEMPLATES' section of the Red Hat Ansible Tower web interface. The breadcrumb path is 'TEMPLATES / ocp-openshift-install'. The interface displays a form for creating or editing a job template. The form includes several sections with tabs for 'DETAILS', 'PERMISSIONS', 'NOTIFICATIONS', 'COMPLETED JOBS', and 'ADD SURVEY'. The 'DETAILS' tab is active, showing the following configuration:

- NAME:** ocp-openshift-install
- DESCRIPTION:** deploy openshift on synergy nodes
- JOB TYPE:** Run (with a 'PROMPT ON LAUNCH' checkbox)
- INVENTORY:** ocp-on-synergy (with a 'PROMPT ON LAUNCH' checkbox)
- PROJECT:** openshift-ansible
- PLAYBOOK:** playbooks/byo/config.yml
- CREDENTIAL:** MACHINE: root-ssh (with a 'PROMPT ON LAUNCH' checkbox)
- FORKS:** 20
- LIMIT:** (empty field with a 'PROMPT ON LAUNCH' checkbox)
- VERBOSITY:** 0 (Normal) (with a 'PROMPT ON LAUNCH' checkbox)
- INSTANCE GROUPS:** (empty field)
- JOB TAGS:** (empty field with a 'PROMPT ON LAUNCH' checkbox)
- SKIP TAGS:** (empty field with a 'PROMPT ON LAUNCH' checkbox)
- LABELS:** (empty field)
- SHOW CHANGES:** OFF (with a 'PROMPT ON LAUNCH' checkbox)

Figure 12: Creating templates in Red Hat Ansible Tower

The following job templates were created as shown in Table 6. Create the additional job templates with the specifications shown below.

Table 6: Red Hat Ansible Tower job templates

Template name	Project	Playbook	Description	Forks
ocp-add_to_oneview	ocp-on-synergy	playbooks/add_to_oneview.yaml	Add a new node to HPE OneView for scaling	default
ocp-cleanup	ocp-on-synergy	playbooks/clean.yaml	Clean up all deployments	20
ocp-fix_inventory	ocp-on-synergy	playbooks/fix_inventory.yaml	Move new host in to normal 'nodes' host group	default
ocp-openshift-install	openshift-ansible	playbooks/byo/config.yml	Deploy Red Hat OpenShift on HPE Synergy nodes	20
ocp-openshift-scaleup	openshift-ansible	playbooks/byo/openshift-node/scaleup.yml	Scale up Red Hat OpenShift cluster with new node	default
ocp-postdeploy	ocp-on-synergy	playbooks/postdeploy.yaml	ocp postdeployment tasks	20
ocp-predeploy	ocp-on-synergy	playbooks/predeploy.yaml	ocp predeployment tasks	20
ocp-provisioning	ocp-on-synergy	playbooks/provisioning.yaml	Provisioning nodes via HPE OneView for ocp	20
ocp-provisioning-limited	ocp-on-synergy	playbooks/provisioning.yaml	Limit provisioning to new_nodes group	20
ocp-scaledown	ocp-on-synergy	playbooks/scaledown.yaml	Remove node from Red Hat OpenShift then from HPE OneView	default

The ocp-scaledown job template requires a survey to supply the required variables. Use the Add Survey button to configure the job to prompt for a target_node and supply the information as shown in Table 7:

Table 7: Survey prompts for ocp-scaledown

Prompt	Description	Answer Variable Name	Answer type	Required
Target Hostname	Enter a hostname to remove from the cluster	target_node	String	Checked

Once the job templates are created, you can create workflow templates. Two workflow templates were created:

ocp-on-synergy: End to End provisioning of Red Hat OpenShift Container Platform on HPE Synergy hardware

Use the workflow editor to add the following steps as shown in Figure 13.

- a. ocp-cleanup
- b. ocp-provisioning
- c. ocp-predeploy
- d. ocp-openshift-install
- e. ocp-postdeploy



Figure 13: Ansible workflow to deploy Red Hat OpenShift Container Platform

ocp-scaleup: Scale up the Red Hat OpenShift Container Platform cluster

This workflow expects to be supplied with a host name and IP for the new node. The variables are supplied using the Add Survey button. Configure the prompts as shown in Table 8, below.

Table 8: Survey prompts for ocp-scaleup

Prompt	Description	Answer Variable Name	Answer type	Required
New Hostname	Enter a hostname for the new node	new_node	String	Checked
New IP	Enter the IP address for the new node	new_ip	String	Checked

Use the workflow editor to add the following steps as shown in Figure 14.

- a. ocp-add_to_onview
- b. ocp-provisioning-limited (provisioning applied to new_nodes group)
- c. ocp-openshift-scaleup
- d. ocp-fix_inventory




Figure 14: Ansible workflow to scale up Red Hat OpenShift Container Platform deployment

Deploy Red Hat OpenShift Container Platform from Red Hat Ansible Tower

Once the workflows and playbooks are configured in Red Hat Ansible Tower, deployment of the Red Hat OpenShift Container Platform can be performed with a single click. From Ansible Tower, select the Templates tab and select the ocp-on-synergy workflow Launch icon to start the deployment as shown in Figure 15.




Figure 15: Deploying Red Hat OpenShift Container Platform from Ansible Tower

Track the status of the workflow from the Jobs tab. The output of the ocp-provisioning step is shown in Figure 16.




Figure 16: Viewing deployment status in Ansible Tower

Once the job completes successfully, container services can be deployed either via the Red Hat OpenShift Container Platform web interface or via the command line interface from one of the master nodes. With the deployment complete the Red Hat OpenShift Container Platform will resemble the deployment illustrated in Figure 17. The deployment will have three master nodes running the etcd cluster, three infrastructure nodes, and three container-native storage nodes, three worker nodes and a load balancer / NFS server node as shown in Figure 17. These nodes provide the basic services and infrastructure for the Red Hat OpenShift Container Platform cluster. Additional application nodes can be added as needed to scale out the cluster. The registry for container applications and routing services are running on the infrastructure nodes. The routers provide routing services between the external network and the container network. Load balancer / NFS node is running HA Proxy to provide load balancing of external traffic among the master nodes. This node is also running an NFS server to provide persistent storage for the registry. There are three nodes running container-native storage to provide containers with persistent storage.




Figure 17: Fully deployed Red Hat OpenShift Container Platform

After deployment the Red Hat OpenShift Container Platform cluster server nodes can be viewed and managed through the HPE OneView management interface as shown below in Figure 18.




Figure 18: HPE OneView Server Profiles

Validation and troubleshooting procedures are found in Appendix H: Red Hat OpenShift Container Platform deployment validation and troubleshooting.

Monitor the solution from Red Hat CloudForms

Red Hat CloudForms was used to monitor the deployment of Red Hat OpenShift Container Platform on HPE Synergy. Details on configuring Red Hat OpenShift Container Platform as a provider, creating custom reports, and monitoring newly deployed applications is found in Appendix E: Using Red Hat CloudForms to monitor the Red Hat OpenShift Container Platform.

Configure container-native storage

The Red Hat OpenShift Container Platform cluster was deployed with a three node containerized glusterfs cluster. A default storage class named glusterfs-storage was created to support persistent storage for containers. This can be viewed by executing `oc describe storageclass` as shown below.

```
oc describe storageclass
Name:          glusterfs-storage
IsDefaultClass: Yes
Annotations:   storageclass.kubernetes.io/is-default-class=true
Provisioner:   kubernetes.io/glusterfs
Parameters:    resturl=http://heketi-storage-
glusterfs.paas.cloudra.local,restuser=admin,secretName=heketi-storage-admin-
secret,secretNamespace=glusterfs
Events:        <none>
```

The `oc create` command will be used to create persistent volume claims on the glusterfs-storage storage class.

Create a text file that will be used by the `oc create` command to create a persistent volume claim using the glusterfs-storage class. In this example the text file was named `pvc.yaml` and the contents of the text file are displayed below.

```
apiVersion: v1
kind: PersistentVolumeClaim
metadata:
  name: glusterpvc
spec:
  accessModes:
    - ReadWriteOnce
  storageClassName: glusterfs-storage
  resources:
    requests:
      storage: 5Gi
```

Use the `pvc.yaml` file with the `oc create` command to create the persistent volume claim.

```
oc create -f pvc.yaml
persistentvolumeclaim "glusterpvc" created
```

Use the `oc get pvc` command to view the persistent volume claim.

```
oc get pvc glusterpvc
```

NAME	STATUS	VOLUME	CAPACITY	ACCESSMODES
STORAGECLASS		AGE		
glusterpvc	Bound	pvc-8482cfed-cec9-11e7-ab79-2a77ef000417	5Gi	RWO
glusterfs-storage		6m		

Use the `oc get pv` command to view persistent volume that was dynamically created on the glusterfs-storage class.

```
oc get pv pvc-8482cfed-cec9-11e7-ab79-2a77ef000417
```

NAME	STATUS	REASON	AGE	CAPACITY	ACCESSMODES	RECLAIMPOLICY	STATUS	CLAIM
STORAGECLASS								
pvc-8482cfed-cec9-11e7-ab79-2a77ef000417	Bound		8m	5Gi	RWO	Delete	Bound	default/glusterpvc
glusterfs-storage								

Lifecycle management for Red Hat OpenShift Container Platform on HPE Synergy

If demand for container deployments exceeds the capacity of the existing worker nodes, new worker nodes can be added using the ocp-scaleup workflow template.

- From Ansible Tower, select the Templates tab and select the Launch icon for the ocp-scaleup workflow template.
- Provide a new hostname and an IP address and then select Launch as shown in Figure 19.




Figure 19: Scale up worker nodes with Ansible Tower

Follow the progress of the scale-up workflow from the Jobs tab. Once the process completes, the new worker node is available for container deployments.

Similarly, if the extra capacity is no longer needed, free up resources using the ocp-scaledown job template and supply the hostname for the server you wish to remove from the cluster.

Deploying a sample application

A sample microservice application was deployed on the Red Hat OpenShift Container Platform. Details on deploying the sample application are found in Appendix F: Deploying a sample application.

Performance benefits of Red Hat OpenShift Container Platform deployment using HPE Synergy Image Streamer

This Reference Configuration includes the artifacts that were used to automate the deployment of bare metal servers in preparation for Red Hat OpenShift deployment. The golden images used for deployment are configured with the pre-requisite packages installed and firewall configuration settings. The plan scripts automatically set the hostname and networking as well as configure the storage for container deployments. Through the use of golden images and plan scripts, the overall deployment time is significantly reduced compared to a manual deployment or a scripted installation using Kickstart files. The process to clone the volume takes less than 3 minutes. The worker OS deployment times shown below include the time to power on the server, POST, and boot the OS.

Table 9: Additional Worker deployment comparison

Deployment method	Deployment type	Deployment time
HPE Synergy Image Streamer	Volume smart clone	5 minutes
Red Hat Satellite OS Kickstart deployment	Scripted OS install	15 minutes
ISO image deployment plus manual configuration	Manual install and configuration	120 minutes (estimated)

Configuration and deployment of the networking, storage and operating system for the 13 nodes required for Red Hat OpenShift Container Platform takes approximately 40 minutes. An additional hour is required for Red Hat OpenShift Container Platform deployment and customization. This could be compared to manual configuration of networking, storage, operating system provisioning and Red Hat OpenShift Container platform deployment provided by a consulting or services organization. This type of deployment could take from 3 – 5 days. The automation also reduces the chances of operator or installer induced errors.

Summary

The world of IT is always evolving and system administrators are being called upon to deliver increasingly complex systems. The hardware at their disposal needs to be flexible and adapt as well. The HPE Synergy platform, coupled with Red Hat Ansible Tower, empowers IT to fully automate - from bare metal to software installation - the deployment of complex systems.

This Reference Configuration has described the solution HPE and Red Hat have jointly created to help customers take full advantage of today's composable platforms. This solution provides IT with a one-click deployment of Red Hat OpenShift Container Platform on HPE Synergy using Ansible Tower.

Utilizing HPE Synergy and Ansible Tower for Red Hat OpenShift Container Platform deployment significantly reduces the initial configuration and deployment time of the solution. It increases the reliability for lifecycle management and operations and builds in best practices to reduce the chances of human error.

This Reference Configuration describes solution testing performed in November 2017.

Appendix A: Bill of materials

The following BOMs contain electronic license to use (E-L TU) parts. Electronic software license delivery is now available in most countries. HPE recommends purchasing electronic products over physical products (when available) for faster delivery and for the convenience of not tracking and managing confidential paper licenses. For more information, please contact your reseller or an HPE representative.

Note

Part numbers are at time of publication and subject to change. The bill of materials does not include complete support options or other rack and power requirements. If you have questions regarding ordering, please consult with your HPE Reseller or HPE Sales Representative for more details. hpe.com/us/en/services/consulting.html.

Table 10: Bill of materials

Quantity	Part number	Description
Rack and network infrastructure		
1	BW908A	HPE 42U 600x1200mm Enterprise Shock Rack
4	AF522A	HPE Intelligent 8.6kVA/L15-30P/NA/J PDU
1	HC790A	HPE Integration Center Routg Service FIO
1	BW932A	HPE 600mm Rack Stabilizer Kit
1	BW909A	HPE 42U 1200mm Side Panel Kit
1	JG505A	HPE 59xx CTO Switch Solution
2	JG510A	HPE 5900AF 48G 4XG 2QSFP+ Switch
4	JD096C	HPE X240 10G SFP+ SFP+ 1.2m DAC Cable
2	JC680A	HPE 58x0AF 650W AC Power Supply
2	JC682A	HPE 58x0AF Bck(pwr) Frt(prt) Fan Tray
HPE Synergy 12000 3 Frame components		
3	797740-B21	HPE Synergy12000 CTO Frame 1xFLM 10x Fan
3	798096-B21	HPE Synergy 12000F 6x 2650W AC Ti FIO PS
2	804353-B21	HPE Synergy Composer
3	804942-B21	HPE Synergy Frame Link Module
1	804938-B21	HPE Synergy 12000 Frame Rack Rail Option
1	804943-B21	HPE Synergy 12000 Frame 4x Lift Handle
18	TK738A	HPE 2.0m 250V 16A C19-C20 Sgl IPD Jpr Crd
2	804937-B21	HPE Synergy Image Streamer
HPE Synergy 480 Gen10 compute components		
15	871942-B21	HPE SY 480 Gen10 CTO Premium Cmptr Mdl (64Gb Memory)
30	873388-B21	HPE Synergy 480 Gen10 6130 Kit
30	873388-L21	HPE Synergy 480 Gen10 6130 Kit
30	815100-B21	HPE 32GB QUAD PC4-2166P-R Kit
15	871573-B21	HPE Smart Array P416ie-m
15	875242-B21	HPE Smart Array P416ie-m SAS Cable Kit
15	777430-B21	HPE Synergy 3820C 10/20Gb CAN
15	875242-B21	HPE 96W Smart Stor Battery 260mm Cbl Kit

Quantity	Part number	Description
HPE Synergy Fabric Components		
2	794502-B23	HPE VC SE 40Gb F8 Module
4	779218-B21	HPE Synergy 20Gb Interconnect Link Mod
6	755985-B21	HPE Synergy 12Gb SAS Connection Module
HPE Synergy Composable Storage Components		
3	835386-B21	HPE Synergy D3940 CTO Storage Module
3	757323-B21	HPE Synergy D3940 IO Adapter
30	785067-B21	HPE 300GB 12G SAS 10K 2.5in SC ENT HDD
Cables and Transceivers		
8	804101-B21	HPE Synergy Interconnect Link 3m AOC
2	720199-B21	HPE BLc 40G QSFP+ QSFP+ 3m DAC Cable
8	720193-B21	HPE BLc QSFP+ to SFP+ Adapter
8	455883-B21	HPE BLc 10G SFP+ SR Transceiver
8	AJ837A	HPE 15m Multi-mode OM3 LC/LC FC Cable
9	861412-B21	HPE CAT6A 4ft Cbl
2	838327-B21	HPE Synergy Dual 10GBASE-T QSFP+ 30m RJ45 Transceiver
Red Hat Subscriptions		
1	MCT3691	Red Hat Ansible Tower with Ansible Engine, Standard (100 Managed Nodes)
12	MCT3479	Red Hat OpenShift Container Platform for RHEL, Standard (1-2 Sockets)
1	MCT1650	Red Hat Satellite Starter Pack (manage up to 50 Registered RHEL Instances)
1	RH00004	Red Hat Enterprise Linux Server, Standard (Physical or Virtual Nodes) (for load balancer/NFS node)
1	MCT2841	Red Hat CloudForms, Standard (Managed Nodes: Physical (2 sockets) or Virtual (16), public cloud)
1	RS00149	Container Storage Add-On for Red Hat OpenShift Container Platform Standard (3 Nodes)

Appendix B: Creating golden images for Red Hat OpenShift Container Platform deployment

This section provides details on how to capture the golden images required for Red Hat OpenShift Container Platform deployment. Two images will be captured: a 50GB image for Red Hat OpenShift Container Platform masters and 25GB image for workers. The process to create the two golden images is exactly the same except for the initial volume size setting. The [HPE-RHEL7.4-OpenShift](#) artifact bundle contains the OS deployment plan which allows you to create an initial 50GB volume and an OS Build plan necessary to capture a Red Hat Enterprise Linux 7.4 image.

Note

It is possible to use the same 50GB golden image for both Red Hat OpenShift masters and workers. Creating a smaller golden image for Red Hat OpenShift workers saves limited volume space on the Image Streamer. If desired, a separate image for the Load Balancer can be created. The Load Balancer image does not require installation of the openshift or docker packages.

Install Red Hat Enterprise Linux 7.4

1. Create a server profile with the Image Streamer deployment network and the management network. The management network is needed to allow for installation of the prerequisite packages which will be pulled from the Red Hat Satellite Server.
2. Use the OS deployment plan HPE-Create Empty volume, set the volume size to 51200 MB and add the management network as shown in Figure 20.

Create Server Profile OS Deployment

OS Deployment

OS deployment plan: HPE-Create Empty volume

Deployment Settings

Setting

Value

VolumeSize

51200

MB

Firmware

Firmware baseline: managed manually

Connections

ID	Name	Network	Port	Boot	
1	Deployment Network A	DEPLOY VLAN10	Mezzanine 3:1-a	ISCSI primary	
	Type	Ethernet			
	MAC address	Auto			
	Requested bandwidth	2.5 Gb/s			
	Initiator name	pending assignment			
	Initiator IP address	pending assignment			
	OS volume	pending assignment			
	Target name	pending assignment			
	Target LUN	pending assignment			
	Target IP address	pending assignment			
2	Deployment Network B	DEPLOY VLAN10	Mezzanine 3:2-a	ISCSI secondary	
	Type	Ethernet			
	MAC address	Auto			
	Requested bandwidth	2.5 Gb/s			
	Initiator name	pending assignment			
	Initiator IP address	pending assignment			
	OS volume	pending assignment			
	Target name	pending assignment			
	Target LUN	pending assignment			
	Target IP address	pending assignment			
3	Management	MGMT1 VLAN60	Auto	Not bootable	
	Type	Ethernet			

Figure 20: Creating the server profile for a golden image

3. Launch the iLO console for the server where the profile was assigned and use iLO virtual media to mount the Red Hat Enterprise Linux 7.4 iso image.
4. Power on the server and when the Red Hat Enterprise Linux installer screen appears, press the “e” key to edit the parameter which enables the RHEL 7.4 install kernel to recognize the Image Streamer iSCSI empty OS volume. Add the `rd.iscsi.ibft=1` kernel boot parameter as shown in Figure 21 and then press Ctrl x to start the installation.

```
setparams 'Install Red Hat Enterprise Linux 7.4'

linuxefi /images/pxeboot/vmlinuz inst.stage2=hd:LABEL=RHEL-7.4\x20Serv\
er.x86_64 quiet rd.iscsi.ibft=1_
initrdefi /images/pxeboot/initrd.img
```

Figure 21: Install Red Hat Enterprise Linux 7.4 from iso image

Set the desired defaults for keyboard and language. The installation source will be local media. Do not set a network or hostname in the golden image. Select Installation Destination and then from the Installation Destination window, select **I will configure partitioning** as shown in Figure 22.




Figure 22: Selecting the iSCSI device for OS installation

5. Leave the default as LVM partitioning and then select to create the partitions automatically.
6. Change both the /boot and / partitions from File System type xfs to ext4 and select the Update Settings button to save the changes as shown in Figure 23.




Figure 23: Set File System type for RHEL7.4

7. Set a default root password so you can log into the image after reboot and complete the configuration. When prompted, unmount the iso image and reboot the server.

Customize the OS deployment

Now that you have completed the basic OS deployment, the next steps customize the golden image including setting the required firewall settings and deploying the required packages. The steps in this section are documented in the [Red Hat OpenShift Installation and Configuration guide](#) but are listed here for ease of deployment.

1. Configure the management network manually so that you can install packages from the Red Hat Satellite Server. Once you have the network configured, connect to the server via SSH which will allow you to cut and paste commands.
2. Configure the firewall settings as follows:


```
firewall-cmd --add-port 4789/udp --permanent
firewall-cmd --add-port 8053/udp --permanent
firewall-cmd --add-port 8053/tcp --permanent
firewall-cmd --add-port 443/tcp --permanent
firewall-cmd --add-port 8443/tcp --permanent
```

```
firewall-cmd --add-port 10250/tcp --permanent
firewall-cmd --add-port 53/tcp --permanent
firewall-cmd --add-port 53/udp --permanent
firewall-cmd --reload
firewall-cmd --list-all    (to verify settings)
```

3. Edit /etc/resolv.conf to set the nameserver and search list. This will allow us to pull the required packages from the Red Hat Satellite Server. For example:

```
nameserver 10.10.173.45
search am2.cloudra.local
```

4. Install the katello package from the Red Hat Satellite Server, for example:

```
rpm -Uvh http://satellite.am2.cloudra.local/pub/katello-ca-consumer-latest.noarch.rpm
```

5. Register with Red Hat Satellite Server. The organization name and activation key can be retrieved from Red Hat Satellite from the Activation Keys page as shown in Figure 24, for example:

```
subscription-manager register --org="my-org" --activationkey="my-key"
```




Figure 24: Red Hat Satellite Server Activation Keys

6. Set up the required packages as follows:

```
subscription-manager list --available --matches '*OpenShift*'
```

7. In the output from the previous command, find the pool ID for a Red Hat OpenShift Container Platform subscription and attach it:

```
subscription-manager attach --pool=<pool_id>
```

8. Disable all yum repositories:

```
subscription-manager repos --disable="*"

yum-config-manager --disable \*
```

9. Enable only the repositories required by Red Hat OpenShift Container Platform 3.7

```
subscription-manager repos \
--enable="rhel-7-server-rpms" \
--enable="rhel-7-server-extras-rpms" \
--enable="rhel-7-server-ose-3.7-rpms" \
--enable="rhel-7-fast-datapath-rpms"
```

10. Install required base packages:

```
yum install -y wget git net-tools bind-utils iptables-services bridge-utils bash-completion kexec-
tools sos psacct

yum update

yum install -y atomic atomic-openshift-utils docker-1.12.6 gdisk
```

11. Edit the /etc/sysconfig/docker file and add --insecure-registry 172.30.0.0/16 to the OPTIONS parameter. For example:

```
OPTIONS='--selinux-enabled --insecure-registry 172.30.0.0/16'
```

12. The golden image must be unregistered from the Red Hat Satellite Server. When servers are deployed from the golden image, they will automatically be re-registered as part of the HPE Synergy Image Streamer scripts.

```
subscription-manager unregister
```

13. The networking you configured on your golden image will be automatically cleaned out by the Capture Image process. Shut down the server gracefully.

Capture the deployed image

1. From HPE OneView, view the OS Deployment section of the server profile used to create the golden image and find the OS volume. This is the volume we will capture as a golden image.
2. From the HPE Synergy Image Streamer UI, select Golden Images and then Create Golden Image.
3. Provide a name for your golden image, such as OpenShift Master, select the OS volume you identified in Step 1 and select the Capture OS build plan RHEL-7.4-generalize and click Create as shown in Figure 25.



Create Golden Image	
Name	OpenShift Master
Description	50GB golden image for OpenShift Master deployments
OS volume	OSVolume-176
Capture OS build plan	RHEL-7.4-generalize-2017-08-18

Figure 25: Create golden image

Creating the smaller golden image

Once the golden image has been created for OpenShift Master, you can modify the same server profile to start the process to create the 25GB volume for Red Hat OpenShift workers and container-native storage nodes.

1. Edit the server profile and set the volume size to 25000MB.
2. A warning message will appear informing you that the existing volume will be deleted. Since you have already captured the golden image, click OK to proceed.
3. Follow the same procedures documented in this section to create the smaller golden image for OpenShift workers.

After this process is complete you should have created two golden images, one 50GB OpenShift Master golden image and one 25GB OpenShift Worker golden image.

Appendix C: Setting the custom attributes in the Red Hat OpenShift deployment plans

The RHEL-7.4-OpenShift deployment plan custom attributes are the same for both master and worker nodes. The values for all attributes are set the same for all deployment plans except for the DeviceMapperDrive attribute as described in Table 11.

Table 11: Custom Attributes for Red Hat OpenShift deployment

Name	Description	Sample Value
ActivationKey	The Red Hat Satellite activation key. This name is used in combination with the OrgName to register with Red Hat Satellite. Figure 24 shows where this can be found on the Red Hat Satellite web interface. The activation key for the load balancer deployment plan does not need to include Red Hat OpenShift Container Platform. If you have a separate activation key that only includes Red Hat Enterprise Linux, you can use this key for the load balancer deployment plan.	HPE-OCF
AnsibleSSHKey	The SSH key from the Red Hat Ansible server is copied to the authorized keys file on deployed servers and allows Ansible scripts to run without login prompting. The SSH key is found on the Ansible server at /root/.ssh/id_rsa.pub	
DeviceMapperDrive	The filesystem location for the container and gluster volumes. This value varies depending on whether or not local storage is available. A single value should be specified for all but container-native storage nodes. The first value is the location of the container (docker) storage. Use a comma to separate values. In the testing done for this Reference Configuration, master, infra, load balancer and worker nodes the value was /dev/sdb. For container-native storage nodes where the container storage was on internal volumes and the gluster storage was on external volumes (HPE Synergy D3940), the value was /dev/sdc/dev/sdb.	/dev/sdb
DeviceMapperForceDelete	Forces a disk wipe of the drives specified in the DeviceMapperDrive attribute so logical volumes can be re-used. This attribute must be set to Yes or the installation will not work properly.	Yes
DNSKey	The DNS key from the DNS server which allows deployed servers to register with DNS. This information can be found in /etc/rndc.key file on the Red Hat Satellite Server. Specify the key name followed by the secret, separated by a colon.	rndc_key: ikfhgqSdaPRLix34AVAMTg==
NewRootPassword	Password for the root user.	
NtpServer	IP address for the NTP server. An NTP server is required or communication between containers could fail.	10.10.10.100
OrgName	The Red Hat Satellite organization name. This name is used in combination with the ActivationKey to register with Red Hat Satellite. Figure 24 shows where this can be found on the Red Hat Satellite web interface.	
ServerFQDN	Fully qualified domain name. This value is set by the Ansible Playbooks.	server1.acme.com
SSH	Enable the SSH service and root login over SSH. The default is Enabled.	Enabled
TeamONIC1	A static IP address for the deployed Red Hat OpenShift server on your production network. Select Static User Assigned for this address. This value is set by the Ansible Playbooks.	
TeamONIC2	This NIC is used for teaming. Leave the default value of static. No IP address is needed. This value is set by the Ansible Playbooks.	

Appendix D: Configuring Red Hat Satellite Server

Red Hat Satellite Server was used in this Reference Configuration to provide access to the required repositories and to provide DNS services. The following sections provide an overview of the Red Hat Satellite Server configuration to support the deployment of Red Hat OpenShift Container Platform.

Configuration to support Red Hat OpenShift Container Platform

Repositories

It is assumed that customers have an active Red Hat Satellite subscription and access to the required subscriptions and repositories. In this Reference Configuration a manifest with the required Red Hat product was created in access.redhat.com. The manifest was then imported into Satellite by selecting Content > Red Hat Subscriptions > Manage Manifest > Choose File > Upload.

The required repositories are then enabled by selecting Content > Red Hat Repositories > RPMs and selecting the required repositories.

Next the selected repositories must be synchronized with Red Hat. This is done by selecting Content > Products > Select the product repository and choose Sync Now. Ensure that the Red Hat Satellite Server is synchronized to the required Red Hat products.

The following repositories are required to be available from the Red Hat Satellite Server to deploy Red Hat OpenShift Container Platform with container-native storage:

- Red Hat Gluster Storage 3 Server (RPMs)
- Red Hat Enterprise Linux Fast Datapath (RHEL 7 Server) (RPMs)
- Red Hat Enterprise Linux Server 7 - Extras (RPMs)
- Red Hat OpenShift Container Platform 3.7 (RPMs)
- Red Hat Enterprise Linux 7 Server (RPMs)
- Red Hat Satellite tools 6.2 (RHEL 7 Server) (RPMs)

RED HAT SATELLITE

Red Hat Access

Admin User

hpe_cloud

Monitor

Content

Containers

Hosts

Configure

Infrastructure

Red Hat Insights

Administer

Products

Filter...

Search

Showing 4 of 4 (4 Total)

0 Selected

Bulk Actions

Repo Discovery

New Product

<input type="checkbox"/>	Name	Description	Sync Status	Sync Plan	Repositories
<input type="checkbox"/>	Red Hat Enterprise Linux Fast Datapath		Last synced 2 months ago. 2 successfully synced repositories.	None	2
<input type="checkbox"/>	Red Hat Enterprise Linux Server		Last synced 2 months ago. 3 successfully synced repositories.	None	3
<input type="checkbox"/>	Red Hat Gluster Storage Server for On-premise		Last synced about 1 month ago. 1 successfully synced repository.	None	2
<input type="checkbox"/>	Red Hat OpenShift Container Platform		Last synced 2 months ago. 1 successfully synced repository.	None	1

Figure 26: Required Red Hat Satellite Repositories

Next create an activation key by selecting Content > Activation Key > New Activation Key. Create the new activation key and ensure the required repositories are enabled as shown in Figure 27. The additional activation key shown in Figure 27 as HPE-RHEL is used for the load balancer and does not require the Red Hat OpenShift Container Platform subscriptions and product content.

The screenshot shows the Red Hat Satellite web interface. The top navigation bar includes 'hpe_cloud', 'Monitor', 'Content', 'Containers', 'Hosts', 'Configure', 'Infrastructure', 'Red Hat Insights', and 'Administer'. The 'Content' menu is expanded, showing 'Activation Keys'. The 'Activation Keys' page has a search bar and a list of activation keys: 'HPE-OCF' and 'HPE-RHEL'. The 'HPE-OCF' key is selected, and the 'Product Content' tab is active. The page displays a list of repository content sets with their status and override options.

Repository Content Set	Enabled?	Override to Yes	Action
Red Hat OpenShift Container Platform			
Red Hat OpenShift Container Platform 3.6 (RPMs)	Enabled?	Override to Yes	<input checked="" type="checkbox"/>
Red Hat Gluster Storage Server for On-premise			
Red Hat Gluster Storage 3 Server (RPMs)	Enabled?	Override to Yes	<input checked="" type="checkbox"/>
Red Hat Enterprise Linux Server			
Red Hat Enterprise Linux 7 Server - Extras (RPMs)	Enabled?	Override to Yes	<input checked="" type="checkbox"/>
Red Hat Enterprise Linux 7 Server (RPMs)	Enabled?	Yes (Default)	<input checked="" type="checkbox"/>
Red Hat Enterprise Linux Fast Datapath			
Red Hat Enterprise Linux Fast Datapath (RHEL 7 Server) (RPMs)	Enabled?	Override to Yes	<input checked="" type="checkbox"/>

Figure 27: Activation key

Appendix E: Using Red Hat CloudForms to monitor the Red Hat OpenShift Container Platform

This section provides details on how the Red Hat OpenShift provider was configured in Red Hat CloudForms and examples on creating reports to view the usage metrics collected. Refer to [Integration with OpenShift Container Platform](#) for full instructions on creating the service account and enabling metrics in Red Hat OpenShift Container Platform. A summary of steps is listed below.

In this Reference Configuration Red Hat CloudForms provides monitoring of the Red Hat OpenShift Container Platform through integration with the Hawkular services running on Red Hat OpenShift Container Platform. The Hawkular monitoring and logging services are automatically enabled as part of the initial Red Hat OpenShift Container Platform installation via Ansible.

Red Hat CloudForms configuration steps

Service account creation

Red Hat CloudForms requires a service account to be created on the Red Hat OpenShift Container Platform. The Ansible postdeploy workflow `cloudforms.yaml` task in this Reference Configuration will create a service account named `cfadmin` and assign the OpenShift cluster-reader role to the `cfadmin` service account. A service token associated with the `cfadmin` service account must be generated. The service token will be used to authenticate the Red Hat CloudForms OpenShift provider to the Red Hat OpenShift Container Platform cluster. This service token will be specified in the Red Hat CloudForms container provider form.

- Use SSH to connect to `ocp-master1`. Log in as `system:admin` and generate a service token using the service account. The service token will be used to provide access from CloudForms to the Red Hat OpenShift cluster.

```
oc login -u system:admin
```

```
oc sa get-token -n openshift-infra cfadmin
```

Once the service token is available you can log in to Red Hat CloudForms, enable metrics collection, and add the Red Hat OpenShift container provider information.

Enable metrics collection

Log in to Red Hat CloudForms as admin user. In the top right corner, click on the drop down menu under Administrator and then select Configuration. Change the settings under Server Roles to On as shown in Figure 28 for

- Capacity & Utilization Coordinator
- Capacity & Utilization Data Collector
- Capacity & Utilization Data Processor




Figure 28: Enable Metrics collection

Configure the container provider

Save the changes and select Compute > Containers > Providers > Configuration > Add Existing Container Provider. Complete the form as shown in Figure 29.

- Specify the FQDN for the cluster as the Hostname.
- Cut and paste the token returned from the `oc sa get-token` command into the Token field.

The screenshot shows the Red Hat CloudForms Management Engine interface. On the left is a navigation sidebar with icons and labels for Cloud Intel, Red Hat Insights, Services, Compute (highlighted), Configuration, Networks, Middleware, Storage, and Control. The main content area shows the breadcrumb path: Containers Providers > Synergy-OpenShift (Dashboard) > Edit Containers Providers 'Synergy-OpenShift'. The form fields are: Name (Synergy-OpenShift), Type (OpenShift Container Platform), Zone (default), Endpoints (Default tab selected), Security Protocol (SSL without validation), Hostname (or IPv4 or IPv6 address) (ocp-cluster.am2.cloudra.local), API Port (8443), and Token (masked with asterisks). A 'Validate' button is at the bottom, and a 'Change stored token' link is to the right of the token field. A note at the bottom states: 'Required. Used to gather Utilization data.'

Figure 29: Configure the Red Hat OpenShift provider in Red Hat CloudForms

Select the Hawkular tab and specify the hostname and port as shown in Figure 30 and click Validate and then Save.

The screenshot shows the 'Endpoints' section of the configuration form. The 'Hawkular' tab is selected. The fields are: Security Protocol (SSL without validation), Hostname (or IPv4 or IPv6 address) (hawkular-metrics.paas.am2.cloudra.local), and API Port (443). A 'Validate' button is at the bottom.

Figure 30: Hawkular metrics collection

An overview of the Red Hat OpenShift Container Platform will be displayed after the container provider makes a successful connection. As Red Hat CloudForms collects the metrics from the Red Hat OpenShift provider, updated statistics are provided as seen in Figure 31.




Figure 31: Red Hat CloudForms OpenShift provider dashboard

Create chargeback and billing reports

Red Hat CloudForms also provides chargeback and billing reports for the Red Hat OpenShift Container Platform-based services. Enabling billing and chargeback for the Red Hat OpenShift cluster requires creating a new charge rate that uses the Red Hat OpenShift Container Platform provider created previously. To create a new chargeback rate select Cloud Intel > Chargeback > Rates > Compute > Configuration > Add a new Chargeback Rate

Provide a description of the new chargeback rate, select the currency and configure the chargeback rate details, then select Add to save the new chargeback rate as shown in Figure 32.

The screenshot shows the Red Hat CloudForms Management Engine interface. The left sidebar contains a navigation menu with the following items: Cloud Intel, Red Hat Insights, Services, Compute, Configuration, Networks, Middleware, Storage, Control, Automation, and Optimize. The 'Compute' item is selected, and the 'Configuration' sub-menu is open, showing 'Rates' and 'Assignments'. The 'Rates' sub-menu is further expanded, showing 'Compute', 'Storage', and 'Default'. The 'Compute' sub-menu is selected, and the 'OCP-Synergy-Containers' item is highlighted.

The main content area displays the 'Compute Chargeback Rate "OCP-Synergy-Containers"' configuration page. The page has a 'Basic Info' section with a 'Description' field containing 'OCP-Synergy-Containers'. Below this is the 'Rate Details' section, which contains a table with the following data:

Group	Description	Range		Rate		Units
		Start	Finish	Fixed	Variable	
CPU	Allocated CPU Count	0.0	Infinity	1.0	0.0	USD / Hour / Cpu
CPU	Used CPU	0.0	Infinity	0.0	0.02	USD / Hour / MHz
Cpu Cores	Used CPU Cores	0.0	Infinity	1.0	0.02	USD / Hour / Cpu core
Disk I/O	Used Disk I/O	0.0	Infinity	0.0	0.005	USD / Hour / KBps
Fixed	Fixed Compute Cost 1	0.0	Infinity	0.0	-	USD / Hour
Fixed	Fixed Compute Cost 2	0.0	Infinity	0.0	-	USD / Hour
Memory	Allocated Memory	0.0	Infinity	0.0	0.0	USD / Hour / MB
Memory	Used Memory	0.0	Infinity	0.0	0.02	USD / Hour / MB

Figure 32: Creating Chargeback reports

A chargeback report can now be created. Select Cloud Intel > Reports > Configuration > Add a new Report. Provide a Menu Name and Title. In the Configure Report Columns section, select Chargeback Container Images from the drop down menu. Select the fields to be included in the report. In this example, the following fields were selected:

- Cpu Cores Used Cost
- Memory Used Cost
- Network I/O Used Cost
- Total Cost

RED HAT® CLOUDFORMS MANAGEMENT ENGINE

Administrator

Cloud Intel >

Red Hat Insights >

Services >

Compute >

Configuration >

Networks >

Middleware >

Storage >

Control >

Automation >

Optimize >

Saved Reports

Reports

Events

Operations

Policy

Performance by Asset...

Virtual Machines

Clusters

Middleware Servers

Middleware Datasto...

Running Processes

Virtual Machines

Trending

Clusters

Storage

Hosts

Tenants

Tenant Quotas

Provisioning

Activity Reports

My Company [All EVM ...]

Custom

OCP-Synergy

2017-10-10 ...

my new report

Editing Report "OCP-Synergy"

Columns Formatting Filter Preview

Basic Report Info

Menu Name: OCP-Synergy

Title: Synergy Based Container Charges

Configure Report Columns

* Base the report on: Chargeback Container Images

Available Fields:

Archived

Chargeback Rates

Cpu Cores Used Metric

Fixed 2 Cost

Fixed Compute Cost 1

Fixed Compute Cost 2

Fixed Compute Metric

Fixed Total Cost

Memory Used

Network I/O Used

Selected Fields:

Cpu Cores Used Cost

Memory Used Cost

Network I/O Used Cost

Total Cost

Figure 33: Creating custom reports

From the Filter tab, select Show Costs by Container Image, specify the provider and select the desired container images for the report. Select the Preview tab to generate a preview of the report as shown in Figure 34.

Editing Report "OCP-Synergy"

Columns Formatting Filter **Preview**

Basic Report Info

Menu Name:

Title:

Report Preview (up to 50 rows)

Project Name	Image Name	Date Range	Cpu Cores Used Cost	Memory Used Cost	Network I/O Used Cost	Total Cost
cc-project1	docker-registry.default.svc:5000/cc-project1/cakephp-mysql-persistent@sha256:bf7ef5629a3c9aa67fbaa11f977244dbb75c5125ae3e54b5b6488688fadcebf4	10/19/2017	\$7.00	\$16.51	\$3.50	\$27.01
cc-project1	registry.access.redhat.com/openshift3/ose-sti-builder@sha256:ffce474721e9a5014a8751d69c782654b907affc660ef331ed07de5f6a941507	10/19/2017	\$7.00	\$4.15	\$3.50	\$14.65
cc-project1	registry.access.redhat.com/rhsc1/mysql-57-rhel7@sha256:d7609c2fee784043f84467ed503a18cae92dbbf28f8fab79e9d71eabae38bb2e	10/19/2017	\$7.00	\$31.81	\$3.50	\$42.31
cc-project1						
Totals:			\$21.00	\$52.48	\$10.50	\$83.98
default	registry.access.redhat.com/openshift3/ose-docker-regi	10/19/	\$72.0	\$543.92	\$36.00	\$65

Figure 34: Chargeback report preview

Appendix F: Deploying a sample application

This section will demonstrate how to create a project using an existing Red Hat Reference Configuration [Building JBoss EAP 7 microservices on OpenShift Container Platform](#). The sample application is deployed from one of the Red Hat OpenShift Container Platform master nodes.

Deploying the application

1. Log in to the first master node as root user.
2. Log in to the Red Hat OpenShift Container Platform as an administrator.

```
oc login -u system:admin
```
3. Create a new project and set the admin to an existing Red Hat OpenShift user account. In this example we used an account named "jdoe".

```
oadm new-project msa --display-name="OpenShift 3 MSA on EAP 7" --description="This is a sample microservices architecture built on JBoss EAP 7" --admin=jdoe
```
4. Log in as the user.

```
oc login -u jdoe
```
5. Create the database pods.

```
oc new-app -e MYSQL_USER=product -e MYSQL_PASSWORD=password -e MYSQL_DATABASE=product -e MYSQL_ROOT_PASSWORD=passwd mysql --name=product-db
```

```
oc new-app -e MYSQL_USER=sales -e MYSQL_PASSWORD=password -e MYSQL_DATABASE=sales -e MYSQL_ROOT_PASSWORD=passwd mysql --name=sales-db
```

```
oc status
```
6. Create the billing service.

```
oc new-app jboss-eap70-openshift~https://github.com/RHsyseng/MSA-EAP7-OSE.git --context-dir=Billing --name=billing-service
```

```
oc get all
```

```
oc get builds
```
7. Create the Red Hat JBoss EAP product-service and sales-service applications.

```
oc new-app -e MYSQL_USER=product -e MYSQL_PASSWORD=password jboss-eap70-openshift~https://github.com/RHsyseng/MSA-EAP7-OSE.git --context-dir=Product --name=product-service
```

```
oc new-app -e MYSQL_USER=sales -e MYSQL_PASSWORD=password jboss-eap70-openshift~https://github.com/RHsyseng/MSA-EAP7-OSE.git --context-dir=Product --name=sales-service
```
8. Create the presentation application.

```
oc new-app jboss-eap70-openshift~https://github.com/RHsyseng/MSA-EAP7-OSE.git --context-dir=Presentation --name=presentation
```


```
oc status
```
9. Expose the presentation service.

```
oc expose service presentation --hostname=msa.paas.cloudra.local
```
10. Access the application from a browser.


```
http://msa.paas.cloudra.local/demo.jsp
```


The sample application output is shown in Figure 35.

ABC HD32CS5002 32-inch LED TV

	HD LED Picture Quality ConnectShare Movie Wide Color Enhancement Clear Motion Rate 60	Product Dimensions: 29.1 x 3.7 x 17.5 Product Weight: 17.0	\$249.99 Availability: 52
---	--	---	---

ABC HD42CS5002 42-inch LED TV

	HD LED Picture Quality ConnectShare Movie Wide Color Enhancement Clear Motion Rate 60	Product Dimensions: 37.8 x 2.2 x 22.3 Product Weight: 20.9	\$424.95 Availability: 64
---	--	---	---

Microtech MM-733N Microwave Oven; 1.6 Cubic Feet



	Inverter Technology for even cooking Inverter Turbo Defrost for quick defrosting 9-Menu Category Sensor Cook system	Product Dimensions: 22.0 x 19.5 x 12.0 Product Weight: 38.8	\$178.00 Availability: 32
--	---	--	---

Figure 35: Sample application deployed on Red Hat OpenShift Container Platform

Monitoring the application from Red Hat CloudForms

Once this service is deployed, it is automatically monitored by Red Hat CloudForms. The Red Hat JBoss EAP 7 application can be viewed under Compute > Containers > Projects > msa. The Summary can be seen in Figure 36.



The screenshot shows the Red Hat CloudForms Management Engine interface. The left sidebar contains navigation links: Cloud Intel, Red Hat Insights, Services, Compute (selected), Configuration, Networks, Middleware, and Storage. The main content area displays the 'msa' project summary under the 'Projects' tab. The summary includes a 'Properties' table with details about the project and a 'Relationships' table showing associated resources.

Properties	
Name	msa
Display name	OpenShift 3 MSA on EAP 7
Creation timestamp	Mon, 20 Nov 2017 15:29:27 +0000
Resource version	362891

Relationships	
Containers Provider	SynergyOCP
Routes	1
Container Services	6
Replicators	6
Pods	10
Nodes	6
Container Images	6
Container Templates	0

Smart Management	
My Company Tags	No My Company Tags have been assigned

Figure 36: Red Hat JBoss EAP 7 msa Project Summary

Additional performance metrics about the application can be view by selecting Capacity & Utilization. Statistics on CPU, Memory, and Network utilization are shown in Figure 37.




Figure 37: Red Hat JBoss EAP 7 Capacity and Utilization information

Details about the Red Hat JBoss EAP 7 container deployment can be view by selecting Relationships. In Figure 38 the pods associated with the JBoss EAP 7 application deployment are displayed.




Figure 38: Red Hat JBoss EAP 7 Pods

Appendix G: Red Hat Ansible Playbooks and customization

Ansible Playbooks

The following Ansible Playbooks were created for this solution:

- cleanup

The cleanup playbook removes the servers from the Red Hat Satellite Server and HPE OneView. Although not necessary on an initial run, having such a playbook in a workflow is handy to facilitate a CI/CD (continuous integration/delivery) environment. When code is pushed to the git repository, or newer versions of the RPMs are available for testing, the entire workflow can be executed again, with the first step ensuring a clean build environment.

- provisioning

The provisioning playbook uses the Ansible Modules for HPE OneView to deploy all the servers needed for the solution. This playbook is responsible for creating the server profiles, assigning the profile to a server and powering on the server.

- predeploy

When deploying a complex infrastructure such as Red Hat OpenShift Container Platform, there are usually some prerequisite steps to prepare the environment, before installing the software itself. The prerequisite tasks for this Red Hat OpenShift Reference Configuration are captured in the `hp_predeploy` role.

- openshift

The official Red Hat OpenShift Container Platform Ansible Playbooks were used for this Reference Configuration. Detailing these playbooks is out of scope for this document. The playbooks can be found on GitHub and instructions on how to use them can be found [here](#). The playbooks require no modification to work with Ansible Tower. As per the installation guide, a host file is created and a number of variables are defined.

- postdeploy

This playbook has tasks that create the CloudForms service account (`cfadmin`) and assigns the Red Hat OpenShift cluster-reader access role to the `cfadmin` service account. This playbook also configures glusterfs as the default storage class for the Red Hat OpenShift Container Platform cluster.

- add_to_oneview

Adds a new node to HPE OneView and Ansible Inventory

- fix_inventory

Removes node from `new_nodes` group

- scaledown

Removes a node from HPE OneView and Red Hat OpenShift Container Platform cluster

- scaleup

Adds an additional compute module to the Red Hat OpenShift Container Platform cluster

Customizing the inventory and variables

Customize the inventory file on the Ansible host. The node names, IP addresses, and installation location (enclosure/bay) are set in the `/etc/ansible/ocp-on-synergy/hosts` file as shown below. Specifying the exact location for deployment of each node during initial installation is needed to insure that one member of each component is deployed in each of the 3 frames for high availability. Additional nodes can be deployed on any available server.

The container-native storage nodes have an additional configuration in the `glusterfs` section. The `glusterfsdevices` specification indicates the device as seen by the Red Hat Enterprise Linux 7.4 OS to use for gluster storage. Note that this location (`/dev/sdb`) can vary depending on whether or not local storage is present and being used for container deployments. This value must match the location specified in the `DeviceMapperDrive` custom attribute in the HPE Synergy Image Streamer deployment plan for the container-native storage node gluster storage. It is the second value in the comma separated list (`/dev/sdc,/dev/sdb` in our example).

```
[tower]
ansible.example.com

[OSEv3:children]
nodes
masters
etcd
lb
glusterfs
nfs
new_nodes

[nodes]
ocp-master1.example.com openshift_schedulable=False ansible_host=192.168.1.112 enclosure_name='FRM1-TOP:
CN1234567A' enclosure_bay=1
ocp-master2.example.com openshift_schedulable=False ansible_host=192.168.1.113 enclosure_name='FRM2-MID:
CN1234567B' enclosure_bay=1
ocp-master3.example.com openshift_schedulable=False ansible_host=192.168.1.114 enclosure_name='FRM3-BTM:
CN1234567C' enclosure_bay=1
ocp-infra1.example.com openshift_node_labels="{ 'region': 'infra' }" ansible_host=192.168.1.115
enclosure_name='FRM1-TOP: CN1234567A' enclosure_bay=2
ocp-infra2.example.com openshift_node_labels="{ 'region': 'infra' }" ansible_host=192.168.1.116
enclosure_name='FRM2-MID: CN1234567B' enclosure_bay=2
ocp-infra3.example.com openshift_node_labels="{ 'region': 'infra' }" ansible_host=192.168.1.117
enclosure_name='FRM3-BTM: CN1234567C' enclosure_bay=2
ocp-cns1.example.com ansible_host=192.168.1.118 enclosure_name='FRM1-TOP: CN1234567A' enclosure_bay=7
ocp-cns2.example.com ansible_host=192.168.1.119 enclosure_name='FRM2-MID: CN1234567B' enclosure_bay=7
ocp-cns3.example.com ansible_host=192.168.1.120 enclosure_name='FRM3-BTM: CN1234567C' enclosure_bay=7
ocp-node1.example.com ansible_host=192.168.1.121 enclosure_name='FRM1-TOP: CN1234567A' enclosure_bay=8
ocp-node2.example.com ansible_host=192.168.1.122 enclosure_name='FRM2-MID: CN1234567B' enclosure_bay=8
ocp-node3.example.com ansible_host=192.168.1.123 enclosure_name='FRM3-BTM: CN1234567C' enclosure_bay=8

[masters]
ocp-master1.example.com
ocp-master2.example.com
ocp-master3.example.com

[infra]
ocp-infra1.example.com
ocp-infra2.example.com
ocp-infra3.example.com

[etcd]
ocp-master1.example.com
ocp-master2.example.com
ocp-master3.example.com

[lb]
ocp-lbnfs.example.com ansible_host=192.168.1.111 enclosure_name='FRM3-BTM: CN1234567C' enclosure_bay=11
[nfs]
ocp-lbnfs.example.com

[glusterfs]
```

```
ocp-cns1.example.com glusterfs_ip=192.168.1.118 glusterfs_devices='["/dev/sdb"]'
ocp-cns2.example.com glusterfs_ip=192.168.1.119 glusterfs_devices='["/dev/sdb"]'
ocp-cns3.example.com glusterfs_ip=192.168.1.120 glusterfs_devices='["/dev/sdb"]'

[new_nodes]
```

Additional variables used by Ansible are configured in the `group_vars/all` file found in `/etc/sysconfig/ansible/ocp-on-synergy`. This file contains the information the Ansible Playbooks use to deploy the server profiles on the HPE Synergy compute modules. The contents of the file as it was used for testing is shown below.

```
---
master_deployment_plan: "HPE-RHEL7.4-OpenShiftMaster"
worker_deployment_plan: "HPE-RHEL7.4-OpenShiftWorker"
cns_deployment_plan: "HPE-RHEL7.4-OpenShiftCNS"
infra_deployment_plan: "HPE-RHEL7.4-OCF-Infra"
lbnfs_deployment_plan: "HPE-RHEL7.4-OpenShiftLBNFS"
master_server_profile_template: "OCP-Master"
worker_server_profile_template: "OCP-Worker"
cns_server_profile_template: "OCP-CNS-Node"
lbnfs_server_profile_template: "OCP-LB-NFS"
infra_server_profile_template: "OCP-Infra"
deployment_plan: "{{ worker_deployment_plan }}"
server_profile_template: "{{ worker_server_profile_template }}"
## ocp
openshift_master_default_subdomain: paas.example.com
openshift_master_cluster_hostname: ocp-cluster.example.com
openshift_master_cluster_public_hostname: ocp-cluster.example.com
## oneview vars
oneview_auth:
  ip: "192.168.1.10"
  username: "Administrator"
  api_version: 300
## network settings
network:
  name: "MGMT1"
  gateway: "192.168.1.1"
  netmask: "255.255.255.0"
  domain: "example.com"
  dns1: "192.168.1.106"
  dns2: "192.168.1.104"
dns_server: "{{ network.dns1 }}"
## satellite
satellite_user: "admin"
satellite_url: "https://192.168.1.106"
inventory_path: "/etc/ansible/ocp-on-synergy"
```

Ansible vault

These playbooks use `ansible-vault` to encrypt sensitive login credentials. Modify `passwords.yml` to reflect the user names and passwords used in your environment and vault it using the commands shown below:

```
$ ansible-vault encrypt passwords.yml --output=roles/passwords/vars/passwords.yml
$ chmod 644 roles/passwords/vars/passwords.yml
```

Appendix H: Red Hat OpenShift Container Platform deployment validation and troubleshooting

Post deployment verification

This section provides post deployment and validation information.

Verify Red Hat OpenShift Container Platform etcd cluster is running

To verify that the Red Hat OpenShift Container Platform deployment was successful, check the etcd cluster health by logging into the first master node and running the following command, substituting the hostnames used in your deployment:

```
etcdctl -C https://ocp-master1.cloudra.local:2379,https://ocp-master2.cloudra.local:2379,https://ocp-master3.cloudra.local:2379 \
--ca-file=/etc/origin/master/master.etcd-ca.crt \
--cert-file=/etc/origin/master/master.etcd-client.crt \
--key-file=/etc/origin/master/master.etcd-client.key \
cluster-health
```

The result of the `etcdctl cluster-health` command is shown below, indicating the cluster is healthy.

```
[root@ocp-master1 ~]# etcdctl -C https://ocp-master1.cloudra.local:2379,https://ocp-master2.cloudra.local:2379,https://ocp-master3.cloudra.local:2379 --ca-file=/etc/origin/master/master.etcd-ca.crt --cert-file=/etc/origin/master/master.etcd-client.crt --key-file=/etc/origin/master/master.etcd-client.key cluster-health
member 3680e0da3823679d is healthy: got healthy result from https://10.60.50.114:2379
member 79cffbdec6e32038 is healthy: got healthy result from https://10.60.50.113:2379
member e8db49bf13a3e053 is healthy: got healthy result from https://10.60.50.112:2379
cluster is healthy
```

List nodes

Executing the `oc get nodes` command will display the Red Hat OpenShift Container Platform nodes and their respective status. Notice that scheduling is disabled on the ocp master nodes. By default scheduling is enabled on the infrastructure nodes, this means that pods containing production applications can be scheduled on these nodes. This can be modified and a node can be marked as schedulable by executing `oadm manage-node <node1> <node2> --schedulable=false`. This will prevent pods from being deployed on the selected node(s).

```
[root@ocp-master1 ~]# oc get nodes
```

NAME	STATUS	AGE	VERSION
ocp-cns1.cloudra.local	Ready	2d	v1.6.1+5115d708d7
ocp-cns2.cloudra.local	Ready	2d	v1.6.1+5115d708d7
ocp-cns3.cloudra.local	Ready	2d	v1.6.1+5115d708d7
ocp-infra1.cloudra.local	Ready	2d	v1.6.1+5115d708d7
ocp-infra2.cloudra.local	Ready	2d	v1.6.1+5115d708d7
ocp-infra3.cloudra.local	Ready	2d	v1.6.1+5115d708d7
ocp-master1.cloudra.local	Ready,SchedulingDisabled	2d	v1.6.1+5115d708d7
ocp-master2.cloudra.local	Ready,SchedulingDisabled	2d	v1.6.1+5115d708d7
ocp-master3.cloudra.local	Ready,SchedulingDisabled	2d	v1.6.1+5115d708d7
ocp-node1.cloudra.local	Ready	2d	v1.6.1+5115d708d7
ocp-node2.cloudra.local	Ready	2d	v1.6.1+5115d708d7
ocp-node3.cloudra.local	Ready	2d	v1.6.1+5115d708d7

List projects

The `oc get projects` command will display all projects that the user has permission to access.

```
[root@ocp-master1 ~]# oc get projects
```

NAME	DISPLAY NAME	STATUS
default		Active
glusterfs		Active
kube-public		Active
kube-system		Active
logging		Active
management-infra		Active
msa	OpenShift 3 MSA on EAP 7	Active
openshift		Active
openshift-infra		Active

List pods

The `oc get pods` command will list the running pods in the current project. The command below shows the pods for the default project.

```
[root@ocp-master1 ~]# oc get pods
```

NAME	READY	STATUS	RESTARTS	AGE
docker-registry-1-9h77j	1/1	Running	0	2d
docker-registry-1-b4fd9	1/1	Running	0	2d
docker-registry-1-jt7zs	1/1	Running	0	2d
registry-console-1-rgb40	1/1	Running	0	2d
router-1-bkztq	1/1	Running	0	2d
router-1-wlj69	1/1	Running	0	2d
router-1-zmp9k	1/1	Running	0	2d

Verify the Red Hat OpenShift Container Platform User Interface

Log into the Red Hat OpenShift Container Platform user interface using the public url defined in the `openshift_master_cluster_public_hostname` variable as shown below.

`openshift_master_cluster_public_hostname: ocp-cluster.cloudra.local`

The login URL in this example is <https://ocp-cluster.cloudra.local:8443/console/>.




Figure 39: Red Hat OpenShift Container Platform portal

Resources and additional links

HPE Reference Architectures, hpe.com/info/ra

HPE GitHub Reference Architectures, <https://github.com/HewlettPackard/image-streamer-reference-architectures>

HPE Servers, hpe.com/servers

HPE Storage, hpe.com/storage

HPE Networking, hpe.com/networking

HPE Synergy, hpe.com/synergy

HPE Technology Consulting Services, hpe.com/us/en/services/consulting.html

Red Hat Ansible Tower, <http://docs.ansible.com/ansible-tower/>

Red Hat Gluster Storage, <https://access.redhat.com/documentation/en/red-hat-gluster-storage/>

Red Hat OpenShift Container Platform, <https://access.redhat.com/documentation/en/openshift-container-platform/>

Red Hat Satellite, <https://access.redhat.com/documentation/en/red-hat-satellite/>

To help us improve our documents, please provide feedback at hpe.com/contact/feedback.



Sign up for updates



**Hewlett Packard
Enterprise**

© Copyright 2017 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Red Hat, Red Hat Enterprise Linux Certified, and Red Hat Ansible are trademarks of Red Hat, Inc. in the United States and other countries. Intel, Xeon, and Intel Xeon, are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

a00038916enw, December 2017