

karim@vbox: ~

Session Actions Edit View Help

Nmap done: 256 IP addresses (5 hosts up) scanned in 48.19 seconds

(karim@vbox)-[~]

\$ arp -a

? (192.168.1.1) at a8:02:db:f2:a7:5c [ether] on eth0

? (192.168.1.13) at 7c:21:4a:f9:8b:bb [ether] on eth0

(karim@vbox)-[~]

\$ arp -a

? (192.168.1.1) at a8:02:db:f2:a7:5c [ether] on eth0

? (192.168.1.13) at 7c:21:4a:f9:8b:bb [ether] on eth0

(karim@vbox)-[~]

\$ sudo ettercap -pkexex

[sudo] password for karim:

ettercap 0.8.4.1 copyright 2001-2026 Ettercap Development Team

Please select a User Interface

(karim@vbox)-[~]

\$ sudo ettercap -pkexex

ettercap 0.8.4.1 copyright 2001-2026 Ettercap Development Team

Please select a User Interface

(karim@vbox)-[~]

\$


```
(karim@vbox) [~]  
$ ifconfig  
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500  
    inet 192.168.33.129 netmask 255.255.255.0 broadcast 192.168.33.255  
    inet6 fe80::20c:29ff:fe9c:f863 prefixlen 64 scopeid 0x20<link>  
    ether 00:0c:29:9c:f8:63 txqueuelen 1000 (Ethernet)  
    RX packets 8 bytes 1330 (1.2 KiB)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 28 bytes 3940 (3.8 KiB)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0  
  
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536  
    inet 127.0.0.1 netmask 255.0.0.0  
    inet6 ::1 prefixlen 128 scopeid 0x10<host>  
    loop txqueuelen 1000 (Local Loopback)  
    RX packets 8 bytes 480 (480.0 B)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 8 bytes 480 (480.0 B)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

```
(karim@vbox)-[~]  
$ nmap -sn 192.168.33.1/24  
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-26 14:14 -0400  
Nmap scan report for 192.168.33.1  
Host is up (0.00050s latency).  
MAC Address: 00:50:56:C0:00:08 (VMware)  
Nmap scan report for 192.168.33.2  
Host is up (0.000095s latency).  
MAC Address: 00:50:56:F1:84:DE (VMware)  
Nmap scan report for 192.168.33.130  
Host is up (0.00014s latency).  
MAC Address: 00:0C:29:DA:53:2A (VMware)  
Nmap scan report for 192.168.33.254
```



```
Nmap scan report for 192.168.33.1
Host is up (0.00050s latency).
MAC Address: 00:50:56:C0:00:08 (VMware)
Nmap scan report for 192.168.33.2
Host is up (0.000095s latency).
MAC Address: 00:50:56:F1:84:DE (VMware)
Nmap scan report for 192.168.33.130
Host is up (0.00014s latency).
MAC Address: 00:0C:29:DA:53:2A (VMware)
Nmap scan report for 192.168.33.254
Host is up (0.00010s latency).
MAC Address: 00:50:56:E6:26:9E (VMware)
Nmap scan report for 192.168.33.129
Host is up.
Nmap done: 256 IP addresses (5 hosts up) scanned in 2.88 seconds
```

```
(karim@vbox)-[~]
$ cd KarScan
```

```
(karim@vbox)-[~/KarScan]
$ ./karscan.sh 192.168.33.130
```

KarScan – target: 192.168.33.130

[*] Report directory: /home/karim/KarScan/reports/192.168.33.130_2026092

[?] **Recon depth – how thorough should reconnaissance be?**

- [1] Quick – reachability + hostname resolution only
- * [2] Standard – quick + traceroute + local ARP/route info (recommended)
- [3] Deep – standard + whois lookup
- [4] Skip recon entirely

Choice [default 2]: 2

[?] **Port scan type – how should we scan 192.168.33.130?**

Choice [default 2]: 2

[?] **Port scan type – how should we scan 192.168.33.130?**

- * [1] Fast – top 100 ports, service/version detection (recommended default)
- [2] Full – all 65535 TCP ports, service/version detection (slow)
- [3] Custom – you specify a port range
- [4] Stealth SYN scan (needs sudo – will fall back to connect scan)
- [5] TCP connect scan only – no version detection (fastest, least info)

Choice [default 1]: 1

► Pre-Scan Profile – 192.168.33.130

[?] **Do you want to try to evade the firewall/IDS?**

- [1] Yes – use a TCP Xmas scan (FIN+PSH+URG flags) to try to slip past simple packet filters
- * [2] No – scan normally (recommended unless you know a firewall is in the way)

Choice [default 2]: 2

[?] **Which protocol do you want to scan?**

- * [1] TCP – the standard choice for this assignment's target services
- [2] UDP – scan UDP ports instead (slower; needed for services like DNS/SNMP/TFTP over UDP)

Choice [default 1]: 1

[?] **What's your operational profile for this scan?**

- [1] Red Team – prioritize staying hidden: slow timing, packet fragmentation, decoys, randomized order
- * [2] Penetration Test – thoroughness over stealth: run the scan exactly as configured, at normal speed

Choice [default 2]: 2

Profile selected: evasion=no, protocol=TCP, mode=Penetration Test

[?] **Report output – what should we generate?**

- [1] Plain text only (scan.txt, findings.txt, summary.txt)
- * [2] Plain text + HTML report (recommended)
- [3] Plain text + HTML + keep raw nmap greppable output

[?] Report output – what should we generate?

- [1] Plain text only (scan.txt, findings.txt, summary.txt)
 - * [2] Plain text + HTML report (recommended)
 - [3] Plain text + HTML + keep raw nmap greppable output
- Choice [default 2]: 2

► Stage 1/4 – Reconnaissance: 192.168.33.130

- [*] Checking host availability (ping)...
- [+] Target is reachable
- [*] Resolving IP / hostname information...
- [+] Resolved IP: 192.168.33.130
- [+] Reverse DNS: Host 130.33.168.192.in-addr.arpa. not found: 3(NXDOMAIN)
- [*] Gathering basic local network information...
- [+] Local network info captured
- [*] Running traceroute (max 10 hops, 2s timeout)...
- [+] Traceroute captured

► Stage 2/4 – Port & Service Enumeration: 192.168.33.130

► Scan Profile

- [*] Firewall evasion: No
- [*] Protocol: TCP
- [*] Operational profile: Penetration Test (standard)
- [*] Technique: TCP scan (technique as selected in the port-scan menu)
- [*] Running: nmap -Pn -sV --top-ports 100 -T3 -oG - 192.168.33.130
- [*] This can take a moment depending on scan type...
- [+] Port 22/tcp open – ssh (OpenSSH 5.3p1 Debian 3ubuntu7 (Ubuntu Linux; protocol 2.0))
- [+] Port 23/tcp open – telnet (Linux telnetd)
- [+] Port 25/tcp open – smtp (Postfix smtpd)
- [+] Port 53/tcp open – domain (ISC BIND 9.7.0-P1)
- [+] Port 80/tcp open – http (Apache httpd 2.2.14 ((Ubuntu)))
- [+] Port 111/tcp open – rpcbind (2 (RPC #100000))
- [+] Port 139/tcp open – netbios-ssn (Samba smbd 3.X - 4.X (workgroup: WORKGROUP))
- [+] Port 389/tcp open – ldap (OpenLDAP 2.2.X - 2.3.X)


```
[+] Port 80/tcp open - http (Apache httpd 2.2.14 ((Ubuntu)))
[+] Port 111/tcp open - rpcbind (2 (RPC #100000))
[+] Port 139/tcp open - netbios-ssn (Samba smbd 3.X - 4.X (workgroup: WORKGROUP))
[+] Port 389/tcp open - ldap (OpenLDAP 2.2.X - 2.3.X)
[+] Port 445/tcp open - netbios-ssn (Samba smbd 3.X - 4.X (workgroup: WORKGROUP))
[+] Port 513/tcp open - login ((no banner captured))
[+] Port 514/tcp open - tcpwrapped ((no banner captured))
[+] Port 2049/tcp open - nfs (2-4 (RPC #100003))
[+] Port 3306/tcp open - mysql (MySQL 5.1.73-0ubuntu0.10.04.1)
[+] Port 8080/tcp open - http (Apache Tomcat|Coyote JSP engine 1.1)
[+] Port 10000/tcp open - http (MiniServ 0.01 (Webmin httpd))
[+] 15 open port(s) recorded
```

► Stage 3/4 - Automated Enumeration

Services matched to a check module:

- port 22 SSH
- port 25 SMTP
- port 53 DNS
- port 80 HTTP
- port 139 SMB
- port 445 SMB
- port 8080 HTTP
- port 10000 HTTP

[?] Run automated service checks?

- * [1] Run all matched checks automatically (recommended)
- [2] Let me choose which checks to run
- [3] Skip automated enumeration

Choice [default 1]: 1

```
[+] SSH detected on port 22
[*] Starting SSH enumeration...
[*] Starting SSH banner check on port 22 ...
[+] SSH banner: OpenSSH 5.3p1 Debian 3ubuntu7 (Ubuntu Linux; protocol 2.0)
[!] [MEDIUM] Outdated OpenSSH version banner on port 22
```



```
[+] SMTP detected on port 25
[*] Starting SMTP enumeration...
[*] Starting SMTP checks on port 25...
[+] SMTP VRFY does not appear to distinguish valid/invalid users
[+] Server rejected unauthenticated relay attempt to an external domain
[+] DNS detected on port 53
[*] Starting DNS enumeration...
[*] Starting DNS checks on port 53...
[?] Do you already know the domain name and want to enter it yourself? [y/N]: n
[?] Do you want KarScan to try to auto-discover the domain name instead? [Y/n]: y
[*] Attempting to auto-discover a domain name (reverse DNS / SOA) ...
[+] Domain name auto-discovery succeeded: localdomain
[!] [INFO] Domain name identified for DNS testing on port 53
    Evidence: localdomain
[+] Zone transfer refused/failed for localdomain
[+] HTTP detected on port 80
[*] Starting HTTP enumeration...
[*] Starting HTTP enumeration on http://192.168.33.130:80...
[+] Server: Apache/2.2.14 (Ubuntu)
[!] [LOW] Server/technology banner disclosed on port 80
    Evidence: curl -skI http://192.168.33.130:80/ → Server: Apache/2.2.14 (Ubuntu)
[!] [LOW] Missing security headers on port 80
    Evidence: curl -skI http://192.168.33.130:80/ → missing: Content-Security-Policy X-Frame-Options X-Content-Type-Options
Strict-Transport-Security
[+] No robots.txt found (or empty)
[!] [INFO] Potentially interesting paths found on port 80
    Evidence: curl probe of common paths on http://192.168.33.130:80 → phpmyadmin [301]
[+] SMB detected on port 139
[*] Starting SMB enumeration...
[*] Starting SMB share enumeration on port 139...
[+] No shares listed via null/guest SMB session
[+] SMB detected on port 445
```

Activate Windows


```
[*] Starting SMB enumeration ...
[*] Starting SMB share enumeration on port 139 ...
[+] No shares listed via null/guest SMB session
[+] SMB detected on port 445
[*] Starting SMB enumeration ...
[*] Starting SMB share enumeration on port 445 ...
[+] No shares listed via null/guest SMB session
[+] HTTP detected on port 8080
[*] Starting HTTP enumeration ...
[*] Starting HTTP enumeration on http://192.168.33.130:8080...
[+] Server: Apache-Coyote/1.1
[!] [LOW] Server/technology banner disclosed on port 8080
    Evidence: curl -skI http://192.168.33.130:8080/ → Server: Apache-Coyote/1.1
[!] [LOW] Missing security headers on port 8080
    Evidence: curl -skI http://192.168.33.130:8080/ → missing: Content-Security-Policy X-Frame-Options X-Content
s Strict-Transport-Security
[+] No robots.txt found (or empty)
[+] HTTP detected on port 10000
[*] Starting HTTP enumeration ...
[*] Starting HTTP enumeration on http://192.168.33.130:10000...
[+] Server: MiniServ/0.01
[!] [LOW] Server/technology banner disclosed on port 10000
    Evidence: curl -skI http://192.168.33.130:10000/ → Server: MiniServ/0.01
[!] [LOW] Missing security headers on port 10000
    Evidence: curl -skI http://192.168.33.130:10000/ → missing: Content-Security-Policy X-Frame-Options X-Content
ns Strict-Transport-Security
[+] No robots.txt found (or empty)
[!] [INFO] Potentially interesting paths found on port 10000
    Evidence: curl probe of common paths on http://192.168.33.130:10000 → admin [200] login [200] wp-admin [200]
200] phpmyadmin [200] config.php.bak [200]
```

► Stage 4/4 – Report Generation

```
[+] Findings written to /home/karim/KarScan/reports/192.168.33.130_20260926_141751/findings.txt
[+] Summary written to /home/karim/KarScan/reports/192.168.33.130_20260926_141751/summary.txt
```



► **Stage 4/4 – Report Generation**

```
[+] Findings written to /home/karim/KarScan/reports/192.168.33.130_20260926_141751/findings.txt  
[+] Summary written to /home/karim/KarScan/reports/192.168.33.130_20260926_141751/summary.txt  
[+] Raw scan log written to /home/karim/KarScan/reports/192.168.33.130_20260926_141751/scan.txt  
[+] HTML report written to /home/karim/KarScan/reports/192.168.33.130_20260926_141751/report.html
```

Report ready: /home/karim/KarScan/reports/192.168.33.130_20260926_141751



lib



modules



reports




karscan.sh



KarScan_all_code.t
xt.pdf



README.md



findings.txt




karscan.log



report.html



scan.txt



summary.txt


```
1 RECON: 192.168.33.130
2 Date: 2026-09-26 14:18:00
3
4 PING 192.168.33.130 (192.168.33.130) 56(84) bytes of data.
5 64 bytes from 192.168.33.130: icmp_seq=1 ttl=64 time=0.423 ms
6 64 bytes from 192.168.33.130: icmp_seq=2 ttl=64 time=0.377 ms
7 64 bytes from 192.168.33.130: icmp_seq=3 ttl=64 time=0.285 ms
8
9 — 192.168.33.130 ping statistics —
10 3 packets transmitted, 3 received, 0% packet loss, time 2044ms
11 rtt min/avg/max/mdev = 0.285/0.361/0.423/0.057 ms
12 Resolved IP: 192.168.33.130
13 Reverse DNS: Host 130.33.168.192.in-addr.arpa. not found: 3(NXDOMAIN)
14
15 -- Local route to target --
16 192.168.33.130 dev eth0 src 192.168.33.129 uid 1000
17     cache
18
19 -- ARP table entry (if on local segment) --
20 192.168.33.130          ether    00:0c:29:da:53:2a    C          eth0
21
22 -- Traceroute --
23 traceroute to 192.168.33.130 (192.168.33.130), 10 hops max, 60 byte packets
24 1  192.168.33.130 (192.168.33.130)  0.229 ms  0.149 ms  0.172 ms
25
26 SCAN PROFILE: 192.168.33.130
27 Firewall evasion requested: No
28 Protocol:                TCP
29 Operational profile:      Penetration Test (standard)
30 Scan technique used:       TCP scan (technique as selected in the port-scan menu)
31 Stealth measures applied:  Penetration Test - standard nmap timing (-T3), no additional stealth overhead, prioritizing speed and completeness
32
33 PORT SCAN: 192.168.33.130
34 nmap -Pn -sV --top-ports 100 -T3 -oG - 192.168.33.130
35
36 # Nmap 7.99 scan initiated Sat Sep 26 14:18:03 2026 as: /usr/lib/nmap/nmap --privileged -Pn -sV --top-ports 100 -T3 -oG - 192.168.33.130
37 Host: 192.168.33.130 () Status: Up
```



```

35
36 # Nmap 7.99 scan initiated Sat Sep 26 14:18:03 2026 as: /usr/lib/nmap/nmap --privileged -Pn -sV --top-ports 100 -T3 -oG - 192.168.33.130
37 Host: 192.168.33.130 () Status: Up
38 Host: 192.168.33.130 () Ports: 22/open/tcp//ssh//OpenSSH 5.3p1 Debian 3ubuntu7 (Ubuntu Linux; protocol 2.0)/, 23/open/tcp//telnet//Linux telnetd/, 25/
open/tcp//smtp//Postfix smtpd/, 53/open/tcp//domain//ISC BIND 9.7.0-P1/, 80/open/tcp//http//Apache httpd 2.2.14 ((Ubuntu))/, 111/open/tcp//rpcbind//2 (RPC
#100000)/, 139/open/tcp//netbios-ssn//Samba smbd 3.X - 4.X (workgroup: WORKGROUP)/, 389/open/tcp//ldap//OpenLDAP 2.2.X - 2.3.X/, 445/open/tcp//netbios-
ssn//Samba smbd 3.X - 4.X (workgroup: WORKGROUP)/, 513/open/tcp//login///, 514/open/tcp//tcpwrapped///, 2049/open/tcp//nfs//2-4 (RPC #100003)/, 3306/open
tcp//mysql//MySQL 5.1.73-0ubuntu0.10.04.1/, 8080/open/tcp//http//Apache Tomcat|Coyote JSP engine 1.1/, 10000/open/tcp//http//MiniServ 0.01 (Webmin httpd)
Ignored State: closed (85)
39 # Nmap done at Sat Sep 26 14:18:45 2026 -- 1 IP address (1 host up) scanned in 41.94 seconds
40
41 PORT      STATE      SERVICE      VERSION
42 -----
43 22        open      ssh          OpenSSH 5.3p1 Debian 3ubuntu7 (Ubuntu Linux; protocol 2.0)
44 23        open      telnet       Linux telnetd
45 25        open      smtp         Postfix smtpd
46 53        open      domain       ISC BIND 9.7.0-P1
47 80        open      http         Apache httpd 2.2.14 ((Ubuntu))
48 111       open      rpcbind      2 (RPC #100000)
49 139       open      netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
50 389       open      ldap         OpenLDAP 2.2.X - 2.3.X
51 445       open      netbios-ssn  Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
52 513       open      login        (no banner captured)
53 514       open      tcpwrapped   (no banner captured)
54 2049      open      nfs          2-4 (RPC #100003)
55 3306      open      mysql        MySQL 5.1.73-0ubuntu0.10.04.1
56 8080      open      http         Apache Tomcat|Coyote JSP engine 1.1
57 10000     open      http         MiniServ 0.01 (Webmin httpd)
58
59 == SSH banner on 192.168.33.130:22 ==
60 OpenSSH 5.3p1 Debian 3ubuntu7 (Ubuntu Linux; protocol 2.0)
61
62 == SMTP banner on 192.168.33.130:25 ==
63
64
65 -- VRFY root --

```



- Snipping Tool

Screenshot copied to clipboard

Automatically saved to screens

Activate Windows

Markup and


```
80
81 === HTTP headers: http://192.168.33.130:80 ===
82 HTTP/1.1 200 OK
83 Date: Sat, 26 Sep 2026 15:21:32 GMT
84 Server: Apache/2.2.14 (Ubuntu)
85 Last-Modified: Sun, 30 Mar 2014 00:35:52 GMT
86 ETag: "10353b-2e9-4f5c81e0490a0"
87 Accept-Ranges: bytes
88 Content-Length: 745
89 Vary: Accept-Encoding
90 Content-Type: text/html
91 X-Pad: avoid browser bug
92
93
94 === robots.txt: http://192.168.33.130:80/robots.txt ===
95 <!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">
96 <html><head>
97 <title>404 Not Found</title>
98 </head><body>
99 <h1>Not Found</h1>
100 <p>The requested URL /robots.txt was not found on this server.</p>
101 <hr>
102 <address>Apache/2.2.14 (Ubuntu) Server at 192.168.33.130 Port 80</address>
103 </body></html>
104
105 === Common path probe: http://192.168.33.130:80 ===
106 phpmyadmin [301]
107
108 === smbclient -L //192.168.33.130 ===
109 Server requested PLAINTEXT password but 'client plaintext auth = no'
110 session setup failed: NT_STATUS_INVALID_PARAMETER
111
112 === smbclient -L //192.168.33.130 ===
113 Server requested PLAINTEXT password but 'client plaintext auth = no'
114 session setup failed: NT_STATUS_INVALID_PARAMETER
```




```
150 </head>
151 <body bgcolor=#6696bc link=#000000 vlink=#000000 text=#000000 leftmargin="0" topmargin="0" marginwidth="0" marginheight="0"
    onLoad='document.forms[0].pass.value = ""; document.forms[0].user.focus()><table width="100%" border="0" cellspacing="0" cellpadding="0" background="/
    unauthenticated/nav/bottom_shadow.jpg">
152     <tr>
153         <td width="100%" nowrap></td>
154     </tr>
155 </table><br><hr>
156 <center>
157
158 <form action=/session_login.cgi method=post>
159 <input type=hidden name=page value='/'>
160 <table border width=40%>
161 <tr bgcolor=#7f7f7f> <td><b>Login to Webmin</b></td> </tr>
162 <tr bgcolor=#b7b7b7> <td align=center><table cellpadding=3>
163 <tr> <td colspan=2 align=center>You must enter a username and password to login to the Webmin server on <tt>192.168.33.130</tt>.</td> </tr>
164 <tr> <td><b>Username</b></td>
165 <td><input name=user size=20 value=''></td> </tr>
166 <tr> <td><b>Password</b></td>
167 <td><input name=pass size=20 type=password></td> </tr>
168 <tr> <td colspan=2 align=center><input type=submit value='Login'>
169 <input type=reset value='Clear'><br>
170 <input type=checkbox name=save value=1> Remember login permanently?
171 </td> </tr>
172 </table></td></tr></table><p>
173 </form></center>
174
175 <hr>
176 </ul>
177 <table border=0 width=100% align=center cellspacing=0 cellpadding=0><tr><td>
178 </td></tr></table>
179 <br>
180 </body></html>
181
182 ≡ Common path probe: http://192.168.33.130:10000 ≡
183 admin [200] login [200] wp-admin [200] .git/HEAD [200] phpmyadmin [200] config.php.bak [200]
184
```

```
00
01 GET HTTP headers: http://192.168.33.130:80 GET
02 HTTP/1.1 200 OK
03 Date: Sat, 26 Sep 2020 15:21:32 GMT
04 Server: Apache/2.2.14 (Ubuntu)
05 Last-Modified: Sun, 30 Mar 2014 00:15:12 GMT
06 ETag: "18353b-3d9-4f3d8e949ad"
07 Accept-Ranges: bytes
08 Content-Length: 745
09 Vary: Accept-Encoding
10 Content-Type: text/html
11 X-Pad: avoid browser bug
12
13
14 GET robots.txt: http://192.168.33.130:80/robots.txt GET
15 404 (TYPE) HTML PUBLIC "-//IETF//DTD HTML 2.0//EN"
16 <html><head>
17 <title>404 Not Found</title>
18 </head><body>
19 <div>404 Not Found</div>
20 <p>The requested URL /robots.txt was not found on this server.</p>
21 <hr>
22 <address>Apache/2.2.14 (Ubuntu) Server at 192.168.33.130 Port 80</address>
23 </body></html>
24
25 GET / Common path probe: http://192.168.33.130:80 GET
26 phpmyadmin [200]
27
28 GET /admin -> http://192.168.33.130:80 GET
29 Server requested PLAINTEXT password but 'client plaintext auth = no'
```

Snipping Tool

Screenshot copied to clipboard
Automatically saved to screenshots
Activate Windows


```
1 FINDINGS - 192.168.33.130
2 Generated: 2026-09-26 14:21:28
3 =====
4
5 [1] SEVERITY: MEDIUM
6 Title: Outdated OpenSSH version banner on port 22
7 Evidence: Banner grabbed via raw TCP connect: "OpenSSH 5.3p1 Debian 3ubuntu7 (Ubuntu Linux; protocol 2.0)"
8 Recommendation: Upgrade OpenSSH to a currently supported release and check the banner's version against the NVD for known CVEs.
9
10 [2] SEVERITY: INFO
11 Title: Domain name identified for DNS testing on port 53
12 Evidence: localdomain
13 Recommendation: No action required - this is the domain name KarScan used to test the DNS server for a zone transfer (AXFR).
14
15 [3] SEVERITY: LOW
16 Title: Server/technology banner disclosed on port 80
17 Evidence: curl -skI http://192.168.33.130:80/ → Server: Apache/2.2.14 (Ubuntu)
18 Recommendation: Suppress or generalize the Server/X-Powered-By headers (ServerTokens/ServerSignature in Apache, expose_php off in PHP, etc.).
19
20 [4] SEVERITY: LOW
21 Title: Missing security headers on port 80
22 Evidence: curl -skI http://192.168.33.130:80/ → missing: Content-Security-Policy X-Frame-Options X-Content-Type-Options Strict-Transport-Security
23 Recommendation: Add the missing security headers appropriate to the application (CSP, X-Frame-Options, X-Content-Type-Options, HSTS for HTTPS).
24
25 [5] SEVERITY: INFO
26 Title: Potentially interesting paths found on port 80
27 Evidence: curl probe of common paths on http://192.168.33.130:80 → phpmyadmin [301]
28 Recommendation: Manually review each path's access control and whether it should be publicly reachable.
29
30 [6] SEVERITY: LOW
31 Title: Server/technology banner disclosed on port 8080
32 Evidence: curl -skI http://192.168.33.130:8080/ → Server: Apache-Coyote/1.1
33 Recommendation: Suppress or generalize the Server/X-Powered-By headers (ServerTokens/ServerSignature in Apache, expose_php off in PHP, etc.).
34
35 [7] SEVERITY: LOW
36 Title: Missing security headers on port 8080
```


Scanned with
 CamScanner™


```
1 SECURITY ASSESSMENT SUMMARY
2
3 Target:      192.168.33.130
4 Resolved IP: 192.168.33.130
5 Scan date:   2026-09-26 14:21:28
6 Duration:    3m37s
7
8 Scan profile:
9 Firewall evasion: No
10 Protocol:    TCP
11 Operational profile: Penetration Test (standard)
12 Technique used: TCP scan (technique as selected in the port-scan menu)
13 Stealth measures: Penetration Test - standard nmap timing (-T3), no additional stealth overhead, prioritizing speed and completeness
14
15 Open ports (15):
16 - 10000 http      MiniServ 0.01 (Webmin httpd)
17 - 111  rpcbind    2 (RPC #100000)
18 - 139  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
19 - 2049 nfs        2-4 (RPC #100003)
20 - 22   ssh         OpenSSH 5.3p1 Debian 3ubuntu7 (Ubuntu Linux; protocol 2.0)
21 - 23   telnet      Linux telnetd
22 - 25   smtp        Postfix smtpd
23 - 3306 mysql       MySQL 5.1.73-0ubuntu0.10.04.1
24 - 389  ldap        OpenLDAP 2.2.X - 2.3.X
25 - 445  netbios-ssn Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
26 - 513  login          (no banner captured)
27 - 514  tcpwrapped    (no banner captured)
28 - 53   domain       ISC BIND 9.7.0-P1
29 - 8080 http        Apache Tomcat|Coyote JSP engine 1.1
30 - 80   http         Apache httpd 2.2.14 ((Ubuntu))
31
32 Findings by severity:
33 HIGH: 0
34 MEDIUM: 1
35 LOW: 6
36 INFO: 3
37
```



```
31
32 Findings by severity:
33   HIGH:    0
34   MEDIUM: 1
35   LOW:     6
36   INFO:    3
37
38 Overall risk rating: Medium
39
40 Risk explanation:
41   No HIGH severity findings, but MEDIUM findings indicate weaknesses
42   (e.g. outdated software, information disclosure) that reduce the
43   effort needed for further compromise and should be scheduled for fixes.
44
45 Recommendations:
46   - [MEDIUM] Outdated OpenSSH version banner on port 22: Upgrade OpenSSH to a currently supported release and check the banner's version against the NVD
    for known CVEs.
47   - [INFO] Domain name identified for DNS testing on port 53: No action required – this is the domain name KarScan used to test the DNS server for a zone
    transfer (AXFR).
48   - [LOW] Server/technology banner disclosed on port 80: Suppress or generalize the Server/X-Powered-By headers (ServerTokens/ServerSignature in Apache,
    expose_php off in PHP, etc.).
49   - [LOW] Missing security headers on port 80: Add the missing security headers appropriate to the application (CSP, X-Frame-Options, X-Content-Type-
    Options, HSTS for HTTPS).
50   - [INFO] Potentially interesting paths found on port 80: Manually review each path's access control and whether it should be publicly reachable.
51   - [LOW] Server/technology banner disclosed on port 8080: Suppress or generalize the Server/X-Powered-By headers (ServerTokens/ServerSignature in Apache,
    expose_php off in PHP, etc.).
52   - [LOW] Missing security headers on port 8080: Add the missing security headers appropriate to the application (CSP, X-Frame-Options, X-Content-Type-
    Options, HSTS for HTTPS).
53   - [LOW] Server/technology banner disclosed on port 10000: Suppress or generalize the Server/X-Powered-By headers (ServerTokens/ServerSignature in Apache,
    expose_php off in PHP, etc.).
54   - [LOW] Missing security headers on port 10000: Add the missing security headers appropriate to the application (CSP, X-Frame-Options, X-Content-Type-
    Options, HSTS for HTTPS).
55   - [INFO] Potentially interesting paths found on port 10000: Manually review each path's access control and whether it should be publicly reachable.
56
57
58 Generated by KarScan (karscan.sh) – Instant Software Solutions security track
59
```


Security Assessment Report

Target: 192.168.33.130 (192.168.33.130) · Generated 2026-09-26 14:21:28

Overall risk: Medium

15
Open ports

0
High

1
Medium

6
Low

3
Info

Scan Profile	
Firewall evasion	No
Protocol	TCP
Operational profile	Penetration Test (standard)
Technique used	TCP scan (technique as selected in the port-scan menu)
Stealth measures	Penetration Test — standard nmap timing (-T3), no additional stealth overhead, prioritizing speed and completeness

Open Ports & Services

Activate Windows

Open Ports & Services

Port	Service	Version / Banner
10000	http	MiniServ 0.01 (Webmin httpd)
111	rpcbind	2 (RPC #100000)
139	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
2049	nfs	2-4 (RPC #100003)
22	ssh	OpenSSH 5.3p1 Debian 3ubuntu7 (Ubuntu Linux; protocol 2.0)
23	telnet	Linux telnetd
25	smtp	Postfix smtpd
3306	mysql	MySQL 5.1.73-0ubuntu0.10.04.1
389	ldap	OpenLDAP 2.2.X - 2.3.X
445	netbios-ssn	Samba smbd 3.X - 4.X (workgroup: WORKGROUP)
513	login	(no banner captured)
514	tcpwrapped	(no banner captured)
53	domain	ISC BIND 9.7.0-P1
8080	http	Apache Tomcat Coyote JSP engine 1.1
80	http	Apache httpd 2.2.14 ((Ubuntu))

Findings

MEDIUM Outdated OpenSSH version banner on port 22

Banner grabbed via raw TCP connect: "quot;OpenSSH 5.3p1 Debian 3ubuntu7 (Ubuntu Linux; protocol 2.0)"quot;

Recommendation: Upgrade OpenSSH to a currently supported release and check the banner's version against the NVD for known CVEs.

INFO Domain name identified for DNS testing on port 53

localdomain

Recommendation: No action required — this is the domain name KarScan used to test the DNS server for a zone transfer (AXFR).

LOW Server/technology banner disclosed on port 80

curl -skI http://192.168.33.130:80/ ->gt; Server: Apache/2.2.14 (Ubuntu)

Recommendation: Suppress or generalize the Server/X-Powered-By headers (ServerTokens/ServerSignature in Apache, expose_php off in PHP, etc.).

LOW Missing security headers on port 80

curl -skI http://192.168.33.130:80/ ->gt; missing: Content-Security-Policy X-Frame-Options X-Content-Type-Options Strict-Transport-Security

Recommendation: Add the missing security headers appropriate to the application (CSP, X-Frame-Options, X-Content-Type-Options, HSTS for HTTPS).

INFO Potentially interesting paths found on port 80

curl probe of common paths on http://192.168.33.130:80 ->gt; phpmyadmin [301]

Recommendation: Manually review each path's access control and whether it should be publicly reachable.

LOW Missing security headers on port 80

```
curl -skI http://192.168.33.130:80/ ->gt; missing: Content-Security-Policy X-Frame-Options X-Content-Type-Options Strict-Transport-Security
```

Recommendation: Add the missing security headers appropriate to the application (CSP, X-Frame-Options, X-Content-Type-Options, HSTS for HTTPS).

INFO Potentially interesting paths found on port 80

```
curl probe of common paths on http://192.168.33.130:80 ->gt; phpmyadmin [301]
```

Recommendation: Manually review each path's access control and whether it should be publicly reachable.

LOW Server/technology banner disclosed on port 8080

```
curl -skI http://192.168.33.130:8080/ ->gt; Server: Apache-Coyote/1.1
```

Recommendation: Suppress or generalize the Server/X-Powered-By headers (ServerTokens/ServerSignature in Apache, expose_php off in PHP, etc.).

LOW Missing security headers on port 8080

```
curl -skI http://192.168.33.130:8080/ ->gt; missing: Content-Security-Policy X-Frame-Options X-Content-Type-Options Strict-Transport-Security
```

Recommendation: Add the missing security headers appropriate to the application (CSP, X-Frame-Options, X-Content-Type-Options, HSTS for HTTPS).

LOW Server/technology banner disclosed on port 10000

```
curl -skI http://192.168.33.130:10000/ ->gt; Server: MiniServ/0.01
```

Recommendation: Suppress or generalize the Server/X-Powered-By headers (ServerTokens/ServerSignature in Apache, expose_php off in PHP, etc.).

expose_php off in PHP, etc.).

LOW Missing security headers on port 8080

```
curl -skI http://192.168.33.130:8080/ ->gt; missing: Content-Security-Policy X-Frame-Options X-Content-Type-Options Strict-Transport-Security
```

Recommendation: Add the missing security headers appropriate to the application (CSP, X-Frame-Options, X-Content-Type-Options, HSTS for HTTPS).

LOW Server/technology banner disclosed on port 10000

```
curl -skI http://192.168.33.130:10000/ ->gt; Server: MiniServ/0.01
```

Recommendation: Suppress or generalize the Server/X-Powered-By headers (ServerTokens/ServerSignature in Apache, expose_php off in PHP, etc.).

LOW Missing security headers on port 10000

```
curl -skI http://192.168.33.130:10000/ ->gt; missing: Content-Security-Policy X-Frame-Options X-Content-Type-Options Strict-Transport-Security
```

Recommendation: Add the missing security headers appropriate to the application (CSP, X-Frame-Options, X-Content-Type-Options, HSTS for HTTPS).

INFO Potentially interesting paths found on port 10000

```
curl probe of common paths on http://192.168.33.130:10000 ->gt; admin [200] login [200] wp-admin [200] .git/HEAD [200] phpmyadmin [200] config.php.bak [200]
```

Recommendation: Manually review each path's access control and whether it should be publicly reachable.