



Relational Data Model – Part 1

Schema and State


What is the Relational Data Model?

- Introduced by Edgar F. Codd of IBM Research in 1970.
“A Relational Model for Large Shared Data Banks”, Communications of the ACM.
- A database contains tables (called relations), and each table is made up of columns and rows.
- Humans have used tables for centuries to keep track of data.



- Used as the standard for relational DBMSs (e.g., Oracle, IBM DB2, Microsofts Access, Microsofts SQL Server, MySQL, postgresSQL, etc.).

Relation



- Correspondence of informal and formal terms:

INFORMAL TERMS	FORMAL TERMS
Table	Relation
Column	Attribute
Data type	Domain
Row	Tuple
Table definition	Relation schema

The Basics

- **Attributes** are used to describe the properties of information. In the relational model, they usually refer to atomic data.

Example: To capture the information of a person, we can use attributes like Name, Age, Gender, Address and PhoneNumber.

- **Domains** are the sets of all possible values for attributes.

- $STRING = \{A, B, CD, \dots\};$

Example: ● $DATE = \{01/01/2005, 03/07/1978, \dots\};$

- $INT = \{\dots, -1, 0, 1, 2, \dots\}.$

- Recall that, **Cartesian product** $D_1 \times \dots \times D_n$ is the set of all possible combinations of values from the sets D_1, \dots, D_n .

Example: Let $D_1 = \{\text{book}, \text{pen}\}$, $D_2 = \{1, 2\}$ and $D_3 = \{\text{red}\}$. Then

- $D_1 \times D_2 \times D_3 = \{(\text{book}, 1, \text{red}), (\text{book}, 2, \text{red}), (\text{pen}, 1, \text{red}), (\text{pen}, 2, \text{red})\}$



The Basics

- The attributes are StudentID, CourseNo, Semester, Status and EnrolDate.
- The domains of attributes are as follows.
 $\text{dom}(\text{StudentID})=\text{INT};$ $\text{dom}(\text{CourseNo})=\text{STRING};$
 $\text{dom}(\text{Semester})=\text{STRING};$ $\text{dom}(\text{Status})=\text{STRING};$
 $\text{dom}(\text{EnrolDate})=\text{DATE}.$
- The whole table can be considered as a set $\{(456, \text{COMP2400}, 2016 \text{ S2}, \text{active}, 25/05/2016), (458, \text{COMP1130}, 2016 \text{ S1}, \text{active}, 20/02/2016), (459, \text{COMP2400}, 2016 \text{ S2}, \text{active}, 11/06/2016)\}.$

ENROL				
StudentID	CourseNo	Semester	Status	EnrolDate
456	COMP2400	2016 S2	active	25/05/2016
458	COMP1130	2016 S1	active	20/02/2016
459	COMP2400	2016 S2	active	11/06/2016

- Is the above set a subset of

$\text{INT} \times \text{STRING} \times \text{STRING} \times \text{STRING} \times \text{DATE}?$

Answer: Yes.



The Basics

- A **relation schema** has a **relation name** and a list of **attributes**.
- Each attribute is associated with a **domain**.
- A relation schema can be expressed by
 - $R(A_1, \dots, A_n)$, or
 - $R(A_1 : \text{dom}(A_1), \dots, A_n : \text{dom}(A_n))$,

where A_1, \dots, A_n are attributes of R and $\text{dom}(A_i)$ is the domain of A_i .

Example: The relation schema in the previous example is

- $\text{ENROL}(\text{StudentID}, \text{CourseNo}, \text{Semester}, \text{Status}, \text{EnrolDate})$, or
- $\text{ENROL}(\text{StudentID: INT}, \text{CourseNo: STRING}, \text{Semester: STRING}, \text{Status: STRING}, \text{EnrolDate: DATE})$.

The Basics

- Let $R(A_1, \dots, A_n)$ be a relation schema.
- A **tuple** in R is a list t of values, i.e., $t \in \text{dom}(A_1) \times \dots \times \text{dom}(A_n)$.

Example: The previous example has the following tuples:

- $(456, \text{COMP2400}, 2016 \text{ S2}, \text{active}, 25/05/2016) \in$
 $\text{INT} \times \text{STRING} \times \text{STRING} \times \text{STRING} \times \text{DATE}.$
 - $(458, \text{COMP1130}, 2016 \text{ S1}, \text{active}, 20/02/2016) \in$
 $\text{INT} \times \text{STRING} \times \text{STRING} \times \text{STRING} \times \text{DATE}.$
 - $(459, \text{COMP2400}, 2016 \text{ S2}, \text{active}, 11/06/2016) \in$
 $\text{INT} \times \text{STRING} \times \text{STRING} \times \text{STRING} \times \text{DATE}.$
- A **relation** $r(R)$ is a set of tuples $r(R) \subseteq \text{dom}(A_1) \times \dots \times \text{dom}(A_n)$.

Example: The previous example has the following relation:

- $r(\text{ENROL}) \subseteq \text{INT} \times \text{STRING} \times \text{STRING} \times \text{STRING} \times \text{DATE}.$



The Basics

- A **relational database schema** S is
 - a set of relation schemas $S = \{R_1, \dots, R_m\}$, and
 - a set of integrity constraints IC .
- A **relational database state** of S is a set of relations such that
 - there is just one relation for each relation schema in S , and
 - all the relations satisfy the integrity constraints IC .



The Basics

- Consider a relational database schema STUENROL that has three relation schemas:
 - STUDENT(StudentID, Name, DoB, Email).
 - COURSE(No, Cname, Unit);
 - ENROL(StudentID, CourseNo, Semester, Status, EnrolDate);

STUDENT			
StudentID	Name	DoB	Email

COURSE		
No	Cname	Unit

ENROL				
StudentID	CourseNo	Semester	Status	EnrolDate

- That is, STUENROL={STUDENT, COURSE, ENROL}.



The Basics

- Relational Database State – Example

STUDENT			
StudentID	Name	DoB	Email
456	Tom	25/01/1988	tom@gmail.com
458	Peter	23/05/1993	peter@gmail.com
459	Fran	11/09/1987	frankk@gmail.com

COURSE		
No	Cname	Unit
COMP1130	Introduction to Advanced Computing I	6
COMP2400	Relational Databases	6

ENROL				
StudentID	CourseNo	Semester	Status	EnrolDate
456	COMP2400	2016 S2	active	25/05/2016
458	COMP1130	2016 S1	active	20/02/2016
459	COMP2400	2016 S2	active	11/06/2016