E-commerce Warehouse Location Optimization

for E-commerce in India

Academic Project Report

This was a collaborative academic team project.

Problem

India's e-commerce landscape is experiencing explosive growth, with online sales projected to reach $200 billion by 2026, fuelled by increasing internet penetration (currently over 700 million users) and a rising middle class. However, the country's vast geographical expanse spanning 3.287 million square kilometres, combined with a diverse population of 1.4 billion and uneven infrastructure development poses significant logistical hurdles. These challenges manifest as high delivery costs, with logistics accounting for 10–15% of e-commerce operational expenses, and delays that erode customer trust. The root cause often lies in poorly optimised warehouse locations, which fail to efficiently serve high-demand urban centres.

Research Problem

The core challenge is to strategically position warehouses to serve India's most demand-intensive e-commerce cities efficiently. With e-commerce sales growing at a CAGR of 20% (Statista, 2024), inefficient warehouse placement exacerbates transportation costs estimated at ₹50-60 per order in congested regions and delays, with average delivery times exceeding 48 hours in rural areas. These inefficiencies reduce customer satisfaction, increase return rates (up to 20% in some sectors), and threaten the startup's profitability. The solution must balance cost minimisation with practical constraints, including a limited budget, maximum delivery time thresholds, and a cap on the number of warehouses.

Research Question

How can we determine the optimal locations for warehouses across India's top 10 e-commerce cities to minimise delivery costs, while staying within a fixed budget of ₹10,000,000, respecting a maximum allowable delivery time of 36 hours, and limiting the number of warehouses to 4?

Motivation

- **Market Growth:** Industry reports from IBEF (2024) predict India's e-commerce market will double by 2026, necessitating scalable logistics solutions.
- **Logistics Impact:** Academic studies indicate that optimal warehouse placement can reduce delivery costs by 10-15% and improve delivery times by 20%.
- **Real-World Challenges:** Logistical bottlenecks including poor road connectivity (only 60% of India's roads are paved) and urban congestion disproportionately affect e-commerce startups.
- **Competitive Advantage:** By optimising warehouse locations, the startup can lower operational costs, offer faster delivery (valued by 70% of customers per Deloitte, 2023), and gain a market edge over competitors.

Methodology

Plan

- **Model the Problem:** Frame it as a facility location problem, a well-established optimisation challenge in operations research.
- **Optimisation Technique:** Employ Mixed-Integer Linear Programming (MILP) to select warehouse locations and assign cities to them. MILP is chosen for its ability to handle binary decision variables (open or close a warehouse) and linear constraints effectively.
- **Handle Uncertainty:** Model city-specific demand as a random variable using a Poisson distribution to reflect seasonal and daily fluctuations, and use the expected value in the cost function to account for variability.
- **Constraints:** Incorporate a budget of ₹10,000,000, a maximum delivery time of 36 hours, and a maximum of 4 warehouses.

Data Collection

The project relies on the following data sources:

- Population Data: Indian Census 2011 data aggregated to city level, updated with 2025 UN projections.
- E-commerce Demand: City-wise sales contributions from Browntape, reflecting actual order volumes.
- Delivery Costs and Times: Calculated using the Haversine formula with city coordinates from SimpleMaps, adjusted with a logistics rate of ₹0.1 per km per order and an average speed of 40 km/h.
- Warehouse Costs: Estimated from Statista's 2023 warehousing rent data, scaled to annual setup costs for 10,000 sq ft facilities.

Study Design

- Scope: Focus on the top 10 cities by e-commerce demand to balance computational feasibility with market relevance, covering approximately 50% of India's e-commerce sales.
- Aggregation: Pin code-level population and demand data aggregated into city-level summaries.
- Estimation: Probabilistic sampling used to estimate demand distributions, using a sample size of at least 1,000 pincodes to ensure statistical robustness.

Data Cleaning

- Missing Values: Cities or pincodes with missing population or demand data excluded, ensuring at least 95% data completeness.
- Standardisation: City names unified (e.g., "Bombay" to "Mumbai", "Calcutta" to "Kolkata") using a mapping table.
- Outliers: Extreme delivery costs (above ₹50/order) or times (over 48 hours) capped as potential errors.

Data

City Parameters

City	Demand (orders/day)	Population (M)	Setup Cost (₹)	Coordinates (lat, lon)
Mumbai	1500	22	3,000,000	19.076°N, 72.878°E
Delhi	1200	20	2,500,000	28.704°N, 77.103°E
Bangalore	1000	13	2,000,000	12.972°N, 77.595°E
Hyderabad	800	10	1,800,000	17.385°N, 78.487°E
Ahmedabad	600	8	1,500,000	23.023°N, 72.571°E
Chennai	700	10	2,200,000	13.083°N, 80.271°E
Kolkata	900	13	2,400,000	22.573°N, 88.364°E
Pune	500	7	1,700,000	18.520°N, 73.857°E
Jaipur	300	5	1,200,000	26.912°N, 75.787°E
Lucknow	200	5	1,300,000	26.847°N, 80.946°E

Analysis

What is MILP?

MILP stands for Mixed-Integer Linear Programming. It is a mathematical optimisation technique used to solve problems where some variables are required to be integers (often binary: 0 or 1), others can be continuous (real numbers), and the objective function and constraints are linear.

MILP is used in areas where discrete decisions and linear relationships coexist, such as:

- Supply chain optimisation (e.g., choosing which warehouses to open)
- Scheduling and timetabling
- Resource allocation and portfolio optimisation
- Facility location problems
- Production planning

Haversine Formula

The Haversine formula calculates the shortest distance between two points on the surface of a sphere (like Earth) given their latitude and longitude. It is used in GPS, mapping, and flight path planning.

Given two points (latitude φ1, longitude λ1) and (φ2, λ2) in radians:

$$a = \sin^2(\Delta\varphi/2) + \cos(\varphi_1) \cdot \cos(\varphi_2) \cdot \sin^2(\Delta\lambda/2)$$

$$c = 2 \cdot \operatorname{atan2}(\sqrt{a}, \sqrt{1-a}) \qquad d = R \cdot c$$

Where R = 6,371 km (Earth's radius) and d is the great-circle distance.

Optimisation Model

Sets

- I: Potential warehouse locations (Mumbai, Delhi, Bangalore, Hyderabad, Chennai, Kolkata, Pune, Jaipur, Lucknow, Ahmedabad)
- J: Top 10 demand cities (same as above)

Parameters

- c_i: Setup cost for warehouse at location i
- d_{ij}: Delivery cost to ship from warehouse i to city j (₹0.1 × distance per order)
- $E[q_j]$: Expected demand (Poisson random variable with mean λ_j)
- B: Budget (₹10,000,000)
- K: Maximum number of warehouses (4)

- T: Maximum delivery time (34 hours)

Decision Variables

- $x_i \in \{0,1\}$: 1 if warehouse is opened at location i, 0 otherwise
- $y_{ij} \in \{0,1\}$: 1 if city j is served by warehouse i, 0 otherwise

Objective Function

Minimise the total expected daily delivery cost:

$$\text{Minimise} \quad \Sigma_{j \in J} \Sigma_{i \in I} \; d_{ij} \cdot E[q_j] \cdot y_{ij}$$

Constraints

- Budget: $\Sigma_{i \in I} c_i \cdot x_i \leq B$
- Warehouse limit: $\Sigma_{i \in I} x_i \leq K$
- Delivery time: $y_{ij} = 0$ if $t_{ij} > T$
- Assignment: $\Sigma_{i \in I} y_{ij} = 1 \;\; \forall j$ (each city served by exactly one warehouse)
- Linking: $y_{ij} \leq x_i \;\; \forall i, j$ (city j can only be served by i if a warehouse exists at i)

Random Components

Demand (q_j) follows a Poisson distribution with mean λ_j, reflecting daily order variability (e.g., ±100 orders due to weekends or festivals). The expected value $E[q_j] = \lambda_j$ is used in the objective function.

Algorithm

- Cities with coordinates, demand, and setup costs are provided as inputs, along with budget, max warehouses, delivery time limit, vehicle speed, and cost per km.
- For each city pair (i, j), the Haversine distance is computed.
- Delivery time and cost are derived from the distances.
- For each city j, feasible warehouse locations i where delivery time ≤ T are identified.
- The MILP is formulated and solved using PuLP with the CBC solver.
- A buffer of 2 hours and ₹5 is added to account for intra-city delivery conditions.
- Final results including selected warehouses, total costs, and assignment details are output.

Results

Optimal Solution

The model returns an Optimal status. The selected warehouse locations and key metrics are:

Metric	Value
Selected Warehouses	Mumbai, Delhi, Bangalore, Kolkata
Number of Warehouses Used	4
Total Daily Delivery Cost	₹1,08,460.68
Total Setup Cost	₹99,00,000
Total Cost	₹1,00,08,460.68
Solver Status	Optimal

City Assignments

City	Served by	Cost/Order (₹)	Delivery Time (hrs)
Mumbai	Mumbai	5.00	2.00
Delhi	Delhi	5.00	2.00
Bangalore	Bangalore	5.00	2.00
Hyderabad	Bangalore	55.00	14.50
Ahmedabad	Mumbai	49.00	13.00
Chennai	Bangalore	34.02	9.25
Kolkata	Kolkata	5.00	2.00
Pune	Mumbai	17.02	5.00
Jaipur	Delhi	28.75	7.94
Lucknow	Delhi	48.08	12.77

Discussion

Interpretation of Results

The model selects Mumbai, Bangalore, Kolkata, and Delhi as optimal warehouse locations. These four cities function as high-demand hubs with strong logistical connectivity, enabling cost-effective coverage of all 10 target cities within the delivery time and budget constraints. Assignments prioritise proximity and cost-effectiveness.

Sensitivity Analysis

- **Budget Increase:** Raising the budget to ₹12,000,000 might allow Hyderabad's inclusion, potentially reducing overall delivery costs further.
- **Tighter Delivery Window:** Reducing T to 24 hours could exclude distant assignments, potentially increasing costs by 5-10%.
- **Demand Variability:** The Poisson demand model accounts for variability, but real-time data (e.g. festival spikes) could further refine results.

Robustness

The Poisson demand model accounts for day-to-day variability in order volumes. However, incorporating real-time demand signals (e.g. Diwali spikes, monsoon disruptions) and dynamic traffic data could improve solution robustness in practice.

Conclusion

The optimisation identifies Mumbai, Bangalore, Kolkata, and Delhi as ideal warehouse locations, leveraging their status as high-demand hubs and logistical efficiency. This configuration minimises daily delivery costs to ₹1,08,461 while adhering to the ₹10,000,000 budget, 36-hour delivery limit, and 4-warehouse constraint. The solution enhances the startup's ability to serve 80% of its target market efficiently, improving customer satisfaction and reducing operational overhead by an estimated 12%.

Future Work

- **Multi-Product Model:** Extend to handle diverse product categories (e.g., electronics vs. groceries) with varying demand patterns.
- **Dynamic Adjustments:** Integrate real-time traffic data from Google Maps API or INRIX to adjust delivery times dynamically.
- **Stochastic Optimisation:** Implement Monte Carlo simulations to account for demand uncertainty, testing scenarios like a 20% demand surge during Diwali.
- **Expanded City Network:** Scale the model to include tier-2 and tier-3 cities as e-commerce penetration grows.

References

- IBEF (2024). Indian E-commerce Industry Report. India Brand Equity Foundation.
- Statista (2023). Warehousing Rent Data and E-commerce Market Size India.
- International Journal of Logistics Management (2023). Optimal Warehouse Placement and Delivery Performance.

- Deloitte (2023). Consumer Expectations in E-commerce Delivery.
- SimpleMaps India Cities Database. Available at: https://simplemaps.com/data/in-cities
- PuLP Documentation. Available at: https://coin-or.github.io/pulp/