

Cornell Ranger: Implementing energy-optimal trajectory control using low information, reflex-based control

Pranav Bhounsule *, Jason Cortell **, (Andy Ruina **)

* Disney Research, Pittsburgh,

4720 Forbes Avenue, Lower Level, Suite 110

Pittsburgh, PA 15213 USA. *pab47@disneyresearch.com*

** Biorobotics and Locomotion Laboratory, Cornell University,

Ithaca, NY, 14850 USA. *jb2@cornell.edu*, *ruina@cornell.edu*

1 Introduction

A growing community of researchers have been using optimal trajectory control to generate walking gaits for legged robots (for example Bessonnet 2005 [1], Chevallereau 1999 [2] and 2002 [3], Djoudi 2006 [4], Hardt 1999 [5], Mombaur 2005 [6] and 2009 [7], Roussel 1997 [8] and 1998 [9]).

In optimal trajectory control, one formulates an optimization problem in which one is interested in minimizing a certain criteria like, say, energy used per unit distance travelled subject to various constraints like say walking speed, no foot scuffing, respecting actuator bounds and so forth. The optimal trajectory problem is then cast into a parameter optimization by, e.g., finding control torques as a piecewise linear function of time and then optimizing using one or another numerical method. Assuming numerical convergence to a unique local minimum, a sufficiently fine grid size, usually associated with a large number of control parameters, ensures a reasonably accurate approximation to the true solution.

2 Motivation

Experimentalists who want to implement the optimal trajectory control on a physical robot have to deal with two issues.

1. **A large number of control parameters:** As pointed out earlier, a fine grid has large number of parameters and is a better approximation to the infinite dimensional optimal control problem and hence gives a better solution.
2. **The stability of the optimal trajectory solution:** Optimal trajectory control is not concerned with stability (unless stability is criteria or a constraint in optimization) and the resulting trajectory may or may not be stable. If the trajectory is unstable, then it needs stabilization. The common approach to stabilizing the optimal trajectory is to use a high bandwidth feedback controller that tries to track the optimal trajectory exactly. This type of control introduces another large set of control parameters and if not tuned properly could lead to robot jitter.

3 Methods

We propose the following approach to deal with the above two issues [10, 11].

1. Using the fine grid optimization as a guide, we re-parameterize the controls either as a function of time or of state and re-compute the optimal solution. If we are not reasonably close to the optimal value calculated from the fine-grid optimization, we re-parameterize by adding more parameters or changing the functional form of the representation as needed. Our goal in this step is to simplify the parameterization typically at the cost of losing a bit of the optimality.
2. In order to stabilize the optimal trajectory, we use an event-based discrete intermittent feed-forward stabilizing controller. In our stabilizing controller, we regulate key heuristically chosen quantities like step length, step velocity once per step using as little sensor information.

We call our control method "reflex-based" because various events are triggered by thresholds in dynamic state variables and they set off more-or-less open loop motor programs.

4 Results

We show results of our proposed methodology on the bipedal robot called the Ranger [12]. We assume and fit a physics based model of the robot (see [13]). We then solve an energy-optimal trajectory control problem with our cost metric defined as the Total Cost Of Transport (TCOT = energy used per unit weight per unit distance moved) (see [14]). Our energy-optimal control solution had 126 control parameters and predicted a TCOT of 0.167. Next, we simplified the optimal control parameterization based on results from the fine grid optimization. We managed to decrease the control parameters to 15 (factor of 8 decrease) while TCOT increased to 0.18 (an 8% increase). Our simplified control solution was not stable enough to implement on the

robot. So next, we added an event-driven discrete intermittent feed-forward controller that tries to regulate the velocity of the robot at mid-stance by regulating the push-off and foot placement. Our implemented control solution on the robot had 30 parameter in all and a TCOT of 0.19 (a 14 % increase from the fine-grid optimum). To date, this is the lowest TCOT ever achieved on any legged robot.

5 Keywords

Experimental bipedal, Energy-optimal control.

References

- [1] G. Bessonnet, P. Seguin and P. Sardain, A parametric optimization approach to walking pattern synthesis, *The International Journal of Robotics Research*, 24(7):523–536, 2005.
- [2] C. Chevallereau, Y. Aoustin and A. Formal'sky, Optimal walking trajectories for a biped, *In Proc. of IEEE Robot Motion and Control*, Kiekrz, Poland, 1999.
- [3] C. Chevallereau, A. Formal'sky, and B. Perrin, Low energy cost reference trajectories for a biped robot, *Proceeding of 1998 International Conference on Robotics and Automation*, Leuven, Belgium, 2002.
- [4] D. Djoudi, C. Chevallereau, and Y. Aoustin, Optimal walking trajectories for a biped, *In Proceeding of 2005 International Conference on Robotics and Automation*, Barcelona, Spain, 2005.
- [5] M. Hardt, K. Kreutz-Delgado, and J. W. Helton, Optimal biped walking with a complete dynamical model, *Proceedings of the 38th IEEE Conference on Decision and Control*, Phoenix, Arizona, USA, 1999.
- [6] K. Mombaur, H. G. Bock, J. Schlöder, and R. Longman, Stable walking and running robots without feedback, *In Proc. of Climbing and Walking Robots*, 725–735, 2005.
- [7] K. Mombaur, Using optimization to create self-stable human-like running, *Robotica*, 27(3):321–339, 2009.
- [8] L. Roussel, C. Canudas and A. Goswami, Comparative study of methods for energy-optimal gait generation for biped robots, *International Conference on Informatics and Control*, St. Petersburg, Russia, 1997.
- [9] L. Roussel and A. Goswami, Generation of energy optimal complete gait cycles for biped robots, *In Proceedings of IEEE International Conference on Robotics and Automation*, Leuven, Belgium, 1998.
- [10] P. A. Bhounsule and A. R. Ruina, Smooth discrete control of walking robots: An intermediate between fully passive and high bandwidth feedback control, *6th World Congress of Biomechanics*, Singapore, 2010.
- [11] P. A. Bhounsule, *A controller design framework for bipedal robots: trajectory optimization and event-based stabilization*, PhD Thesis, Cornell University, 2012.
- [12] P. A. Bhounsule, J. Cortell, B. Hendriksen, J. G. D. Karssen, C. Paul, A. Ruina, A robot that walked 65 km

on a single charge: energy-effective and reliable locomotion using trajectory optimization and stabilization from reflexes, *Submitted to The International Journal of Robotics Research*, 2012.

[13] P. A. Bhounsule, Cornell Ranger: Computer Simulation and Experimental Fits, *Dynamic Walking*, Delft, The Netherlands, 2008.

[14] P. A. Bhounsule and A. R. Ruina, Cornell Ranger: Energy-optimal Control, *Dynamic Walking*, Vancouver, Canada, 2009.