

검사증명서
MILL TEST CERTIFICATE



15 516(Per 2)
HYUNDAI STEEL
소재: 철강, 용접: 탄소강, 규격: 430
DME-41003558 1480 Sukhwanmp-Ro, Songok-Eup, Dangjin-Si, Chungnam, Korea

주문번호
Order No. : F231000002

품명
Commodity : Cold Rolled Coil

제품규격
Specification : IS 513 ISCS90Y / SPFC590DP

고객사
Customer : MAHINDRA AUTO STEEL PVT. LTD.

주문자
Contractor : LX INTERNATIONAL CORP.

증명서 번호
Certificate No. : 20231130-NN-253-001

발행일자
Date of Issue : 2023-11-30

제품차수 Dimension	수량 Quantity	중량 Weight (Kg)	제강번호 Heat No.	제품번호 Product No.	인장시험 Tensile Test			OILING	Post Treatment	Re	화학성분 Chemical Composition (%)						단위 Unit 2 : x 100 3 : x 1,000 4 : x 10,000 5 : x 100,000
					YP	TS	EL				C	Si	Mn	P	S	Sol -Al	
1.20X1570XC	1	15,860	S86267	CZ4448A	376	639	30	G	XX	0.8	662	664	1.666	157	24	32	28-46751-52-55-56-57-58 -59-60-61-62-63-64-65 -66-67-69-71
1.20X1570XC	1	15,840	S86267	CZ4448B	376	639	30	G	XX	0.8	662	664	1.666	157	24	32	
1.20X1570XC	1	16,140	S86267	CZ4449A	369	628	30	G	XX	0.8	662	664	1.666	157	24	32	
1.20X1570XC	1	16,220	S86267	CZ4449B	369	628	30	G	XX	0.8	662	664	1.666	157	24	32	
1.20X1570XC	1	15,430	S86265	CZC103A	364	633	30	G	XX	1.0	715	713	1.644	140	24	30	
1.20X1570XC	1	15,780	S86265	CZC103B	364	633	30	G	XX	1.0	715	713	1.644	140	24	30	
1.20X1570XC	1	16,320	S86265	CZC104A	363	626	31	G	XX	0.9	715	713	1.644	140	24	30	
1.20X1570XC	1	16,200	S86265	CZC104B	363	626	31	G	XX	0.9	715	713	1.644	140	24	30	
1.20X1570XC	1	16,190	S86265	CZC105A	364	627	31	G	XX	0.9	715	713	1.644	140	24	30	
1.20X1570XC	1	16,250	S86265	CZC105B	364	627	31	G	XX	0.9	715	713	1.644	140	24	30	
1.20X1570XC	1	16,280	S86267	CZC106A	364	613	33	G	XX	0.8	662	664	1.666	157	24	32	
1.20X1570XC	1	16,450	S86267	CZC106B	364	613	33	G	XX	0.8	662	664	1.666	157	24	32	
1.20X1570XC	1	16,130	S86267	CZC577A	369	602	30	G	XX	0.9	662	664	1.666	157	24	32	
1.20X1570XC	1	16,160	S86267	CZC577B	369	602	30	G	XX	0.9	662	664	1.666	157	24	32	
1.20X1570XC	1	16,160	S86265	CZC578A	366	630	30	G	XX	0.8	715	713	1.644	140	24	30	
1.20X1570XC	1	16,310	S86265	CZC578B	366	630	30	G	XX	0.8	715	713	1.644	140	24	30	
1.20X1570XC	1	16,300	S86267	CZC579A	368	624	31	G	XX	0.8	662	664	1.666	157	24	32	
*Post Treatment - XX:No Treatment MG-Cr-FREE AF-PI(conductivity) CF-Cr-Free for Automobile GR:Galling Resistance Coating CH,CL,CM,CR Coated PL,PF,CR-FREEPhosphated EF,GF, SF:Cr-Free PX:Phosphated IH:Inorganic Heat-resistance Coating LP:Lubricant Pre-phosphated MF:Cr-Free AFT(Phosphated) AF:Resin film for Fuel Tank(Automobile) PP:Pre-Phosphated																	
*OILING - T:Super Light, L:Light, G:General, H:Heavy, S:Super Heavy, D:Dos Oiled, 1:Customer Requirement(L-G), 2:Customer Requirement(G-H)																	
It is certified that the material described below fully conforms to IS 513(part 2):2016 Chemical composition and Mechanical properties of the product, as tested in accordance with the Scheme of Testing and Inspection contained in the BIS Certification Marks License No. CM/L-4100045869 are as indicated below against each order No. etc. (PLEASE REFER TO IS 513(part 2):2016 FOR DETAILS OF SPECIFICATION REQUIREMENTS)																	
Signature Kim. M. J.																	Chief of Cold Rolled Quality Team

* 본 검사증명서는 원본인 전자문서(전자서명 정보 포함)로부터 출력된 사본입니다. 전자문서의 내용은 원본과 동일하게 확인하실 수 있습니다.(http://smhyundai-steel.com/csm/login.jsp)
* This Mill Test Certificate is a copy that has been printed from original electronic document(with digital signing)
* You are able to check an original electronic document at Hyundai Steel's customer Portal (http://smhyundai-steel.com/csm/login.jsp) * QRcode scanner App : QReal
* [사용상 주의사항] 본 검사증명서에 명기된 규격 외 사용시 제품손상 및 안전상 문제가 발생할 수 있습니다.
* [Caution for Use] Damage on products and safety problems may arise if used other than to the spec stated in this Mill Test Certification.