

IS 513 (Feb. 2)
HYUNDAI
STEEL



주요특징: 동남-동남기 층을 북부 산업로 1430
DMLA100245569 1480 Eukhusanp-Ro, Songak Eup, Dangjin-Si, Chungnam, Korea

고객사 : MAHINDRA AUTO STEEL PVT. LTD.

주문자 : LX INTERNATIONAL CORP
Contractor

증명서 번호
Certificate No. : 20231130-NN-252-001

발행일자
Date of Issue
: 2023-11-30

제품치수 Dimension	수량 Quantity	중량 Weight (Kg)	제검번호 Heat No.	제품번호 Product No.	인장시험 Tensile Test			Q L U N G	P o s t n	Pa	화학성분 원위 Unit							
					YP	TS	EL				Chemical Composition (%)							
											C	Si	Mn	P	S	Sol -Al		
1.20X1080XC	1	14,780	S87100	CZC9286A	383	473	31	G	XX	0.18	1.1	666	7	732	96	41	34	2546786
*** Sub Total(004) *** 1 14,780(Kg)																		
0.80X1245XC	1	14,200	S87308	CZC793A	382	450	33	G	XX	0.22	1.0	602	16	607	121	63	36	
0.80X1245XC	1	14,220	S87308	CZC793B	382	450	33	G	XX	0.22	1.0	602	16	607	121	63	36	
0.80X1245XC	1	14,360	S87308	CZC794A	385	446	36	G	XX	0.22	1.1	602	16	607	121	63	36	
0.80X1245XC	1	14,450	S87308	CZC794B	385	446	36	G	XX	0.22	1.1	602	16	607	121	63	36	
0.80X1245XC	1	14,370	S87311	CZC795A	371	435	35	G	XX	0.23	1.2	635	10	577	103	57	33	
0.80X1245XC	1	14,300	S87311	CZC795B	371	435	35	G	XX	0.23	1.2	635	10	577	103	57	33	
0.80X1245XC	1	14,450	S87311	CZC796A	380	439	34	G	XX	0.23	1.2	635	10	577	103	57	33	
0.80X1245XC	1	14,400	S87311	CZC796B	380	439	34	G	XX	0.23	1.2	635	10	577	103	57	33	
*** Sub Total(007) *** 8 114,750(Kg)																		
1.40X1218XC	1	12,030	S87086	CZC902A	371	477	32	G	XX	0.18	1.2	667	7	770	100	45	38	2546787-88-89-90
1.40X1218XC	1	12,050	S87086	CZC902B	371	477	32	G	XX	0.18	1.2	667	7	770	100	45	38	
1.40X1218XC	1	12,110	S87086	CZC903A	386	488	31	G	XX	0.17	1.2	667	7	770	100	45	38	
1.40X1218XC	1	12,000	S87086	CZC903B	386	488	31	G	XX	0.17	1.2	667	7	770	100	45	38	
*** Sub Total(008) *** 4 48,190(Kg)																		
*** Lot Total *** 13 177,720(Kg) PO/Contract No. : 23.11																		
*Post Treatment - XX:No Treatment MG:Cr-FREE AF:FC(Conductivity) CF:Cr-Free for Automobile GR:Galling Resistance Coating CH,CL,CM:Cr Coated PL,PF:Cr-FREEPhosphated EF,GF,SF:Cr-Free PX:Phosphated LH:Inorganic Heat-Resistance Coating LP:Lubricant Pre-phosphated MF:Cr-Free AFT(Phosphated) AF:Resin film for Fuel Tank(Automobile) PP:Pre-Phosphated *OILING - T:Super Light, L:Light, G:General, H:Heavy, S:Super Heavy, D:Dos Oiled, 1:Customer Requirement(L~G), 2:Customer Requirement(G~H)																		

It is certified that the material described below fully conforms to S 513(part 2):2016 Chemical composition and Mechanical properties of the product, as tested in accordance with the Scheme of Testing and Inspection contained in the BIS Certification Marks Licence No. CML-4100045889 are as indicated below against each order No. etc.

(PLEASE REFER TO S 513(part 2):2016 FOR DETAILS OF SPECIFICATION REQUIREMENTS)

Signature

Kim. M. J.

Chief of Cold Rolled Quality Team

본 검사증명서는 원본인 전자시험 정보 포털로부터 출력된 시본입니다. 전자시험의 내용은 현대제철 고객센터에서 확인하실 수 있습니다. (<http://sm.hyundai-steel.com/cscm/login.jsp>)
 This Mill Test Certificate is a copy that has been printed from original electronic document(with original signing).
 You are able to check an original electronic document at hyundai-steel's customer portal. (<http://sm.hyundai-steel.com/cscm/login.jsp>) * QRcode scanner App : 'Qreal'
 사용자 편의를 위해 전자시험정보 및 평가기준 규격 및 시험기 체중량 등 안전성 문제가 발생될 수 있습니다.
 [Caution for User] Damage on products and safety problems may arise if used other than to the spec stated in this Mill Test Certification.