

Git & friends

Paolo Burgio
paolo.burgio@unimore.it



UNIMORE
UNIVERSITÀ DEGLI STUDI DI
MODENA E REGGIO EMILIA

High Performance
Real Time **Lab**



They call me 007

0 LINES ADDED

0 LINES MODIFIED

7 MERGE CONFLICTS



What is a version control?

A system that keeps records of your changes

- › Allows you to revert any changes and go back to a previous state

Enables collaborative development

- › Allows you to know who made what changes and when (with a bug...)

...but not only this!!

- › Forces you to follow well-known development flows
 - (Ever heard of DevOps?)
- › Provides a set of tools to automate testing, integration and deployment
 - (Ever heard of CI/CD?)
- › Provides an easy way to write documentation

*Ultimately, let you focus on coding, coding, coding,
removing all of (what programmers think is) clutter!*



Git



- › “Widestly” adopted version control
- › Based on distributed repositories
- › Created by Linus Torvalds to support Linux kernel development, in 2005

git LISTEN: US

UK: ^{*} /'ɡɪt/ | US: (git)

[definizione](#) | [Sinonimi inglesi](#) | [in spagnolo](#) | [in francese](#) | [Coniugatore \[IT\]](#) | [Conjugator \[EN\]](#) | [nel contesto](#) | [immagini](#)

WordReference English-Italiano Dictionary © 2022:


Principal Translations/Traduzioni principali		
<u>Inglese</u>		<u>Italiano</u>
git <i>n</i>	UK, <i>pejorative, slang</i> (contemptible man) (colloquiale, offensivo) George is such a git!	cretino, idiota, scemo <i>nm</i>



Step 1: let's start simple

"Somewhere"/"on cloud" there is a remote repository with your codebase (called "origin")

- › Users clone this repo on their local machine
- › ...keep their local copy updated by pulling recent changes from the remote
- › And push their modifications





<https://github.com>



The most famous public git repo service


- › Free version + payment version
- › Acquired by BigM in 2016 (tbc)
- › Web console to access

Why do we use this?

- › Preview for slides, past exams, code...
- › Issues!! You now are a team!
- › Let's set up an account

Why GitHub?

- › And not, for instance, GitLab.com?
- › ...or HiPeRT's on-premise GitLab?





Local tools

Baseline: command line tool

- › Comes with most of the GNU/Linux distros
- › (You can always “apt” it)

Under Win, multiple options

- › <https://git-scm.com/> - also, with (very ugly) UI
- › Use WSL
- › Powershell?

Integrated in most commonly used IDEs

- › .but, soon, we'll only work on web tools



Let's start!

Do the following

- › Create a GitHub account
- › Navigate to HiPeRT Lab's page
 - <https://github.com/HiPeRT>
 - <https://github.com/pburgio> for older stuff
- › Clone the repo
 - We will use git over https, but there are also other protocols


```
$ git clone https://<URL>
```



Basic workflow

A project is a sequence of commits

- › They are snapshots of your code in a given moment of time
- › Create with `git commit` (...or some “sugar” tool)
- › The granularity of a commit is on you
 - Typically, small changes of code that at least compiles..



Commits track incremental changes! (`git diff`)

- › Every commit is identified by a hashcode, and has a parent
- › Most recent (...) commit is also called HEAD
- › It is **mandatory** to add a comment to every commit

\$ `git log` to see all information





The git flow

Working with commits

- › Before committing, files must be added to the staging area

```
$ git add <file> <file> && git commit
```

..or...

```
$ git commit -a
```

To check the status of your staging area and commits

```
$ git status
```


Watch out

- › `-a` options does not apply to new files
- › Empty folders are never added by git
- › You can always amend a previous commit, if you forgot to add something

```
$ git commit --amend
```



The git flow (cont'd)





The git flow (cont'd)


- › You can remove/delete files
- › Renaming files means deleting + adding

When you're done, transfer files to the remote repo by

```
$ git push [origin] [master]
```

Always make sure you have the latest version!


```
$ git pull [origin] [master]
```





Pulling and auto-merging

- › Based on the actual time of commit, local history is updated
- › The local codebase is automatically updated (aka: files are merged), including modifications both from local and remote
- › A new commit is created



Let's assume this is the most recent of the two



Merge...and conflicts



- › It is extremely easy to mess things up, if codebases are significantly different!!!
- › Git works at the code line level
 - What if we modify the same code line?
 - Some modern systems track also single words

If there are merge conflicts, the local repo stays in conflicting state

- › Until you solve the conflicts locally, and manually merge them
 - Easier if you do it on IDEs
 - Using appropriate flags in the checkout command

Tips & tricks

- › Frequently pull changes
- › Always make sure your code works by re-running the testing automation
- › Create small commits, “packed” by “working area” (ex: one for the code, one for the makefiles, one for the scripts...)
 - This also forces you to keep the workspace clean and well structured!!



Useful commands

Checkout and (hard or soft) reset

- › To unstage/delete local modifications and/or commits

Revert

- › To switch back to a specific commit

Cherry-pick

- › Commits are incremental. They simply trace the difference against parent commit
- › You can apply a commit/difference also to any other commit (not only parent)
- › By cherry-picking



The history of my project

A typical sw project is structured in quite a rigid way

- › A main branch ("master"), containing the latest released version (with full commit history)
- › Multiple branches that correspond to specific works/subprojects
- › You have total freedom on branches. Company-specific rules apply here
 - "develop", "bugfix/", "hotfix/", "features/", "pb_<SOMETHING>" (initials of the developer)

Once a project is started, you might **never** push onto the master branch

- › You typically fork the master, or the "Development" branch, and then issue a pull request
- › Which is served by the repo Maintainer
 - Typically a sadist, with very limited empathy and sense of humour
 - Sysadmins are good candidates for this role
- › There are access rules and user roles, both at the org and repo level, and also at the branch level, etc



Torvalds is a nice person....

```
On Sun, Sep 18, 2011 at 1:35 PM, Eric Dumazet <eric.dumazet@gmail.com> wrote:
> [PATCH] tcp: fix build error if !CONFIG_SYN_COOKIE
> commit 946cedccbd7387 (tcp: Change possible SYN flooding
> messages) added a build error if CONFIG_SYN_COOKIE=n
```

Christ Eric, you clearly didn't even compile-test this one either.

Which is pretty bad, considering that the whole and only *point* of the patch is to make it compile.

The config option is CONFIG_SYN_COOKIES (with an 'S' at the end), but your patch has 'CONFIG_SYN_COOKIE' (without the S).

Which means that now it doesn't compile when syncookies are *enabled*. I really wanted to release -rc7 today. But no way am I applying these kinds of totally untested patches. Can you guys please get your act Together?

PLEASE?

Stop with the "this might just work" crap. Because -rc7 is just too late to dick around like that.

Linus





...sometimes he really is

```
On Thu, Aug 25, 2011 at 1:21 PM, Arnaud Lacombe  
<lacombar@gmail.com> wrote:  
> On Thu, Aug 25, 2011 at 4:10 PM, Andy Lutomirski  
<luto@mit.edu> wrote:  
>>  
>> Arnaud, can you test this?  
>>  
> All good.  
>  
> Tested-by: Arnaud Lacombe <lacombar@gmail.com>
```

Thanks guys. Applied and pushed out,

Linus





What typically happens...


- › Developers clone a branch from an updated repo
 - Typically, you clone Master, or Develop
- › Anyway: your starting point

```
$ git clone <SOME_URL>
$ git checkout Develop # Assume it exists
$ git branch MY_LOCAL # Create from the Develop
branch
$ git branch -l # To check
$ git checkout MY_LOCAL # Switch to it
```


You can also do all of these together

```
$ git checkout -b MY_LOCAL
```

Maintainer



Developer



■ Master, or Develop branch

■ MY_LOCAL branch






What typically happens...

- › Developer starts his work, producing new commits
- › In a local branch
- › Similarly, remote repo gets some updates for some reason


(You can push your local branch to back up your work on the cloud)

```
$ git push origin MY_LOCAL
```

Maintainer



Developer



■ Develop branch

■ MY_LOCAL branch






What typically happens...

- › When developer is ready, he pulls to update with whatever is in the cloud
- › He's in charge of "making his commits consistent" with the whole story
- › This implies re-testing the whole thing!!


```
$ git pull origin Develop
```

```
$ git merge Develop
```

Maintainer



Developer



■ Develop branch

■ MY_LOCAL branch






What typically happens...

- › After the merge is done, the “final commit” is created
- › And then we can push on the cloud
- › And issue a pull request
 - By email, or by automated tools


```
$ git push origin MY_LOCAL
```

(Remember, you cannot push Master)

Maintainer



Developer



■ Develop branch

■ MY_LOCAL branch







What typically happens...

- › Request is accepted, and modifications apply to the Develop branch
- › Hopefully

Maintainer



Developer



■ Develop branch

■ MY_LOCAL branch






What typically happens...

- › Typically, the “other” branch is then deleted remotely by maintainer
- › The story is now consistent, and a “unique” timeline exist
- › We need to pull the Develop branch one more time, to make my local copy consistent (and delete local branch)


```
$ git pull origin Develop
```

```
$ git branch -d[D] MY_LOCAL
```

Maintainer



Developer



■ Develop branch

■ MY_LOCAL branch





Advanced features



Ignore files

Some folders and files are not useful for your projects!

- › `.vscode`
- › `ROS2:install/ build/ log/ ...`

So, why adding them to the repo?

Add `.gitignore` file in your repo (or in some subfolder)..

- › Specify files to ignore
- › Can use wildcards
- › Comments start with `#`

Remember to commit your
`.gitignore` file!

```
# Ignore VSCode local configurations
.vscode/*

# Ignore ROS2 temp folders
install/*
logs/*
build/*

# Ignore specific file
i_love_maneskin.txt
```



Submodules

You can include a git repo as part of another git repo!

- › Maintainability, scalability, etc...

Syntax

- › ..from the folder where you want to include...
- › `$ git submodule add <REPO-URL>`
- › It will create a `.gitmodules` file in the root folder

```
[submodule "my_module"]
  path = src/my_module
  url = https://github.com/something/my_module.git
```

Where:

- › `url` can also be relative
- › You will also need to commit the `.gitmodules` file
- › Update with `$ git submodule update -init --recursive`



Verifying your identity

You might have noticed that on first commit, Git requested you to set your identity, locally

- › By "simply" setting a global, **unchecked**, name/email tuple

```
$ git commit -m "my first commit"
Author identity unknown

*** Please tell me who you are.

Run

  git config --global user.email "you@example.com"
  git config --global user.name "Your Name"

to set your account's default identity.
Omit --global to set the identity only in this repository.
```


- › **PROBLEM:** you can not guarantee the identity of the committer!!

```
pol@polso:/media/pol/DATA/Unimore/Workspace/ProgSW$ git log
commit 76944a4a8516ab6aba1eafc8b8ed594a7b112127 (HEAD -> master, origin/master, origin/HEAD)
Author: Paolo Burgio <paolo.burgio@gmail.com>
Date:   Mon Feb 23 13:02:54 2026 +0100

    Added 00 and 01

commit 5c85984b70972af134a26cd0f6f7cf9278e0b54b
Author: Paolo Burgio <paolo.burgio@gmail.com>
Date:   Mon Feb 23 13:02:45 2026 +0100

    Updated README.md; fix in FAQ.md
```





Digital signature

Use the GNU Privacy Guard (GPG) - <https://www.gnupg.org/>



Step 1: Generate a signing key

```
$ gpg --gen-key
```

...and check

```
$ gpg --list-keys
```

```
/home/pol/.gnupg/pubring.kbx
```

```
-----
```

```
pub    ed25519 2026-02-25 [SC] [expires: 2029-02-24]
```

```
      0123456789ABCDEF
```

```
uid           [ultimate] Paolo Burgio <paolo.burgio@gmail.com>
```

```
sub    cv25519 2026-02-25 [E] [expires: 2029-02-24]
```

Step 2: Let Git know that you want to sign it with this key

```
$ git config --global user.signingkey 0123456789ABCDEF
```



Digital signature (cont'd)

Step 3: Sign your commits (use the `-S` flag)

```
$ git commit -a -S -m 'Modified 01 to add slides on commit signatures'
```

Then you will see a validated commit





Multiple repos for release/nightly work

You can add as many remote repos you want

- › Origin is the one you cloned from
- › Typically a *private* one for nightly builds

In Git philosophy, all repos are equal!

- › Each of them has a maintainer

Origin (created by default when you clone)



```
$ git remote -v # To list them
```

```
$ git remote add <name> <url>
```



repo1




pburgio



Code like a pro: Continuous Integration, Continuous Deployment

Git enables workflows to automate build, testing, docs...

- › Not covered in the course
- › ..a seminar, maybe?



References



Course website

- › <http://hipert.unimore.it/people/paolob/pub/ProgSW/index.html>

My contacts

- › paolo.burgio@unimore.it
- › <http://hipert.mat.unimore.it/people/paolob/>