

Application Layer Protocols (HTTP.SMTP/POP) Examination Lab


Objectives:

Capture traffic and observe the PDUS for HTTP, SMTP, POP.

Task 1: Observe HTTP traffic exchange between a client and server.

Step 1 – Run the simulation and capture the traffic.

- Enter **Simulation** mode.
- Click on the PC1. Open the **Web Browser** from the **Desktop**.
- Enter **www.bracu.ac.bd** into the browser. Clicking on **Go** will initiate a web server request. Minimize the Web Client configuration window.
- Two packets appear in the **Event List**, a DNS request needed to resolve the URL to the IP address of the web server and an ARP request needed to resolve the IP address of the server to its hardware MAC address.
- Click the **Auto Capture / Play** button to run the simulation and capture events. • Sit tight and observe the packets flowing through the network.



- When the above message appears Click "View Previous Events".
- Click on PC1. The web browser displays a web page appears.

Step 2 – Examine the following captured traffic.

Our objective in this lab is only to observe HTTP traffic.

	Last Device	At Device	Type
1.	PC1	Switch 0	HTTP
2..	Local Web Server	Switch 1	HTTP

- Find the following packets given in the table above in the **Event List**, and click on the colored square in the **Info** column.

(sec)	Last Device	At Device	Type	Info
--	PC1	PC1	DNS	
--	PC1	PC1	ARP	
	PC1	Switch0	ARP	
	Switch0	PC0	ARP	
	Switch0	Switch1	ARP	

- When you click on the Info square for a packet in the event list the **PDU Information** window opens. If you click on these layers, the algorithm used by the device (in this case, the PC) is displayed. View what is going on at each layer.
- Examine the PDU information for the remaining events in the exchange.

For packet 1:

What kind of HTTP packet is packet no. 1?

[HTTP Request packet](#)

Click onto “Inbound PDU details” tab. Scroll down at the end, what do you see?

[HTTP Data:Accept-Language: en-us](#)

[Accept: */*](#)

[Connection: close](#)

[Host: www.bracu.ac.bd](#)

HTTP REQUEST					Bytes
0	4	8	16		
HTTP Data:Accept-Language: en-us					^
Accept: */*					v

For packet 2:

Click onto “Inbound PDU details” tab. Scroll down at the end, what do you see? What kind of HTTP packet is this?

[HTTP Data:Connection: close](#)

[Content-Length: 151](#)

[Content-Type: text/html](#)


[Server: PT-Server/5.2](#)

HTTP RESPONSE					Bytes
0	4	8	16		
HTTP Data:Connection: close					^
Content-Length: 151					v

Task 2: Observe email traffic exchange between a client and email server using SMTP and POP3.

Step 1 – Run the simulation and capture the traffic.

- On the Event List window click “Reset Simulation” button. All previous packets will disappear.
- At the bottom of the Event List window, there is a filter which filters the protocols that we want to see. Click Edit filters. Another window appears showing different protocols, unclick HTTP and click SMTP and POP3.




- Click a space anywhere outside the popup window, then it will disappear. • Your Event List Filter should be as shown below:



2

- Now click on the PC1. Close the web browser window. Open the **Email** from the **Desktop**. A mail browser window will open. Click “compose”, another window appears.



- Fill the window as shown and press send.
- Minimize the client window .
- Click the **Auto Capture / Play** button to run the simulation and capture events. • Sit tight and observe the packets flowing through the network.
- This interaction is between the sender client and its email server.

Step 2 – Examine the following captured traffic.

Our objective in this lab is only to observe SMTP traffic.

	Last Device	At Device	Type
3.	PC1	Switch 0	DNS
4.	PC1	Switch 0	SMTP
5.	Bracu Email Server	Switch 1	SMTP

- Find the following packets given in the table above in the **Event List**, and click on the colored square in the **Info** column.
- Examine the PDU information.

For packet 4::

What is the purpose of this DNS packet?

The purpose of this DNS packet is to resolve the domain name mail.bracu.ac.bd into its corresponding IP address so that PC1 can locate the email server on the network. As shown in the PDU details, PC1 (192.168.10.11) sends a DNS query over UDP destination port 53 to the local DNS server (192.168.10.2), specifically requesting the IP mapping for mail.bracu.ac.bd. PC1 requires this IP address before it can establish a connection and deliver the composed email message (sakib@bracu.ac.bd) via SMTP.

For packet 5& 6::

Explain why SMTP packet was sent to the email server and the server replied with an SMTP packet?

The client PC1 (192.168.10.11) sent an initial SMTP packet to the email server (192.168.10.4) over TCP destination port 25 to push and deliver the newly composed email message (sakib@bracu.ac.bd) using standard SMTP commands. In response, the email server replied with an SMTP packet back to PC1 (192.168.10.11) on destination port 1027 to acknowledge receipt of the email data and return a status code (such as 250 OK), confirming that the server successfully accepted the message and placed it in the delivery queue.

Step 3 – Run the simulation and capture the traffic for POP.

- On the Event List window click “Reset Simulation” button. All previous packets will disappear.
- Now click on the PC0. Open the **Email** from the **Desktop**. A mail browser window will open. Click “**receive**”, minimize the window.
- Click the **Auto Capture / Play** button to run the simulation and capture events. • Sit tight and observe the packets flowing through the network.
- This interaction is between the sender client and its email server.

Step 2 – Examine the following captured traffic.

Our objective in this lab is only to observe POP traffic.

	Last Device	At Device	Type
6.	PC1	Switch 0	DNS
7.	PC1	Switch 0	POP3
8.	Bracu Email Server	Switch 1	POP3

- Find the following packets given in the table above in the **Event List**, and click on the colored square in the **Info** column.
- Examine the PDU information.

For packet 6::

What is the purpose of this DNS packet?

The purpose of this DNS packet is to resolve the domain name mail.bracu.ac.bd into its corresponding IP address so that PC0 can locate and connect to the incoming mail server. As observed in the PDU details, PC0 (192.168.10.10) sends a DNS query over UDP destination port 53 to the local DNS server (192.168.10.2), specifically requesting the IP mapping for mail.bracu.ac.bd. PC0 requires this resolved IP address before it can establish a TCP connection with the mail server to fetch stored emails using the POP3 protocol.

For packet 7&8::

Explain why POP packet was sent to the email server and the server replied with a POP

packet?

The client PC0 (192.168.10.10) sent an initial POP3 packet to the email server (192.168.10.4) over TCP destination port 110 to request and pull the stored email messages from its user mailbox. In response, the email server replied with a POP3 packet back to PC0 (192.168.10.10) on destination port 1025 to transmit the requested email content and return server status responses (such as +OK), allowing PC0 to successfully download and display the email.

•