



TECHNISCHE  
UNIVERSITÄT  
WIEN

DISSERTATION

# Cool Science

ausgeführt am Atominstitut



der Technische Universität Wien  
Fakultät für Physik

unter der Anleitung von  
**Univ.Prof. Dipl.-Ing. Dr.techn. Gorge Hammond**  
und

**Projektass. Dr.rer.nat Rodney MacKay MSc.**  
**Projektass. Dr.techn. Dr.techn. Dr.techn. Dipl.-Ing.**  
**Samantha Carter**

durch

**Daniel Jackson**

Matrikelnummer: 9-18-27-15-21-36

Stadionallee 2  
1020 Wien

Wien, am 23.03.2020

*“The Setesh guard’s nose drips.”*  
TEAL’C

# Contents

<b>1</b>	<b>Electron beam setup</b>	<b>1</b>
1.1	Charatarization of a working CRT . . . . .	1
1.2	High Voltage Power Supply HVPS . . . . .	3
	<b>Todo list</b>	<b>4</b>
	<b>References</b>	<b>5</b>

# 1 Electron beam setup

chapter about electron beam setup

Charakterisierung der intakten CRT -> Frank Charakterisierung HVPS -> Frank

Skizze inkl. externe Power Supplies, wie wird die CRT betrieben?

Heater Wie sieht der Innen aus? CRT Mount ??

## 1.1 Charatarization of a working CRT


HAMEG HM507 oscilloscopes were used for testing purposes. These contain a D14-363GY/123[1] CRT hereinafter abbreviated as ‘D14’, ‘tube’, or ‘CRT’. Although the HM507 has only a bandwidth of 0 MHz to 50 MHz, which is not sufficient for the hyperfine splitting frequency of 461.7 MHz of  $^{39}\text{K}$ , it was used nevertheless because of its simple construction and availability. A schematic view of the device is shown in fig. 1.1 with the back pin arrangement in fig. 1.2.

<http://www.to>

The voltages and currents of the necessary pins to drive the CRT were measured with a voltage probe with an attenuation ratio of and are summarized in table 1.1. It was not possible to measure pin g3 directly. Therefore a HVPS (section 1.2) was used to set a voltage and the beam diameter was observed. The best focus was achieved with a voltage of  $-1.813 \times 10^3 \text{ V}$ .


model number

1:100 or 100:1



**Figure 1.1:** Electrode configuration (from [1])

how to cite figure



**Figure 1.2:** Pin arrangement, bottom view (from [1])

how to cite figure

**Table 1.1:** D14-363GY/123 CRT pin measurements

number	pin	voltage/V	current/ $\mu\text{A}$
1	f	$-1.99 \times 10^3$	$86.6 \times 10^3$
2	k	-2.00	-7.6
3	g1	-2.03	0
4	g3	-	$-1.813 \times 10^3$
5	i.c.	71.7	0.1
6	g5	64.0	7.2
12	g2, g4	71.0	0
14	f	$-1.97 \times 10^3$	$-86.2 \times 10^3$

## <sub>1</sub> 1.2 High Voltage Power Supply HVPS

# Todo list

1

<div> <div></div> <a href="http://www.tobiastiecke.nl/archive/PotassiumProperties.pdf">http://www.tobiastiecke.nl/archive/PotassiumProperties.pdf</a> </div>	<a href="#">1</a>	2
<div> <div></div>                     model number                 </div>	<a href="#">1</a>	3
<div> <div></div>                     1:100 or 100:1                 </div>	<a href="#">1</a>	4
<div> <div></div>                     how to cite figure                 </div>	<a href="#">2</a>	5
<div> <div></div>                     how to cite figure                 </div>	<a href="#">2</a>	6

# References

- [1] Frank Philipse. *D14363GY123*. URL: <https://frank.pocnet.net/sheets/186/d/D14363GY123.pdf> (visited on 03/10/2020).