

Predator SS

SIMPLIFIED STRETCH

SERIAL NUMBER

Please refer to the serial number in all correspondence with Highlight or any Highlight Distributor. This identifies your machine and will help in our ability to quickly and efficiently respond to your needs.

HIGHLIGHT
INDUSTRIES, INC.

OPERATION MANUAL NUMBER: PREDSS_COMBINED / 2025

2694 Prairie St SW • Grand Rapids, MI 49519
(616) 531-2464 • (800) 531-2465 • fax (616) 531-0506
highlightindustries.com • info@highlightindustries.com

Table of Contents

Table of Contents	1
Table of Figures.....	2
General Information	3
Safety Messages	4
Introduction and Warranty	6
Revision History.....	8
Specifications.....	9
Specifications	10
System Overview Prints.....	11
Installation & Adjustments.....	13
Machine Placement	14
Machine Set-Up.....	15
Microprocessor Card	18
Operation Instructions.....	20
Operator Controls	21
Film Loading	24
Machine Operating Instructions	26
Maintenance	27
Preventative Maintenance	28
Maintenance Schedule	31
Trouble-shooting	32
Self Test Troubleshooting	33
Troubleshooting Guide	36
Power Problems	37
Turntable Problems	38
Film Carriage Problems	39
Technical References	40
Recommended Spare Parts	41
Electrical Drawings	42
Mechanical Drawings.....	47
Notes	60

Table of Figures

Figure 1A: Predator SS Low Profile Overview Layout 12

Figure 1B: Predator SS High Profile Overview Layout 12

Figure 2: Bracket in its Shipping Position 16

Figure 3: Bracket in its Operation Position 16

Figure 4: Microprocessor Card for the Predator SS 18

Figure 5: Operator Controls Diagram for the Predator SS..... 21

Figure 6: Film Loading/Threading Diagram 24

Figure 7A: Turntable Belt Adjustment..... 29

Figure 7B: Film Carriage Lift Chain Adjustment 30

Figure 8: Self Test Error Display 34

Highlight Industries, Inc.


Predator SS Turntable Stretch Wrapper Operation Manual

General Information

Safety Messages

For the best result with the Predator Turntable Stretch Wrapper, carefully read this manual and all of the warning labels attached to the equipment before installing and operating it, and follow instructions exactly. Keep this manual for machine reference.

Definitions and Symbols



High Voltage!

This symbol indicates high voltage. It calls your attention to items or operations that could be dangerous to you or other persons operating the equipment. Read the message and follow the instructions carefully.



Warning!


This symbol indicates a potentially hazardous situation which, if not avoided, can result to bodily injury, or serious damage to the product.



Notes


This symbol indicates an area or subject of special merit, emphasizing the equipment's capabilities, common errors in operation or maintenance, or other special instructions that can provide benefits to users.

General Precautions – Read These First!




High Voltage!

Disconnect AC input power before checking components, performing maintenance, cleaning up, and when the machine is not in use. Do NOT connect or disconnect wires and connectors while power is applied to circuit.




High Voltage!

Wiring work should be carried out only by qualified personnel. Otherwise, there is a danger of electric shock or fire.



High Voltage!

The user is responsible for conforming to all applicable code requirements with respect to grounding all requirements. Do NOT use extension cords to operate the equipment.



High Voltage!

Motor control equipment and electronic controllers are connected to hazardous line voltages. When servicing drives and controllers, there may be exposed components with housings or protrusions at or above line potential. Extreme care should be taken to protect against shock.



Warning!

Loose clothing must NOT be worn while the machine is in operation. Stay clear of moving parts while the machine is running.

Introduction and Warranty

Introduction

Thank you for your purchase of a *Predator SS* Turntable Stretch Wrapper! Designed for the high volume industrial user the Predator SS will stretch wrap any load to the maximum stretch level of any film with full independent control of the film force. This allows even light unstable loads to be wrapped at the lowest possible cost and the maximum load holding force.

Limited Warranty

Highlight Industries, Inc. warrants its Predator manufactured by it, and sold pursuant to this order, will be of merchantable quality, free from defects in material and workmanship as determined at the date of shipment, by generally recognized, applicable and accepted practices and procedures in the industry, for a period of three (3) years from the Highlight invoice date, under normal use and service.

When the Purchaser gives Highlight written notice of any alleged defect within the applicable warranty period, Highlight will, at its option repair or replace the same free of charge F.O.B. its manufacturing plant, installation not included. Equipment replaced under the warranty shall have the same warranty as new equipment but does not extend the warranty of the original equipment.

Satisfaction of this warranty, consistent with other provisions herein, will be limited to the replacement or repair or modification of, or issuance of a credit for, the equipment involved, at Highlight's option.

Highlight neither assumes nor authorizes any person to assume for it any other obligation in connection with the sale of Highlight's equipment.

This warranty shall not apply to any equipment which has been repaired or altered by unauthorized personnel in any way so as to, in the judgment of Highlight, affect serviceability, or which has been subjected to misuse, negligence, accident, or to equipment made by Highlight which has been operated in a manner contrary to Highlight's instructions.

In no event regardless of the cause, shall Highlight be liable for penalties or penalty clauses of any description or any damages resulting from loss of profits, use of products or for any incidental indirect or consequential damages, even if advised of the possibility of such damages. This limitation of Highlight's liability will apply regardless of the form of action, whether in contract or tort, including negligence. Any action against Highlight must be brought within twelve (12) months after cause of action accrues.

"This warranty in lieu of all other warranties whether expressed, implied or statutory including implied warranties of merchantability of fitness or extends only to the buyer or customer purchasing from Highlight Industries, Inc or an authorized distributor."

About This Document

The purpose of this manual is to provide you with information necessary to install, operate, troubleshoot, and maintain the Predator SS Turntable Stretch Wrapper. The audience for this manual should have basic knowledge of mechanical and electronic components, standard electrical wiring practices, and schematics symbols.

To guarantee safe operation of the equipment, carefully observe the safety messages throughout this manual. Keep this operating manual and distribute it to all users for reference.

Application Assistance

If any assistance is desired, contact the distributor from whom you have purchased the unit, or call the number listed on the bottom of each page of this manual. To receive quick and proper technical support for the equipment you have purchased, please be prepared to provide the following information:

1. Machine Serial Number
2. Date of Purchase
3. Symptoms of any problems

Revision History

Revision	Revision Comment	Date of Revision
	Initial Release	2025
A	Updated Electrical and Mechanical Parts List	2025

Highlight Industries, Inc.

Predator SS Turntable Stretch Wrapper Operation Manual

Specifications

Specifications

Machine Dimensions

	Low Profile	High Profile
Length (inch)	98	98
Width (inch)	60	48
Height (inch)	91/130	91/130
Turntable Diameter (inch)	60	48 x 48
Turntable Height from Floor (inch)	3.25	13.5
Operation Space (inch)	105 x 75 x 120	105 x 60 x 120
Maximum Pallet Size (inch)	52 x 52 x 72	52 x 52 x 72
Shipping Weight (lbs.)	1050	1050

Electrical Specifications

- 120VAC, 60Hz, Single Phase, 15Amp

Turntable

- 4,000 lbs Maximum Turntable Load Capacity
- 12 RPM Maximum Turntable Speed
- 20-30 Loads Per Hour

Film Carriage

- Adjustable Raise and Lower Speeds
- Automatic Package Height Detection

Film Delivery

- Infinite/Manual Film Force Adjustment
- 10 Inch Diameter Roll Capacity
- 20 Inch Height Roll Capacity (30 Inch Optional)

System Overview Prints

**Note**

Shown below are STANDARD assembly drawings. It may not reflect your purchased system, especially when optional items are added. Refer to the Technical References section of the manual for more detailed information.





Figure 1A: Predator SS Low Profile Overview Layout




Figure 1B: Predator SS High Profile Overview Layout

Highlight Industries, Inc.

Predator SS Turntable Stretch Wrapper Operation Manual

Installation & Adjustments

Machine Placement

Receiving and Inspections

The Predator Turntable Stretch Wrapper has gone through quality control tests at the factory before shipment. Upon receiving, please do the following:

1. Inspect the entire machine for visual damage during shipment. If found, immediately report this damage to the trucking line. *Highlight Industries, Inc.* has taken every precaution during the packaging and loading of this equipment, however, it is YOUR RESPONSIBILITY to inspect for damage before installation.
2. Make sure the part or serial number indicated on the machine corresponds with the part number of your order.

Positioning of the Machine

Place the Predator Turntable Stretch Wrapper close to an area where you will be wrapping your loads. Make sure that there is sufficient room to load/unload the machine and that you do not stretch the power cable. Remember, you will need to plug the machine in to a 120VAC, 15-Amp outlet.

Floor Weight Bearing/Stress Tolerance

The floor must be able to bear the weight of the machine, the weight of the maximum load, plus a safety factor. The floor must also be able to tolerate the stress of the machine's operation. If the fork trucks will operate on the same weight bearing area, add the weight of the trucks to the weight bearing stress tolerance requirements.

The Predator can be installed on any type of floor constructions that meets the weight bearing and stress tolerance requirements.



Warning!

Highlight does not recommend anchoring machines to the floor unless there is a critical space concern or other concern about the machine moving when bumped (such as near an aisle way or other machine). Allowing the machine to move slightly when bumped greatly reduces the likeliness of damage as it prevents the impact from going directly into the turntable/frame.


Machine Set-Up

Unpacking and Moving the Machine

It is very important to read all instructions before undertaking any of these steps. The following steps should help achieving a safe and quick machine set-up.

1. Place the skidded machine close to the designated wrap area. Remove all shipping fasteners holding the machine to the pallet. The machine may be crated with the tower tilted down with the motor cover front carriage roller removed for shipping purposes.
2. Place the forks of the forklift through the tubes provided on the base of the machine, remove the machine from the shipping skids, and place it in the designated wrap area.
3. If the OPTIONAL ramp (Part Number #600038) is purchased for a **low profile** machine:

Select a ramp position as illustrated below. The ramp can be positioned anywhere in a 180° rotation around the front of the turntable. There should be ¼" gap between the turntable and the ramp. The ramp should be fully supported by the floor and anchored to the floor.



4. When a machine is ordered with a 110" extended tower or a scale package, the carriage photo eye bracket will need to be unbolted from its shipping position (Figure 2) to its operating position (Figure 3).



Figure 2: Bracket in its Shipping Position



Figure 3: Bracket in its Operation Position



Warning!

It is very important that the machine be leveled. Uneven floors will cause premature turntable support roller failure.

Power and Control Wiring Checks

1. Using a volt meter, check the AC voltage coming to the machine and insure the proper voltage is present.
2. Make sure the Emergency Stop button on the operator panel is fully pressed in. Turn the disconnect switch to the ON position. Power should be applied to the drive board, operating touch-panel, photoelectric sensors, switches, and LED's.
3. Press the Emergency Stop button. Make sure all machine power is completely removed when the Emergency Stop button is depressed. Pull the Emergency Stop button out to resume.
4. Open the electric control box. Make sure all machine power is completely removed when the electrical control box is open. Close the electrical control box to resume.
5. Trip the carriage foot security bar. Make sure all machine power is completely removed when the carriage foot security bar is tripped. Clear the bar to resume.



Warning!

Ensure that the Emergency Stop button light is ON when the button is pushed in and OFF when the button is pulled out.

Microprocessor Card

Microprocessor Card Description




Figure 4: Microprocessor Card for the Predator SS

S1: Operating voltage selector (220 VAC or 110 VAC)

Connector P1: Turntable/Film Carriage Relay Output

Connector P2: Power Input

Connector P3: Operator Panel Input

Connector P4/P10: Transformer Input/Output

Connector P5: Turntable Proximity Sensor Input

Connector P7: Film Carriage Limit Switches Input

Relay 1: Film Carriage Down

Relay 2: Film Carriage Up

Relay 3: Turntable/Film Carriage Stop

Relay 4:	Power Input
Relay 5:	Turntable Running
Fuse 1:	Carriage Motor (5 Amp)
Fuse 2/2A:	Power Input (10 Amp)
Fuse 3:	Turntable Motor (8 Amp)
Fuse 6:	Transformer Input (1 Amp)
Fuse 7:	Transformer Output (1 Amp)
LED 1 is ON:	Film Carriage Motor fuse is blown
LED 2 is ON:	Turntable Motor fuse is blown
LED 3/3A is ON:	Power Input fuse is blown
LED 7 is ON:	Cycle starts
LED 8 is ON:	Film Carriage is moving up
LED 10 is ON:	Film Carriage is moving down
LED 11 is ON:	Turntable is rotating
LED 15 is ON:	Start Button is pushed
LED 16 is ON:	Pause Button is pushed
LED 19 is ON:	Package Height Photo Sensor is unblocked
LED 23 is ON:	Carriage Max Up Limit Switch is not tripped
LED 24 is ON:	Carriage Max Down Limit Switch is tripped
LED 25 is ON:	Emergency Stop Button is not pushed
LED 26 is ON:	Turntable Home/Count proximity switch is blocked
LED 36 is ON:	Transformer Input/Output is blown
VR1:	Film Carriage Max Speed setting
VR2:	Turntable Max Speed setting

Replacing Microprocessor Card

1. Turn the disconnect switch to **OFF** position.
2. Removed the old microprocessor card by pulling all connectors off and loosening the four mounting screws.
3. Install the new microprocessor card; connect all connectors and tighten the mounting screws.
4. Turn the disconnect switch to **ON** position. The display should show “- -“. If not, check all connectors and fuses again.

Highlight Industries, Inc.

Predator SS Turntable Stretch Wrapper Operation Manual

Operation Instructions

Operator Controls

The operator panel for the Predator SS is shown and described as follows:
















Figure 5: Operator Controls Diagram for the Predator SS

	FUNCTION
	This displays the system information: EO = Emergency Stop condition -- = System is normal -- Blinking = PWS is bad or both carriage up and down are on A = Mode A is selected B = Mode B is selected CO = Continue operation by pushing START button S = System is in Manual
	This displays the selected wrapping mode: <i>Mode A</i> = The LED light on the button's upper left is on. In Mode A, the bottom wrap is applied first, and then the top wrap follows. The film carriage comes down to its home position after wrapping cycle is finished. <i>Mode B</i> = The LED light on the button's upper right is on. In Mode B, after a bottom to top wrapping is completed, the carriage stays on the top. The START button flashes at this point. To resume the operation, push START. When the carriage reaches the bottom, the START button goes off. Push START button again to begin a new cycle.
	The TURNTABLE JOG button allows you to manually operate the turntable. When this button is pushed, the light on the button's upper left is on. Push START button to run the table. Pushing the button again will stop the turntable, and the light will turn off. This button may be used in conjunction with the CARRIAGE JOG button.
	The CARRIAGE JOG button allows you to manually operate the carriage. When this button is pushed, one of the lights on the button's upper right or left is on. The upper left light indicates that the carriage will go up when the START button is pushed. Conversely, the upper right light indicates the carriage will go down when the START button is pushed. To pause the operation, simply push this button again. Both indicator lights will go off. This button may be used in conjunction with the TURNTABLE JOG button.
	Push this RESET button, followed by a START button, to reset the system. The turntable will return to its home position, and the carriage will lower all the down.
	Push this TOP WRAPS button to select the number of top wraps desired (0 to 9).

	Push this BOTTOM WRAPS button to select the number of bottom wraps desired (0 to 9).
	Turn the CARRIAGE SPEED adjustment knob clockwise to increase, and counterclockwise to decrease the carriage speed.
	Turn the TURNTABLE SPEED adjustment knob clockwise to increase, and counterclockwise to decrease the turntable speed.
	The BANDING button is used for applying multi-layer reinforcing wraps in automatic or manual mode. Push and hold this button: the carriage will stop raising/lowering. When released, the carriage will resume its movement.
	The EMERGENCY STOP button stops the turntable in the event of emergency. This will <i>NOT</i> stop the turntable instantly. The turntable will coast to a stop, depending on the load's weight, after this button is pushed.
	This switches the main power ON or OFF.

**WARNING!**

The FOOT SAFETY BAR, located underneath the film carriage, works only when the machine is ON. When the bar is activated, the main power will shut OFF. Releasing the bar will re-activate the main power. Push START button to resume the operation.

Film Loading

Follow the procedure below to thread the film onto the Film Carriage.

**Warning!**

Be sure the Emergency Stop button is pressed before threading the film and while the film is being threaded.

1. Raise top core holder, place the film on the film mandrel and close top core holder
2. Set the Stretch Handle to the **OFF** position to release the tension. (See figure below)





Figure 6: Film Loading/Threading Diagram

3. Follow the *Film Feed Diagram* and thread the 6-foot film tail ALL THE WAY through the rollers.



4. After threading, rotate the Stretch Tension Knob clockwise to increase film tension; or counterclockwise to decrease film tension.
5. Attach the film securely to the pallet. Tying the end of the film in a knot often helps secure the film to the pallet.
6. Set the Stretch Handle to the **ON** position before beginning a wrap cycle

**Note**

The Stretch Tension numbers (0 to 100) DO NOT indicate the stretch percentage of your film. The numbers are used for reference only.

Note

If top core does not sit level on top of film roll, loosen bolts holding the top core bracket and adjust height thru the slots in the bracket. Tighten bolts before operating the equipment.

Machine Operating Instructions

Normal System Start-Up

After the machine has been positioned and supplied with proper voltage, you are ready to begin operating. Read thoroughly and follow these steps to operate your system:

1. Place product on the turntable
2. Make sure the film carriage is situated at the max down position.
3. Thread the film as instructed, and attach it to the product.
4. Set the desired number for top and bottom wrap counts.
5. Select wrapping mode “A” or “B”.
6. Press the “Start button to initiate cycle.

Stop Condition

Follow the procedure below in the event of an emergency.

1. Press the “STOP” button. This cancels the current wrapping cycle and immediately stops the system.
2. Correct the problem.
3. Pull the “STOP” button out, and then perform normal system start-up procedure.



Note

After pressing the “E-STOP” button, wait for at least 60 (sixty) seconds before pulling the button back out. This will allow the microcontroller card to completely turn off.

Applying Reinforcement Wraps

Automatic operation can be paused in order to apply reinforcement wraps to an additional top sheet or corner boards on the product. Follow the procedure below.

1. Press the “START” button as normal to initiate cycle.
2. As the carriage travels up, press the “Banding” button. The carriage will stop and reinforcing wraps will be applied.
3. Letting go of the “Banding” button will resume the cycle.

Highlight Industries, Inc.

Predator SS Turntable Stretch Wrapper Operation Manual

Maintenance

Preventative Maintenance

As with all machinery, proper attention and maintenance is the key to long component life, maximum performance, and safe operation. By spending a few minutes reading and following these preventive measures, you should reduce the downtime and prolong the life of your system.

It is important to understand that these maintenance schedules are minimum recommendations. *Highlight Industries, Inc.* cannot possibly know, evaluate, or advise the various trades in all schedules of periodic maintenance. Accordingly, anyone who maintains or services a stretch wrap machine must first satisfy himself/herself as to the schedules of preventive maintenance based on cycling operation and environmental locations.

**Warning!**

All maintenance operations require the equipment to be powered down and locked out for personnel safety.

Lock-out/ Tag-out Procedures

Be sure that anyone performing any type of maintenance on this equipment is familiar with and is adhering to the lock-out/tag-out procedures set forth by the General OSHA or the State OSHA guidelines.

Visual Checks

Visual checks should be conducted at least once per month:

1. Keep the machine and surrounding area as clean as possible, especially near moving components.
2. Check for loose hardware, especially set screws located in: sprocket hubs, bearing hubs, and flanges.
3. Check for oil leaks around the speed reducers.
4. Check for dry seals at the bearings.
5. Check for chain wear and proper tension on the power roller stretch sprockets. The correct amount of chain tension can be checked by pulling the chain taut and having 3/8" slack.
6. Check for loose electrical connections and for frayed cords and cables. Replace immediately any damaged cords and cables.

Turntable Belt Adjustment (Low Profile Only)

Refer to the figure below to adjust the turntable belt. First, loosen the four motor flange (M10) screws. Turn the (M10) bolt on the adjuster tab until the belt is tensioned. Retighten the four motor flange screws.




Figure 7A: Turntable Belt Adjustment

Film Carriage Lift Chain Adjustment

Refer to the figure below to adjust the film carriage lift chain. First, loosen nut (M12) on the adjustment bracket. Turn the bottom bolt until desired tension is achieved. Retighten nut (M12). Note that the driving chain and adjustment bracket should be parallel with the movable pulley base.




Figure 7B: Film Carriage Lift Chain Adjustment

Sprockets and Chains

All sprockets should be inspected for wear, and chains should be checked for proper tension and lubrication on a periodic basis. Failure to do so will lead to premature sprocket failure. Any general-purpose chain lube should be sufficient for lubrication. Replace chain guards when preventative maintenance is complete.

Maintenance Schedule

Part	Schedule	Service With
Carriage Lift Belt	Check and tighten every six months.	
All serviceable bearings	Initially first 1,000 cycles; every 10,000 cycles thereafter.	Mobil EP-1 grease

**Note**

For additional maintenance information about specific components on the machine, refer to the components operation manuals shipped inside the main enclosure.

Highlight Industries, Inc.

Predator SS Turntable Stretch Wrapper Operation Manual

Trouble- shooting

Self Test Troubleshooting

**Warning!**

Make sure that only qualified personnel will perform inspection, troubleshooting, and part replacement.

An operator may check the status of the machine by running one of the self-tests. If the procedures are carried out properly, the INFO screen will display the location of the problem.

To run Self-test A, follow the procedure below:

1. Turn the turntable and carriage speed adjustment knobs to maximum (clockwise) position.
2. Put a load on the turntable (about 3-feet tall).
3. While holding down the **TURNTABLE JOG** and **CARRIAGE JOG** buttons, turn the main disconnect switch ON.
4. Release the buttons after the screen shows “EE”
5. Push the **START** button. The machine will run the test, which takes approximately two minutes.
6. The screen will display the alarm code. Refer to the table below for code information.

Display	Possible Problem Location(s)
E1	Film carriage max upper limit switch
E2	Film carriage max down limit switch
E3	Turntable count/home proximity switch
E4	Package height photo sensor

To run self-test B, follow the procedure below:

1. Turn the turntable and carriage speed adjustment knobs to maximum (clockwise) position.
2. Put a load on the turntable (about 3-feet tall).
3. While holding down the **TOP WRAPS** and **BOTTOM WRAPS** buttons, turn the main disconnect switch ON.

4. Release the buttons after the screen shows “99”
5. The limit switches and sensors should be on during operation. The screen will display the alarm code that gives information about alarm code.





Figure 8: Self Test Error Display

Display	Possible Problem Location(s)
A1	Film Carriage Safety Bar
	EMERGENCY STOP button
	Electrical enclosure safety switch
B1	Film carriage max upper limit switch
C1	Film carriage max down limit switch
D1	Turntable count/home proximity switch
E1	BANDING push button
F1	START push button
G1	Package height photo sensor
A2	START light
B2	Turntable motor
C2	Carriage motor


Additional INFO Messages

	During normal machine operation, the following messages might be displayed: EO = Emergency Stop condition - - = System is normal - - = Blinking = Power supply is bad or both carriage up and down limit switch inputs are on A = Mode A is selected B = Mode B is selected CO = Continue operation by pushing START button S = System is in Manual
---	--

Troubleshooting Guide

**Warning!**

Make sure that only qualified personnel will perform inspection, troubleshooting, and part replacement.

**High Voltage!**

Disconnect all power including external control power that may be present before servicing the machine. Wait 3 (three) minutes for the microcontroller card to fully discharge. The machine INFO and/or LED's are not accurate indicators of the absence of voltage.

The diagrams in this section will guide you in identifying typical problems while operating the Predator Turntable Stretch Wrapper, and provide you with corresponding solution(s). Problems are divided in reference to the machine functions: power, turntable, and film carriage.

If further assistance is required, contact the distributor from whom you have purchased the equipment, or call the number listed on the bottom page of this manual. To receive quick and proper technical support, please be prepared to provide the following information:

1. Machine serial number
2. Date of purchase
3. Symptoms of any problem

Power Problems

Problem	Possible Cause	Possible Solution
The machine does not power up. (INFO screen is blank)	The machine is not plugged in.	Plug the machine into a 120VAC, 20A outlet.
	The Main Disconnect is turned off.	Turn the Main Disconnect on.
	A fuse is blown.	Replace the fuse(s).
	The power supply has malfunctioned.	Ensure fuses F6 and F7 are not blown. Replace the power supply (transformer card).
	Power to the machine is not correct	Use a voltmeter to check that the machine is receiving 120VAC.
The INFO display shows E0	The Emergency Stop button is pressed.	Turn the breaker back on, or replace if necessary.
	The film carriage foot safety switch is tripped.	Remove any obstructions and check that the switch is working properly.
	The electrical enclosure door switch is open.	Ensure the door is closed and that the safety switch is made.
The INFO display is flashing '- -'	The power supply has malfunctioned.	Ensure fuses F6 and F7 are not blown. Replace the power supply (transformer card).
	The carriage raised/lowered limit switches are both tripped.	Ensure there are no obstructions and that the switches are working properly.

Turntable Problems

Problem	Possible Cause	Possible Solution
The turntable does not rotate manually.	The Start Button was not pressed.	The Start button needs to be pressed at the same time as the turntable job button to activate manual mode.
	The Turntable speed potentiometer is not set high enough.	Adjust the turntable speed towards 100%.
	The turntable is mechanically restricted.	Check the condition of the motor, chain, and rollers under the turntable. Replace as necessary.
	The turntable speed potentiometer has failed.	Use a multi-meter to check the resistance of the potentiometer.
	A fuse on the microcontroller card has blown.	Check fuses and replace as needed.
	The motor is not wired correctly.	Check wiring to the motor and replace as necessary.
The turntable does not stop at home.	The Turntable Home proximity switch is malfunctioning.	Check the wiring to the proximity switch and that it is adjusted properly (only 8mm sensing range). Replace as necessary.

Film Carriage Problems

Problem	Possible Cause	Possible Solution
The Film Carriage does not Raise or Lower manually or in the wrap cycle.	The Start Button was not pressed.	The Start button needs to be pressed at the same time as the carriage raise/lower button to activate manual mode.
	The Carriage Banding button is tripped.	Ensure the banding button is not tripped and that the button is working properly.
	The Film Carriage Raised/Lowered limit switch is malfunctioning.	Ensure that the carriage limit switch is clear of any obstruction and moves smoothly. Check wiring to the limit switch and replace as necessary.
	The film carriage speed potentiometer is not set high enough.	Adjust the speed potentiometer towards 100%.
	The film carriage speed potentiometer has failed.	Use a multi-meter to check the resistance of the potentiometer.
	A fuse on the microcontroller card has blown.	Check fuses and replace as needed.
	The motor is not wired correctly.	Check wiring to the motor and replace as necessary.
The Film Carriage rises some, but does not rise to the top of the package.	The Product Height Detection photo eye is positioned too high.	Slide the Product Height Detection photo eye lower.
	The Product Height Detection photo eye does not see the load.	Black or clear loads may require an optional advanced sensor instead of the standard diffuse sensor.
		Check wiring to the sensor.
		Replace the sensor as necessary.
	The Product Height Detection photo eye is not adjusted properly.	Adjust position or sensitivity of the sensor.
The Film Carriage rises too far above the package.	The Product Height Detection photo eye is positioned too low.	Slide the Product Height Detection photo eye higher.
	The Product Height Detection photo eye is not adjusted properly and always sees a 'package'.	Adjust the sensitivity of the sensor (see the Photo Sensor Adjustments and/or Pre-Operation Adjustments section).

Highlight Industries, Inc.

Predator SS Turntable Stretch Wrapper Operation Manual

Technical References

Recommended Spare Parts

Low Profile:

The table below provides the recommended spare parts list for the Predator SS **Low Profile** Turntable Stretch Wrapper.

Machine Section	HLI Part Number	Item Description	Qty.
Turntable	300013	BELT B-172	1
Turntable	500010	PLASTIC SUPPORT WHEEL	6
Turntable	300037	TURNTABLE DRIVE MOTOR – 1/4HP (60" DIA TURNTABLE)	1
Turntable	300031	TURNTABLE DRIVE REDUCER (60" DIA TURNTABLE)	1
Tower	300038	CARRIAGE LIFT MOTOR – 1/4HP	1
Tower	300030	CARRIAGE LIFT REDUCER	1


High Profile:

The table below provides the recommended spare parts list for the Predator SS **High Profile** Turntable Stretch Wrapper.


Machine Section	HLI Part Number	Item Description	Qty.
Electrical	401362	FUSE, 250 VAC, 1 AMP, GMA	2
Electrical	403261	FUSE, 250 VAC, 10 AMP, GMA	2
Electrical	401365	FUSE, 250 VAC, 5 AMP, GMA	2
Electrical	404648	FUSE, 250 VAC, 8 AMP, GMA	2
Electrical	400639	MICRO SWITCH YZ-8108	1
Turntable	301869	SWIVEL CASTER	1
Turntable	305285.2	DRIVE CASTER	1
Turntable	307018	TURNTABLE DRIVE MOTOR –1/2HP	1
Turntable	306934	TURNTABLE DRIVE REDUCER	1
Tower	300038	CARRIAGE LIFT MOTOR – 1/4HP	1
Tower	300030	CARRIAGE LIFT REDUCER	1

Electrical Drawings


Electrical Schematics




Electrical Schematics (continued)



Enclosure Layout



Sensor Layout (drawing for representational purposes only)




Electrical Parts List

Machine Section	HLI Part Number	Item Description	Qty.
1	401495	MICROPROCESSOR CARD	1
2	401361	TRANSFORMER CARD	1
3	401362	FUSE, 250 VAC, 1 AMP, GMA	2
4	401363	EPROM	1
5	403261	FUSE, 250 VAC, 10 AMP, GMA	2
6	401365	FUSE, 250 VAC, 5 AMP, GMA	2
7	401366	RELAY LY2 DC24V	5
8	404648	FUSE, 250 VAC, 8 AMP, GMA	1
11	401367	BUTTON WHITE	1
12	401368	BUTTON SEAT CONTACTOR Nox1	1
13	400609	AUTO RUN GREEN LAMP: COVER	1
	400610	SEAT	1
	400611	LIGHT	1
14	401371	KNOB RN-99F,ø6.4	2
15	400649	VARIOUS RESISTOR 5K	2
16	401372	EMG. SWITCH	1
17	401373	BUTTON SEAT CONTACTOR NCx1	1
18	401374	MAIN POWER SWITCH	1
21	400639	LIMIT SWITCH TZ-8108	2
22	400636	LIMIT SWITCH TM-1307	1
23	404168	Prox Switch, 18mm, 8mm Range, 4 WIRE, 10-30VDC, NO/NC NPN	1
23a	403867	Cable, M12, 5-W Straight Female, 4-Meter Plug, Shielded	1
24	400637	LIMIT SWITCH TZ-7110	1
25	400643	PHOTO SENSOR A3R-2MX(OPTION)	1
N/S	310008	BUTTON MEMBRANE LABEL FOR CONTROL PANEL	1
N/S	403409	CARRIAGE CONTROL CABLE – STD	1
	403721	CARRIAGE CONTROL CABLE – 110	

Mechanical Drawings

Low Profile Turntable Frame Assembly




Low Profile Turntable Parts List


Machine Section	HLI Part Number	Item Description	Qty.
1	300037	MOTOR VP3310D 1/4HP →1.5M	1
	300040	MOTOR VP3330D 1/2HP →1.8M	1
2	200091	SCREW M8X20L & W.	4
3	200092	SCREW M10x20L & S.W. & W.	4
4	300031	SPEED REDUCER 1/4HP →1.5M	1
	300032	SPEED REDUCER 1/2HP →1.8M	1
5	300002	KEY 5X20L	1
6	200093	SCREW M10x25L & S.W. & W.	4
7	500034	MOTOR ADJUST SEAT →1.5M	1
	500035	MOTOR ADJUST SEAT →1.8M	1
8	500014	MOTOR PULLEY 4"22 →1.5M	1
	500015	MOTOR PULLEY 4"28 →1.8M	1
9	207303	SET SCREW, M8 x 10L	2
10	200095	SCREW M10x70L	1
11	200077	SCREW M6x12L & W.	1
12	500083	MOTOR BOX FIX PLATE	1
13	500087	PIN	2
14	300006	RING STW-10	2
15	600000	TURNTABLE SEAT 1.5M	1
	600001	TURNTABLE SEAT 1.8M	1
16	700060	SUPPORT ROLLER ASSEMBLY – 1.5M	12
		SUOPRT ROLLER ASSEMBLY – 1.8M	14
16a	300009	RING STW-17	48
16b	300021	BEARING 6203ZZ →1.5M	24
	300021	BEARING 6203ZZ →1.8M	28
16c	500010	SUPPORTING PLASTIC WHEEL →1.5M	12
	500010	SUPPORTING PLASTIC WHEEL →1.8M	14
16d	500009	SUPPORTING PLASTIC WHEEL SHAFT →1.5M	12
	500009	SUPPORTING PLASTIC WHEEL SHAFT →1.8M	14
20	300009	RING STW-17	1
21	300021	BEARING 6203ZZ	2
22	500011	BELT LOCK PULLEY	1
23	500012	BELT LOCK PULLEY SHAFT	1
24	200078	SCREW M6x16L	3

25	200098	SCREW M3x25L & W.	2
26	400641	PROXIMITY SWITCH PS-05N-3M	1
27	500013	PROXIMITY SWITCH FIX SEAT	1
28	200103	SCREW M4x20L	2
29	200128	NUT M5	6
30	300013	BELT B-172 →1.5M	1
	300014	BELT B-183 →1.8M	1
31	200113	SCREW M8x25L	4
32	500004	TURNTABLE PLATE 1.5M	1
	500005	TURNTABLE PLATE 1.8M	1
33	200084	SCREW M8x20L	4
34	500007	WHEEL 22"	1
35	500006	LOCATING PLATE	1
36	200108	SCREW M5x10L & W.	4
37	500008	PULLEY FIXING PLATE	1
38	500085	BELT PULLEY SEAT RING	1
39	300012	RING RTW-42	1
40	500084	BELT PULLEY SHAFT	1
41	300018	BEARING 6004ZZ	2
42	300010	RING STW-20	1
43	500086	BELT PULLEY BEARING SEAT	1
44	200088	SCREW M10x16L	4
45	200100	SCREW M4x8L & W.	4
46	500081	MOTOR COVER →1.5M	1
	500082	MOTOR COVER →1.8M	1
47	600028	TURNTABLE MOTOR BOX 1.5M	1
	600029	TURNTABLE MOTOR BOX 1.8M	1
48	200100	SCREW M4x8L & W.	2
49	600038	RAMP (FOR 60" TURNTABLE - NOT SHOWN)	OPT
50	600039	RAMP PORCH – 24" (FOR 60" TURNTABLE - NOT SHOWN)	OPT
51	602297	RAMP PORCH – 48" (FOR 60" TURNTABLE - NOT SHOWN)	OPT

High Profile Turntable Frame Assembly



Tower Assembly




Tower Parts List

Machine Section	HLI Part Number	Item Description	Qty.
1	500492	TOWER – STD	1
	500317	TOWER – 110	1
2	300038	ELEVATOR UNIT MOTOR VP3310D	1
3	200091	SCREW M8x20L & S.W.	4
4	200090	SCREW M10x25L & S.W. & W.	5
5	300030	ELEVATOR UNIT SPEED REDUCER VTM-40	1
6	200085	SCREW M8x25L & S.W. & W.	4
7	500135	CHANNEL SUPPORT	2
8	200078	SCREW M6x16L & S.W. & W.	4
9	500136	CHAIN WHEEL COVER - STD	1
	500290	CHAIN WHEEL COVER - 110	1
10	500041	UP & DOWN CHAIN WHEEL (LOWER) 11 TEETH	1
11	200099	SCREW M4x6L & W.	2
12	300020	BEARING 6202-2NR	1
13	500102	SPEED REDUCER BEARING SEAT	1
14	200076	SCREW M6x10L & W.	2
15	200120	SCREW M6x8L	1
16	300000	PIN Ø4X8	1
17	200082	SCREW M8x12L	2
18	500103	BEARING ADJUST SEAT	1
19	200077	SCREW M6x12L & W.	4
20	500003	UPPER CHAIN WHEEL SHAFT	1
21	300017	BEARING 6002ZZ	2
22	500089	UPPER CHAIN WHEEL	1
23	500093	RING	2
24	300008	RING STW-15	2
25	501864	ADJUST BAR WASHER	1
26	200140	NUT M12	1
27	300049	CHAIN - STD	1
	500488	CHAIN - 110	1
28	500025	ELEVATOR UNIT CHAIN SCREW SHAFT	2
29	200147	WASHER M12	4
30	500092	CHAIN ADJUST SEAT	1

31	200133	NUT M12	3
32	300007	RING STW-12	6
33	300016	BEARING 6001ZZ	8
34	500090	UP & DOWN DRIVING WHEEL	4
35	500091	UP & DOWN DRIVING WHEEL SHAFT	4
36	500040	CHAIN WHEEL SEAT	1
37	200131	NUT M10 & S.W. & W.	6
38	600008	ELEVATOR UNIT SEAT (INNER)	1
39	200084	SCREW M8x20L & S.W. & W.	2
40	200083	SCREW M8x16L & S.W. & W.	6
41	500138	LIMIT PLATE	2
42	200125	SCREW M6x16L & S.W & NUT	4
43	500139	CHANNEL - STD	1
	500140	CHANNEL - 110	1
44	200078	SCREW M6x16L	1
45	500141	FIX PIECE	1
46	500142	HANDEL WHEEL	1
47	400637	LIMIT SWITCH TZ-7110	1
48	200105	SCREW M4x30L & W	2
49	300041	LOCK w/ KEY	2
50	500143	CONTROL BOX	1
50a	310008	BUTTON MEMBRANE LABEL FOR CONTROL PANEL	1
51	200076	SCREW M6x10L & S.W.	1
52	300048	LOCK LATCH PLATE	2
53	200076	SCREW M6 x 10L & S.W.	4
54	204905	SCREW M5 x 16L	1
55	500106	HINGE	2

Film Carriage Assembly



Film Carriage Parts List

Machine Section	HLI Part Number	Item Description	Qty.
1	500000	HANDLE	1
2	500144	FILM FIX SEAT(UPPER)	1
3	500145	SHAFT	1
4	300006	RING STW-10	2
5	200079	SCREW M6*20L & S.W. & W.	4
6	200089	SCREW M10*20L	1
7	500146	FILM MOVING SHAFT	1
8	500147	FILM SEAT SPRING	1
9	500148	FILM SEAT(UPPER)	1
10	500101	FILM SEAT SHAFT	1
11	500149	ELEVATOR UNIT SEAT(OUTER)-20"	1
	504260	ELEVATOR UNIT SEAT(OUTER)-30"	1
12	500150	PEDAL	1
13	200079	SCREW M6*20L & S.W. & W.	4
14	700072	LOWER CORE HOLDER ASSEMBLY	1
	W	FILM SEAT SHAFT	
	X	SPRING	
	Y	BEARING NTB/A51730	
	Z – 500107	FILM FIX SEAT	
	Za – 500111	BRAKE	
	Zb – 500109	FILM BRAKE PLATE	
	Zd – 500112	WASHER	
18	500151	FILM FIX SEAT(LOWER)	1
19	207388	SCREW M10*25L	1
23			
24	500152	LIMIT SWITCH SEAT	1
25	400639	LIMIT SWITCH TZ-8108	2
26	200101	SCREW M4*12L	2
27	500130	TERMINAL COVER	1
28	200102	SCREW M4*16L	4
29	200101	SCREW M4*12L	4
31	200077	SCREW M6*12L & S.W. & W.	2
32	200137	NUT M6	2

33	200103	SCREW M4*20L	1
34	200079	SCREW M6*20L	2
35	500016	SPRING	1
36	200127	NUT M4	2
37	500913	HANDLE KNOB	1
38	500153	HANDLE	1
39	200077	SCREW M6*12L & S.W. & W.	2
40	300006	RING STW-10	1
41	500154	RING	1
42	200157	SCREW M6*100L	2
43	200129	NUT M6	4
44	500155	STRETCH SEAT COVER(UPPE)	1
45	500156	WHEEL	1
46	200121	SCREW M6*10L	1
47	200130	NUT M8 & S.W.	2
48	500157	STRETCH SEAT SHAFT	1
49	200130	NUT M8 & W.	1
50	500158	RING	1
51	500159	UPPER STRETCH SEAT	1
52	500160	TENSION ADJUST SEAT	1
53	500161	STRETCH SPRING	1
54	500162	BRAKE PLATE	1
55	500163	TENSION ADJUST SCREW	1
56	500164	GEAR SCREW FIX SEAT	1
57	500154	RING	1
58	500000	HANDLE	1
59	200077	SCREW M6*12L & S.W. & W.	2
60	500165	BREAK PLATE SHAFT	1
61	200129	NUT M6 & S.W.	2
62	500166	BREAK WHEEL FIX SHAFT	1
63	500167	BRAKE WHEEL	1
64	300002	PIN 5*5*20L	1
65	200084	SCREW M8*20L & S.W. & W.	2
66	300051	BEARING 6004ZZ-NR	2
67	500168	PRE-STRETCH SHAFT-20"	1
	504261	PRE-STRETCH SHAFT-30"	1

68	400640	WIRE PROTECTOR	1
69	400636	LIMIT SWITCH TM-1307	1
70	200104	SCREW M4*25L	2
71	500169	LOWER STRETCH SEAT	1
72	200084	SCREW M8*20L & S.W. & W.	2
73	300010	RING STW-20	1
74	500158	RING	2
75	500170	MOVING SHAFT PIN	2
76	200833	SCREW M6*12L	4
77	500171	MOVING SHAFT	1
	500172	MOVING SHAFT	1
78	300052	RING STW-22	4
79	300006	RING STW-10	4
80	300015	BEARING 6000ZZ	4
81	500173	IDLER ROLLER-20"	1
	504262	IDLER ROLLER-30"	1
82	500174	IDLER ROLLER SHAFT-20"	2
	504263	IDLER ROLLER SHAFT-30"	2
83	500175	IDLER ROLLER-20"	1
	504264	IDLER ROLLER-30"	1
85	200127	NUT M4 (OPTION)	2
86	400643	PHOTO SENSOR A3R-2MX (OPTION)	1
87	200101	SCREW M4x12L & W. (OPTION)	2
88	200110	SCREW M6x12L (OPTION)	2
89	500094	FIX PIECE (OPTION)	1
90	200079	SCREW M6*20L & S.W. & W. (OPTION)	2
91	500176	PHOTO SENSOR ADJUST SEAT (OPTION)	1
92	500000	HANDLER (OPTION)	1
93	500095	PHOTO SENSOR ADJUST BAR (OPTION)	2
94	500096	CONNECTING PLATE (OPTION)	1
95	200077	SCREW M6*12L & S.W. & W. (OPTION)	2
96	304629	SPACER, ANTI-SQUEAK	1

Advanced Eye – Optional

1) REMOVE EXISTING EYE BRACKET FROM THE TOP OF THE TWO VERTICAL RODS. THE EXISTING EYE MAY TO BE REMOVED FROM BRACKET TO REVEAL SCREW HEADS.

2) MOUNT UPGRADE EYE BRACKET ON TOP OF 2 RODS USING THE EXISTING HARDWARE.

3) ROUTE NEW CABLE TO THE BOX WHERE THE EXISTING EYE WIRING IS TERMINATED FOLLOWING THE ROUTE OF THE EXISTING CABLE. REMOVE THE COVER.

4) CUT OFF EXISTING, GREY EYE CABLE AND BARE WIRES FROM THE MACHINE SIDE.

5) CONNECT THE NEWLY BARED WIRES FROM THE EXISTING GREY CABLE TO THE WIRES IN THE UPGRADE EYE CABLE USING THE WIRING SCHEDULE BELOW. CRIMP WITH SUPPLIED FITTINGS.

6) REPLACE THE WIRING COVER.

WIRE COVER

4

Ref.	Qty.	Part No.	Description
1	1	540879	EYE BRACKET
2	1	409305	ADVANCED EYE-300CM
3	1	405011	CABLE - MB X 4M
4	3	407218	BUTT CONNECTOR

HIGHLIGHT
INDUSTRIES, INC.
2694 PRAIRIE SW
WYOMING MI. 49509

CONFIDENTIAL STATEMENT
THIS DOCUMENT IS THE PROPERTY OF HIGHLIGHT INDUSTRIES, INC. AND MAY BE USED FOR ANY PURPOSE OTHER THAN THE ORIGINAL INTENDED WITHOUT WRITTEN PERMISSION OF HIGHLIGHT INDUSTRIES, INC.

TOLERANCES U.S.
3 Place Dim. +/- 0.030

Scale: 1/8

By:
Date: 12/27/22
Material:
Finish:

Rev. 1/8

EcN Number:

Part #
740088

Description:
ADVANCED EYE UPGRADE
PREDATOR SS
LANBAO
Assembly:

8

Highlight Industries, Inc.

Predator SS Turntable Stretch Wrapper Operation Manual

Notes

[illegible]

[illegible]