SOC Manager - Response Checke

Student: Matan Ohayon / S22

Class: TMagen773637

Lecturers: Eliran Berkovich

Summary

This script is designed to help SOC (Security Operations Center) teams stay alert and practice real-world incident response. It allows a SOC manager or administrator to automatically launch different cyber attacks against the internal network. The goal is to simulate real threats, so the SOC team can detect, investigate, and respond to them in a controlled environment.

The system offers multiple types of attacks (such as DDoS, SMB/RDP brute-force, enumeration attacks, etc.) and records each executed action into a log file. This logging feature helps the manager verify whether the SOC team responded correctly and met their mission objective.

By using this tool, organizations can continuously train their security teams, measure their effectiveness, and improve their defensive capabilities without putting production systems at risk.

Required Tools & Wordlists

Tools & Utilities

Nmap, Hydra ,Hping3 ,CrackMapExec/CME, wGet

Wordlists

SecLists (usernames) & Rockyou (passwords) from GitHub security community collections.

Discovering available hosts

The script begins by scanning for active hosts using Nmap. After detection, The user can choose a host from the discover phase, Choose random target from the list found or Costum IP Address.

```
┌──(kali㉿kali)-[~/Desktop]
└─$ ./soc.sh 192.168.253.0/24
Discovered Hosts:
[1] Available Host 192.168.253.2
[2] Available Host 192.168.253.160
[3] Available Host 192.168.253.129
[R] Random Target
[C] Custom IP
Choose target number, R for random, or C for custom: 2
Target chosen 192.168.253.160
```

Attack Vectors

The script uses full port scanning to detect SSH, SMB, and RDP. Based on results. SMB options appear if ports 445 or 139 detected, RDP attack options appear if port 3389 detected and All targets allow DDoS attack but the user can choose which service he wants to flood. Each attack vector will prompt the SOC manager with description that explain the attack before executing.

```
Available Attack Vectors:
[0] DDoS
[1] SMB Attacks
[R] Random Attack
Choose Attack Vector index or R for random: 1
Attack chosen SMB Attacks
Description: Attacks SMB (file sharing) via brute-force or enumeration.
```

Wordlists

When choosing a Brute-Force attack the manager can choose to specify specific wordlist or use the default one. Then he can choose the thread count for hydra brute-force.

```
SMB Attack Options:
[0] SMB Brute Force (Hydra)
[1] SMB Enumeration (CrackMapExec)
Choose SMB attack: 0

SMB Brute Force (Hydra) on 192.168.253.160
This will try username/password combinations against SMB (port 445).
Use default wordlists for Hydra?
Users: /usr/share/seclists/Usernames/top-usernames-shortlist.txt
Passwords: /usr/share/wordlists/rockyou.txt
Use defaults? (y/n): y
Choose Hydra thread count (1-8): 8
```

Logs

The script will automatically logs the attack initiated via the script into a log located at /var/log/attacks.log

```
┌──(kali㉿kali)-[~/Desktop]
└─$ cat /var/log/attacks.log
[2025-11-25 12:17:30] SMB Enum (CrackMapExec) on 192.168.253.160
[2025-11-25 14:02:49] SMB Brute (Hydra) on 192.168.253.160 (users: pass: threads:8)
```

By S22 / Matan Ohayon