

exercise1-newton (Score: 13.0 / 13.0)

1. [Test cell](#) (Score: 1.0 / 1.0)
2. [Test cell](#) (Score: 1.0 / 1.0)
3. [Test cell](#) (Score: 1.0 / 1.0)
4. [Written response](#) (Score: 1.0 / 1.0)
5. [Test cell](#) (Score: 1.0 / 1.0)
6. [Coding free-response](#) (Score: 2.0 / 2.0)
7. [Test cell](#) (Score: 1.0 / 1.0)
8. [Coding free-response](#) (Score: 2.0 / 2.0)
9. [Written response](#) (Score: 3.0 / 3.0)

Lab 2

1. 提交作業之前，建議可以先點選上方工具列的**Kernel**，再選擇**Restart & Run All**，檢查一下是否程式跑起來都沒有問題，最後記得儲存。
2. 請先填上下方的姓名(name)及學號(student_id)再開始作答，例如：

```
name = "我的名字"
student_id= "B06201000"
```

3. 四個求根演算法的實作可以參考[lab-2 \(https://yuanyuyuan.github.io/itcm/lab-2.html\)](https://yuanyuyuan.github.io/itcm/lab-2.html)，裡面有教學影片也有範例程式可以套用。
4. **Deadline: 10/9(Wed.)**

In [1]:

```
name = "林以翎"
student_id = "B06201024"
```

Exercise 1 - Newton

Use the Newton's method to find roots of

$$f(x) = \cosh(x) + \cos(x) - c, \text{ for } c = 1, 2, 3,$$

Import libraries

In [2]:

```
import matplotlib.pyplot as plt
import numpy as np
```

1. Define the function $g(c)(x) = f(x) = \cosh(x) + \cos(x) - c$ with parameter $c = 1, 2, 3$ and its derivative df .

In [3]:

(Top)

```
def g(c):
    assert c == 1 or c == 2 or c == 3
    def f(x):
        # Hint: return ...
        # ===== 請實做程式 =====
        return np.cosh(x)+np.cos(x)-c
        # =====
    return f

def df(x):
    # Hint: return ...
    # ===== 請實做程式 =====
    return np.sinh(x)-np.sin(x)
    # =====
```

Pass the following assertion.

In [4]:

cell-b59c94b754b1fc9e

(Top)

```
assert g(1)(0) == np.cosh(0) + np.cos(0) - 1
assert df(0) == 0
### BEGIN HIDDEN TESTS
assert g(2)(0) == np.cosh(0) + np.cos(0) - 2
assert g(3)(0) == np.cosh(0) + np.cos(0) - 3
assert df(1) == np.sinh(1) - np.sin(1)
### END HIDDEN TESTS
```

2. Implement the algorithm

In [5]:

(Top)

```
def newton(
    func,
    d_func,
    x_0,
    tolerance=1e-7,
    max_iterations=5,
    report_history=False
):
    """
    Parameters
    -----
    func : function
        The target function.
    d_func : function
        The derivative of the target function.
    x_0 : float
        Initial guess point for a solution f(x)=0.
    tolerance : float
        One of the termination conditions. Error tolerance.
    max_iterations : int
        One of the termination conditions. The amount of iterations allowed.
    report_history: bool
        Whether to return history.

    Returns
    -----
    solution : float
        Approximation of the root.
    history: dict
        Return history of the solving process if report_history is True.
    """
    # ===== 請實做程式 =====
    # Set the initial conditions
```

```

x_n = x_0
num_iterations = 0

# history of solving process
if report_history:
    history = {'estimation': [], 'error': []}

while True:

    # Find the value of f(x_n)
    f_of_x_n = func(x_n)

    # Evaluate the error
    error = abs(f_of_x_n)

    if report_history:
        history['estimation'].append(x_n)
        history['error'].append(error)

    # Satisfy the criterion and stop
    if error < tolerance:
        print('Found solution after', num_iterations, 'iterations.')
        if report_history:
            return x_n, history
        else:
            return x_n

    # Find the differential value of f'(x_n)
    d_f_of_x_n = d_func(x_n)

    # Avoid zero derivative
    if d_f_of_x_n == 0:
        print('Zero derivative. No solution found.')
        if report_history:
            return None, history
        else:
            return None

    # Check the number of iterations
    if num_iterations < max_iterations:
        num_iterations += 1

    # Find the next approximation solution
    x_n = x_n - f_of_x_n / d_f_of_x_n

    # Satisfy the criterion and stop
    else:
        print('Terminate since reached the maximum iterations.')
        if report_history:
            return x_n, history
        else:
            return x_n

# =====

```

Test your implementation with the assertion below.

In [6]:

cell-4d88293f2527c82d

(Top)

```

root = newton(
    lambda x: x**2 - x - 1,
    lambda x: 2*x - 1,
    1.2,
    max_iterations=100,
    tolerance=1e-7,
    report_history=False
)
assert abs(root - ((1 + np.sqrt(5)) / 2)) < 1e-7

```

Found solution after 4 iterations.

3. Answer the following questions under the case $c = 1$.

Plot the function to find an interval that contains the zero of f if possible.


In [7]:

(Top)

```
c = 1
f = g(c)

# Hint: search_range = np.arange(左端點, 右端點, 點與點之間距),
# e.g. search_range = np.arange(0.0, 1.0, 0.01)
# ===== 請實做程式 =====
search_range = np.arange(0.0, 1.0, 0.01)
# =====

fig, ax = plt.subplots(figsize=(9, 4))
ax.plot(search_range, f(search_range))
ax.set_title(r'$f(x)=\cosh(x)+\cos(x)-c$, $c=${d}' % c)
ax.grid(True)
ax.axhline(y=0)
ax.axvline(x=0)
plt.show()
```



According to the figure above, estimate the zero of f .

For example,

```
root = 3          # 單根
root = -2, 1      # 多根
root = None       # 無解
```

In [8]:

(Top)

```
# Hint: root = ?
# ===== 請實做程式 =====
root = None
# =====
```

In [9]:

cell-d872c7c57f11c968

(Top)

```
print('My estimation of root:', root)
### BEGIN HIDDEN TESTS
if root == None:
    print('Right answer!')
else:
    raise AssertionError('Wrong answer!')
### END HIDDEN TESTS
```

My estimation of root: None
Right answer!

Try to find the zero with a tolerance of 10^{-10} . If it works, plot the error and estimation of each step. Otherwise, state the reason why the method failed on this case.

(Top)

Under the case $c = 1$, since $f(x) > 0$ for all x , it does not have root. Then either the algorithm reaches its max iteration or exists h s.t. $f'(h) = 0$ during the algorithm.

4. Answer the following questions under the case $c = 2$.

Plot the function to find an interval that contains the zero of f if possible.


In [10]:

(Top)

```
c = 2
f = g(c)

# Hint: search_range = np.arange(左端點, 右端點, 點與點之間距),
# e.g. search_range = np.arange(0.0, 1.0, 0.01)
# ===== 請實做程式 =====
search_range = np.arange(-0.5, 0.5, 0.01)
# =====

fig, ax = plt.subplots(figsize=(9, 4))
ax.plot(search_range, f(search_range))
ax.set_title(r'$f(x)=\cosh(x)+\cos(x)-c$, $c=2$')
ax.grid(True)
ax.axhline(y=0)
ax.axvline(x=0)
plt.show()
```



According to the figure above, estimate the zero of f .

For example,

```
root = 3          # 單根
root = -2, 1      # 多根
root = None       # 無解
```

In [11]:

(Top)

```
# Hint: root = ?
# ===== 請實做程式 =====
root = 0
# =====
```

In [12]:

cell-20fddbe6fa4c437b (Top)

```
print('My estimation of root:', root)

### BEGIN HIDDEN TESTS
assert type(root) is float or int, 'Wrong type!'
### END HIDDEN TESTS
```

My estimation of root: 0

Try to find the zero with a tolerance of 10^{-10} . If it works, plot the error and estimation of each step. Otherwise, state the reason why the method failed on this case.

In [13]:

(Top)

```
solution, history = newton(
    f,
    df,
    1.2,
    max_iterations=100,
    tolerance=1e-10,
    report_history=True
)
```

Found solution after 19 iterations.

In [14]:

```
fig, axes = plt.subplots(3, 1, figsize=(16, 9))
ax1, ax2, ax3 = axes

num_iterations = len(history['estimation'])
iterations = range(num_iterations)
for ax in axes:
    ax.set_xticks(iterations)

# Plot the estimation in history
ax1.plot(iterations, history['estimation'])
ax1.set_ylabel('Estimation')


# Plot the estimation error (log(error)) in history
ax2.plot(iterations, history['error'])
ax2.set_ylabel('Estimated Error')
ax2.set_yscale('log')

exact_solution_0 = 0
exact_solution = exact_solution_0

for i in range(1,num_iterations):
    exact_solution = np.hstack((exact_solution,exact_solution_0))

# Plot the estimation actual error (estimation - exact solution) in history
actual_error = np.abs(history['estimation']-exact_solution)
ax3.plot(iterations, actual_error)
ax3.set_ylabel('Actual error')
ax3.set_yscale('log')
ax3.set_xlabel('Iterations')

plt.tight_layout()
plt.show()
```



5. Answer the following questions under the case $c = 3$.

Plot the function to find an interval that contains the zeros of f if possible.


In [15]:

(Top)

```
c = 3
f = g(c)

# Hint: search_range = np.arange(左端點, 右端點, 點與點之間距),
# e.g. search_range = np.arange(0.0, 1.0, 0.01)
# ===== 請實做程式 =====
search_range = np.arange(-2.0, 2.0, 0.01)
# =====

fig, ax = plt.subplots(figsize=(9, 4))
ax.plot(search_range, f(search_range))
ax.set_title(r'$f(x)=\cosh(x)+\cos(x)-c$, $c=${d}' % c)
ax.grid(True)
ax.axhline(y=0)
ax.axvline(x=0)
plt.show()
```



According to the figure above, estimate the zero of f .

For example,

```
root = 3          # 單根
root = -2, 1      # 多根
root = None       # 無解
```

In [16]:

(Top)

```
# Hint: root = ?
# ===== 請實做程式 =====
root = -1.8, 1.8
# =====
```

In [17]:

cell-06ec0b20844075c7

(Top)

```
print('My estimation of root:', root)

### BEGIN HIDDEN TESTS
assert type(root) == tuple, 'Should be multiple roots!'
### END HIDDEN TESTS
```

My estimation of root: (-1.8, 1.8)

Try to find the zero with a tolerance of 10^{-10} . If it works, plot the error and estimation of each step. Otherwise, state the reason why the method failed on this case.

In [18]:


(Top)

```
solution, history = newton(  
    f,  
    df,  
    1.2,  
    max_iterations=100,  
    tolerance=1e-10,  
    report_history=True  
)
```

Found solution after 6 iterations.

In [19]:

```
fig, axes = plt.subplots(3, 1, figsize=(16, 9))  
ax1, ax2, ax3 = axes  
  
num_iterations = len(history['estimation'])  
iterations = range(num_iterations)  
for ax in axes:  
    ax.set_xticks(iterations)  
  
# Plot the estimation in history  
ax1.plot(iterations, history['estimation'])  
ax1.set_ylabel('Estimation')  
  
# Plot the estimation error (log(error)) in history  
ax2.plot(iterations, history['error'])  
ax2.set_ylabel('Estimated Error')  
ax2.set_yscale('log')  
  
exact_solution_0 = 1.85792082915020  
exact_solution = exact_solution_0  
  
for i in range(1, num_iterations):  
    exact_solution = np.hstack((exact_solution, exact_solution_0))  
  
# Plot the estimation actual error (estimation - exact solution) in history  
actual_error = np.abs(history['estimation'] - exact_solution)  
ax3.plot(iterations, actual_error)  
ax3.set_ylabel('Actual error')  
ax3.set_yscale('log')  
ax3.set_xlabel('Iterations')  
  
plt.tight_layout()  
plt.show()
```




In [20]:

```
solution, history = newton(  
    f,  
    df,  
    -1.2,  
    max_iterations=100,  
    tolerance=1e-10,  
    report_history=True  
)
```

Found solution after 6 iterations.

In [21]:

```
fig, axes = plt.subplots(3, 1, figsize=(16, 9))  
ax1, ax2, ax3 = axes  
  
num_iterations = len(history['estimation'])  
iterations = range(num_iterations)  
for ax in axes:  
    ax.set_xticks(iterations)  
  
# Plot the estimation in history  
ax1.plot(iterations, history['estimation'])  
ax1.set_ylabel('Estimation')  
  
# Plot the estimation error (log(error)) in history  
ax2.plot(iterations, history['error'])  
ax2.set_ylabel('Estimated Error')  
ax2.set_yscale('log')  
  
exact_solution_0 = -1.85792082915020  
exact_solution = exact_solution_0  
  
for i in range(1, num_iterations):  
    exact_solution = np.hstack((exact_solution, exact_solution_0))  
  
# Plot the estimation actual error (estimation - exact solution) in history  
actual_error = np.abs(history['estimation'] - exact_solution)  
ax3.plot(iterations, actual_error)  
ax3.set_ylabel('Actual error')  
ax3.set_yscale('log')  
ax3.set_xlabel('Iterations')  
  
plt.tight_layout()  
plt.show()
```



Discussion

For all cases above(c=1,2,3), do the results(e.g. error behaviors, estimations, etc) agree with the theoretical analysis?

(Top)

Under the case $c = 1$, by the discussion above, the algorithm doesn't work.\ Under the case $c = 2$ and $c = 3$, by observasion, error behaviors and estimations agree with the theoretical analysis, it converge very fast.\ Note that under the case $c = 2$, we can't choose 0 as the initial guessing solution. Since $f'(0) = 0$, the algorithm doesn't work.

In []: