

[Explore more...](#)

## SQL | Join (Cartesian Join & Self Join)



### SQL| JOIN (Inner, Left, Right and Full Joins)

In this article, we will discuss about the remaining two JOINS:

- **CARTESIAN JOIN**
- **SELF JOIN**

Consider the two tables below:

**Student**

| ROLL_NO | NAME   | ADDRESS | PHONE      | Age |
|---------|--------|---------|------------|-----|
| 1       | Ram    | Delhi   | 9455123451 | 18  |
| 2       | RAMESH | GURGAON | 9652431543 | 18  |
| 3       | SUJIT  | ROHTAK  | 9156253131 | 20  |
| 4       | SURESH | Delhi   | 9156768971 | 18  |

**StudentCourse**

| COURSE_ID | ROLL_NO |
|-----------|---------|
| 1         | 1       |
| 2         | 2       |
| 2         | 3       |
| 3         | 4       |



1. **CARTESIAN JOIN:** The CARTESIAN JOIN is also known as CROSS JOIN. In a CARTESIAN JOIN there is a join for each row of one table to every row of another table. This usually happens when the matching column or WHERE condition is not specified.

- In the absence of a WHERE condition the CARTESIAN JOIN will behave like a CARTESIAN PRODUCT . i.e., the number of rows in the result-set is the product of the number of rows of the two tables.
- In the presence of WHERE condition this JOIN will function like a INNER JOIN.
- Generally speaking, Cross join is similar to an inner join where the join-condition will always evaluate to True

#### Syntax:

```
SELECT table1.column1 , table1.column2, table2.column1...  
FROM table1  
CROSS JOIN table2;
```

**table1:** First table.

**table2:** Second table

#### Example Queries(CARTESIAN JOIN):

- In the below query we will select NAME and Age from Student table and COURSE\_ID from StudentCourse table. In the output you can see that each row of the table Student is joined with every row of the table StudentCourse. The total rows in the result-set =  $4 * 4 = 16$ .

```
SELECT Student.NAME, Student.AGE, StudentCourse.COURSE_ID  
FROM Student  
CROSS JOIN StudentCourse;
```

#### Output:

| NAME   | AGE | COURSE_ID |
|--------|-----|-----------|
| Ram    | 18  | 1         |
| Ram    | 18  | 2         |
| Ram    | 18  | 2         |
| Ram    | 18  | 3         |
| RAMESH | 18  | 1         |
| RAMESH | 18  | 2         |

|        |    |   |
|--------|----|---|
| RAMESH | 18 | 2 |
| RAMESH | 18 | 3 |
| SUJIT  | 20 | 1 |
| SUJIT  | 20 | 2 |
| SUJIT  | 20 | 2 |
| SUJIT  | 20 | 3 |
| SURESH | 18 | 1 |
| SURESH | 18 | 2 |
| SURESH | 18 | 2 |
| SURESH | 18 | 3 |

2. **SELF JOIN:** As the name signifies, in SELF JOIN a table is joined to itself. That is, each row of the table is joined with itself and all other rows depending on some conditions. In other words we can say that it is a join between two copies of the same table.**Syntax:**

```
SELECT a.coulmn1 , b.column2
FROM table_name a, table_name b
WHERE some_condition;
```

**table\_name:** Name of the table.

**some\_condition:** Condition for selecting the rows.

### Example Queries(SELF JOIN):

```
SELECT a.ROLL_NO , b.NAME
FROM Student a, Student b
WHERE a.ROLL_NO < b.ROLL_NO;
```

**Output:**

| ROLL_NO | NAME   |
|---------|--------|
| 1       | RAMESH |
| 1       | SUJIT  |
| 2       | SUJIT  |
| 1       | SURESH |
| 2       | SURESH |
| 2       | SURESH |



|   |        |
|---|--------|
| 3 | SURESH |
|---|--------|

This article is contributed by **Harsh Agarwal**. If you like GeeksforGeeks and would like to contribute, you can also write an article using [contribute.geeksforgeeks.org](https://www.geeksforgeeks.org/contribute) or mail your article to [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org). See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

## Recommended Posts:

- [SQL | Alternative Quote Operator](#)
- [SQL | Concatenation Operator](#)
- [SQL | MINUS Operator](#)
- [SQL Interview Questions](#)
- [SQL | Constraints](#)
- [SQL | CREATE](#)
- [Lossless Join and Dependency Preserving Decomposition](#)
- [Functional Dependency and Attribute Closure](#)
- [SQL | Union Clause](#)
- [SQL | Join \(Inner, Left, Right and Full Joins\)](#)
- [SQL | Wildcard operators](#)
- [DBMS | Nested Queries in SQL](#)
- [SQL query to find second highest salary?](#)
- [Having vs Where Clause?](#)
- [Commonly asked DBMS interview questions | Set 1](#)

**Article Tags :** [Articles](#) [DBMS](#) [SQL](#) [SQL-Clauses-Operators](#)

**Practice Tags :** [DBMS](#) [SQL](#)



Be the First to upvote.



**2.6**☐ To-do ☐ DoneBased on **17** vote(s)

Feedback

Add Notes

Improve Article

Please write to us at [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org) to report any issue with the above content.

Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.

Load Comments

Share this post!

A computer science portal for geeks

710-B, Advant Navis Business Park,  
Sector-142, Noida, Uttar Pradesh - 201305  
[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

**COMPANY**

About Us  
Careers  
Privacy Policy  
Contact Us

**LEARN**

Algorithms  
Data Structures  
Languages  
CS Subjects  
Video Tutorials

**PRACTICE**

Company-wise  
Topic-wise  
Contests  
Subjective Questions

**CONTRIBUTE**

Write an Article  
Write Interview Experience  
Internships  
Videos

@geeksforgeeks, Some rights reserved

