# **Robot Operating System**

#### Content of the labs


The goal of these labs is to discover several of the aspects of using and programming with ROS. There are 4 labs that will deal about increasing complexity of the ROS ecosystem. Most of the labs can be done on your own computer, assuming that you have a working ROS installation.

#### Setting up the computer

Computers from the lab room at ECN should be already set up. If you want to install ROS on your own, you can find several ways to do so, depending on your motivation:

- Go to ROS website and follow the tutorials by your own.
- Download the Virtual Machine on my webpage. This VM corresponds more or less to the ECN computers.
- If you have an Ubuntu, go to my webpage where you can find several helper scripts to install ROS, setup your profile and install V-REP, a simulator that is used for some labs.

At ECN, we assume the ROS workspace is located at ~/ros. Most of the official tutorials use ~/catkin\_ws or something similar but we think a simple ros folder is quite explicit. The directory tree is thus:



If you decide to use another workspace path, adapt the command lines accordingly.

## How to compile

The main tool used to compile ROS packages is called <code>catkin</code>. Basically, calling <code>catkin</code> build will crawl through all your packages and resolve the dependency tree. It will then compile first the independent packages, then the others. The actual compilation is done through <code>cmake</code> and <code>make</code> but <code>catkin</code> use them automatically.

You have to call **catkin build** each time you have a new package, either because you downloaded one in your workspace or because you manually created one.



### How to use QtCreator with ROS

As we saw during C++ labs, an IDE such as Qt Creator is pretty useful. For ROS it will be even more as ROS uses many classes and the IDE will give you autocompletion and hints for their methods. A guide on how to use Qt Creator with ROS is available on my webpage.

Do not forget to launch Qt Creator from the command line ( qtcreator ) or use the desktop shortcut that simulates a console launch.

Once catkin build is called, remember that the build directory of a given package called package\_name is at ~/ros/build/package\_name.

ECN computers and the Virtual Machine are configured to compile in Debug mode by default, which helps the bug hunt.



- 1 Lab 1 launchfiles, remaps and gui tools
- 2 Lab 2 package creation, dependencies and topics
- 3 Lab 3 transforms and services
- 4 Lab 4 working with images

