

Module 4 - Instructions

Oliver Engist

3/25/2020

In the next assignment we want to replicate some plots from the paper “Female Socialization: How Daughters Affect Their Legislator Fathers’ Voting on Women’s Issues” (Washington, 2008). The paper explores whether having a daughter makes politicians more sensitive to women’s rights issues and how this is reflected in their voting behavior. The main identifying assumption is that after controlling for the number of children, the gender composition is random. This might be violated if families that have a preference for girls keep having children until they have a girl. In this assignment we will prepare a dataset that allows us to test whether families engage in such a “female child stopping rule”.

I encourage you to take a look at the paper, as we will come back to it later in the course.

Setup

- Load the libraries “Rio” and “tidyverse”
- Change the path of the working directory to your working directory.

```
library(rio)
library(tidyverse)
setwd("~/Module_4")
```

- import the data sets *basic.dta* and *genold108.dta*

```
Basic <- import("basic.dta")
Genold <- import("genold108.dta")
```

- create a subset of the 108th congress from the *basic* dataset

```
Subset <- Basic %>% filter(congress==108)
```

- join this subset with the *genold* dataset

```
Data <- left_join(Subset, Genold, by=c("statenam", "district", "name"))
```

Data preparation

- check table 1 in the appendix of the paper and decide which variables are necessary for the analysis (check the footnote for control variables)
- drop all other variables.

```
Data <- Data %>% select("totchi", "ngirls", "genold", "district", "statenam",
                      "name", "white", "female", "party", "repub", "age", "srvlng",
                      "rgroup", "region")
```

- Recode *genold* such that gender is a factor variable and missing values are coded as NAs.

```
Data$genold[Data$genold==""] <- NA
Data$genold <- as.factor(Data$genold)
```

- Recode *party* as a factor with 3 levels (D, R, I)

```
Data$party[Data$party==1] <- "D"
Data$party[Data$party==2] <- "R"
Data$party[Data$party==3] <- "I"
```

```
Data$party <- as.factor(Data$party)
```

- Recode *rgroup* and *region* as factors.

```
Data$rgroup <- as.factor(Data$rgroup)
Data$region <- as.factor(Data$region)
```

- generate variables for age squared and service length squared

```
Data$agesq <- Data$age^2
Data$svlngsq <- Data$svlng^2
```

- create an additional variable of the number of children as factor variable

```
Data$nkids <- as.factor(Data$totchi)
```

Replicating Table 1 from the Appendix

We haven't covered regressions in R yet. Use the function *lm()*. The function takes the regression model (formula) and the data as an input. The model is written as $y \sim x$, where x stands for any linear combination of regressors (e.g. $y \sim x_1 + x_2 + female$). Use the help file to understand the function.

- Run the regression $total.children = \beta_0 + \beta_1 gender.oldest + \gamma'X$ where γ stands for a vector of coefficients and X is a matrix that contains all columns that are control variables.¹

```
# First, I drop Bernie Sanders and recode Virgil Goode
Data <- Data[!((Data$party=="I") & (Data$genold=="NA")),] # Dropping Bernie Sanders
Data$party[(Data$party=="I")] <- "D" # Recoding Virgil Goode as a Republican
```

```
# Regression with number of children as dependent variable
reg.totchi <- lm(totchi ~ genold + white + female + repub + age + agesq + svlng +
  svlngsq + rgroup + region, data=Data)
```

```
# Regression with number of daughters as dependent variable
reg.ngirls <- lm(ngirls ~ genold + white + female + repub + age + agesq + svlng +
  svlngsq + rgroup + region + nkids, data=Data)
```

- Save the main coefficient of interest (β_1)

```
# Regression with number of children as dependent variable
b1.totchi <- round(summary(reg.totchi)$coefficients[2, c(1,2)], digits=2)
# Saving coeff and std.err. and rounding to two decimals

# Regression with number of children as dependent variable
b1.ngirls <- round(summary(reg.ngirls)$coefficients[2, c(1,2)], digits=2)
```

¹This is just a short notation instead of writing the full model with all control variables $totchi = \beta_0 + \beta_1 genold + \gamma_1 age + \gamma_2 age^2 + \gamma_3 Democrat + \dots + \epsilon$ which quickly gets out of hand for large models.

- Run the same regression separately for Democrats and Republicans (assign the independent to one of the parties). Save the coefficient and standard error of *genold*

```
# Regression with number of children as dependent variable for Democrats
reg.totchi.D <-
  lm(totchi ~ genold + white + female + repub + age + agesq + srvlng +
      srvlngsq + rgroup + region, Data, subset = (party=="D"))
b1.totchi.D <-
  round(summary(reg.totchi.D)$coefficients[2, c(1,2)], digits=2)
# Saving coeff. and std.err.

# Regression with number of children as dependent variable for Democrats
reg.ngirls.D <-
  lm(ngirls ~ genold + white + female + repub + age + agesq + srvlng +
      srvlngsq + rgroup + region + nkids, Data, subset = (party=="D"))
# nkids introduces fixed effects
b1.ngirls.D <- round(summary(reg.ngirls.D)$coefficients[2, c(1,2)], digits=2)

# Regression with number of children as dependent variable for Republicans
reg.totchi.R <-
  lm(totchi ~ genold + white + female + repub + age + agesq + srvlng +
      srvlngsq + rgroup + region, Data, subset = (party=="R"))
b1.totchi.R <-
  round(summary(reg.totchi.R)$coefficients[2, c(1,2)], digits=2)

# Regression with number of daughters as dependent variable for Republicans
reg.ngirls.R <-
  lm(ngirls ~ genold + white + female + repub + age + agesq + srvlng +
      srvlngsq + rgroup + region + nkids, Data, subset = (party=="R"))
b1.ngirls.R <- round(summary(reg.ngirls.R)$coefficients[2, c(1,2)], digits=2)
```

- Collect all the *genold* coefficients from the six regressions, including their standard errors and arrange them in a table as in the paper.

```
Table <- matrix(c(b1.ngirls, b1.totchi, b1.ngirls.D, b1.totchi.D, b1.ngirls.R,
                  b1.totchi.R), nrow=2, ncol=6)
rownames(Table) <- c("Estimate", "Std.error")
colnames(Table) <- c("Full Congress Number of children",
                    "Full congress Number of children",
                    "Democrats Number of daughters",
                    "Democrats Number of children",
                    "Republicans Number of daughters",
                    "Republicans Number of children")
```

- print the table

```
knitr::kable(Table, format="markdown")
```

	Full Congress Number of children	Full congress Number of children	Democrats Number of daughters	Democrats Number of children	Republicans Number of daughters	Republicans Number of children
Estimate	1.36	-0.09	1.39	0.07	1.23	-0.28
Std.error	0.08	0.15	0.11	0.18	0.11	0.23