

week2a

June 15, 2023

Notebook file for Week 2, T1 Relaxation experiment

Import libraries. The nmrbase folder needs to be located within the folder containing this Jupyter notebook

```
[ ]: import numpy as np
import scipy
import matplotlib.pyplot as plt
import nmrbase.expbases as expbase
import nmrbase.expdata as expdata
```

T1 Relaxation NOTE: To analyze and report multiple datasets, simply copy the necessary blocks of code.

```
[ ]: filename = r"../DIRECTORY/FILENAME"  #Defines the path to the data file. Here
      ↳the path is relative to the current folder.
```

```
[ ]: a = expbase.expbases()
a.load(filename)  # load data

f1=plt.figure()
ax1=f1.subplots()
a.plotm(ax1,5)
```

```
[ ]: ## TASKS:
## fine tune with set_xlim and set_ylim parameters to zoom in on the echo
ax1.set_ylim([-0.15,0.15])
ax1.set_xlim([0.25,0.35])

f1
```

```
[ ]: a.pproc['digfmin']=2000  # set appropriate digital filter parameters
a.pproc['digfmax']=3500
a.digfilt()  # perform digital filter operation
```

```
[ ]: ## TASKS:
## fine tune with set_xlim and set_ylim parameters to zoom in on the echo
f2=plt.figure()
ax2=f2.subplots()
```

```

a.plottm(ax2,5)    # plot the 5th scan (the 1st scan doesn't have signal because
    ↳the polarization is too short)
ax2.set_ylim([-0.15,0.15])
ax2.set_xlim([0.25,0.35])

```

```

[ ]: f3=plt.figure()
ax3 = f3.subplots()

a.pproc['ftmin']=0                # time interval for Fourier transform (0 =
    ↳all data)
a.pproc['ftmax']=0
a.pproc['ffmin']=0                # frequency interval for spectrum display
    ↳(0 = all data)
a.pproc['ffmax']=0
a.proc()                          # calculate Fourier transform of the data
    ↳in a
## this will use the digitally filtered data from before. Instead, the original
    ↳data can be processed by loading it again.

a.plotfrq(ax3,0)                  # plot the frequency domain data of the
    ↳first scan from the data set

## TASKS:
## change parameter "ftmin" and "ftmax" to select the time interval
    ↳corresponding to the echoes for the Fourier transform
## change parameter "ffmin" and "ffmax" to select the frequency range of the
    ↳NMR signal
## include statements to label axes
## use statements to change appearance such as font size, etc.

```

```

[ ]: # Polarization-duration-resolved integration of peaks on NMR spectra
f4=plt.figure()
ax4=f4.subplots()

a.pproc['intmin']=0              # set correct frequency range for integration
a.pproc['intmax']=0

a.integrate()                    # perform integration

#find the starting polarization duration and increment, then set the correct
    ↳x-axis
dx=a.pinc["inc"][0]
x0=a.ppre["poltime"]
print('x0 =',x0,'s', dx =',dx','s')    # x0 is the starting polarization
    ↳duration, and dx is the increment

```

```

a.idt.x0=x0
a.idt.dx=dx

a.idt.plot(ax4,disp=[0])           # disp=0 plots only the NMR signal
    ↳ in trace 0

ax4.set_xlabel("seconds [s]")
ax4.set_ylabel("Y LABEL")

## TASKS:
## change the intmin and intmax parameters to select the correct frequency
    ↳ range for integration
## use set_xlabel and set_ylabel to set the labels to get a publication quality
    ↳ figure

```

Fitting of the integral to time axis. NOTE: For some results to fit, optimize the initial conditions

```

[ ]: # Fitting of the integral

ax5 = plt.figure().subplots()
a.idt.plot(ax5,disp=[0])           # to be overlayed by fitted curve,
    ↳ disp=0 plots only the NMR signal in trace 0

def fun(t,a,b,c):
    return FORMULA                 # INPUT the formula used for
    ↳ fitting. Use "np.exp()" for exponential, and t for time-axis.

y = a.idt.dta[0]
x = np.linspace(a.idt.x0,a.idt.x0+a.idt.dx*(a.pinc['n'][0]-1),a.pinc['n'][0])

a.p1,a.p2=scipy.optimize.curve_fit(fun,x,y,p0=[y[0],1.5,0],maxfev=5000)
    ↳ # OPTIMIZE the initial conditions

print('T\u2081 = ',round(1/a.p1[1],SF1),'±',round(np.linalg.eig(a.p2)[0][1]**0.
    ↳ 5,SF2),'s')

# REPLACE "SF1" and "SF2" with positive integers to report the fitting results
    ↳ with correct significant figures

x=np.linspace(x[0],x[-1],1000)     # use 1000 points to
    ↳ generate a smooth curve
a.fit_points = a.p1[0]*np.exp(-a.p1[1]*x)+a.p1[2]
pl,=ax5.plot(x,a.fit_points,'r-')

ax5.set_xlabel("seconds [s]")       # SET the labels to get a
    ↳ publication quality figure
ax5.set_ylabel("Y LABEL")

```

```
pl.figure.set_tight_layout('pad')  
pl.figure.canvas.draw()
```

```
## TASKS:
```

```
## change the initial fitting parameters to obtain proper fitting
```

```
## report the fitted relaxation constants with proper significant figures
```

```
## use set_xlabel and set_ylabel to set the labels to get a publication quality  
↪ figure
```

```
## adjust appearance of figure as needed
```