

week3

August 23, 2023

Notebook file for Week 3, Diffusion experiment

Import libraries. The nmrbase folder needs to be located within the folder containing this Jupyter notebook

```
[ ]: import numpy as np
import scipy
import matplotlib.pyplot as plt
import nmrbase.exbase as exbase
import nmrbase.expdata as expdata
```

Diffusion NOTE: To analyze and report multiple datasets, simply copy the necessary blocks of code.

```
[ ]: filename = r"../DIRECTORY/FILENAME"    #Defines the path to the data file. Here,
      ↪the path is relative to the current folder.
```

```
[ ]: a = exbase.exbase()
a.load(filename)                                # load data

f1=plt.figure()
ax1=f1.subplots()
a.plottm(ax1,1)
```

```
[ ]: ## TASKS:
## fine tune with set_xlim and set_ylim parameters to zoom in on the echo

ax1.set_ylim([VALUE,VALUE])
ax1.set_xlim([VALUE,VALUE])

f1
```

```
[ ]: a.pproc['digfmin']=1500    # set appropriate digital filter parameters
a.pproc['digfmax']=3500
a.digfilt()                    # perform digital filter operation
```

```
[ ]: ## TASKS:
## fine tune with set_xlim and set_ylim parameters to zoom in on the echo

f2=plt.figure()
```

```
ax2=f2.subplots()

a.plottm(ax2,1)    # plot the 1st scan
ax2.set_ylim([VALUE,VALUE])
ax2.set_xlim([VALUE,VALUE])
```

```
[ ]: ## TASKS:
## change parameter "ftmin" and "ftmax" to select the time interval
    ↳corresponding to the echoes for the Fourier transform
## change parameter "ffmin" and "ffmax" to select the frequency range of the NMR
    ↳signal
## include statements to label axes
## use statements to change appearance such as font size, etc.

f3=plt.figure()
ax3 = f3.subplots()

a.pproc['ftmin']=VALUE                # time interval for Fourier transform
    ↳(0 = all data)
a.pproc['ftmax']=VALUE
a.pproc['ffmin']=VALUE                # frequency interval for spectrum
    ↳display (0 = all data)
a.pproc['ffmax']=VALUE
a.pproc['dispper']=0.2                # leave 20% space between each acquired
    ↳spectrum
a.proc()                             # calculate Fourier transform of the data
    ↳in a
## this will use the digitally filtered data from before. Instead, the original
    ↳data can be processed by loading it again.

a.plotfrq(ax3,0)                      # plot the frequency domain data of the
    ↳first scan from the data set
```

```
[ ]: # Gradient-duration-resolved integration of peaks on NMR spectra

## TASKS:
## change the intmin and intmax parameters to select the correct frequency range
    ↳for integration
## use set_xlabel and set_ylabel to set the labels to get a publication quality
    ↳figure

f4=plt.figure()
ax4=f4.subplots()

a.pproc['intmin']=VALUE                # set correct frequency range for integration
a.pproc['intmax']=VALUE
```

```

a.integrate()                                # perform integration

#find the starting gradient duration and increment, then set the correct x-axis
dx=a.pinc["inc"][0]
x0=a.p["p2"]
print('x0 =',x0,'s , dx =',dx,'s')          # x0 is the starting gradient
    ↳duration, and dx is the increment
a.idt.x0=x0
a.idt.dx=dx

a.idt.plot(ax4,disp=[0])                     # disp=0 plots only the NMR signal in
    ↳trace 0

ax4.set_xlabel("seconds [s]")
ax4.set_ylabel("Y LABEL")

```

Fitting of the integral to time axis. NOTE: For some results to fit, optimize the initial conditions

```

[ ]: # Fitting of the integral

## TASKS:
## change the initial fitting parameters to obtain proper fitting
## report the fitted gradient strength/diffusion coefficient with proper
    ↳significant figures
## use set_xlabel and set_ylabel to set the labels to get a publication quality
    ↳figure
## adjust appearance of figure as needed

ax5 = plt.figure().subplots()
a.idt.plot(ax5,disp=[0])                     # to be overlayed by fitted curve,
    ↳disp=0 plots only the NMR signal in trace 0
big_delta=a.p.get('tau',0.1)                 # time interval between gradients

def fun(t,a,b):
    return FORMULA                           # INPUT the formula used for fitting.
    ↳ Use "np.exp()" for exponential, and t for small-delta (gradient duration).

y = a.idt.dta[0]
x = np.linspace(a.idt.x0,a.idt.x0+a.idt.dx*(a.pinc['n'][0]-1),a.pinc['n'][0])

a.p1,a.p2=scipy.optimize.curve_fit(fun,x,y,p0=[A_VALUE,B_VALUE],maxfev=5000)
    ↳ # SELECT the initial conditions, especially the exponential index

print(round(a.p1[1],SF1),'±',round(np.linalg.eig(a.p2)[0][1]**0.5,SF2))
    ↳ # REPLACE "SF1" and "SF2" with positive integers to report the
    ↳fitting results with correct significant figures

```

```

x=np.linspace(x[0],x[-1],1000)                                # use 1000 points to
↳generate a smooth curve
a.fit_points = a.p1[0]*np.exp(-a.p1[1]*x**2*(big_delta-x/3))
pl,=ax5.plot(x,a.fit_points,'r-')

ax5.set_xlabel("seconds [s]")                                # SET the labels to get a
↳publication quality figure
ax5.set_ylabel("Y LABEL")
pl.figure.set_tight_layout('pad')
pl.figure.canvas.draw()

```