

WPT CCEE Mock

Total points 7/40 ?

0 of 0 points

Name *

zdcvsdv

Centre *

Juhu ▼

PRN *

14

Questions

7 of 40 points



✗ How can you make an e-mail link? *

0/1

- ☐ A) < a href="xxx@yyy">
- ☒ B) < mail href="xxx@yyy">
- ☐ C) < a href="mailto:xxx@yyy">
- ☐ D) < mail>xxx@yyy

✗

Correct answer

- ☒ C) < a href="mailto:xxx@yyy">

✓ Which of the following is not a difference between HTML and XHTML? * 1/1

- ☒ A) Charset in both html and xhtml is "text/html"
- ☐ B) Tags and attributes are case-insensitive in HTML but not in XHTML
- ☐ C) Special characters must be escaped using character entities in XHTML unlike HTML
- ☐ D) Charset in html is "text/html" where as in xhtml it is "application/xml+xhtml"

✓



✗ Which of the following is not a HTML5 tag? *

0/1

- ☒ A) <track>
- ☐ B) <video>
- ☐ C) <slider>
- ☐ D) <source>

✗

Correct answer

- ☒ C) <slider>

✗ What will be the output of following CSS code snippet? *

0/1

`h1 {color: red text-decoration: underline; font-style: italic;}`

- ☒ A) color: red, text-decoration: underline works
- ☐ B) only font-style: italic works
- ☐ C) color: red, text-decoration: underline and font-style: italic all works
- ☐ D) text-decoration: underline and font-style: italic works

✗

Correct answer

- ☒ B) only font-style: italic works



✗ What will be the output of the following CSS code snippet? *

0/1

```
span {  
    border: 1px solid red;  
    outline: green dotted thick;  
}
```

- ☒ A) All span elements will have a green thick border and a red outline ✗
- ☐ B) All span elements will have a red border and a green dotted outline
- ☐ C) All span elements will have a outer green dotted border and an inner red border
- ☐ D) All span elements will have an outer red border and inner green dotted border

Correct answer

- ☒ C) All span elements will have a outer green dotted border and an inner red border

✓ Which of the following CSS Property sets the stacking order of positioned *1/1 elements?

- ☐ A) y-index
- ☒ B) z-index ✓
- ☐ C) x-index
- ☐ D) all of the mentioned



✗ What will be the output of the following JavaScript code? *

0/1

```
<p id="demo"></p>
<script>
var js = 10;
js *= 5;
document.getElementById("demo").innerHTML = js;
</script>
```

- ☐ A) 10
- ☐ B) 50
- ☐ C) 5
- ☒ D) Error

✗

Correct answer

- ☒ B) 50



✖ What will be the output of the following JavaScript code? *

0/1

```
// JavaScript Comparison Operators
function compare()
{
    int num=2;
    char b=2;
    if(a==B)
        return true;
    else
        return false;
}
```

- ☐ A) false
- ☐ B) true
- ☒ C) compilation error
- ☐ D) runtime error

✖

Correct answer

- ☒ B) true



✗ Will the following JavaScript code work? *

0/1

var js = (function(x) {return x*x;})(10));

- ☐ A) Exception will be thrown
- ☒ B) Memory leak
- ☐ C) Error
- ☐ D) Yes, perfectly no doubt

✗

Correct answer

- ☒ D) Yes, perfectly no doubt

✗ Which of the following is not an error in JavaScript? *

0/1

- ☐ A) Missing of Bracket
- ☐ B) Division by zero
- ☒ C) Syntax error
- ☐ D) Missing of semicolons

✗

Correct answer

- ☒ B) Division by zero



✗ What is the observation made in the following JavaScript code? *

0/1

```
var count = [1,,3];
```

- ☐ A) The omitted value takes "undefined"
- ☐ B) This results in an error
- ☒ C) This results in an exception
- ☐ D) The omitted value takes an integer value

✗

Correct answer

- ☒ A) The omitted value takes "undefined"

✗ What will the following jQuery code do? *

0/1

```
$(document).ready(function(){  
    $("pre").siblings();  
});
```

- ☒ A) It will return all parent elements of <pre> element
- ☐ B) It will return all children elements of <pre> element
- ☐ C) It will return all sibling elements of <pre> element
- ☐ D) It will return all nonrelative elements of <pre> element

✗

Correct answer

- ☒ C) It will return all sibling elements of <pre> element



✗ What is the use of jQuery Selectors? *

0/1

- ☐ A) jQuery selectors are used to select and manipulate HTML element(s).
- ☒ B) jQuery selectors are used to import the HTML elements from the other file. ✗
- ☐ C) jQuery selectors are used to select and manipulate JSON elements(s).
- ☐ D) jQuery selectors are used to select and manipulate ReactJS classes.

Correct answer

- ☒ A) jQuery selectors are used to select and manipulate HTML element(s).

✗ Which is the correct jQuery selector to select all <div> elements with class name "new"?

*0/1

- ☒ A) \$(".new") ✗
- ☐ B) \$("div.new")
- ☐ C) \$(".div.new")
- ☐ D) \$(".div#new")

Correct answer

- ☒ B) \$("div.new")



✗ Which of the following is an equivalent replacement of `$(document).ready(f)`?

*0/1

- ☐ A) `jQuery(f)`
- ☐ B) `$(f)`
- ☒ C) `#(f)`
- ☐ D) `read(f)`

✗

Correct answer

- ☒ B) `$(f)`

✓ Which of the following jQuery method is used to merge the content of two or more objects into the first object?

*1/1

- ☒ A) jQuery `extend()` method
- ☐ B) jQuery `eq()` method
- ☐ C) jQuery `data()` method
- ☐ D) jQuery `param()` method

✓



✓ In the below statement, what is the type of "student"? *

1/1

```
{"student":{"name":"Alvin", "age":21, "city":"Mumbai"}}
```

- ☐ A) String
- ☐ B) Array
- ☒ C) Object
- ☐ D) Class



✗ Which of the following code will throw an error? *

0/1

- ☐ A) JSON.parse('{"name":" John", "age":30, "city":"New York"}');
- ☒ B) JSON.parse(null);
- ☐ C) JSON.parse(undefined);
- ☐ D) JSON.parse('');



Correct answer

- ☒ C) JSON.parse(undefined);



✗ Which number types are available in the JavaScript but not supported in the JSON? *0/1

- ☐ A) Fractional and Rational
- ☒ B) Infinity and Rational
- ☐ C) Rational and Irrational
- ☐ D) Infinity and NaN

✗

Correct answer

- ☒ D) Infinity and NaN

✗ Which method returns the specific header information? *

0/1

- ☐ A) getResponseHeader()
- ☐ B) getSpecifcHeader()
- ☒ C) getHeaderOnly()
- ☐ D) getHeaderInfo()

✗

Correct answer

- ☒ A) getResponseHeader()



✗ How to convert the below statement to the synchronous request?
`xhttp.open("GET", "info.php", true);`

*0/1

- ☐ A) Convert the third parameter to "false"
- ☐ B) Convert the third parameter to "sync"
- ☒ C) Convert the first parameter to "sync_GET"
- ☐ D) All of the above

✗

Correct answer

- ☒ A) Convert the third parameter to "false"

✗ When do uncaught exceptions generate events? *

0/1

- ☐ A) When handlers are registered
- ☐ B) When handlers are deregistered
- ☒ C) When handler functions are called
- ☐ D) When handlers do not have a matching catch clause

✗

Correct answer

- ☒ A) When handlers are registered



✗ What will be the return value of the write() method when the Node cannot *0/1 write the data immediately and has to buffer it internally?

- ☒ A) 0
- ☐ B) 1
- ☐ C) True
- ☐ D) False

✗

Correct answer

- ☒ D) False

✓ Which method of fs module is used to write a file? *

1/1

- ☐ A) fs.write(path, flags[, mode], callback)
- ☒ B) fs.writeFile(path, flags[, mode], callback)
- ☐ C) fs.writePath(path, flags[, mode], callback)
- ☐ D) None of the above.

✓



✗ Which of the following API creates a server? *

0/1

- ☐ A) net.createServer([options][, connectionListener])
- ☐ B) net.connect(options[, connectionListener])
- ☒ C) net.createConnection(port[, host][, connectListener])
- ☐ D) None of the above.

✗

Correct answer

- ☒ A) net.createServer([options][, connectionListener])

✗ What is the default scope in the Node.js application ? *

0/1

- ☒ A) Global
- ☐ B) Local
- ☐ C) Global Function
- ☐ D) Local to object

✗

Correct answer

- ☒ B) Local



✗ XML is ? *

0/1

- ☐ A) Platform Independent
- ☒ B) Language Independent
- ☐ C) Both A & B
- ☐ D) None

✗

Correct answer

- ☒ C) Both A & B

✗ Comment in XML document is given by *

0/1

- ☐ A) <?-- -->
- ☐ B) <!-- --!>
- ☐ C) <!-- -->
- ☒ D) </-- -->

✗

Correct answer

- ☒ C) <!-- -->



✗ Which of the following method can be used with any of the HTTP verbs: get, set, put, or delete? *0/1

- ☐ A) app.get(route, callback)
- ☒ B) res.send()
- ☐ C) app.listen(port, [host], [backlog], [callback])
- ☐ D) app.method(path, handler)

✗

Correct answer

- ☒ D) app.method(path, handler)

✓ Which of the following do you need to install to acquire cookie abilities in Express.js? *1/1

- ☒ A) cookie-parser
- ☐ B) Cookie—
- ☐ C) Parser_cookie
- ☐ D) Use_cookies

✓



✗ Debug is ____ by default in express.js? *

0/1

- ☐ A) On
- ☐ B) Off
- ☒ C) Debug feature is not available.
- ☐ D) Itna kon padhta h

✗

Correct answer

- ☒ B) Off

✗ In React what is used to pass data to a component from outside? *

0/1

- ☐ A) setState
- ☒ B) render with arguments
- ☐ C) props
- ☐ D) PropTypes

✗

Correct answer

- ☒ C) props



✗ How can you access the state of a component from inside of a member function? *0/1

- ☒ A) this.getState()
- ☐ B) this.values
- ☐ C) this.prototype.stateValue
- ☐ D) this.state

✗

Correct answer

- ☒ B) this.values

✗ How many elements does a react component return? *

0/1

- ☒ A) 2 Elements
- ☐ B) 1 Element
- ☐ C) Multiple Elements
- ☐ D) Depends on it's KARMA.

✗

Correct answer

- ☒ B) 1 Element



✗ What is the use of "webpack" command in React.js? *

0/1

- ☒ A) The "webpack" command is used to transpile all the JavaScript down into one file. ✗
- ☐ B) It runs React local development server.
- ☐ C) It is a module bundler.
- ☐ D) None of the above.

Correct answer

- ☒ C) It is a module bundler.

✗ What will happen if you render an input element with disabled = {false}? * 0/1

- ☐ A) It will be rendered as disabled
- ☒ B) It will not be rendered at all ✗
- ☐ C) It will be rendered as enabled
- ☐ D) You cannot set it false.

Correct answer

- ☒ C) It will be rendered as enabled



✗ We can update the state in React.js by calling to setState() method. *0/1
These calls are:

- ☒ A) Synchronous in nature. ✗
- ☐ B) Asynchronous in nature.
- ☐ C) Are asynchronous but can be made synchronous when required.
- ☐ D) None of the above.

Correct answer

- ☒ B) Asynchronous in nature.

✓ In which of the following condition, the React.js Lifecycle method static *1/1
getDerivedStateFromProps(props, state) is called?

- ☐ A) The component is created for the first time.
- ☐ B) The state of the component is updated.
- ☒ C) Both of the above. ✓
- ☐ D) None of the above.



✗ Which of the following statement is correct about the Bootstrap wells? *0/1

- A) By default, the size of wells is medium.
B) Using .well-sm and .well-lg classes, we can change the size of wells.
C) The .well-sm class is for small wells, and the .well-lg class is for large wells. And both classes should be used in conjunction with .well class.

- ☐ 1. Only A
☒ 2. Both A & C
☐ 3. Both B & C
☐ 4. All A, B and, C

✗

Correct answer

- ☒ 4. All A, B and, C

✗ Which of the following is bootstrap's global default font-size? *

0/1

Select one:

- ☐ A) 10px
☐ B) 14px
☒ C) 12px
☐ D) 13px

✗

Correct answer

- ☒ B) 14px

FEEDBACK

0 of 0 points



I promise , I will study like never before and will Top the CCEE *

☒ Bolo Haan

How was your experience?

sadaF

This content is neither created nor endorsed by Google. - [Terms of Service](#) - [Privacy Policy](#)

Google Forms



