



University Institute of Engineering
Department of Computer Science & Engineering

EXPERIMENT: 3

NAME : Himanshi Kaushal

UID: 23BCS12735

BRANCH : BE-CSE

SECTION/GROUP : KRG-2A

SEMESTER : 5th

SUBJECT CODE : 23CSP-339

SUBJECT NAME : ADBMS

1. Aim Of The Practical :

[EASY] :

1. Basic table creation and Duplicate handling:

Generate an employee relation with single attribute ID. Retrieve the maximum ID value while excluding duplicates.

2 .Product Sales Analysis:

Select products which have never been sold.
Calculate the total quantity sold for each respective product.

[MEDIUM] :

1 . To identify the top earners in every department:

If multiple employees share the same highest salary within a department, all of them should be celebrated equally.
The final result should present the department name, employee name, and salary of these top-tier professionals arranged by department.

[HARD] :

1 . To merge the datasets and identify each unique employee (by EmpID) along with their lowest recorded salary across both systems.

Combine two tables A and B.

Return each EmpID with their lowest salary, and the corresponding Ename.

2. Tools Used : Microsoft SQL Server

3. Code :

EASY:

Q_1:

```
create table employees_tbl(
    e_id int
);
insert into employees_tbl values
(1),
(1),
(2),
(3),
(3),
(4),
(5),
(5),
(6),
(7),
(7);
select max(a.e_id) as max_distinct_id from (select e_id, count(e_id) as id_cnt from employees_tbl group by e_id) as a
where a.id_cnt = 1;
```

Q_2:

-- select product which has not been sold once

-- find the total quantity of sold for each respective product

```
create table tbl_products
(
    id int primary key identity,
    [name] nvarchar(50),
    [description] nvarchar(250)
)
```

```
create table tbl_productsales
(
    id int primary key identity,
    productid int foreign key references tbl_products(id),
    unitprice int,
    quantitysold int
)
```

```
insert into tbl_products values ('tv','52 inch black color lcd tv')
insert into tbl_products values ('laptop','very thiin black color acer laptop')
insert into tbl_products values ('desktop','hp high performance desktop')
insert into tbl_productsales values (3,450,5)
insert into tbl_productsales values (2,250,7)
insert into tbl_productsales values (3,450,4)
insert into tbl_productsales values (3,450,9)
```

```
select * from tbl_products where tbl_products.id not in (select distinct productid from tbl_productsales);
```

```
select name, (select sum(tbl_productsales.quantitysold) from tbl_productsales where productid =
tbl_products.id) as [product sales] from tbl_products;
```

MEDIUM :

Q_1 :

```
create table department (  
    id int primary key,  
    dept_name varchar(50)  
);  
  
-- create employee table  
create table employee (  
    id int,  
    name varchar(50),  
    salary int,  
    department_id int,  
    foreign key (department_id) references department(id)  
);  
  
-- insert into department table  
insert into department (id, dept_name) values  
(1, 'it'),  
(2, 'sales');  
  
-- insert into employee table  
insert into employee (id, name, salary, department_id) values  
(1, 'joe', 70000, 1),  
(2, 'jim', 90000, 1),  
(3, 'henry', 80000, 2),  
(4, 'sam', 60000, 2),  
(5, 'max', 90000, 1);  
  
select d.dept_name, e.name, e.salary, d.id  
from department as d  
inner join  
employee as e  
on  
e.department_id = d.id  
where e.salary in  
(  
    select max(e2.salary)  
    from employee as e2  
    where e2.department_id = e.department_id  
)  
order by d.dept_name
```

HARD :

Q_1 :

```
create table table_a (  
    empid int primary key,  
    ename varchar(50),  
    salary int  
);  
  
create table table_b (  
    empid int primary key,  
    ename varchar(50),  
    salary int  
);  
  
insert into table_a(empid, ename, salary) values
```

```
(1, 'aa', 1000),
(2, 'bb', 300);
```

```
insert into table_b(empid, ename, salary) values
(2, 'bb', 400),
(3, 'cc', 100);
```

```
select empid, ename, min(salary) as minsalary
from (
select *from table_a
union all
select *from table_b
) as combined
group by empid, ename;
```

4. Output:

[EASY]:

Q_1:

```
Output:
max_distinct_id
-----
6
```

Q_2:

```
Output:
id      name      description
-----
1 tv      52 inch black color lcd tv
name      product sales
-----
tv      NULL
laptop      7
desktop      18
```

[MEDIUM]:

Q_1:

```
Output:
dept_name      name      salary      id
-----
IT      MAX      90000      1
IT      JIM      90000      1
SALES      HENRY      80000      2
```

[HARD]:

Q_1:

Output:		
empid	ename	minsalary

1	aa	1000
2	bb	300
3	cc	100

5. Learning Outcomes :

- Understood how to create a basic table and remove duplicates while retrieving values.
- Understood how to analyze product sales data by finding unsold products and calculating total quantities.
- Understood how to identify top earners in each department, including handling ties fairly.
- Understood how to merge datasets from multiple sources to get unified employee records.
- Understood how to use aggregate functions to find the lowest salary for each employee across systems.