

```

package main

import "fmt"

func main() {
    var name string
    s := []string{}

    fmt.Print("Enter student name: ")

    fmt.Scan(&name)
    s = append(s, name)
    fmt.Println("slice is print")
    fmt.Println(s)

    fmt.Print("the append function\n")
    fmt.Print("Enter another student name: ")

    fmt.Scan(&name)
    s = append(s, name)
    fmt.Print("the new slice is print: ")
    fmt.Println(s)

    fmt.Println("that is update function")
    fmt.Println("Enter new name for first student: ")

    fmt.Scan(&name)
    s[0] = name
    fmt.Println("new name after update is |:")

    fmt.Println(s)

    fmt.Println("remove by index")
    s = s[1:]
    fmt.Println(s)
}

```

Output:

```

PS C:\Users\hp\OneDrive\Desktop\NEW AGE PROGRAMMING> go run "c:\Users\hp\OneDrive\Desktop\NEW AGE PROGRAMMING\lab2\arryss.go"
Enter student name:
Rahul
slice is print
[Rahul]
the append function
Enter another student name: Sita
the new slice is print: [Rahul Sita]
that is update function
Enter new name for first student:
Ajay
new name after update is :
[Ajay Sita]
remove by index
[Sita]
PS C:\Users\hp\OneDrive\Desktop\NEW AGE PROGRAMMING>

```

Code 2;

```
package main
```

```
import "fmt"
```

```
func main() {
```

```
    var name string
```

```
    s := []string{}
```

```
    fmt.Print("Enter student name: ")
```

```
        fmt.Scan(&name)
```

```
        s = append(s, name)
```

```
    fmt.Println("slice is print")
```

```
    fmt.Println(s)
```

```
    fmt.Print("the append function\n")
```

```
    fmt.Print("Enter another student name: ")
```

```
    fmt.Scan(&name)
```

```
    s = append(s, name)
```

```
        fmt.Print("the new slice is print: ")
```

```
    fmt.Println(s)
```

```
    fmt.Println("that is update function")
```

```
    fmt.Println("Enter new name for first student: ")
```

```
    fmt.Scan(&name)
```

```
    s[0] = name
```

```
    fmt.Println("new name after update is :")
```

```
fmt.Println(s)
```

```
fmt.Println("remove by index")
```

```
s = s[1:]
```

```
fmt.Println(s)
```

```
}
```