Question	Answer	
which of the function operator can not be overloaded ? <= >= ?: == *	ans: ?:	
Which of the following anomalies is/are solved using normalization? Multiple answers may be correct. PL ONE OR MORE Creation anomalies Insertion anomalies Delion anomalies Upitate anomales	**ans: Insertion anomalies** Deletion anomalies Update anomalies all three are correct	
What kind of joins is a default in SQL? P ONE option O inner Outer Self None of the above	ans: inner	
Which of the following statements is/are correct? Multiple answers may be correct. Pick ONE OR MORE options A prime attribute is an attribute that is a part of the candidate key. A prime attribute is an attribute that is a part of the primary key. A non-prime attribute is an attribute that is not a part of the prime key. None of these	ans:A prime attribute is an attribute that is a part of the candidate key. A prime attribute is an attribute that is a part of the primary key. A non-prime attribute is an attribute that is not a part of the prime key	
Select the expression that causes a MySQL error. Pick ONE option SELECT customer_id, ANY_VALUE(amount) FROM transactions GROUP BY customer_id SELECT customer_id, RAND(amount) FROM transactions GROUP BY customer_id SELECT customer_id, SUBSTRING_INDEX(GROUP_CONCAT(amount ORDER BY RAND()), 'i, 1) FROM transactions GROUP BY customer_id none of the above, all expressions are correct	ans: select customer_id , substring _index....	

Question	Answer	
Which of the following statements) are NOT correct: Pick ONE OR MORE options The PRIMARY KEY must be unique and not null for each table. The DROP command is used to remove the table definition and its contents whereas the TRUNCATE command to delete all the rows from the table DELETE command is a DDL command whereas DROP is a DML command ACD properties in databases refer to Atomicity, Complexity, Isolation, and Duplicacy	answer both C & D ans: DELETE command is a DDL comnd where as drop is DML command or ACID properties in dbs reffers to atomicity,comp, iso and duplicacy ans: DELETE command is a DDL comnd where as drop is DML command	
Select the extraneous expression (not the same as the others). Pick ONE option SELECT FROM categories ORDER BY id SELECT FROM categories ORDER BY id ASC SELECT FROM categories ORDER BY id DESC None of the above, all expressions are the same	ans: SELECT FROM categories ORDER BY is DESC	

double read_double (FILE * fp) {
double d;
 	
assert(fp != NULL);
 	
fscanf(fp, " %lf", d);
 	
return d;
}
The code above contains a common error. Which one of the fllowing describes it?
 	
Pick ONE option
 	
fscanf() will fail to match floating-point numbers not preceded by whitespace.
 	
The format specifier %lf indicates that the corresponding argument should be long double rather than double.
 	
The call to fscanf() requires a pointer as its last argument.
 	
The format specifier %lf is recognized by fprintf() but not by fscanf().
 	
d must be initialized prior to usage.
	ans:The call to fscanf() requires a
	pointer as its last argument.	

Question	Answer	
The referential integrity constraint of a relational database can be specified with the help of? P ONE option Primary Key Secondary Key Foreign Key All of the above	ans: Foreign Key	
The all-or-none property is commonly referred to as___ Pick ONE option Isolation Durability Atomicity None of the mentioned	ans: Automicity	
What does the following query do? UPDATE student SET marks = marks 1.20; Pick ONE option Increase the marks by 120% Decrease the marks by 20% Increase the marks by 20% None of the above	ans: Increase the marks by 20 %	
In a Company, 26 employees are in HR, 32 are in IT, and 30 are in Management. Of these, 5 employees are in all three roles while 37 are in only one. How many employees are in 2 of the 3 roles?	ans: 46	

void incr();
int main(){
incr();
incr();
incr();
return 0;
}
void incr(){
static int i;
cout<<++i<<" ";
} Output of the code;
	ans: 1 2 3	

Question	Answer	
What command should you try if DBMS_OUTPUT.PUT_LINE is not doing what it is supposed to do? Pick ONE option SET ECHO ON SET DISPLAY ON SET TERMOUT ON SET SERVEROUTPUT ON	ans: SET SERVEROUTPUT ON	
it possible to create an object of an empty class type such as: class xyz If so, what is the size of such an object? Pick ONE option Yes, it is possible, and its size is zero. Yes, it is possible, add its size is greater than zero. No, it is not possible to create an empty class; it results in a compiler error. No, it results in a runtime error:	ans:Yes, it is possible , add its size is greater than zero	
What value does ? represent? X32G, V16J ,T8M, ?, P2S Pick ONE option S64N R4P R4Q S8P	ans : R4P	
What kind of Joins is a default in SQL? Pick ONE option Inner Outer Self None of the above	ans : inner	

Question	Answer	
Is it possible to create an object of an empty class type such as: class xyz {}; If so, what is the size of such an object? Pick ONE option 1.Yes, it is possible, and its size is zero. 2.Yes, it is possible, and its size is greater than zero. 3.No, it is not possible to create an empty class it results in a compiler error. 4.No, it results in a runtime error	ans : 2.Yes, it is possible, and its size is greater than zero.	
Choose the correct explanation of the next query: SELECT FROM users clients Pick ONE option 1.Selects everything in the "users" table, then adds columns from the "clients" table. 2.If the "users" table exists, selects everything from there. Otherwise, queries the "clients" t 3.Selects everything in the "users" table, then assigns the clients allas 4.Selects everything in the "users" table, then adds rows from the "clients" table	ans : 2.If the "users" table exists, selects everything from there. Otherwise, queries the "clients" t	

Two Strings are said to be the same if they are of teh same length and have same character at each at index. Backspacing in a string removes the previous character in the string.
 	
Given two strings containing lowercase english letters and the character '#' which represents a backspace key, determine if the two final strings are equal. Return 1 if they are equal or 0 if they are not. Note that backspacing an empty string results in an empty string.
 	
Example:
s1 = "axx#bb#c"
s2 = "axbd#c#c"
after operation s1 = "axbc" s2 = "axbc" : hence same
	#include <bits/stdc++.h>
	using namespace std;
	
	int solve(string s1, string s2) {
	  stack<char> stack1, stack2;
	  for (char c : s1) {
	  if (c == '#' && !stack1.empty()) {
	  stack1.pop();
	  } else if (c != '#') {
	  stack1.push(c);
	  }
	  }
	  for (char c : s2) {
	  if (c == '#' && !stack2.empty()) {
	  stack2.pop();
	  } else if (c != '#') {
	  stack2.push(c);
	  }
	  }
	  return stack1 == stack2;
	}
	int main()
	{
	  string str1, str2;
	  cin >> str1 >> str2;
	  cout << solve(str1, str2);
	  return 0;
	}	

Question	Answer	
what kind of join is default in sql	inner join	

what is the output of the following code? #include<stdio.h>
int main()
{
int s=0;
while(s++<10)
{
if(s<4 && s<9)
continue;
printf("\n%d\t",s);
}
return 0;
}
	4 5 6 7 8 9 10	

the sql command select ROUND(45.926,-2) FROM DUAL	prints 0	
What is the value of the postfix expression 6 3 2 4 + – *?	-18	
what is relation in rdbms	table	
"curated" is coded into "ufeasvd" how would amazing be encoded?	JOHZBNB	

#include <iostream>
 	
using namespace std;
 	
class Integer{
int num;
public: Integer(){
num=0;
cout<<"1";
}
Integer(int arg){
cout<<"2";
num=arg;
}
int getValue(){
cout<<"3";
return num;
}
};
int main(){
Integer i;
i=10;
cout<<i.getValue();
return 0;
}
	12310	

The average time required to perform a successful sequential search for an element in an array A(1 : n) is given by	(n+1)/2	
which of the path is valid for depth first search from node 1.	1 5 4 2 3 0	
Evaluate the prefix expression: *+2-21/-42+-531		
in a virtual memory system that uses optimal page replacement policy, How many page fault occur number of frames: 4 Refrences: 1 2 3 4 4 4 5 5 3 2 1 4 2 1 5	6	

Question	Answer	
in a virtual memory system that uses (MRU) most recently used page replacement policy, How many page fault occur number of frames: 4 Refrences: 1 2 3 4 2 5 2 6 4 1 5 6 5 2 4 3	9	
consider the following table arrival and burst time for four processor the non premptive forst come first serve schduling algorithm is used. schduling is caary only at the arrival or completion of process. find the avg turn around time for the process.	10.25	
In a virtual memory system that uses (LRU) Least recently used page replacement policy calculate the number of page fault that occur. number of frames: 4 references: 1 4 3 2 1 2 6 2 1 5 6 3 2 4 5	10	
In a virtual memory system that uses (FIFO) used page replacement policy calculate the number of page fault that occur. number of frames: 4 references: 1,2,3,4,5,1,3,1,2,5	7	
what value does '?' represents?		
Which of the following statement(s) is/are true? Pick ONE OR MORE options Each thread within a process has its own separate memory space. Each thread within a process is independent with respect to the code section. Each thread within a process has its own program counter and stack space. None of the above	d	
which of the following statements is true about heap data structure and it's role in sorting? a) heap sort function in o(nlogn) asymptotic complexity and heap of n elements may b constructed in o(n) asymptotic c b)Heap sort functions in o(nlogn) time and heap of n elements may be no better than o(nlogn) time. C) heap sort functions o(n^2) time and heap of n elements may be constructed no better than o(nlogn) time d) none of the above correct	b	
A10 A12 B18 B42 _ C888?	C162	
Which expression causes a MySQL error? Pick ONE option a)CREATE TABLE users (first_name VARCHAR(255), last name VARCHAR(255), CONSTRAINT unique_name UNIQ b)CREATE TABLE users (first name VARCHAR(255) UNIQUE, last name VARCHAR(255) UNIQUE) c)CREATE TABLE users (first_name VARCHAR(255), last_name VARCHAR(255), UNIQUE (first_name, last_name)) d)None of the above, all expressions are correct	b)CREATE TABLE users (first name VARCHAR(255) UNIQUE, last name VARCHAR(255) UNIQUE)	

Question	Answer	
Consider four processes, PILIP[2], P(3), P[4] They are synchronized using four mutex locks as follow wait (m[1]); wait (m[(1+1) N4]); #Critical Section release (m[1]); release (m[(1+1) %4]): Which of the following conditions of a deadlock e mer for the above synchronization? Pick ONE OR MORE options Mutual exclusion of resources using locks Hold and wait No preemption	Mutual Exclusion of resources using locks Hold and wait	

struct customer ptr = malloc(sizeof(struct customer));
 	
Which of the following statements is used to reallocate ptr to be an array of **size**
 	
Pick ONE option
 	
ptr=realloc(ptr, 10* sizeof(struct customer));.
 	
realloc(ptr. 9* sizeof(struct customer));
 	
ptr malloc(9* sizeof(struct customer));
 	
ptr realloc(ptr, 9 sizeof(struct customer));
 	
realloc(ptr. 10* sizeof(struct customer));
	ptr = realloc(ptr, size * sizeof(struct customer));	

Given the following functional dependencies, find the highest normal form. Assume that the given relation is in 1NF alr R(ABCDEF) Functional Dependencies: BC -> E BE->F AF-> DE Pick ONE option INF 2NF 3NF Bcnf	the highest normal form for the given relation is BCNF.	

Question	Answer	
Out of the nine ingredients, a chef will use exactly. Given the following statements and the fact that the cnel will use de The ingredients are apricats, bacon cake, donuts, eggs figs gingerbread, hazelnut and ice cream If bacon is not used the chef well not use gngerbread hazelnut or ice cream 2 if apricots are used bacon and cake are used 3- donuts are not used, apricots are not used. 4. Eggs are used. Pick ONE option aprico cake donut cannot be determined	donut	
Given the following functional dependencies, find the highest normal form. Assume that the given relation is in 1NF already R(ABCDEF) Functional Dependencies: BC -> E BE->F AF-> DE Pick ONE option INF 2NF 3NF Bcnf	bcnf	
Which expression causes a MySQL error? Pick ONE option CREATE TABLE users (first name VARCHAR(255), last n	none of these	

Question	Answer	

#include<bits/stdc++.h>
using namespace std;
 	
class Integer{
 	
  int num;
 	
  public:
 	
  Integer (){
 	
  num = 0; cout << "1";
  }
 	
  Integer(int arg){
 	
  cout << "2"; num = arg;
  }
 	
  int getValue(){
 	
  cout << "3"; return num;
  }
 	
};
 	
  int main()
  {
 	
  Integer i;
 	
  i = 10;
 	
  cout << i.getValue();
 	
  return 0;
 	
 }
	12310	

// Online C++ compiler to run C++ program online
#include <iostream>
using namespace std;
int func(int i){
  if(i%2)return 0;
  else return 1;
}
int main() {
  // Write C++ code here
  int i = 3;
  i = func(i);
  i = func(i);
  cout << func(i) << endl;
  return 0;
}
	0	

Question	Answer	
In a Company, 26 employees are in HR, 32 are in IT, and 30 are in Management. Of these, 5 employees are in all three roles while 37 are in only one. How many employees are in 2 of the 3 roles?	46	
Out of the nine ingredients, a chef wants to use exactly five. Given the following state	2	
The ingredients are apricots, bacon, cake, donuts, eggs, figs, grapes, hazelnuts, and	3	
1. If bacon is not used, then grapes, hazelnuts, and ice cream are not used.	4	
2. If apricots are used then bacon and cake are used:	5	
3. If donuts are not used, apricots are not used.	ans - 5	
4. Apricots and eggs are used.		
The average time required to perform a successful sequential search for an element in an array A containing n elemen	(n+1)/2	
	logan	
	n(n+1)/2	
	n2	
	ans - (n+1) /2	
Which is the correct order of execution of operations in SQL? Pick ONE option	SELECT, FROM, JOIN, WHERE, GROUP BY, HAVING, ORDER BY SELECT, FROM, GROUP BY, WHERE, HAVING, ORDER BY FROM, GROUP BY, WHERE, ORDER BY, HAVING, SELECT SELECT, FROM, GROUP BY, HAVING, WHERE, ORDER BY	
	ans - SELECT, FROM, JOIN, WHERE, GROUP BY, HAVING, ORDER BY	
Which of the following statement(s) is/are correct about threads? Pick ONE OR MORE options	User threads are easier to manage than kernel threads. User threads allow us to do multiprocessing. Kernel threads are faster than user threads. The kernel doesn't know about the user-level thread.	
	ans - The kernel doesn't know about the user-level thread.	
char buf [] ="Hello World"; char *buf="Hello world!"; in terms of code generation , how do the two definations of buf, both presented above , differ?	Ans : The first definition certainly allows the contents of buf to be safely modified at runtime; the second definition does not.	
Out of the nine ingredients, a chef wants to use exactly five. given the following statements, how many of the 5 ingredients are known? the ingredients are apricots, bacon, cake, donuts, eggs, figs, grapes, hazelnuts, and ice cream. if bacon is not used, then grapes, hazelnuts, and ice cream are not used. if apricots are used then bacon and cake are used. if donuts are not used, apricots are not used. apricots and eggs are used. pick one option 2 3 4 5	If bacon is not used, then grapes, hazelnuts, and ice cream are not used	
Identify which of the following statements is true, with regards to the heap data structure and its role in sorting. Pick ONE option Heap sort functions in	ans : heap sort functions in O(nlogn) time and a heap of n elements may be constructed in no better than O(nlogn) time.	

Question	Answer	
the non -preemptive based scheduling algorithm is used . scheduling is carried out only at the arrival or complete find the average wating time for the above processes . Note : the higest priority process is scheduled first	ans : 2	
using preemptive priority based scheduling where a smaller priority value represents higher priority.choose the correct average response time for the following priority process arrival burst time 30 p1 1 5 10 p2 2 3 20 p3 4 1		
/* Read a double value from fp. */ double read_double (FILE * fp) { double d; assert(fp != NULL); fscanf(fp, %lf, d); return d; } The code above contains a common error. Which one of the following describes it?	The format specifier %lf indicates that the corresponding argument should be long double rather than double.	

Let we have P[0] , P[1] .. , P[4] be the processes and M[0] ,.....M[4] be the mutex locks(binary semaphore) i nitialised to 1 and process P[i] executes :
 	
wait(m[i]) ;
 	
wait(m[(i+1) mod 4];
 	
critical section
 	
signal(m[i]) ;
 	
signal(m[(i+1) mod 4];
	ans : circular wait	

In a Company, 26 employees are in HR, 32 are in IT, and 30 are in Management. Of these, 5 employees are in all three roles while 37 are in only one. How many employees are in 2 of the 3 roles?	ans : 36	