r	ANSWER			
what kind of join is default in sql	inner join			

what is the output of the following code? #include<stdio.h>
int main()
{
int s=0;
while(s++<10)
{
if(s<4 && s<9)
continue;
printf("\n%d\t",s);
}
return 0;
}
	4 5 6 7 8 9 10			

the sql command select ROUND(45.926,-2) FROM DUAL	prints 0			
What is the value of the postfix expression 6 3 2 4 + – *?	-18			
what is relation in rdbms	table			
"curated" is coded into "ufeasvd" how would amazing be encoded?	JOHZBNB			

#include <iostream>
 	
using namespace std;
 	
class Integer{
int num;
public: Integer(){
num=0;
cout<<"1";
}
Integer(int arg){
cout<<"2";
num=arg;
}
int getValue(){
cout<<"3";
return num;
}
};
int main(){
Integer i;
i=10;
cout<<i.getValue();
return 0;
}
	12310			

The average time required to perform a successful sequential search for an element in an array A(1 : n) is given by	(n+1)/2			
which of the path is valid for depth first search from node 1.	1 5 4 2 3 0			
Evaluate the prefix expression: *+2-21/-42+-531				
in a virtual memory system that uses optimal page replacement policy, How many page fault occur number of frames: 4 Refrences: 1 2 3 4 4 4 5 5 3 2 1 4 2 1 5	6			
in a virtual memory system that uses (MRU) most recently used page replacement policy, How many page fault occur number of frames: 4 Refrences: 1 2 3 4 2 5 2 6 4 1 5 6 5 2 4 3	9			
consider the following table arrival and burst time for four processor the non premptive forst come first serve schduling algorithm is used. schduling is caary only at the arrival or completion of process. find the avg turn around time for the proces	10.25			
In a virtual memory system that uses (LRU) Least recently used page replacement policy calculate the number of page fault that occur. number of frames: 4 references: 1 4 3 2 1 2 6 2 1 5 6 3 2 4 5	10			
In a virtual memory system that uses (FIFO) used page replacement policy calculate the number of page fault that occur. number of frames: 4 references: 1,2,3,4,5,1,3,1,2,5	7			
what value does '?' represents?				

The referential integrity constraint of a relational database can be specified with the help P ONE option Primary Key Secondary Key Foreign Key All of the above	ans: Foreign Key			
The all-or-none property is commonly referred to as___ Pick ONE option Isolation Durability Atomicity None of the mentioned	ans: Automicity			

What does the following query do? UPDATE student SET marks = marks 1.20; Pick ONE option Increase the marks by 120% Decrease the marks by 20% Increase the marks by 20% None of the above	ans: Increase the marks by 20 %			
In a Company, 26 employees are in HR, 32 are in IT, and 30 are in Management. Of these, 5 employees are in all three roles while 37 are in only one. How many employees are in 2 of the 3 roles?	ans: 46			

void incr();
int main(){
  incr();
  incr();
  incr();
  return 0;
}
void incr(){
  static int i;
  cout<<++i<<" ";
} Output of the code;
	ans: 1 2 3			

What command should you try if DBMS_OUTPUT.PUT_LINE is not doing what it is supposed to do? Pick ONE option SET ECHO ON SET DISPLAY ON SET TERMOUT ON SET SERVEROUTPUT ON	ans: SET SERVEROUTPUT ON			

it possible to create an object of an empty class type such as: class xyz If so, what is the size of such an object? Pick ONE option Yes, it is possible, and its size is zero. Yes, it is possible, add its size is greater than zero. No, it is not possible to create an empty class; it results in a compiler error. No, it results in a runtime error:	ans:Yes, it is possible , add its size is greater than zero			
What value does ? represent? X32G, V16J ,T8M, ?, P2S Pick ONE option S64N R4P R4Q S8P	ans : R4P			
what is the maximum no of key in a B-Tree of order 5 and height 4. In computer science A B- Tree is a self balancing tree data structure that maintain the data in sorted order.	ans: 624			
Select the expression that causes a MySQL error. Pick ONE option SELECT customer_id, ANY_VALUE(amount) FROM transactions GROUP BY customer_id SELECT customer_id, RAND(amount) FROM transactions GROUP BY customer_id SELECT customer_id, SUBSTRING_INDEX(GROUP_CONCAT(amount ORDER BY RAND()), 'i, 1) FROM transactions GROUP BY customer_id none of the above, all expressions are correct		ans: select customer_id , substring _index....		

Which of the following statements) are NOT correct: Pick ONE OR MORE options The PRIMARY KEY must be unique and not null for each table. The DROP command is used to remove the table definition and its contents whereas the TRUNCATE command to delete all the rows from the table DELETE command is a DDL command whereas DROP is a DML command ACD properties in databases refer to Atomicity, Complexity, Isolation, and Duplicacy	answer both C & D ans: DELETE command is a DDL comnd where as drop is DML command or ACID properties in dbs reffers to atomicity,comp, iso and duplicacy ans: DELETE command is a DDL comnd where as drop is DML command			
Select the extraneous expression (not the same as the others). Pick ONE option SELECT FROM categories ORDER BY id SELECT FROM categories ORDER BY id ASC SELECT FROM categories ORDER BY id DESC None of the above, all expressions are the same	ans: SELECT FROM categories ORDER BY is DESC			

double read_double (FILE * fp) {
double d;
 	
assert(fp != NULL);
 	
fscanf(fp, " %lf", d);
 	
return d;
}
The code above contains a common error. Which one of the fllowing describes it?
 	
Pick ONE option
 	
fscanf() will fail to match floating-point numbers not preceded by whitespace.
 	
The format specifier %lf indicates that the corresponding argument should be long double rather than double.
 	
The call to fscanf() requires a pointer as its last argument.
 	
The format specifier %lf is recognized by fprintf() but not by fscanf().
 	
d must be initialized prior to usage.
	ans:The call to fscanf() requires a pointer as its last argument.			


```
class A {

   public:
  A()
   {
      cout<<"1";
   }
   ~A()
   {
      cout<<"2";
   }

};


class B {

   public:
  B()
   {
      cout<<"3";
   }
   ~B()
   {
      cout<<"4";
   }

};


class C :public A, public B{

   public:
   C():B(),A()
   {
      cout<<"5";
   }
   ~C()
   {
      cout<<"6";
   }

};


int main()
{
 C c;
 return 0;
}
```

135642

int main()
{
  for(int i=1;i<=5;i++)
  {
  fork();
  }
  printf("HELLO");
}
	32			

which of the function operator can be overloaded ? . sizeof & ?:	ans: &			
Which of the following anomalies is/are solved using normalization? Multiple answers may be correct. PL ONE OR MORE Creation anomalies Insertion anomalies Delion anomalies Upitate anomales		ans: Insertion anomalies Deletion anomalies Update anomalies all three are correct		
What kind of joins is a default in SQL? P ONE option O inner Outer Self None of the above	ans: inner			
Which of the following statements is/are correct? Multiple answers may be correct. Pick ONE OR MORE options A prime attribute is an attribute that is a part of the candidate key. A prime attribute is an attribute that is a part of the primary key. A non-prime attribute is an attribute that is not a part of the prime key. None of these	ans:A prime attribute is an attribute that is a part of the candidate key. A prime attribute is an attribute that is a part of the primary key. A non-prime attribute is an attribute that is not a part of the prime key			

Let the following statement return 10 rows. SELECT * FROM namelist; In Oracle, what will this statement return? SELECT * FROM namelist WHERE ROWNUM>5; a) 4 rows b) syntax error c) 6 rows d) 5 rows	5 rows			
Which expression causes a MySQL error? Pick ONE option a)CREATE TABLE users (first_name VARCHAR(255), last name VARCHAR(255), CON b)CREATE TABLE users (first name VARCHAR(255) UNIQUE, last name VARCHAR(25 c)CREATE TABLE users (first_name VARCHAR(255), last_name VARCHAR(255), UNI d)None of the above, all expressions are correct	b)CREATE TABLE users (first name VARCHAR(255) UNIQUE, last name VARCHAR(255) UNIQUE)			

Consider four processes, PILIP[2], P(3), P[4] They are synchronized using four mutex lo wait (m[1]); wait (m[(1+1) N4]); #Critical Section release (m[1]); release (m[(1+1) %4]): Which of the following conditions of a deadlock e mer for the above synchronization? Pick ONE OR MORE options Mutual exclusion of resources using locks Hold and wait No preemption	Mutual Exclusion of resources using locks Hold and wait			

struct customer ptr = malloc(sizeof(struct customer));
Which of the following statements is used to reallocate ptr to be an array of **size**
Pick ONE option
ptr=realloc(ptr, 10* sizeof(struct customer));.
realloc(ptr. 9* sizeof(struct customer));
ptr malloc(9* sizeof(struct customer));
ptr realloc(ptr, 9 sizeof(struct customer));
realloc(ptr. 10* sizeof(struct customer));
	ptr = realloc(ptr, size * sizeof(struct customer));			

Given the following functional dependencies, find the highest normal form. Assume that R(ABCDEF) Functional Dependencies: BC -> E BE->F AF-> DE Pick ONE option INF 2NF	the highest normal form for the given relation is BCNF.			
Out of the nine ingredients, a chef will use exactly. Given the following statements **The ingredients are apricats, bacon cake, donuts, eggs figs gingerbread, hazelnu** **If bacon is not used the chef well not use gngerbread hazelnut or ice cream** **2 if apricots are used bacon and cake are used 3- donuts are not used, apricots a** **4. Eggs are used.**	donut			

Given the following functional dependencies, find the highest normal form. Assume that the given relation is in 1NF already R(ABCDEF) Functional Dependencies: BC -> E BE->F AF-> DE Pick ONE option INF 2NF 3NF Bcnf	bcnf			
Which expression causes a MySQL error? Pick ONE option CREATE TABLE users (firs	none of these			

#include<bits/stdc++.h>
using namespace std;
 	
class Integer{
 	
int num;
 	
public:
 	
Integer (){
 	
num = 0; cout << "1";
}
 	
Integer(int arg){
 	
cout << "2"; num = arg;
}
	12310			

// Online C++ compiler to run C++ program online
#include <iostream>
using namespace std;
int func(int i){
if(i%2)return 0;
else return 1;
}
int main() {
// Write C++ code here
int i = 3;
i = func(i);
i = func(i);
cout << func(i) << endl;
return 0;
}
	0			

Which of the following statement(s) is/are true? Pick ONE OR MORE options Each thread within a process has its own separate memory space. Each thread within a process is independent with respect to the code section. Each thread within a process has its own program counter and stack space. None of the above	d			

which of the following statements is true about heap data structure and it's role in sortin a) heap sort function in o(nlogn) asymptotic complexity and heap of n elements may b c b)Heap sort functions in o(nlogn) time and heap of n elements may be no better than o(C) heap sort functions o(n^2) time and heap of n elements may be constructed no bette d) none of the above correct	b			
A10 A12 B18 B42 _ C888?	C162			
An input restricted dequeue is a linear list in which items may be inserted atone end but removed from either end. Such a data structure can be operated	both as a queue and as a stack			
Which normalization form is based on transitive dependency	3NF			
Select the expression that causes a MySQL error. Pick ONE- SELECT Id, name fROM customer ORDER BY name Asc SELECT Id, name fROM customer ORDER BY name SELECT Id, name fROM customer ORDER BY 2 all are correct	all are correct			

```
#include <iostream>

using namespace std;

class Base{
    int a,b;

    public:
    Base()
    {
        a=0;b=0;
    }

    Base(int a,int b)
    {
        this->a=a;
        this->b=b;

    }


    void display()
    {
        cout<<a<<b;

    }

};



class Derived{
    int c,d;

    public:
    Derived()
    {
        c=0;d=0;
    }

Derived(int a,int b)
    {
        c=a;
        d=b;

    }


    void display()
    {
        cout<<c<<d;

    }
```

The non-preemptive priority-based scheduling algorithm used. Scheduling is carried out only at the arrjval or completion of processes Find the average waiting time for thc above processes. Note: The highest priority process IS scheduled first-	3.5			
select * FROM (SELECT b.department, Avg(a.salary) AS avg_Salary from a left join b on a.id = b.id GROUP BY b. department) ASC WHERE c.avg_salary>1500	2			