admins
- admin_id INT
- city VARCHAR(255)
- state VARCHAR(255)
- email VARCHAR(255)
- mobile_number VARCHAR(255)
- name VARCHAR(255)
- password VARCHAR(255)
- role VARCHAR(255)
- Indexes

wallet_transactions
- wallet_wallet_id INT
- transactions_transaction_id INT
- Indexes

cab_response
- rosponse_id INT
- cab_status ENUM(...)
- from_location VARCHAR(255)
- time VARCHAR(255)
- time_stamp DATETIME(6)
- to_location VARCHAR(255)
- total_bill DOUBLE
- driver_driver_id INT
- user_user_id INT
- Indexes

wallet
- wallet_id INT
- time_stamp DATETIME(6)
- wallet_balence DOUBLE
- wallet_status ENUM(...)
- user_id INT
- Indexes

drivers
- driver_id INT
- city VARCHAR(255)
- state VARCHAR(255)
- age INT
- dob DATE
- driver_name VARCHAR(255)
- email VARCHAR(50)
- licence_number VARCHAR(255)
- location VARCHAR(255)
- mobile_number VARCHAR(13)
- password VARCHAR(255)
- rating DOUBLE
- role VARCHAR(255)
- Indexes

users
- user_id INT
- city VARCHAR(255)
- state VARCHAR(255)
- data_entered DATETIME(6)
- email VARCHAR(50)
- mobile_number VARCHAR(255)
- name VARCHAR(40)
- password VARCHAR(255)
- role VARCHAR(255)
- Indexes

car
- car_id INT
- car_number VARCHAR(255)
- car_type ENUM(...)
- rate_per_km DOUBLE
- driver_driver_id INT
- Indexes

transactions
- transaction_id INT
- amount DOUBLE
- driver_email VARCHAR(255)
- from_location VARCHAR(255)
- time_stamp DATETIME(6)
- to_location VARCHAR(255)
- user_email VARCHAR(255)
- Indexes

cab_booking
- cab_booking_id INT
- booking_time DATETIME(6)
- cab_status ENUM(...)
- distance_in_km DOUBLE
- driver_id INT
- from_location VARCHAR(255)
- to_location VARCHAR(255)
- total_bill DOUBLE
- user_email VARCHAR(255)
- Indexes