

HireHub - Today's Learning Notes

1. JSX: {} vs \${}

In JSX, {} is used for a JavaScript expression. \${} is used only inside a template literal.

```
className={styles.title}
className={`card ${styles.card}`}
```

2. Inline Style

The style prop accepts a JavaScript object. That is why inline React styles often have double braces.

```
style={{ backgroundColor: "#e3f2fd" }}
```

3. Saved Jobs State

We stored saved jobs in App.jsx because both Jobs and SavedJobs need this data.

```
const [savedJobs, setSavedJobs] = useState([]);
```

4. Saving a Job

handleSavedJobs receives the clicked job and adds it to the savedJobs array.

```
const handleSavedJobs = (job) => {
  if (!savedJobs.some((savedJob) => savedJob.id === job.id)) {
    const currentJobs = [...savedJobs, job];
    setSavedJobs(currentJobs);
  } else {
    alert("Job Already Saved");
  }
};
```

5. Passing Functions Through Props

The Save Job button is inside JobCard, so handleSavedJobs travels from App -> Jobs -> JobCard through props.

6. Apply vs Save

Apply Now and Save Job have separate functionality. Apply currently shows an alert; Save adds the job to savedJobs.

```
const saveButton = () => {
  handleSavedJobs(job);
};

const applyButton = () => {
  alert("Applied for the job successfully");
};
```

7. Displaying Saved Jobs

SavedJobs receives savedJobs as a prop and uses map() to display each saved job using JobCard.

8. Conditional Rendering

We use isSaved so the same JobCard can behave differently on Jobs and Saved Jobs pages.

```
{!isSaved && <button>Save Job</button>}
{isSaved && <button>Delete</button>}
```

9. Removing Jobs with filter()

`filter()` creates a new array excluding the job whose id matches the id we want to delete.

```
const handleRemoveJob = (id) => {  
  const updatedJobs = savedJobs.filter((job) => job.id !== id);  
  setSavedJobs(updatedJobs);  
};
```

10. `some()` Function

Hinglish: `some()` array ke elements ko check karta hai ki koi bhi ek element given condition ko satisfy karta hai ya nahi. Ek match mila -> true, nahi mila -> false.

```
savedJobs.some((savedJob) => savedJob.id === job.id)
```

11. Concepts Practiced

`useState`, `props`, functions as props, lifting state up, prop drilling, `map()`, `filter()`, `some()`, spread operator (...), `onClick`, and conditional rendering.

Next Step

Improve the Saved Jobs UI and handle the case when there are no saved jobs.