

HireHub - Day 3 Learning Notes

1. Why Status is Stored in appliedJobs

The application status belongs to the user's application, not the original job data. Therefore, when a user applies for a job, we create a new object that contains all job details along with a new status property.

Example:

```
const jobWithStatus = {
  ...job,
  status: "Applied"
};
```

2. Spread Operator

The spread operator (...job) copies all properties from the original object into a new object.

Example:

```
const jobWithStatus = {
  ...job,
  status: "Applied"
};
```

3. Immutability in React

Instead of modifying an existing object,

```
job.status = "Applied";
```

React recommends creating a new object because immutable updates make state updates predictable and allow React to detect changes correctly.

4. Difference Between { ...job } and { job }

{ ...job }

Copies all properties into the new object.

{ job }

Creates a nested object where the entire job object is stored under the key "job".

5. Why map() is Used

map() returns a new array.

Example:

```
const numbers = [1, 2, 3];

const doubled = numbers.map((num) => num * 2);

// Output:
// [2, 4, 6]
```

In React we use map() to update one object while keeping every other object unchanged.

6. Updating Status

```
const changeStatus = (jobId, status) => {
  const updatedJobs = appliedJobs.map((item) => {
    if (item.id === jobId) {
      return {
        ...item,
        status,
      };
    }
    return item;
  });

  setAppliedJobs(updatedJobs);

  localStorage.setItem(
    "appliedJobs",
    JSON.stringify(updatedJobs)
  );
};
```

7. Passing Only Required Data

Instead of passing the entire job object,

```
changeStatus(job.id, status);
```

we pass only

```
changeStatus(id, status);
```

because only the id is required.

8. Controlled Dropdown

```
<select
  value={status}
  onChange={(e) => changeStatus(id, e.target.value)}
>
```

React controls the selected value using state.

9. Bugs Fixed Today

- Fixed typo in status.
- Fixed duplicate checking.
- Stored the result returned by map().
- Updated localStorage.
- Used id instead of job.id.

Today's Achievements

- Added Apply functionality.
- Added Status Tracking.
- Learned map().

- Learned Immutability.
- Updated localStorage.
- Connected the dropdown.
- Built changeStatus().

Next Session

- UI polishing
- Better status badges
- Disable dropdown for Selected/Rejected
- Build Job Details Page