

Himanshu Kamane

Kamanehimanshu76@gmail.com

Task 1: Dijkstra's Shortest Path Finder

Code Dijkstra's algorithm to find the shortest path from a start node to every other node in a weighted graph with positive weights.

Solution:

```
package cam.day9;
import java.util.*;
public class Dijkstra {
    public static Map<Character, Integer> dijkstra(Map<Character, Map<Character,
Integer>> graph, char start) {
        Map<Character, Integer> distances = new HashMap<>();
        PriorityQueue<Node> priorityQueue = new
PriorityQueue<>(Comparator.comparingInt(node -> node.distance));
        Set<Character> visited = new HashSet<>();
        for (char node : graph.keySet()) {
            distances.put(node, Integer.MAX_VALUE);
        }
        distances.put(start, 0);
        priorityQueue.offer(new Node(start, 0));
        while (!priorityQueue.isEmpty()) {
            Node current = priorityQueue.poll();
            if (visited.contains(current.name)) {
                continue;
            }
            visited.add(current.name);
            for (Map.Entry<Character, Integer> neighbor :
graph.get(current.name).entrySet()) {
                int distance = current.distance + neighbor.getValue();
                if (distance < distances.get(neighbor.getKey())) {
                    distances.put(neighbor.getKey(), distance);
                    priorityQueue.offer(new Node(neighbor.getKey(), distance));
                }
            }
        }
    }
}
```

```

    }
}
return distances;
}
static class Node {
    char name;
    int distance;
    Node(char name, int distance) {
        this.name = name;
        this.distance = distance;
    }
}
public static void main(String[] args) {
    Map<Character, Map<Character, Integer>> graph = new HashMap<>();
    graph.put('A', Map.of('B', 2, 'C', 5));
    graph.put('B', Map.of('A', 2, 'C', 1, 'D', 7));
    graph.put('C', Map.of('A', 5, 'B', 1, 'D', 3));
    graph.put('D', Map.of('B', 7, 'C', 3));
    char startNode = 'A';
    Map<Character, Integer> distances = dijkstra(graph, startNode);
    System.out.println("Shortest distances from node " + startNode + ":");
    for (char node : distances.keySet()) {
        System.out.println("To node " + node + ": " + distances.get(node));
    }
}
}

```

Output:

Shortest distances from node A:

To node A: 0

To node B: 2

To node C: 3

To node D: 6

Task 2: Kruskal's Algorithm for MST

Implement Kruskal's algorithm to find the minimum spanning tree of a given connected, undirected graph with non-negative edge weights.

Solution:

```
package cam.day9;
import java.util.*;
public class Kruskal {
    static class Edge {
        char source;
        char destination;
        int weight;
        Edge(char source, char destination, int weight) {
            this.source = source;
            this.destination = destination;
            this.weight = weight;
        }
    }
    static class Subset {
        char parent;
        int rank;
        Subset(char parent, int rank) {
            this.parent = parent;
            this.rank = rank;
        }
    }
    public static List<Edge> kruskalMST(Map<Character, Map<Character,
Integer>> graph) {
        List<Edge> result = new ArrayList<>();
        List<Edge> edges = new ArrayList<>();
        // Convert graph to list of edges
        for (char source : graph.keySet()) {
            for (Map.Entry<Character, Integer> entry : graph.get(source).entrySet()) {
                char destination = entry.getKey();
                int weight = entry.getValue();
```

```

        edges.add(new Edge(source, destination, weight));
    }
}
// Sort edges by weight
Collections.sort(edges, Comparator.comparingInt(e -> e.weight));
Map<Character, Subset> subsets = new HashMap<>();
for (char vertex : graph.keySet()) {
    subsets.put(vertex, new Subset(vertex, 0));
}
int i = 0;
int numEdges = 0;
while (numEdges < graph.size() - 1 && i < edges.size()) {
    Edge nextEdge = edges.get(i++);
    char x = find(subsets, nextEdge.source);
    char y = find(subsets, nextEdge.destination);
    if (x != y) {
        result.add(nextEdge);
        union(subsets, x, y);
        numEdges++;
    }
}
return result;
}

public static char find(Map<Character, Subset> subsets, char vertex) {
    if (subsets.get(vertex).parent != vertex) {
        subsets.get(vertex).parent = find(subsets, subsets.get(vertex).parent);
    }
    return subsets.get(vertex).parent;
}

public static void union(Map<Character, Subset> subsets, char x, char y) {
    char xRoot = find(subsets, x);
    char yRoot = find(subsets, y);
    if (subsets.get(xRoot).rank < subsets.get(yRoot).rank) {
        subsets.get(xRoot).parent = yRoot;
    } else if (subsets.get(xRoot).rank > subsets.get(yRoot).rank) {

```

```

        subsets.get(yRoot).parent = xRoot;
    } else {
        subsets.get(yRoot).parent = xRoot;
        subsets.get(xRoot).rank++;
    }
}

public static void main(String[] args) {
    Map<Character, Map<Character, Integer>> graph = new HashMap<>();
    graph.put('A', Map.of('B', 4, 'C', 1));
    graph.put('B', Map.of('A', 4, 'C', 2, 'D', 1));
    graph.put('C', Map.of('A', 1, 'B', 2, 'D', 5));
    graph.put('D', Map.of('B', 1, 'C', 5));
    List<Edge> mst = kruskalMST(graph);
    System.out.println("Edges in the Minimum Spanning Tree:");
    for (Edge edge : mst) {
        System.out.println(edge.source + " - " + edge.destination + " : " +
edge.weight);
    }
}
}

```

Output:

Edges in the Minimum Spanning Tree:

A - C : 1

B - D : 1

B - C : 2

Task 3: Union-Find for Cycle Detection

Write a Union-Find data structure with path compression. Use this data structure to detect a cycle in an undirected graph.

Solution:

```
package cam.day9;
import java.util.*;
public class UnionFind {
    private int[] parent;
    private int[] rank;
    public UnionFind(int size) {
        parent = new int[size];
        rank = new int[size];
        for (int i = 0; i < size; i++) {
            parent[i] = i;
            rank[i] = 0;
        }
    }
    public int find(int x) {
        if (parent[x] != x) {
            parent[x] = find(parent[x]);
        }
        return parent[x];
    }
    public void union(int x, int y) {
        int xRoot = find(x);
        int yRoot = find(y);
        if (xRoot == yRoot) {
            return;
        }
        if (rank[xRoot] < rank[yRoot]) {
            parent[xRoot] = yRoot;
        } else if (rank[xRoot] > rank[yRoot]) {
            parent[yRoot] = xRoot;
        }
    }
}
```

```

    } else {
        parent[yRoot] = xRoot;
        rank[xRoot]++;
    }
}

public static boolean hasCycle(Map<Character, List<Character>> graph) {
    UnionFind uf = new UnionFind(graph.size());
    for (char node : graph.keySet()) {
        int parentX = uf.find(node - 'A');
        for (char neighbor : graph.get(node)) {
            int parentY = uf.find(neighbor - 'A');
            if (parentX == parentY) {
                return true; // Cycle detected
            }
            uf.union(parentX, parentY);
        }
    }
    return false; // No cycle detected
}

public static void main(String[] args) {
    // Example graph represented as an adjacency list
    Map<Character, List<Character>> graph = new HashMap<>();
    graph.put('A', Arrays.asList('B', 'C'));
    graph.put('B', Arrays.asList('A', 'C', 'D'));
    graph.put('C', Arrays.asList('A', 'B', 'D'));
    graph.put('D', Arrays.asList('B', 'C'));
    System.out.println("Graph:");
    for (char node : graph.keySet()) {
        System.out.print(node + " --- ");
        for (char neighbor : graph.get(node)) {
            System.out.print(neighbor + " ");
        }
        System.out.println();
    }
    if (hasCycle(graph)) {

```

```
        System.out.println("The graph contains a cycle.");  
    } else {  
        System.out.println("The graph does not contain a cycle.");  
    }  
}  
}
```

Output:

Graph:

A --- B C

B --- A C D

C --- A B D

D --- B C

The graph contains a cycle.