

Public Key Infrastructure (PKI Lab)

Lab 7

Himanshu Sharma – 202117006

Task 1: Becoming a Certificate Authority (CA)

Creating a directory to hold configuration files and certificates. Copy the configuration file into current directory.

```
[04/10/22]seed@VM:~/lab7$ cp /usr/lib/ssl/openssl.cnf openssl.cnf
```

```
[04/10/22]seed@VM:~/lab7$ mkdir demoCA
[04/10/22]seed@VM:~/lab7$ cd demoCA
[04/10/22]seed@VM:~/../demoCA$ mkdir certs crl newcerts
[04/10/22]seed@VM:~/../demoCA$ touch index.txt
[04/10/22]seed@VM:~/../demoCA$ echo "1000" > serial
[04/10/22]seed@VM:~/../demoCA$ ls
certs  crl  index.txt  newcerts  serial
```

Start to generate self-signed certificate for the CA

```
[04/10/22]seed@VM:~/lab7$ openssl req -new -x509 -keyout ca.key -out ca.crt -config openssl.cnf
Generating a 2048 bit RSA private key
.....
.....+++
.....+++
.....
```

Fill the appropriate details for certificate. Make country name, state name, organization name same in this policy_match configuration.

```
Country Name (2 letter code) [AU]:INDIA
string is too long, it needs to be less than 2 bytes long
Country Name (2 letter code) [AU]:IN
State or Province Name (full name) [Some-State]:RAJASTHAN
Locality Name (eg, city) []:JAIPUR
Organization Name (eg, company) [Internet Widgits Pty Ltd]:HTT
Organizational Unit Name (eg, section) []:SOFTWARE
Common Name (e.g. server FQDN or YOUR name) []:HIMANSHU
Email Address []:samitihs4@gmail.com
```

```
[04/10/22]seed@VM:~/lab7$ ls
ca.crt  ca.key  demoCA  openssl.cnf
```

Task 2: Creating a certificate for SEEDPKILab2020.com

Step1: Generate public/private key pair

We executed the following command to generate key pair and use pass phase to encrypt private key in server.key

```
[04/10/22]seed@VM:~/lab7$ openssl genrsa -aes128 -out server.key 1024
Generating RSA private key, 1024 bit long modulus
.....+++++
.....+++++
e is 65537 (0x10001)
Enter pass phrase for server.key:
Verifying - Enter pass phrase for server.key:
```

Following command is used to see the content of the file present in server.key

```
[04/10/22]seed@VM:~/lab7$ ls
ca.crt  ca.key  demoCA  openssl.cnf  server.key
[04/10/22]seed@VM:~/lab7$ openssl rsa -in server.key -text
Enter pass phrase for server.key:
Private-Key: (1024 bit)
modulus:
    00:d3:f1:4e:a8:72:ed:6a:92:ee:2f:9a:f7:01:da:
    88:c3:bb:bf:85:06:38:34:e0:0d:8f:bb:86:06:0f:
    37:4d:4b:23:88:49:eb:91:38:ba:76:6b:5f:40:f0:
    da:c3:e4:91:89:5d:a8:a9:71:94:14:12:5c:2b:0a:
    a4:bc:4c:68:49:af:5e:16:bd:11:91:ce:88:88:ba:
    46:61:d7:83:1c:48:30:65:d1:a5:c1:01:11:5c:b8:
```

Step 2: Generate a certificate signing request (CSR)

To generate a certificate a signing request is to be generated to sign the keys. Use SEEDPKILab2020.com as common name for the certificate request. While keeping most information same as our root CA.

```
[04/10/22]seed@VM:~/lab7$ openssl req -new -key server.key -out server.csr -config openssl.cnf
Enter pass phrase for server.key:
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name
or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [AU]:IN
State or Province Name (full name) [Some-State]:RAJASTHAN
Locality Name (eg, city) []:JAIPUR
Organization Name (eg, company) [Internet Widgits Pty Ltd]:HTT
Organizational Unit Name (eg, section) []:SOFTWARE
Common Name (e.g. server FQDN or YOUR name) []:SEEDPKILab2020.com
Email Address []:samitihs4@gmail.com

Please enter the following 'extra' attributes
to be sent with your certificate request
A challenge password []:himanshu
An optional company name []:htt
```

Here we are generating the certificate as per the certificate signing request, Our trusted CA will generate certificate and use ca.crt and ca.key to convert server.csr to server.crt

```
[04/10/22]seed@VM:~/lab7$ openssl ca -in server.csr -out server.crt
-cert ca.crt -keyfile ca.key -config openssl.cnf
Using configuration from openssl.cnf
Enter pass phrase for ca.key:
Check that the request matches the signature
Signature ok
Certificate Details:
    Serial Number: 4096 (0x1000)
    Validity
        Not Before: Apr 10 09:41:33 2022 GMT
        Not After : Apr 10 09:41:33 2023 GMT
    Subject:
        countryName           = IN
        stateOrProvinceName   = RAJASTHAN
        organizationName      = HTT
        organizationalUnitName = SOFTWARE
        commonName            = SEEDPKILab2020.com
        emailAddress          = samitihs4@gmail.com
    X509v3 extensions:
        X509v3 Basic Constraints:
```

```
Certificate is to be certified until Apr 10 09:41:33 2023 GMT (365 days)
Sign the certificate? [y/n]:y

1 out of 1 certificate requests certified, commit? [y/n]y
Write out database with 1 new entries
Data Base Updated
```

Presented all the details of the certificate and accept all condition to generate certificate.

Task 3: Deploying Certificate in an HTTPS Web Server

Step 1: Configuring DNS

To let our computer recognize seedpkilab2020.com as internal domain and direct its traffic to local server we edit /etc/hosts file.

```
[04/10/22]seed@VM:~/lab7$ gedit /etc/hosts
[04/10/22]seed@VM:~/lab7$ sudo gedit /etc/hosts
```

127.0.0.1	www.csrflabelgg.com
127.0.0.1	www.csrfabattacker.com
127.0.0.1	www.repackagingattacklab.com
127.0.0.1	www.seedlabclickjacking.com
127.0.0.1	SEEDPKILab2020.com


Combine the secret key and certificate into one single file server.pem

```
[04/10/22]seed@VM:~/lab7$ cp server.key server.pem
[04/10/22]seed@VM:~/lab7$ cat server.crt >> server.pem
```

Launch the web server using server.pem.


```
[04/10/22]seed@VM:~/lab7$ openssl s_server -cert server.pem -www
Enter pass phrase for server.pem:
Using default temp DH parameters
ACCEPT
```

The server is listening on port 4433. Browse <https://seedpkilab2018.com:4433>




Step 3: Getting the browser to accept our CA certificate


In the previous screenshot we can see the error mentioning the website owner is not configured.



It was because our certificate was not included in Firefox certificate repository. We added our CA certificate to the browser.



After adding our certificate to the repo restart the web server. Browser the website.




Step 4: Testing our HTTPS website

Now that our website is up and running. We will do following task


1. Change the byte in the server.pem file and restart the server. In some case the website run smoothly without any changes. But at some places the change in single byte do not restart the server.

```
Data:
  Version: 3 (0x2)
  Serial Number: 4096 (0x1000)
  Signature Algorithm: sha256WithRSAEncryption
  Issuer: C=IN, ST=RAJASTHAN, L=JAIPUR, O=HTT, OU=SOFTWARE, CN=HIMANSHU/
```

```
Data:
  Version: 3 (0x2)
  Serial Number: 4096 (0x1000)
  Signature Algorithm: sha256WithRSAEncryption
  Issuer: C=IN, ST=RAJASTHAM, L=JAIPUR, O=HTT, OU=SOFTWARE, CN=HIMANSHU/
```



2. Use localhost – when browsing <https://localhost:4433>, it is reported unsafe. Because the localhost has no certificate, the website is using a certificate identified for seedpkilab2020.com



Task 4: Deploying certificate in an Apache-based HTTPS website

We create two directories for https and http protocol website. In https directory we added our server certificate and private key file to the folder.

```
[04/10/22]seed@VM:~/lab7$ sudo mkdir /var/www/Example_One
[04/10/22]seed@VM:~/lab7$ sudo mkdir /var/www/Example_Two
[04/10/22]seed@VM:~/lab7$ sudo cp server.pem server.crt /var/www/Example_Two/
[04/10/22]seed@VM:~/lab7$
```

The changes are made in the /etc/apache2/sites-available/000-default.conf to host http website.

```
<VirtualHost *:80>
    ServerName SEEDPKILab2020.com
    DocumentRoot /var/www/Example_One
    DirectoryIndex index.html
</VirtualHost>
```

The changes are made in the /etc/apache2/sites-available/default-ssl.conf to host https website. These changes are made to configure apache server for our website.

```
<VirtualHost *:443>
    ServerName SEEDPKILab2020.com
    DocumentRoot /var/www/Example_Two
    DirectoryIndex index.html
    SSLEngine On
    SSLCertificateFile /var/www/Example_Two/server.crt
    SSLCertificateKeyFile /var/www/Example_Two/server.pem
</VirtualHost>
```

Now we need to test our configuration and restart our server by following commands

```
[04/10/22]seed@VM:~/lab7$ sudo apachectl configtest
```

Enable SSL module

```
[04/10/22]seed@VM:~/lab7$ sudo a2enmod ssl
Considering dependency setenvif for ssl:
Module setenvif already enabled
Considering dependency mime for ssl:
Module mime already enabled
Considering dependency socache_shmcb for ssl:
Module socache shmcb already enabled
```



Enable the site we just edited.

```
[04/10/22]seed@VM:~/lab7$ sudo a2ensite default-ssl
Site default-ssl already enabled
```

Restart Apache server.

```
[04/10/22]seed@VM:~/lab7$ sudo service apache2 restart
Enter passphrase for SSL/TLS keys for SEEDPKILab2020.com:443 (RSA):
*****
```

Browse the website <http://seedpkilab2020.com>. It works fine.



Browse the website <https://seedpkilab2020.com>. Our website is up and running.

