

SQL-05 | Window Functions

Lecture Queries

WINDOW Functions

Window Functions

Window fns give the ability to put the values from one row of data into context compared to a group of rows, or partition.

We can answer questions like

- If the dataset were sorted, where would this row land in the results?
- How does a value in this row compare to a value in the prior row?
- How does a value in the current row compare to the average value for its group?

So, window functions **return group aggregate calculations alongside individual row-level** information for items in that group, or partition.

Question: Get the price of the most expensive item per vendor?

CustID	OrderID	TotalDue
1	101	\$100
2	102	\$150
1	103	\$90
3	104	\$80
2	105	\$200
1	106	\$150

Partition by CustID



CustID	OrderID	TotalDue
1	101	\$100
1	103	\$90
1	106	\$150

CustID	OrderID	TotalDue
2	102	\$150
2	105	\$200

CustID	OrderID	TotalDue
3	104	\$80

CustID	OrderID	TotalDue
1	101	\$100
2	102	\$150
1	103	\$90
3	104	\$80
2	105	\$200
1	106	\$150

Partition by CustID
Order by TotalDue

CustID	OrderID	TotalDue
1	103	\$90
1	101	\$100
1	106	\$150

CustID	OrderID	TotalDue
2	102	\$150
2	105	\$200

CustID	OrderID	TotalDue
3	104	\$80

CustID	OrderID	TotalDue
1	101	\$100
2	102	\$150
1	103	\$90
3	104	\$80
2	105	\$200
1	106	\$150

Partition by CustID
Order by TotalDue
(default frame)

CustID	OrderID	TotalDue
1	103	\$90

CustID	OrderID	TotalDue
1	103	\$90
1	101	\$100

CustID	OrderID	TotalDue
1	103	\$90
1	101	\$100
1	106	\$150

CustID	OrderID	TotalDue
2	102	\$150

CustID	OrderID	TotalDue
2	102	\$150
2	105	\$200

CustID	OrderID	TotalDue
3	104	\$80

Question: Rank the products on their price per vendor and the associated **product_id**.

```
SELECT  
    vendor_id,  
    market_date,  
    product_id,  
    original_price,  
    ROW_NUMBER() OVER (PARTITION BY vendor_id ORDER BY  
original_price DESC) AS price_rank  
FROM farmers_market.vendor_inventory  
ORDER BY vendor_id, original_price DESC
```

RANK()

The **RANK** function numbers the results just like **ROW_NUMBER** does, but gives rows with the same value the same ranking.

```
SELECT
  vendor_id,
  market_date,
  product_id,
  original_price,
  RANK() OVER (PARTITION BY vendor_id ORDER BY
original_price DESC) AS
  price_rank
FROM farmers_market.vendor_inventory
```


DENSE_RANK()

If you don't want to skip rank numbers for tied values like in case of RANK, use the DENSE_RANK function.

```
SELECT
  vendor_id,
  market_date,
  product_id,
  original_price,
  DENSE_RANK() OVER (PARTITION BY vendor_id ORDER
BY original_price DESC) AS
  price_rank
FROM farmers_market.vendor_inventory
```

Return the “**top tenth**” of the inventory, when sorted by price?

The dynamic solution is to use the NTILE function.

```
SELECT
    vendor_id,
    market_date,
    product_id,
    original_price,
    NTILE(10) OVER (ORDER BY original_price DESC) AS price_ntile
FROM farmers_market.vendor_inventory
ORDER BY original_price DESC
```

Question: As a farmer, you want to figure out which of your products were above the average price per product on each market date?

```
SELECT  
    vendor_id,  
    market_date,  
    product_id,  
    original_price,  
    AVG(original_price) OVER (PARTITION BY market_date ORDER BY  
    market_date) AS average_cost_product_by_market_date  
FROM farmers_market.vendor_inventory
```

Question: As a farmer, you want to figure out which of your products were above the average price per product on each market date?

```
SELECT
    vendor_id,
    market_date,
    product_id,
    original_price,
    AVG(original_price) OVER (PARTITION BY market_date ORDER BY
    market_date) AS average_cost_product_by_market_date
FROM farmers_market.vendor_inventory
```

Extract the farmer's products that have prices above the market date's average product cost.

- Using a **subquery**, we can filter the results to a single vendor, with **vendor_id 8**, and
- only **display products that have prices above the market date's average product cost**.

```
SELECT * FROM
(
  SELECT
    vendor_id,
    market_date,
    product_id,
    original_price,
    ROUND(AVG(original_price) OVER (PARTITION BY market_date ORDER BY
    market_date), 2) AS average_cost_product_by_market_date
  FROM farmers_market.vendor_inventory )x
WHERE x.vendor_id = 8
      AND x.original_price > x.average_cost_product_by_market_date
ORDER BY x.market_date, x.original_price DESC
```

Question: Count how many different products each vendor brought to market on each date, and displays that count on each row.

```
SELECT
  vendor_id,
  market_date,
  product_id,
  original_price,
  COUNT(product_id) OVER (PARTITION BY market_date, vendor_id)
  vendor_product_count_per_market_date
FROM farmers_market.vendor_inventory
ORDER BY vendor_id, market_date, original_price DESC
```

Question: Calculate the running total of the cost of items purchased by each customer, sorted by the date and time and the ***product_id***

```
SELECT customer_id,  
       market_date,  
       vendor_id,  
       product_id,  
       quantity * cost_to_customer_per_qty AS price,  
       SUM(quantity * cost_to_customer_per_qty) OVER (PARTITION BY  
customer_id ORDER BY market_date, transaction_time, product_id) AS  
customer_spend_running_total  
FROM farmers_market.customer_purchases
```

Question: Using the **vendor_booth_assignments** table in the Farmer's Market database, display each vendor's booth assignment for each **market_date** alongside their previous booth assignments.

```
SELECT
    market_date,
    vendor_id,
    booth_number,
    LAG(booth_number,1) OVER (PARTITION BY vendor_id ORDER BY market_
    date, vendor_id) AS previous_booth_number

FROM farmers_market.vendor_booth_assignments
```


Question: The Market manager may want to filter these query results to a specific market date to determine which vendors are new or changing booths that day, so we can contact them and ensure setup goes smoothly.

Check it for date: 2019-04

```
SELECT * FROM
(SELECT
    market_date,
    vendor_id,
    booth_number,
    LAG(booth_number, 1) OVER (partition by vendor_id order by
market_date) AS prev_booth
FROM farmers_market.vendor_booth_assignments) AS x
WHERE x.market_date = "2019-04-10"
AND
(x.booth_number <> x.prev_booth OR x.prev_booth IS NULL)
```

Reference

[Window functions.](#)