



- Power Output: 0.5W
- Squelch Levels: 0-9
- CTCSS/DCS STE
- Monitor

- Wiide/Narrow Bands
- Low Battery Alert
- Busy Channel Lockout (BCL)
- Auto Power Saving



100	General	
Frequency Range	446.0~446.2MHz	
Channel Capacity	16	
Channel Spacing	25KHz/12.5KHz	
Operating Temperature	-20°C ~+60°C	
Antenna Impedance	50Ω	
Working Voltage	7.4VDC(±20%)	
Battery Capacity	2200mAh (Li-Poly)	
Frequency Stability	≤±2.5ppm	
Dimensions	126*61*40mm	
Weight	238g (Battery included)	
	Transmitter	
Power Output	0.5W	
Modulation	16KΦF3E(Width)/8K50F3E(Narrow)	
Noise and Harmonic	≤-36dB	
FM Noise	≤-40dB	
Audio Distortion	≤5%	
Adjacent Channel Power	≥55 dB(Width)/55 dB(Narrow)	
Modulation Limitation	≤5KHz(Width)/2.5KHz(Narrow)	
	Receiver	
Sensitivity	≤0.2µV(Width)/ 0.25µV (Narrow)	
Adjacent Channel Selectivity	≥60dB(Width)/ 50dB (Narrow)	
Intermodulation	≥60dB(Width)/ 50dB (Narrow)	
Spurious Suppression	≥60dB(Width)/ 50dB (Narrow)	
SNR	≥45dB(Width)/ 40dB (Narrow)	
Audio Output Power	0.5W	

Standard Accessories











Optional Accessories





