

```
himasree@LAPTOP-41COT5AA:~/OSLab$ nano p3.c
himasree@LAPTOP-41COT5AA:~/OSLab$ gcc p3.c -o p3
himasree@LAPTOP-41COT5AA:~/OSLab$ ./p3
Parent process started
Parent PID: 553
Parent PPID: 325

Parent is Running...
Parent PID: 553
Child PID: 554
Parent is Waiting for child...

Child process created
Child PID: 554
Child PPID: 553
Child is Running...
Child is Terminating...
Child has Terminated.
Parent continues Running.
himasree@LAPTOP-41COT5AA:~/OSLab$ |
```

```
himasree@LAPTOP-41COT5AA:~/OSLab$ cat p3.c
#include <stdio.h>
#include <unistd.h>
#include <sys/wait.h>

int main()
{
    pid_t pid;

    printf("Parent process started\n");
    printf("Parent PID: %d\n", getpid());
    printf("Parent PPID: %d\n", getppid());

    pid = fork();

    if (pid < 0)
    {
        printf("Fork failed\n");
        return 1;
    }
    else if (pid == 0)
    {
        // Child process
        printf("\nChild process created\n");
        printf("Child PID: %d\n", getpid());
        printf("Child PPID: %d\n", getppid());

        printf("Child is Running...\n");

        sleep(5);
    }
}
```

```
        printf("Child is Terminating...\n");
    }
    else
    {
        // Parent process
        printf("\nParent is Running...\n");
        printf("Parent PID: %d\n", getpid());
        printf("Child PID: %d\n", pid);

        printf("Parent is Waiting for child...\n");

        wait(NULL);

        printf("Child has Terminated.\n");
        printf("Parent continues Running.\n");
    }

    return 0;
}
hinasree@APT0P-41C0T5AA:~/OSLab$ |
```