

Practical -6

```
himasree@LAPTOP-41COT5AA:~/OSLab$ nano server.c
himasree@LAPTOP-41COT5AA:~/OSLab$ nano client.c
himasree@LAPTOP-41COT5AA:~/OSLab$ gcc server.c -o server
himasree@LAPTOP-41COT5AA:~/OSLab$ ./server
hello
Client: hello
Server: Message received
|
```

```
himasree@LAPTOP-41COT5AA:~$ cd ~/OSLab
himasree@LAPTOP-41COT5AA:~/OSLab$ gcc client.c -o client
himasree@LAPTOP-41COT5AA:~/OSLab$ ./client
Enter message: hello
Enter message: |
```

```
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <sys/stat.h>
#include <string.h>

int main() {
    char buf[100];

    mkfifo("myfifo", 0666);

    int fd = open("myfifo", O_RDONLY);

    while (1) {
        read(fd, buf, sizeof(buf));
        printf("Client: %s\n", buf);

        if (strcmp(buf, "exit") == 0)
            break;

        printf("Server: Message received\n");
    }

    close(fd);
    unlink("myfifo");

    return 0;
}
```

```
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <string.h>

int main() {
    char buf[100];

    int fd = open("myfifo", O_WRONLY);

    while (1) {
        printf("Enter message: ");
        fgets(buf, sizeof(buf), stdin);

        buf[strcspn(buf, "\n")] = '\0';

        write(fd, buf, strlen(buf) + 1);

        if (strcmp(buf, "exit") == 0)
            break;
    }

    close(fd);

    return 0;
}
```