

```

himasree@LAPTOP-41COT5AA:~/OSLab$ nano skill2.q2.c
himasree@LAPTOP-41COT5AA:~/OSLab$ gcc skill2.q2.c -o skill2.q2
himasree@LAPTOP-41COT5AA:~/OSLab$ ./skill2.q2

Enter command: ls
Unknown command.

Enter command: help
Commands: help, start, stop, exit

Enter command: ls
Unknown command.

Enter command: ^C
himasree@LAPTOP-41COT5AA:~/OSLab$ nano skill2.q2.c
himasree@LAPTOP-41COT5AA:~/OSLab$ gcc skill2.q2.c -o skill2.q2
himasree@LAPTOP-41COT5AA:~/OSLab$ ./skill2.q2

shell> help
Available commands:
ls
pwd
help
exit

shell> ls
LinuxLab      exp1    exp6    form.c    program02  program24  program33  q3        skill2.q2
MYProject    exp1.c  exp6.c  p1        program02.c program24.c program33.c q3.c      skill2.q2.c
MyProject    exp2    exp7    p1.c      program1   program25  program4    q4        source.txt
copy.c       exp2.c  exp7.c  p2        program1.c program25.c program4.c  q4.c      trace.txt

```

```

shell> help
Available commands:
ls
pwd
help
exit

shell> hello
Command not found: hello

shell> exit
Shell terminated.

```

```

#include <stdio.h>
#include <string.h>
#include <unistd.h>
#include <termios.h>
#include <stdlib.h>

#define SIZE 100

int main()
{
    char input[SIZE];
    char ch;
    int i;
    struct termios old, new;

    tcgetattr(STDIN_FILENO, &old);

    new = old;
    new.c_lflag &= ~(ICANON | ECHO);

    tcsetattr(STDIN_FILENO, TCSANOW, &new);

    while (1)
    {
        i = 0;

        printf("\nshell> ");
        fflush(stdout);

        while (1)

```

```

{
    read(STDIN_FILENO, &ch, 1);

    if (ch == '\n' || ch == '\x')
    {
        input[i] = '\0';
        printf("\n");
        break;
    }

    if (ch == 127 || ch == 8)
    {
        if (i > 0)
        {
            i--;
            printf("\b \b");
            fflush(stdout);
        }
    }
    else
    {
        if (i < SIZE - 1)
        {
            input[i] = ch;
            i++;

            printf("%c", ch);
            fflush(stdout);
        }
    }
}
while (1)

```

```

}

if (strcmp(input, "exit") == 0)
{
    break;
}
else if (strcmp(input, "help") == 0)
{
    printf("Available commands:\n");
    printf("ls\n");
    printf("pwd\n");
    printf("help\n");
    printf("exit\n");
}
else if (strcmp(input, "ls") == 0)
{
    system("ls");
}
else if (strcmp(input, "pwd") == 0)
{
    system("pwd");
}
else if (strlen(input) == 0)
{
    continue;
}
else
{
    printf("Command not found: %s\n", input);
}

```

```

    tcsetattr(STDIN_FILENO, TCSANOW, &old);

    printf("Shell terminated.\n");

    return 0;
}
himasree@LAPTOP-41COT5AA:~/OSLab$ |

```