

```
GNU nano 8.7.1 client.c
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
    int client_fd;
    struct sockaddr_un address;
    char message[] = "Hello Server";

    client_fd = socket(AF_UNIX, SOCK_STREAM, 0);

    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);

    connect(client_fd, (struct sockaddr *)&address, sizeof(address));

    write(client_fd, message, strlen(message) + 1);

    close(client_fd);

    return 0;
}

GNU nano 8.7.1 Server.c
#include <stdio.h>
#include <unistd.h>
#include <sys/socket.h>
#include <sys/un.h>
#include <string.h>

#define SOCKET_PATH "/tmp/my_socket"

int main()
{
    int server_fd, client_fd;
    struct sockaddr_un address;
    char buffer[100];

    // Create socket
    server_fd = socket(AF_UNIX, SOCK_STREAM, 0);

    // Set socket address
    address.sun_family = AF_UNIX;
    strcpy(address.sun_path, SOCKET_PATH);

    // Remove old socket
    unlink(SOCKET_PATH);

    // Bind socket to path
    bind(server_fd, (struct sockaddr *)&address, sizeof(address));

    // Wait for client
    listen(server_fd, 5);

    while(1)
    {
        client_fd = accept(server_fd, NULL, NULL);
        read(client_fd, buffer, 100);
        printf("Message from client: %s\n", buffer);
    }
}
```

```
hp@Hima:~/OSSP$ cd OSSP
hp@Hima:~/OSSP$ nano client.c
hp@Hima:~/OSSP$ gcc client.c -o client
hp@Hima:~/OSSP$ ./client
hp@Hima:~/OSSP$

hp@Hima:~/OSSP$ cd OSSP
hp@Hima:~/OSSP$ nano Server.c
hp@Hima:~/OSSP$ gcc Server.c -o Server
hp@Hima:~/OSSP$ ./Server
Server waiting...
Message from client: Hello Server
hp@Hima:~/OSSP$
```